

## Series UJ40-500



### Standard Equipment

- 15m 4-core oil resistance electric cable with 4-pin plug
- 20m wear resistance high pressure hose with steel fittings
- High pressure dry-shut trigger gun with 1000mm stainless-steel lance and nozzle
- User manual book with part list

### Optional Accessories

- Extension hoses with connectors
- Extension electric cable
- Rotating nozzle
- Drain and pipe cleaning nozzles
- Spare part kits
- High pressure protection clothing, helmet with face shield and earmuff
- Hose protection
- Optional booster pump

# ULTRAJET

## High Pressure Water Blaster 500bars

**ULTRAJET** UJ40-500 is a professional heavy-duty high-pressure water blaster with a high-performance crank shaft, ceramic pistons and the simplest design – aimed to reduce the Total Cost of Ownership (TCOO). Fully designed and manufactured in Singapore, these water blasters are designed to reduce the complexity of maintenance without compromising the quality and durability for heavy duty usage under the toughest conditions.



High-pressure cleaning companies



Building sites and boatyards



Iron and steel works and mechanical engineering firms



Food-industry companies



Oil, chemical and energy companies

## Series UJ40-500

### Highlights

- Made in Singapore with EU pump
- Heavy duty structural frame
- Ceramic plungers
- Asynchronous three-phase 30 KW high-efficiency IP55 motor
- Low water inlet pressure protection switch
- Rupture disc system
- Stainless steel pressure gauge with glycerin
- 50 microns water filter with replaceable cartridge
- Weatherproof star-delta control panel with E stop and trip warning light

### Contact us

#### Address:

ASEA Marine Pte Ltd  
50 Tuas Ave 11, #03-01  
Singapore 6309107

#### Phone

+65 6970 8700

#### Email

[sales@aseamarine.sg](mailto:sales@aseamarine.sg)

#### Website

[www.aseamarine.sg](http://www.aseamarine.sg)

# ULTRAJET



Weatherproof star-delta control panel with E stop and trip warning light



Direct water inlet pre-filter to ensure zero water contamination into pump



Rupture Disc System



Water Supply Sensor

## Technical Specifications

	UJ40/500-30	UJ40/500-30
Pump Pressure (Bar/Psi)	500/72500	500/7250
Flowrate (liter per minute)	30	30
Max inlet temperature (°C)	35	35
Power Voltage/phase	380V/3ph	440V/3ph
Power Frequency (hz)	50	60
Power consumption (HP/kW)	37/28	37/28
Motor Class	IP 55/F	IP 55/F
Pump RPM	1450	1750
Load Current (A)	43	43
Weight (Kg)	440	440
Dimension (mm)	790 x 1300 x 1200	790 x 1300 x 1200