



Lifting Sling with reinforced eyes



Lifting sling with high-duty steel end fittings



Endless Lifting slings used in basket lift



Pipe sling with reinforced eyes



Lowering-in belt with ram's head fitting and plates



Multi-leg lifting systems with high-duty steel end fittings



Multi-leg lifting systems with safety hook



Lifting sling with SECUTEX coating and 'C' hook



Lifting Sling with SECUTEX Protective Sleeve



Endless roundsling basket lift



Endless roundsling chaked lift



Multi-leg roundsling system with high-duty steel end fittings




Endless roundsling straight lift



Lifting Sling with SECUTEX coating and steel end fittings



Eye Slings



**FLAT LIFTING SLINGS / SAFETY FACTOR 7:1**

We manufacture Double Ply slings as per European Norm, EN 1492-1 with a Safety Factor of 7:1. The color of the webbing indicates the Safety Working Load/ Working Load Limit of the sling. We have two programmes for this type of slings based on the webbing width.

1. Individual certificates provide each sling.
2. Each sling is provided with protection for the eyes.
3. All slings can be provided with protective polyester sleeve of any length.



**Flat Polyester Sling Type IE (webbing width in inch)**



Webbing from West Europe (without black lines)				100 % 	200 % 	140 % 7° - 45° 	80 % 	100 % 45° - 60° 
Ref.	SWL / WLL	Width	Color	SWL/WLL in kg at different modes				
IE1	1 T	1"	Violet	1000	2000	1400	800	1000
IE2	2 T	2"	Green	2000	4000	2800	1600	2000
IE3	3 T	3"	Yellow	3000	6000	4200	2400	3000
IE4	4 T	4"	Grey	4000	8000	5600	3200	4000
IE5	5 T	5"	Red	5000	10000	7000	4000	5000
IE6	6 T	6"	Brown	6000	12000	8400	4800	6000
IE8	8 T	8"	Blue	8000	16000	11200	6400	8000
IE10	10 T	10"	Orange	10000	20000	14000	8000	10000
IE12	12 T	12"	Orange	12000	24000	16800	9600	12000

**Flat Polyester Sling Type ME (webbing width in mm)**



**ME3 SLING (3 TONNES)**  
with 3 Black Lines.



In addition to the color the number of black lines on these slings indicates its SWL/WWL.

Webbing from West Europe (with black lines)				100 %	200 %	140 % 7° - 45°	80 %	100 % 45° - 60°
Ref.	SWL / WLL	Width	Color	SWL/WLL in kg at different modes				
ME1	1 T	30mm	Violet	1000	2000	1400	800	1000
ME2	2 T	60mm	Green	2000	4000	2800	1600	2000
ME3	3 T	90mm	Yellow	3000	6000	4200	2400	3000
ME4	4 T	120mm	Grey	4000	8000	5600	3200	4000
ME5	5 T	150mm	Red	5000	10000	7000	4000	5000
ME6	6 T	180mm	Brown	6000	12000	8400	4800	6000
ME8	8 T	240mm	Blue	8000	16000	11200	6400	8000
ME10	10 T	300mm	Orange	10000	20000	14000	8000	10000

**Type of eyes (Soft Eyes)**

**FLAT EYE**  
Category 1



**FOLDED EYE**  
Category 2



**REVERSED EYE**  
Category 3



**EYE REINFORCEMENT:**

Soft Eyes can be reinforced with leather or polyester protection.



Leather



Polyester

**Slings with metal fittings (Hard Eyes)**

Eyes can be provided with metal fittings for more safety and durability.

**NON-REEVING**


Category 4

**REEVING**

Category 5

**Protective Polyester Sleeve**

Sleeves can be provided for all sizes of slings to protect them from sharp edges and abrasion. Using sleeves will enhance life of the sling.

**WEBBING BELT FOR SLING**

**WEBBING BELT FOR SLINGS**



**TYPE**

Polyester 1-Ply Webbing belt for slings

**Technical specifications**

- Colour coded according to DIN-EN1492-1
- Capacity stripes: each stripe is equal to 1 tonne capacity.
- Each 25 or 30mm belt width is equal to 1 tonne capacity, depending order's request.
- 200M per roll or any length as per order's request.
- All the safety factor 5:1; 6:1; 7:1 is on the basis of double ply webbing sling, which is made of two 1-ply belt.

**Characteristics**

- Low elongation

**Norms**

- According to Machine Directive 89/392/EC.E27C



Belt Width (mm)	Colour coded according to DIN-EN1492-1	Working load limit of 2-ply webbing sling (t)	Net weight of 200m (kgs)			Rolls Per Carton (rolls)			Dimension of Carton (mm)
			5:1	6:1	7:1	5:1	6:1	7:1	
25	WLL 1T	1	14	17	19	2	6	6	51X31X32
30	WLL 1T	1	14	17	19	5	5	6	51X31X32
50	WLL 2T	2	27	34	38	1	1	1	51X31X32
60	WLL 2T	2	27	34	38	1	1	1	51X31X32
75	WLL 3T	3	42	50	57	1	1	1	51X31X32
90	WLL 3T	3	42	50	57	1	1	1	51X31X32
100	WLL 4T	4	55	66	76	1	1	1	51X31X32
120	WLL 4T	4	55	66	76	1	1	1	51X31X32
125	WLL 5T	5	69	83	95	1	1	1	51X51X41
140	WLL 5T	5	69	83	95	1	1	1	51X51X41
150	WLL 6T	6	82	98	114	1	1	1	51X51X41
200	WLL 8T	8	124	130	160	1	1	1	55X55X50
250	WLL 10T	10	156	164	208.6	1	1	1	55X55X50
300	WLL 12T	12	186	202	220	1	1	1	55X55X50