## http://waterheatertimer.org/calculate-water-heater-recovery.html



## TECHNICAL SERVICE DEPARTMENT Technical Service Bulletin 1-800-432-8373



## Recovery Rating on the Residential Gas Water Heaters Labeling

The formula and computations for the amount of hot water a gas water heater can produce are different based on the authority of the label. The American National Standards Institute (ANSI) regulates the rating plate and has their formula; the Department of Energy (DOE) regulates the yellow energy guide and has their formula; and the specification sheet Gallons Per Hour (GPH) recovery is an industry accepted mathematical formula that has been in use for years.

Effective with the ANSI Standard Z21.10.1a-2002; CSA 4.1-2001, all residential gas water heaters must have the recovery rating listed on the manufacturer's rating label. By ANSI definition, this recovery is listed in gallons per hour and is the result of the formula:

## Manufacturer's input rating in Btu per hour 1179 BTU/Gallon

To show how this works, lets use an example of a 42V40-40F. This is a 40,000 BTU input 40-gallon capacity water heater.

- 40-gallon tank
- 40.4 GPH recovery at 90 degree rise per the specification sheet and industry accepted formula
- 33.9 gallons recovery per ANSI formula on the rating plate
- 70 gallons first hour delivery per DOE on the yellow energy guide label

As you can see, there is a wide range of delivery capacities notes on the water heater's labeling.

Below is a table that will show you some normal BTU input results using the ANSI formula:

| Manufacturers<br>Input Rating in<br>BTU/hr | ANSI<br>Constant | ANSI Recovery<br>Rating | Manufacturers<br>Input Rating in<br>BTU/hr |
|--|------------------|-------------------------|--|
| 26000                                      | 1179             | 22.1                    | 52000                                      |
| 28000                                      | 1179             | 23.7                    | 54000                                      |
| 30000                                      | 1179             | 25.4                    | 56000                                      |
| 32000                                      | 1179             | 27.1                    | 58000                                      |
| 34000                                      | 1179             | 28.8                    | 60000                                      |
| 36000                                      | 1179             | 30.5                    | 62000                                      |
| 38000                                      | 1179             | 32.2                    | 64000                                      |
| 40000                                      | 1179             | 33.9                    | 66000                                      |
| 42000                                      | 1179             | 35.6                    | 68000                                      |
| 44000                                      | 1179             | 37.3                    | 70000                                      |
| 46000                                      | 1179             | 39.0                    | 72000                                      |
| 48000                                      | 1179             | 40.7                    | 74000                                      |
| 50000                                      | 1179             | 42.4                    |  |

| Manufacturers<br>Input Rating in<br>BTU/hr | ANSI<br>Constant | ANSI Recovery<br>Rating |
|--|------------------|-------------------------|
| 52000                                      | 1179             | 44.1                    |
| 54000                                      | 1179             | 45.8                    |
| 56000                                      | 1179             | 47.5                    |
| 58000                                      | 1179             | 49.2                    |
| 60000                                      | 1179             | 50.9                    |
| 62000                                      | 1179             | 52.6                    |
| 64000                                      | 1179             | 54.3                    |
| 66000                                      | 1179             | 56.0                    |
| 68000                                      | 1179             | 57.7                    |
| 70000                                      | 1179             | 59.4                    |
| 72000                                      | 1179             | 61.1                    |
| 74000                                      | 1179             | 62.8                    |

This recovery number may be different from the First Hour Deliver computation on the yellow Energy Guide Label attached to your water heater. The First Hour Deliver rating includes recovery, *PLUS* storage available and the units ability to reheat water while being consumed. Therefore, the First Hour Deliver number will be higher than on the manufacturer's rating plate.