



(Please note machine specifications may vary slightly depending on model / age / manufacturer)

Scissor Lifts



Model Number	LEO	GR-20	1930 /1932	2032	2630 / 2632	2646	3246	3268 DC	3369 LE	4047	260 MRT / 2668 RT	3268 RT	3369 RT	5390
Working Height	15ft / 4.9m	25.9ft / 8.02m	25ft / 7.62m	26.6ft / 8.10m	32ft / 9.92m	32.1ft / 9.80m	37.8ft / 11.5m	38ft / 11.75m	39.65ft / 12.06m	44.11ft / 13.70m	32ft / 9.92m	38ft / 11.75m	39ft / 11.9m	59ft / 18.15m
Platform Capacity	397lbs / 180kg	350lbs / 159kg	500lbs / 227kg	800lbs / 363kg	500lbs / 227kg	1000lbs / 454kg	700lbs / 318kg	1000lbs / 454kg	1000lbs / 454kg	770lbs / 350kg	1250lbs / 567kg	1000lbs / 454kg	1000lbs / 454kg	1500lbs / 680kg
Stowed Height	5.6ft / 1.69m	6.6ft / 1.98m	6.5ft / 1.98m	6.9ft / 2.03m	7.5ft / 2.26m	7.5ft / 2.26m	7.10ft / 2.39m	8.3ft / 2.45m	9ft / 2.74m	8.4ft / 2.54m	7.75ft / 2.32m	8.5ft / 2.45m	8.6ft / 2.45m	10.4ft / 3.15m
Stowed with Rails Folded	5.6ft / 1.69m	6.6ft / 1.98m	6.5ft / 1.98m	6.9ft / 2.03m	6.4ft / 1.94m	5.6ft / 1.68m	5.10-6.4ft / 1.80-1.94m	6ft / 1.83m	6.5ft / 1.94m	6.2ft / 1.88m	5.7ft / 1.70m	6ft / 1.83m	6.35ft / 1.92m	8.125ft / 2.47m
Overall Width	2.49ft / 0.76m	2.75ft / 0.8m	2.49 - 2.8ft / 0.76 - 0.81m	2.8ft / 0.81m	2.49 - 2.8ft / 0.76-0.81m	3.10ft / 1.17m	3.10ft / 1.17m	5.8ft / 1.73m	5.9ft / 1.75m	3.11ft / 1.19m	5.9ft / 1.75m	5.8ft / 1.73m	5.9ft / 1.75m	7.6ft / 2.29m
Power Source	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Diesel	Diesel	Diesel	Diesel
Non-Marking Tyres	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No	No

Boom Lifts



Model Number	STAR 10	TOUCAN 10E	300AJP	Z33/18	Z34/22	E400AJPN	N40E	E450AJ	450AJ	Z-45/25	460SJ	600AJ / Z60/34	660SJ / S65	800AJ / Z80/60	860SJ / S85
Working Height	32.10ft / 10m	33.1ft / 10.10m	36.6ft / 11.14m	39.4ft / 12m	40.6ft / 12.52m	46.6ft / 14.19m	46.6ft / 14.19m	51ft / 15.7m	51ft / 15.7m	51.10ft / 15.97m	52.5ft / 16m	66.7-66.4ft / 20.47-20.39m	72.8-71ft / 22.15-21.80m	86-84ft / 26.21-25.77m	92.6-91ft / 28.21-27.70m
Platform Capacity	441lbs / 200kg	441lbs / 200kg	507lbs / 230kg	441lbs / 200kg	500lbs / 227kg	500lbs / 227kg	500lbs / 227kg	507lbs / 230kg	500lbs / 227kg	500lbs / 227kg	500lbs / 227kg	500lbs / 227kg	500lbs / 227kg	500lbs / 227kg	500lbs / 227kg
Max Outreach	9.10 / 3m	10.1ft / 3.08m	20.6ft / 6.25m	18.3ft / 5.57m	22.3ft / 6.78m	22.5ft / 6.83m	20.6ft / 6.25m	24ft / 7.24m	25ft / 7.62m	24.7ft / 7.49m	41ft / 12.5m	36.3-39.9ft / 11.05-12.10m	56.9-56.2ft / 17.3-17.10m	51.8-60ft / 15.74-18.29m	70-76.6ft / 22.86-23.30m
Stowed Height	6.6ft / 1.99m	6.6ft / 1.99m	6.8ft / 2.01m	6.6ft / 1.98m	6.7ft / 2.0m	6.57ft / 1.97m	6.7ft / 2.0m	6.8ft / 2.01m	7.5ft / 2.27m	7ft / 2.13m	7.10ft / 2.39m	8.1-8.4ft / 2.54-2.69m	8.5-8.11ft / 2.57-2.72m	9.10ft / 3.00m	10-9.2ft / 3.05-2.80m
Stowed with Rails Folded	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Overall Width	3.3ft / 0.99m	3.3ft / 0.99m	4ft / 1.22m	4.11ft / 1.50m	5.8ft / 1.73m	4.11ft / 1.50m	4.11ft / 1.50m	6ft / 1.82m	6.10ft / 2.10m	7.6ft / 2.29m	7.7ft / 2.3m	8.2-8.1ft / 2.49-2.46m	8.2-7.11ft / 2.49-2.41m	8-8.2ft / 2.44-2.49m	8.2ft / 2.50m
Power Source	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Non-Marking Tyres	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No	No	No	No	No