

N type gas meter

Model: N□□□/NL□□□



Model	For city gas	N1	N1.6	N2.5	N4	N6	N10	N16	N25	N40	N65	N100	N120
	For petroleum gas	NL1	NL1.6	NL2.5	NL4	NL6	NL10	NL16	NL25	NL40	NL65	NL100	—
Measured fluid	City gas, LP gas, other inert gases												
Accuracy	±1.5% (0.05Qmax~0.1Qmax=±3%)												
Max. operating flow rate (m ³ /h)	1	1.6	2.5	4	6	10	16	25	40	65	100	120	
Max. operating pressure	3.5kPa												
Connecton screw (connection size)	M34×1.5 (20A)								M72 ×3 (50A)				M110×4 (80A)
	W36.3 山11.5 (20A)								W76.2 山11 (50A)				
	—	W36.9 山11 (20A)				M56 ×2 (32A)		M64 ×2 (40A)					
	W28.8 山12 (15A)		—						M64 ×2 (50A)		M72 ×2 (50A)		
Operating ambient temperature	-5°C~+60°C						-5°C~+40°C						
Quality	2.2kg	2.2kg	2.7kg	3.5kg	3.5kg	9kg	9kg	22kg	35kg	66kg	66kg	66kg	