

Gas Meter with Pulse Transmitter

Model: NDS-N□□□/NDS-NL□□□/DM-NL□□□

NDS-NNH□□ (for medium pressure) / NDS-NDHP□□ (for medium pressure)



Construction	3-wire no-voltage contact pulse, non-explosionproof	Maximum contact voltage	DC24V
Contact capacity	2.4W (Resistive load)	Minimum operating load	DC1.5V 5 μ A
Maximum contact current	DC0.1A	Contact withstand voltage	300V AC for 1 minute
Contact contact resistance	100m Ω or less (initial value)		

■ Pulse rate

Model	Maximum flow rate in use (m ³ /h)											
	1	1.6	2.5	4	6	10	16	25	40	65	100	120
NDS-N□□□	1	1.6	2.5	4	6	10	16	25	40	65	100	120
NDS-NL□□□	1	1.6	2.5	4	6	10	16	—	—	—	—	—
DM-NL□□□	—	—	—	—	—	—	—	25	40	65	100	—
NDS-NNH□□	—	2.5	—	—	6	10	16	—	—	—	—	—
NDS-NDHP□□	—	—	—	—	6	10	16	25	—	—	—	—
Standard (m ³ /P)	0.1				1				1			
Special Note (m ³ /P)	0.01				0.1				—			

* Pulse counter is optional.