

6002PS

PIPE SIZE 12" (300mm) (368.3mm) (495.3mm) (94.0mm) 15" 17.6' 23.00" 4.0" N/A 1502PS (375mm) (447.0mm) (584.2mm) (101.6mm) 18" 21.2" 26.50" 4.2" N/A 1802PS (538.5mm) (673.1mm) (450mm) (106.7mm) 24" 33.25" 4.5 27.8" N/A 2402PS (600mm) (706.1mm) (844.5mm) (114.3mm) 40.50" 30" 35.1" 5.2" N/A 3002PS (750mm) (891.5mm) (1028.7mm) (132.1mm) 36" 41.1" 47.00" 5.5" 41.1" 3602PS (1043.9mm) (1193.8mm) (1043.9mm) (139.7mm) (900mm) 42" 47.7" 48.0" 53.00" 5.7" 4202PS (1050mm) (1211.6mm) (1219.2mm) (1346.2mm) (144.8mm) 48" 53.6" 54.0" 59.00" 5.7" 4802PS (1200mm) (1361.4mm) (1371.6mm) (1498.6mm) (144.8mm)

NOTES

PERFORMANCE HIGHLY DEPENDENT ON INSTALLATION. CONTRACTOR MUST ENSURE MANHOLE GASKET IS UNIFORMLY SEATED AROUND STRUCTURE ADAPTER. EXTRA PRECAUTIONS MUST BE TAKEN TO PREVENT DIFFERENTIAL SETTLEMENT BETWEEN THE PIPE AND MANHOLE.

SEE STANDARD DETAIL STD-201 AND INSTALLATION GUIDE 1.05: WATERSTOP INSTALLATION FOR INSTALLATION RECOMMENDATIONS.

© 2016 ADS, INC

60"

(1500mm)

66.3"

(1684.0mm)

67.3"

(1709.4mm)

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

72.00"

(1828.8mm)

6.4"

(162.6mm)

3	ADDED METRIC UNITS	TJR	01/30/16		
REV.	DESCRIPTION	BY	MM/DD/YY	CHK'D	

12"-60" HDPE GROUTED
WATERSTOP MH CONNECTION

DRAWING NUMBER: STD-203



DRAIN BY CKS

DAYE 10/10/06

OCT BY NTS

BHEET 1 OF 1