

**SEALS
LEAKS**
Asphalt Can't

ROOFS • GUTTERS • VENTS • FLASHINGS • LIGHTS

sticks to
WET
surfaces

SEALS EVERYTHING THAT GOES
Through the ROOF!
Seals Leaks Asphalt Can't



WARNING: FLAMMABLE
IRRITANT. VAPOR HARMFUL.
Read Cautions On Back Panel

ADVERTENCIA: INFLAMABLE
IRRITA. VAPOR NOCIVO.
Lea Las Precauciones En El Panel Posterior

10.5 FL. OZ. (310ml)

SEALS EVERYTHING THAT GOES

Through the ROOF!

Seals Leaks Asphalt Can't

SEALS LEAKS *Asphalt Can't*

When there's a nagging roof leak that others can't fix, or when you don't want to take your chances, use **Through the Roof!** Its unique co-polymer rubber formula creates a permanent, invisible seal, even when applied in the middle of a rain storm. (It works great on dry surfaces, too). Through the Roof! will stick to almost any roofing surface - metal, plastic, asphalt, wood, concrete, and more. Plus, it won't freeze. So go ahead and fix that gutter in a Minnesota winter. You might get some concerned stares from your neighbors, but they'll be grateful the next time you host the neighborhood party and their heads stay dry.



Features & Benefits

- ✓ Superior bond durability
- ✓ Humidity & rain proof
- ✓ All-weather formula
- ✓ Sticks to wet surfaces
- ✓ Excellent UV resistance
- ✓ Brush-on formula (available in Qt. or Gallon sizes)
- ✓ Crystal Clear * 19 times clearer than silicone
- ✓ Gunnable down to 0°F
- ✓ Sticks to difficult surfaces
- ✓ Super Elastic - 600% maximum stretch
- ✓ Permanently flexible
- ✓ Strong tear resistance
- ✓ Dripless plunger
- ✓ Freeze-thaw stable in package
- ✓ Full 10.5oz in every cartridge
- ✓ Does not support mold and mildew growth
- ✓ Paintable

Application Basics

Dry Time

Full cure:

1 week (depending on temperature and humidity)

Paintable:

1-2 days with water-based paint

3-4 weeks with oil-based paint



Clean up / Removal

Tools: Mineral spirits or paint thinner

Hands: Citrus-based cleaners

Application Range

0° to 120°F
(-18° to 49°C)

Service Range

-25° to 180°F
(-32° to 82°C)



| Description | Item # |
|----------------------|--------|
| 10.5 OZ. Black | 14060 |
| 10.5 OZ. Black - VOC | 14065 |
| 10.5 OZ. White | 14030 |
| 10.5 OZ. White - VOC | 14035 |
| 10.5 OZ. Clear | 14010 |

| Description | Item # |
|---------------------------|--------|
| Cobra 6-Pack | 14026 |
| 1 Quart Clear | 14003 |
| 1 Quart can Clear - VOC | 14023 |
| 1 Gallon pail Clear | 14004 |
| 1 Gallon pail Clear - VOC | 14024 |



COBRA™
Lap Joint Nozzle
Fast & Deadly Accurate




Lap Joints Made Easy

You need a flat caulk bead, you have a round nozzle. How does that make sense? That's what we thought. We bring you the right tool, the Cobra Nozzle™. It extrudes a wide bead to easily cover all kinds of lap joints, like roof flashing and window fins, and sandwich joints like thresholds. It comes with a 6-pack of Through the Roof® clear sealant, well-known for fixing and preventing leaks. Together they help you do your best work. Your customers will think so too.

Alyster Plunger

10.5 oz. cartridges feature Sashco's unique Alyster plunger. A flexible telescopic diaphragm not only stops material flow, it actually pulls material back into the nozzle!

- **Tight Seal** - Increases shelf life and minimizes leakage.
- **Stop Flow** - The flexible telescopic diaphragm assures that material flow will stop when caulk gun pressure is released.



Where to Use

For repairs that stick, but won't stick out, use Through the Roof! on common roofing fixtures, including:

Metal

- Roofs
- Vents
- Gutters
- Flashing
- Aluminum
- Brass
- Copper
- Galvanized Steel
- Powder-coated metals
- Steel

Other Roof Surfaces

- Acrylic & Polycarbonate Skylights

- Brick
- Asphalt
- Ceramic tile
- Concrete
- Glass
- Mortar
- Polyisobutylene

Other Surfaces

- Stone
- Stucco
- Terra Cotta
- Tile
- Vinyl
- Wood

Where to NOT Use

Adhesion is poor on the following substrates. A test patch is recommended:

- Aquaseal®*
- Cultured marble
- Kynar®*
- Teflon coatings
- Polypropylene
- Polyethylene
- Silicone
- Waxes
- TPO

Through the Roof! has excellent adhesion on these surfaces, but it can wrinkle them. A test patch is recommended:

- EPDM
- Vulcanized rubber

Through the Roof! dissolves foam insulation. Do not use on:

- Polystyrene foam insulation

**Aquaseal® and Kynar® are registered trademarks of their respective owners.*

| PROPERTY | VALUE |
|--------------------|--|
| Colors | Clear (All Sizes); Black, White 10.5 OZ. only |
| Packaging | 10.5 OZ. plastic cartridge, 1 quart and 1 gallon containers |
| Paintability | With latex paint/stain in 1-2 days or oil-based paint/stain after 3-4 weeks |
| Joint Size | Cartridge – up to 2" wide; Brush grade - N/A |
| Clarity (NTU) | < 15 |
| Application Range | 0° to 120°F (-18° to 49°C) surface temp. |
| Service Range | -25° to 180°F (-32° to 82°C) |
| Tensile Properties | Cartridge – Recovery at 50% stretch: 96% in 1 minute at 100% stretch: 96% in 1 minute Brush – Recovery at 50% stretch: 100% in 3 minutes at 100% stretch: 96% in 5 minutes |
| VOC | Sashco has VOC compliant Through the Roof products for each region of the country. Exception: 10.5 OZ cartridges of Through the Roof colors are not available in California Contact Customer Service with questions. |
| Shelf Life | 5 years |

TEST DATA:

| PROPERTY | RESULTS | TEST METHOD |
|-------------------------------------|--|-------------|
| Hardness, Shore A (21-day cure) | Cartridge - 35 Brush - 33 | ASTM C661 |
| Slump | Cartridge - < 1/8" Brush - slumps | ASTM D2202 |
| Solids | Cartridge: 57.8% by wt. Brush: 36.0% by wt. Brush lower VOC: 45.4% by wt. Cartridge lower VOC: 53.1% by wt. | ASTM C1250 |
| Extrusion Rate | Cartridge - 80 g/min (1/8" orifice at 40 psi) Brush grade - N/A | ASTM C603 |
| Cured | 1 week (dependent on temperature, humidity and bead size/thickness) | ASTM C679 |
| Tack-free | 30 minutes | ASTM C679 |
| Low Temp. Flexibility | Pass | ASTM C734 |
| Freeze-Thaw Stable | Won't freeze | ASTM C731 |
| Adhesion-in-peel Passing Substrates | See "ADHERES TO" section | ASTM C794 |

SPECIFICATIONS:

- Meets FHA requirements.

The data reported here are believed to be reliable. No warranty is made concerning their accuracy or the results obtained from their use.

800-767-5656
sashco.com

Keep up with Sashcoinc on:

TRFBROCH

