

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Diesel Exhaust Fluid
Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cleaning of waste gases

1.3. Details of the supplier of the safety data sheet

DEF CHEM INC., (AZURE DEF)
301 East Alton Ave.
Santa Ana, CA. 92707 USA
Tel: 949-390-0724

Contact: Iraj (AJ) Vatankhah
Email: iraj@azuredef.com
www.azuredef.com

1.4. Emergency telephone number

Emergency number : Domestic North America: 949-390-0724

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 3 H335

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS-US) :

P261 - Avoid breathing vapours
P264 - Wash hands, forearms and face thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, protective clothing, protective gloves
P302+P352 - If on skin: Wash with plenty of soap and water
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a doctor, a POISON CENTER if you feel unwell
P321 - Specific treatment (see first aid instructions on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

Diesel Exhaust Fluid

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Urea	(CAS No) 57-13-6	15 - 40
Urea, N,N-methylenebis-	(CAS No) 13547-17-6	<= 1
Imidodicarbonic diamide	(CAS No) 108-19-0	<= 1
Alkalinity, as Ammonia		<= 0.1

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.
- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : May cause gastrointestinal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Carbon dioxide. Dry powder.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : The product is not flammable.
- Explosion hazard : Product is not explosive.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Precautionary measures fire : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

Diesel Exhaust Fluid

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Sweep or shovel spills into appropriate container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Avoid breathing vapours, mist. Use personal protective equipment as required. Ensure good ventilation of the work station. If process is performed that may cause airborne particles, appropriate respiratory protection should be used to avoid breathing any dust or vapors. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage conditions : Store in a dry, cool and well-ventilated place. Keep container tightly closed. Keep only in original container. Containers which are opened should be properly resealed and kept upright to prevent leakage. Do not store in unlabeled containers.
- Storage temperature : -5 - 30 °C (23 - 86 °F)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Urea (57-13-6)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Urea, N,N-methylenebis- (13547-17-6)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Imidodicarbonic diamide (108-19-0)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

8.2. Exposure controls

- Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

- Personal protective equipment : Gloves. Protective goggles. Protective clothing.



- Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Change contaminated gloves immediately. Suitable gloves for this specific application can be recommended by the glove supplier.

- Eye protection : Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

- Skin and body protection : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

- Respiratory protection : Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear, colorless liquid.

Diesel Exhaust Fluid

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color	: Colorless. Yellow.
Odor	: Characteristic.
Odor Threshold	: No data available
pH	: 10 [Conc. (% w/w): 10%]
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: -11 °C (12.2 °F)
Boiling point	: 103 °C (217.4 °F)
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 0.4 mm Hg @ 20 °C (68 °F)
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.087 - 1.093 g/cm ³ @ 20 °C (68 °F)
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 0.14 mPa.s (0.14 cP)
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid contact with : Incompatible materials.

10.5. Incompatible materials

Oxidizing agent. Nitrites.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon oxides (CO, CO₂). Nitrogen oxides. Ammonia.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Urea (57-13-6)	
LD50 oral rat	8471 mg/kg

Skin corrosion/irritation	: Causes skin irritation. pH: 10 [Conc. (% w/w): 10%]
Serious eye damage/irritation	: Causes serious eye irritation. pH: 10 [Conc. (% w/w): 10%]
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.

Diesel Exhaust Fluid

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May cause gastrointestinal irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No information available.

12.2. Persistence and degradability

Diesel Exhaust Fluid

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

Diesel Exhaust Fluid

Bioaccumulative potential	No information available.
---------------------------	---------------------------

12.4. Mobility in soil

Diesel Exhaust Fluid

Ecology - soil	No information available.
----------------	---------------------------

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

14.1 In accordance with DOT Not regulated for transport

14.2 In accordance with IMDG Not regulated for transport

14.3 In accordance with IATA Not regulated for transport

SECTION 15: Regulatory information

15.1. US Federal regulations

Diesel Exhaust Fluid

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory
All the constituents of this preparation are registered in the EINECS inventory or in the ELINCS list

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

15.2. International regulations

No additional information available.

15.3. US State regulations

California Proposition 65

This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm.

SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created.


Diesel Exhaust Fluid

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 07/20/2018
Other information

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard : 0 - Materials that will not burn.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 1
Flammability : 0
Physical : 0
Personal Protection :

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.