



FLOAT VALVES

KERAFLO AYLESBURY DELAYED ACTION FLOAT VALVES

Types K & KAX controls water storage level differentials of 75mm Standard or high flow rates / Further details refer to data sheet



Size	3/4"	1.0"	1.1/4"	1.1/2"	2.0"	3.0"
------	------	------	--------	--------	------	------

KERAFLO AYLESBURY DELAYED ACTION FLOAT VALVES

Types KB & KP accommodate water storage level differentials are adjustable up to 1820 mm Standard or high flow rates / Further details refer to data sheet



Size	3/4"	1.0"	1.1/4"	1.1/2"	2.0"	3.0"
------	------	------	--------	--------	------	------

EQUILIBRIUM FLOAT VALVE

Only copper floats recommended / Male BSP Rated 5 Bar (max) / WRAS approved



Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"	2.1/2"	3.0"	4.0"
Float	1/2	6.0	8.0	8.0	10.0	12.0	14.0	15.0	16.0
Thread	5/16	5/16	7/16	7/16	9/16	5/8	3/4	3/4	3/4

SIDE ENTRY BRASS FLOAT VALVE

BS 1212 part 1 : HP & LP / Male BSP Varying length tails



Body	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"
Floats	4.1/2	6.0	8.0	10.0	10.0	12.0

BRASS FLOAT VALVE

BS 1212 part 2 : HP & LP / Male BSP x 1.1/4" to 3.0" tail Side entry with 8.3/4" x 3.1/2" bent arms Floats 1/2" = 4.1/2" / 3/4" = 6.0"



Body	1/2"	3/4"				
Floats	4.1/2	6.0				

FLUIDMASTER FLOAT VALVE DF400UK

Pro series Fluidmaster PRO400UK Float Valve Bottom inlet adjustable height 225mm - 355mm 1/2" Plastic Tail



Size	1/2"					
------	------	--	--	--	--	--



BALL FLOATS

BALLFLOAT QUALIFLOAT D45PTOR-Q

Qualifloat / 5/16" Plastic Thread / 4.1/2" (114mm) Diameter For use in hot or cold water to BS2456



Size	4.1/2"				
------	--------	--	--	--	--

BALLFLOAT PLASTIC FLOAT D50BTOR

Plastic Float / 5/16" Brass Thread (Bagged in 75's) 4.1/2" (114mm) / 5" (127mm) / 6" (153mm) Diameter



Size	4.1/2"	5.0"	6.0"		
------	--------	------	------	--	--

BALLFLOAT ELONGATED FLOAT D45PTOR-EL

Elongated Float / 5/16" Brass Thread / 4.1/2" (114mm) Diameter



Size	4.1/2"				
------	--------	--	--	--	--

BALLFLOAT PLASTIC FLOAT D910BTOR

Plastic Float / 7/16" / 9/16" / 5/8" Brass Thread 8" (203mm) / 10" (254mm) / 12" (305mm) Diameter



Size	8.0"	10.0"	12.0"		
------	------	-------	-------	--	--

COPPER BALLFLOAT

Copper Float / BS1968 / BSW Stud Soldered - Cold water only



Float "	4.1/2	5.0	6.0	7.0	8.0	10.0	12.0	14.0	15.0
Stud "	5/16	5/16	5/16	5/16	7/16	9/16	5/8	3/4	3/4



C. A. BALDWIN & CO LTD

VALVE GUIDE

- GATE VALVES
- BUTTERFLY VALVES
- NON RETURN VALVES
- FLOAT VALVES
- BALL FLOATS
- RADIATOR VALVES
- SAFETY VALVES
- PRESSURE REDUCING VALVES
- BALL VALVES
- STOPCOCKS

QUALITY IS OUR STRENGTH

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com



NON RETURN VALVES

SINGLE / DOUBLE CHECK

FLOGUARD DZR SINGLE CHECK VALVE

Threaded. WRAS.



Size	3/4"	1.0"	1.1/4"	1.1/2"	2.0"				
------	------	------	--------	--------	------	--	--	--	--

DOUBLE DZR CHECK VALVE

Compression



Size	15mm	22mm	28mm						
------	------	------	------	--	--	--	--	--	--

FLOGUARD DZR DOUBLE CHECK VALVE

Threaded



Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"			
------	------	------	------	--------	--------	------	--	--	--

SINGLE CHECK VALVE

Compression



Size	15mm	22mm	28mm						
------	------	------	------	--	--	--	--	--	--

SWING GATE

ART 384 BSPT BRONZE NON RETURN VALVE

PN20 / Bronze Disc / Temperature -10 -180 Deg C



Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"			
------	------	------	------	--------	--------	------	--	--	--



NON RETURN VALVES

SWING GATE

HERZ HV515306 NON RETURN VALVE EN1092-2

Swing Gate / PN16



Size	2.0"	2.1/2"	3.0"	4.0"	5.0"	6.0"	8.0"	12.0"	
------	------	--------	------	------	------	------	------	-------	--

ART 170 CAST IRON NON RETURN VALVE

Flanged / PN16 / Temperature -10 - 230 Deg C
Bronze Trim



Size	2.0"	2.1/2"	3.0"	4.0"	5.0"	6.0"	8.0"	12.0"	
------	------	--------	------	------	------	------	------	-------	--

ART84M / 84R BRASS NRV METAL DISC

Metal Disc / PN16 / Temperature 0 -100 Deg C
Rubber Disc / PN16 Temperature 0 - 100 Deg C



Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"	2.1/2"	3.0"	4.0"
------	------	------	------	--------	--------	------	--------	------	------

SPRING LOADED

CIM 30 / 32 SPRING NON RETURN VALVE

Spring Operated
CIM 30 - Female x Female / CIM 32 - Male x Female



CIM 30	3/8"	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"	2.1/2"	3.0"
CIM 32	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"			

ART 66 BRASS SPRING NON RETURN VALVE

Spring Operated.
PN20 / 0 -100 Deg C.



Size	3/8"	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"	2.1/2"	3.0"	4.0"
------	------	------	------	------	--------	--------	------	--------	------	------



NON RETURN VALVES

WAFER

ART962 SS DUAL PLATE WAFER NON RETURN VALVE

PN16 / Wafer
EPDM Seat



Size	2.0"	2.1/2"	3.0"	4.0"	5.0"	6.0"			
------	------	--------	------	------	------	------	--	--	--

HERZ HVWC25-07 WAFER CHECK VALVE

PN16 / Dual Plate.



Size	2.1/2"	3.0"	4.0"	5.0"	6.0"	8.0"	12.0"		
------	--------	------	------	------	------	------	-------	--	--

ART 121 DUAL PLATE WAFER NON RETURN VALVE

PN16 / Wafer
EPDM Seat



Size	2.0"	2.1/2"	3.0"	4.0"	5.0"	6.0"			
------	------	--------	------	------	------	------	--	--	--

BRONZE / STAINLESS STEEL

SOCLA 418 CI BALL CHECK VALVE

Ball Flanged / PN16



Size	2.0"	2.1/2"	3.0"	4.0"					
------	------	--------	------	------	--	--	--	--	--

ART 380 BSPT BRONZE LIFT CHECK VALVE

PN20 / Bronze Disc / Temperature -10 - 180 Deg.C



Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"			
------	------	------	------	--------	--------	------	--	--	--

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com



GATE VALVE

COMPRESSION

PEGLER M63 BRASS COMPRESSION GATE VALVE

Wheelhead / Copper x Copper Compression



NB	15	22	28	35	42	54
BODY	72	81	90	107	113	129

PEGLER M63GM GUNMETAL COMPRESSION GATE VALVE

Wheelhead / Copper x Copper Compression



NB	15	22	28			
BODY	72	81	90			

PEGLER M63LS BRASS COMPRESSION LOCKSHIELD GATE VALVE

Lockshield / Copper x Copper Compression



NB	15	22	28			
BODY	72	81	90			

HERZ 5154 BRASS COMPRESSION GATE VALVE

Wheelhead / Copper x Copper. 16bar at -10 to 110 Deg. C / WRAS.



NB	15	22	28			
BODY	N/A	N/A	N/A			

HERZ 5154LS BRASS COMPRESSION GATE VALVE

Lockshield key. Copper x Copper. 16bar at -10 to 110 deg C. WRAS.



NB	15	22	28	35	42	
BODY	N/A	N/A	N/A	N/A	N/A	

ART 615 BRASS COMPRESSION GATE VALVE

Wheelhead / Copper x Copper. BS5154 16bar at -10 to 110 deg C.



NB	15	22	28	35	42	
BODY	N/A	N/A	N/A	N/A	N/A	



GATE VALVE

THREADED

LAMONITE BRASS COMPRESSION GATE VALVE

Wheelhead / Copper x Copper Compression Olive retained by bolted end



NB	67	76	108			
BODY	160	183	N/A			

ART 175 BRASS GATE VALVE

Wheelhead / Female BSP taper thread. BS5154. 25bar at -10 to 188 deg C.



NB	15	22	28	15	22	28
BODY	72	81	90	72	81	90

ART 610 BRASS GATE VALVE

Wheelhead / Female BSP taper thread. BS5154. 20bar at -10 to 180 deg C.



NB	15	22	28			
BODY	72	81	90			

CRANE D159/235 BRONZE GATE VALVE

Wheelhead & Lockshield / Kitemarked Female BSP ISO7-1 / WRAS (85 Deg.c) Rated PN32 / Temperature -10 - 100 Deg.C



NB	8	10	15	20	25	32	40	50	65	80
BODY	46	46	53	57	65	72	77	82	105	111

HATTERSLEY 33X/33LS BRONZE GATE VALVE

Wheelhead & Lockshield / Kitemarked Female BSP ISO7-1 / WRAS (85 Deg.c) Rated PN20 / Temperature -10 - 100 Deg.C



NB	8	10	15	20	25	32	40	50		
BODY	43	43	52	56	65	73	76	90		

CRANE D151A DZR GATE VALVE

Wheelhead / Female BSP taper thread. 20bar at -10 to 100 deg C / WRAS



NB	15	20	25	32	40	50
BODY	50	54	62	70	72	88



GATE VALVE

BRONZE THREADED

HERZ HV5520 BRONZE GATE VALVE

Wheelhead / Female BSP taper threads / BS5154. 20bar at -10 to 100 deg C. Max 9bar at 180 deg C / WRAS



NB	15	22	28			
BODY	N/A	N/A	N/A			

HERZ HV5520LS BRONZE GATE VALVE

Lockshield 20bar at -10 to 100 deg C. Max 9bar at 180 deg C / WRAS



NB	15	22	28	35	42	
BODY	N/A	N/A	N/A	N/A	N/A	

CRANE D151 PN20 BRONZE GATE VALVE

Wheelhead / Female BSP taper threads. ISO7. 20bar at 0 - 100 deg C. BS5154. Kitemarked.



NB	15	22	28	35	42	
BODY	N/A	N/A	N/A	N/A	N/A	

CRANE D151 BRONZE GATE VALVE

Wheelhead / Kitemarked Female BSP ISO7-1 / WRAS (85 Deg.c) Rated PN20 / Temperature -10 - 100 Deg.C



NB	8	10	15	20	25	32	40	50	65
BODY	43	43	50	52	61	70	72	79	96

CRANE 237 BRONZE GATE VALVE

Lockshield / Kitemarked Female BSP ISO7-1 / WRAS (85 Deg.c) Rated PN20 / Temperature -10 - 100 Deg.C



NB	8	10	15	20	25	32	40	50	65
BODY	43	43	50	52	61	70	72	79	96

ART 375 PN20 BRONZE GATE VALVE

Wheelhead / Female BSP taper threads. ISO7. 32bar at 0 - 100 deg C. BS5154. Kitemarked.



NB	15	20	25	32	40	50			
BODY	48	53	59	62	67	74			

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com



GATE VALVE

FLANGED EN 1092-2 :PN6

HATTERSLEY 549 CAST IRON GATE VALVE

Cast Iron / BS 5150
Flanged EN109-2 PN6
Rated 6 Bar / Temperature 0-120 Deg.C



NB	50	65	80	100	125	150	200	250	300
BODY	150	170	180	190	200	210	230	250	270

CRANE FM52 CAST IRON GATE VALVE

Cast Iron / BS 5150
Flanged EN109-2 PN6
Rated 6 Bar / Temperature 0-120 Deg.C



NB	50	65	80	100	125	150	200	250	300
BODY	150	170	180	190	200	210	230	250	270

FLANGED EN 1092-2 :PN6

HERZ HV5150 CAST IRON GATE VALVE

Cast Iron / BS 5150
Flanged EN109-2 PN16
Rated 16 Bar / Temperature -10-180 Deg.C



NB	50	65	80	100	125	150	200	250	300
BODY	178	190	203	229	254	267	292	330	398

ART 105 CAST IRON GATE VALVE

Cast Iron / BSEN 1171 / Stainless Steel Stem / Bronze Trim
Flanged EN109-2 PN16
Rated 16 Bar / Temperature -10-120 Deg.C



NB	50	65	80	100	125	150	200	250	300
BODY	150	170	180	190	200	210	230	250	270

ART 235 CAST IRON GATE VALVE

Cast Iron / BS 5150 / Stainless Steel Stem / Bronze Trim
Flanged EN109-2 PN16
Rated 16 Bar / Temperature -10-230 Deg.C



NB	50	65	80	100	125	150	200	250	300
BODY	150	170	180	190	200	210	230	250	270



GATE VALVE

FLANGED EN 1092-2 :PN16

HATTERSLEY 541 CAST IRON GATE VALVE

Cast Iron / BS 5150
Flanged EN109-2 PN16
Rated 16 Bar / Temperature 0 -120 Deg.C



NB	50	65	80	100	125	150	200	250	300
BODY	178	190	203	229	254	267	292	330	396

CRANE FM63 PN16 CAST IRON GATE VALVE

Cast Iron / BS 5150
Flanged EN109-2 PN16
Rated 16 Bar / Temperature 0 -120 Deg.C



NB	50	65	80	100	125	150	200	250	300
BODY	178	190	203	229	254	267	292	330	396

FLANGED BS10:Table: D/E D/E:PN16

ART 210 CAST IRON GATE VALVE

Wheelhead / Flanged BS10: Table D/E.
10bar at -10 -180.deg C. BS 3564.



NB	50	65	80	100D	100E	125	150	200	250
BODY	178	190	203	229		190	210	241	273

For detailed information and specifications
please telephone:
020 7703 2138

or email:
sales@cabaldwin.com

don't forget to view our website
www.cabaldwin.com



BUTTERFLY VALVE

SEMI & FULLY LUGGED

HERZ HV-BF-SLL SEMI LUGGED LEVER BUTTERFLY VALVE

Cast Iron Body / SS disc & Shaft / EPDM Seat / Lever Operated
Suit PN10/16 & ANSI 150 Flanges
Rated PN16 / Temperature -10 - 120 Deg.C / WRAS



NB	50	65	80	100	125	150
BODY	43	46	46	52	56	56

HERZ HV-BF-SLG PN16 SEMI LUGGED GEARED BUTTERFLY VALVE

Cast Iron Body / SS disc & Shaft / EPDM Seat / Gear Operated
Suit PN10/16 & ANSI 150 Flanges
Rated PN16 / Temperature -10 - 120 Deg.C / WRAS



NB	50	65	80	100	125	150
BODY	43	46	46	52	56	56

ART 115 SEMI LUGGED LEVER BUTTERFLY VALVE

Cast Iron Body / SS disc & Shaft / EPDM Seat / Gear Operated
Suit PN10/16 & ANSI 150 Flanges
Rated PN16 / Temperature -10 - 120 Deg.C / WRAS



NB	50	65	80	100	125	150
BODY	43	46	46	52	56	56

ART 135 PN16 LUGGED AND TAPPED BUTTERFLY VALVE

Lever operated. PN16 drilling. ISO 5211 mount.
16 bar at -20 to 110 deg C. WRAS
Disc and Shaft. Stainless Steel. Seat EPDM. Ductile Iron body.



NB	50	65	80	100	125	150	200	250	300
BODY	41.4	44	44.6	51.4	53.8	55.1	69.5	65	75.9

HERZ HV-BF-FLL PN16 LUGGED AND TAPPED BUTTERFLY VALVE

Cast Iron Body / SS disc & Shaft / EPDM Seat / Lever Operated
Fully lugged
Rated PN16 / Temperature -10 - 120 Deg.C / WRAS



NB	50	65	80	100	125	150
BODY	43	46	46	52	56	56

HERZ HV-BF-FLG PN16 LUGGED AND TAPPED BUTTERFLY VALVE

Cast Iron Body / SS disc & Shaft / EPDM Seat / Gear Operated
Fully lugged
Rated PN16 / Temperature -10 - 120 Deg.C / WRAS



NB	50	65	80	100	125	150	200	250	300
BODY	43	46	46	52	56	56	60	68	78

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com



RADIATOR VALVES

MANUAL

TERRIER 367 ANGLE RADIATOR VALVE

Wheelhead and Lockshield / Brass or Chrome
Compression body with BSP spigot tail



Size	15mm					
	1/2"					

TERRIER 368 STRAIGHT RADIATOR VALVE

Wheelhead and Lockshield / Chrome
Compression body with BSP spigot tail



Size	15mm	N/A				
	1/2"	1/2"				

BELMONT 97 ANGLE RADIATOR VALVE

Wheelhead and Lockshield / Brass or Chrome
For steel or copper tube



Size	15mm	22mm				
	1/2"	3/4"				

BELMONT 98 STRAIGHT RADIATOR VALVE

Wheelhead and Lockshield / Brass or Chrome
For steel or copper tube



Size	15mm	22mm				
	1/2"	3/4"				

HERZ RL1 LOCKSHIELD RADIATOR VALVE

Two pipe or lockshield / Brushed nickle
Spindle is capped to avoid misuse.
Rated at 10 Bar / Temperature 110.Deg.C Max



Size	1/2"	3/4"				
------	------	------	--	--	--	--

HERZ GP5524 STRAIGHT / ANGLE RADIATOR VALVE

Wheelhead and Lockshield / Brushed nickle
Commercial & Industrial range of radiator Wheelhead Valves
Rated at 10 Bar / Temperature 110.Deg.C Max



Size	3/8"	1/2"	3/4"			
------	------	------	------	--	--	--



RADIATOR VALVES

MANUAL PRE-SETTABLE

HERZ DR-T-90 STRAIGHT / ANGLE RADIATOR VALVE

Wheelhead / Brushed nickle
BSP inlet with male union outlet
Rated at 10 Bar / Temperature 110.Deg.C Max



Size	3/8"	1/2"	3/4"	1.0"	1.1/4"	
------	------	------	------	------	--------	--

HERZ DR-T-90 STRAIGHT / ANGLE RADIATOR VALVE

Lockshield / Brushed nickle
BSP inlet with male union outlet
Rated at 10 Bar / Temperature 110.Deg.C Max



Size	3/8"	1/2"	3/4"	1.0"	1.1/4"	
------	------	------	------	------	--------	--

HERZ RL5 PRESETTABLE STRAIGHT RADIATOR VALVE

Two pipe or lockshield / Brushed nickle
Valve is capped to void misuse.
Rated at 10 Bar / Temperature 110 Deg.C (max)



Size	3/8"	1/2"	3/4"	1.0"		
------	------	------	------	------	--	--

THERMOSTATIC & MANUAL SINGLE PIPE / GRAVITY

HERZ TS-E ANGLE / STRAIGHT / REVERSE RADIATOR VALVE

Single pipe / Brushed Nickle
Thermostatic or Manual Operation / Female BSP
Rated at 10 Bar / Temperature: 110 Deg.C (max)



Size	3/8"	1/2"	3/4"			
------	------	------	------	--	--	--

HERZ RL-1-E ANGLE / STRAIGHT RADIATOR VALVE

Single pipe / Brushed Nickle
Presettable Lockshield / Female BSP
Rated at 10 Bar / Temperature: 110 Deg.C (max)



Size	3/8"	1/2"	3/4"	1.0"		
------	------	------	------	------	--	--



RADIATOR VALVES

THERMOSTATIC

HERZ TS-90 ANGLE / STRAIGHT THERMOSTATIC RADIATOR VALVE BODIES

Thermostatic / Brushed Nickle
Corner bodies adaptable to series of sensor heads / Female BSP
Rated at 10 Bar / Temperature: 110 Deg.C (max)



Size	3/8"	1/2"	3/4"			
------	------	------	------	--	--	--

THERMOSTATIC VALVE SENSORS

CLASSIC / QUATTRO / HIGH LIFT THERMOSTATIC SENSOR

Classic	Quattro	High Lift (Single Pipe)
6 - 28 Deg. C	0 - 28 Deg. C	8 - 25 Deg. C



HERZCULES VANDAL RESISTANT SENSOR

To prevent unauthorised interference
8 - 26 Deg. C

Turndown	4 Deg	10 Deg			
----------	-------	--------	--	--	--



DESIGN REMOTE CONTROL

Wall mounted and fully adjustable
6 - 28 Deg. C

Capillary	2m	5m	8m	10m	
-----------	----	----	----	-----	--



DESIGN REMOTE SENSING PHIAL

Mainly used for
0 - 30 Deg. C

Capillary	2m	5m	8m	10m	
-----------	----	----	----	-----	--



C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com



SAFETY VALVES

HOT WATER SYSTEMS / STEAM / AIR

GOETZE 642 BSP LEVER SAFETY VALVE SET PTFE/EPDM

Calibrated with certificate / Gunmetal Body
Suitable for all non inflammable gases / liquids & all HVAC applications
Range 0.5 - 16 Bar / Female BSP

Size	1/2"	3/4"	1.0"	1.1/4"	2.0"	2.1/2"
------	------	------	------	--------	------	--------



GOETZE 645 BSP HIGH LIFT SAFETY VALVE PTFE/EPDM

Calibrated with certificate / Gunmetal Body
Suitable for all non inflammable gases / liquids & all HVAC applications
Range 0.5 - 16 Bar / WRAS / Female BSP

Male	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"
Female	3/4"	1.0"	1.1/4"	1.1/2"	2.0"	2.1/2"



NABIC 500 HIGH LIFT SAFETY VALVE PTFE/EPDM SEAT

Factory calibration / Bronze Body / Certificate with order
Suitable for all non inflammable gases / liquids & all HVAC applications
Range 0.3 - 10.5 Bar / WRAS / Female BSP / High Capacity Discharge

Size	15	20	25	32	40	50
------	----	----	----	----	----	----



NABIC 542 PRESSURE RELIEF VALVE PTFE/EPDM SEAT

Factory calibration / Bronze Body / Certificate with order
Suitable for all non inflammable gases / liquids & all HVAC applications
Range 0.3 - 10.5 Bar / WRAS / Female BSP

Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"
------	------	------	------	--------	--------	------



NABIC 500T THERMAL PRESSURE RELIEF VALVE

Factory calibration / Gunmetal Body / Certificate with order
Unvented hot water applications / Operating temperature 95 Deg.C
Range 0.3 - 1.5 Bar / Male / Female BSP

Body	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"
Tappings	25	45	65	105	165	255



ALTECH 311 PRESSURE RELIEF VALVE BSP

Factory sealed set at 3.0 Bar / Female BSP
Set pressure relief valves for domestic water heaters & boilers
Settings 2.5, 6, 7 & 8 Bar / No gauge point / WRAS

Size	1/2"	3/4"				
------	------	------	--	--	--	--



SAFETY VALVES

HOT WATER SYSTEMS / STEAM / AIR

WATTS MSV PRESSURE RELIEF VALVE BSP

Factory sealed set at 3.0 Bar / Female BSP
Set pressure relief valves for domestic water heaters & boilers
Temperature 0 - 110 Deg.C / No gauge point

Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"
------	------	------	------	--------	--------	------



GOETZE 810 DISCHARGE SAFETY VALVE

Brass Safety Valve / Male BSP
Suitable for all pneumatic & non toxic gases
Range 0.2 - 50 Bar / Temperature -60 - 225 Deg.C

Size	1/4"	1/2"	1.0"			
------	------	------	------	--	--	--



GOETZE 812 DISCHARGE SAFETY VALVE

Brass atmospheric discharge / Male BSP
Suitable for all pneumatic & non toxic gases
Range 0.2 - 45 Bar / Temperature -60 - 225 Deg.C

Size	1/2"	1.0"				
------	------	------	--	--	--	--



PRESSURE REDUCING VALVES

HATTERSLEY 416 BRONZE PRESSURE REDUCING VALVE

Outlet pressure adjustable between 1 - 8.0 Bar / Male union BSP
Gauge points / WRAS
Rated 40 Bar / Temperature -10 - 95 Deg.C

Size	1/2"					
------	------	--	--	--	--	--



GOETZE 681 GUNMETAL PESSURE REDUCING VALVE (ADJ1-8BAR)

Outlet pressure adjustable between 1 - 8 Bar / Bronze Body
Male Iron Unions / Dual gauge
Rated 40 Bar / Temperature 10 - 95 Deg.C

Size	1/2"	3/4"				
------	------	------	--	--	--	--



PRESSURE REDUCING VALVES

RELIANCE / SAMSON

RWC 312 COMPACT CARTRIDGE PRESSURE REDUCING VALVE

Compression / Brass body with dual gauge points
Adjustable pressure adjustable between 0.5 - 5 Bar / Rated 16 Bar
Red Handle max 40 Deg. C / Blue Handle 80 Deg.C max

Size	15mm					
------	------	--	--	--	--	--



RWC 312.52 PRV(0.5-5BAR) 60C. COMPRESSION

Compression.

Size	15mm					
------	------	--	--	--	--	--



RWC 315I COMMERCIAL PRESSURE REDUCING VALVE

Capillary / Compression Unions
Adjustable outlet press / 1-6 Bar / Dual gauge points
Brass body / red cartridge with position indicator

Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	
------	------	------	------	--------	--------	--



SYR 315MI ADJ PRV(1.5-6BAR)

Male Union.

Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	
------	------	------	------	--------	--------	--



809T-146 BRASS PRESSURE REDUCING VALVE WRAS

Hot & cold water to 80 Deg. C (max)
Adjustable 0.6 - 6 Bar / FBSP Union / Dual gauge points
Rated 16 Bar / Temperature 40 Deg.C

Size	1/2"	3/4"	1.0"	1.1/4"	1.1/2"	2.0"
------	------	------	------	--------	--------	------



SAMSON 50EM PRESSURE REDUCING VALVE

Outlet pressure adjustable 1.5 - 6.0 Bar / Female BSP
Rated 16 Bar / Temperature 40 Deg.C

Size	1/2"					
------	------	--	--	--	--	--



C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com



BALL VALVE

QUARTER TURN

HERZ DZR COMPRESSION BALL VALVE

Lever operated. Red. Fullbore. Forged Brass Chrome ball.
16 bar at 0 to 120 deg C. WRAS approval.



NB	15	22	28	35	42	54
BODY	76.5	81	95	108.5	122	134

CIM 309 DZR COMPRESSION BALL VALVE

Tee handle operated. Colour (Red or Blue).
16 bar at 0 to 120 deg C. WRAS approval. 24bar at -20 -150 deg C.



NB	15	22	28			
BODY	77	87	95			

ART 89 BRASS COMPRESSION BALL VALVE

Lever operated (colour options Yellow, Red, Blue).
Full bore, Nickel plated body.
25bar at -10 to 110 deg C. WRAS and EN331 approvals.



NB	15	22	28	35	42	54
BODY	70.5	80	91.5	109	123	150

ART 59 DZR COMPRESSION BALL VALVE

Full bore, Matt finish body.
Lever operated (colour options Yellow, Red, Blue)
25bar at -10 to 110 deg C. WRAS approval.



NB	15	22	28	35	42	54
BODY	70.5	80	91.5	109	123	150

CAST IRON FLANGED

ART 77 CAST IRON FLANGED BALL VALVE

Lever operated. PN16 drilling. ISO 5211 mount.
16 bar at -20 to 110 deg C. WRAS.
Disc and Shaft. Stainless Steel. Seat EPDM. Ductile Iron body.



NB	50	65	80	100	125	150	200	250	300
BODY	41.4	44	44.6	51.4	53.8	55.1	69.5	65	75.9



BALL VALVE

MULTIFUNCTIONAL with NRV / STRAINER / BOTH

323 BALLSTOP BALL VALVE WITH INTEGRAL CHECK VALVE, BLACK AND RED BAND

Tee handle. Black. Female Bsp ISO228.
Brass body and CP ball with internal check valve.
16bar at 5 to 90 deg C. Min pressure to open check valve.



NB	15	20	25	32	40	50
BODY	51	57	70	83	89	110

CIM 620 BALL VALVE WITH COMBINATION STRAINER

Tee handle. Red or Blue. Fullbore. Strainer port. Nickel finish.
Strainer mesh 0.65mm. 25bar at 0 to 150 deg C.



NB	15	20	25			
BODY	81	92	112			

CIM 621 BALL VALVE WITH COMBINATION STRAINER AND NRV

Tee handle. Red or Blue. Fullbore. Strainer port. Nickel finish.
Strainer mesh 0.65mm. 25bar at 0 to 150 deg C.



NB	15	20	25			
BODY	101	117	141			

CIM 623 FILTRASFERA BALL VALVE WITH STRAINER. CXC

Tee handle operated. Colour Red or Blue.
16 bar at 0 to 120 deg C. WRAS approval. 24bar at -20 -150 deg C.



NB	15	22	28			
BODY	97	110	127			

CIM 628 BALL VALVE WITH STRAINER AND NRV. CXC

Tee handle. Red or Blue. Compression BS EN 1254-2.
Fullbore, strainer port, NP finish, strainer mesh 0.65mm.
25bar at 0 to 150 deg C.



NB	15	22	28			
BODY	97	110	127			

ART 70 'L' THREE PORT BRASS BALL VALVE

Lever operated / Red / Female BSP / ISO228
Reduced bore. Brass body and CP ball, PTFE seat and seals.
32bar (8 - 25mm) 25bar (32 -50mm) at -20 to 150 deg C.



NB	15	20	25	32	40	50
BODY	80	90	105	115	138	161



BALL VALVE

VOLUME FLOW CONTROL

CP961 FLOW REGULATING BALL VALVE. COMPRESSION TO BS EN1254-2

Key operation. Lever optional. Black, Red, Blue. WRAS approval.
DZR Brass Nickel plated body and chrome ball, EPDM O rings and PTFE seal.
Cartridges 2.5, 4, 6, 8, 10, 12, 15, 18, 26 Ltrs/min as selected.



NB	15	20	25						
BODY	81	92	112						

CP961 FLOW REGULATING BALL VALVE. COMPRESSION TO BS EN1254-2

Lever operated. Black. Compression BS EN 1254-2. WRAS approval.
DZR Brass Nickel plated body and chrome ball, NBR O rings and PTFE seal.
Maximum - inlet pressure 2bar. Temperature 100 deg C.
Min opening pressure 0.15bar. Cartridges are colour coded.



NB	15	20	25	32	40	50			
BODY	59	65	80.5	91	104	125.5			

QUARTER TURN THREADED BSP

ART 40P BRASS BALL VALVE, FEMALE BSP PARALLEL TO ISO228

Lever operated. (Yellow 15/100mm. Red or Blue 15/50mm).
Full bore. WRAS and EN331. Gas approvals.
40bar (8-40mm) 25bar(65-100mm) at 0 -130 deg C.



NB	15	22	28	35	42	54
BODY	76.5	81	95	108.5	122	134

ART 45P BRASS BALL VALVE, FEMALE BSP PARALLEL TO ISO228

Full bore. WRAS and EN331. Gas approvals. Disc and Shaft. Stainless.
40bar (8-25mm) 32bar (32-50mm) 25bar (65-100mm)
at 0 to 150 deg C maximum.



NB	15	20	25	32	40	50	65	80	100
BODY									

ART 71 'T' THREE PORT BRASS BALL VALVE

Lever operated / Red / Female BSP / ISO228
Reduced bore. Brass body and CP ball, PTFE seat and seals.
32bar (8 - 25mm) 25bar (32 -50mm) at -20 to 150 deg C.



NB	15	20	25	32	40	50
BODY	80	90	105	115	138	161

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com



STOPCOCK

SOLDER

YORKSHIRE 501 STOPCOCK

Crutchhead. Copper x Copper with gunmetal body and Brass headwork, BS1010. WRAS.



Size	15	22	28			
------	----	----	----	--	--	--

YORKSHIRE DZR 501 CAPILLARY STOPCOCK SOLDER RING

The body and all parts in contact with water are resistant to dezincification.



Size	15	22	28	35	42	
------	----	----	----	----	----	--

YORKSHIRE GM 501 CAPILLARY STOPCOCK SOLDER RING

All Gunmetal.



Size	15	22	28	35	42	
------	----	----	----	----	----	--

YORKSHIRE 508 BRASS UNION STOPCOCK SOLDER RING

Crutchhead. Copper x Copper with Solder Ring unions.



Size	15	22	28			
------	----	----	----	--	--	--

YORKSHIRE 508 DZR UNION STOPCOCK SOLDER RING

Crutchhead. Copper x Copper with Solder Ring unions.



Size	15	22	28	35	42	
------	----	----	----	----	----	--

YORKSHIRE GM 508 UNION STOPCOCK SOLDER RING

Crutchhead. Copper x Copper with Solder Ring unions.



Size	35	42	54			
------	----	----	----	--	--	--



STOPCOCK

COMPRESSION

PEGLER M59 COMPRESSION BRASS STOPCOCK

Crutchhead. Copper x Copper.



Size	15	22	28			
------	----	----	----	--	--	--

PEGLER GM59 COMPRESSION STOPCOCK

Crutchhead. Copper x Copper.



Size	15	22	28	35	42	
------	----	----	----	----	----	--

PEGLER M59ECCP COMPRESSION STOPCOCK

Key operated. Copper x Copper.



Size	15	22	28	35		
------	----	----	----	----	--	--

PEGLER PL59 COMPRESSION STOPCOCK

Crutchhead. Compression for MDPE.



Size	15	22	28			
------	----	----	----	--	--	--

POLYPIPE BRASS STOPCOCK

For MDPE Pipe services / Gunmetal Body



Size	20	25	32			
------	----	----	----	--	--	--

BRASS CONVERSION STOPCOCK

For MDPE Pipe services



Size	15	20				
------	----	----	--	--	--	--



STOPCOCK

THREADED

PEGLER 744F FEMALE BSP BS1010 STOPCOCK

Crutchhead. Female Bsp. WRAS.



NB	15	22	25	32	40	50
BODY	57	67	86	96	103	130

PEGLER 744FGK FEMALE BSP BS1010 STOPCOCK

Lockshield. Female Bsp. WRAS.



NB	15	22	25	32		
BODY	57	67	86	105		

PEGLER 744F FEMALE BSP BS1010 STOPCOCK

Wheelhead. Female Bsp. WRAS. Usually supplied for hose reels and fire services.



NB	15	22	25	32	40	50
BODY	57	67	86	96	103	130

PEGLER M59ECCP COMPRESSION STOPCOCK

Tap handle. Copper x Copper. Chrome Cold and Hot.



Size	15	22	28			
------	----	----	----	--	--	--

PEGLER M59ECCP COMPRESSION STOPCOCK

Tap handle. Copper x Copper. Chrome Cold and Hot.



Size	15	22	28			
------	----	----	----	--	--	--



C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com

C. A. Baldwin & Co. Ltd.,

Valan House, 146-154 Wells Way, Camberwell, London SE5 7SY
Telephone: 020 7703 2138 info@cabaldwin.com www.cabaldwin.com