



Item#: **21655**
LED 8' SPEC-SELECT™
DESIGNER STRIP

DIRECT LINEAR AMBIENT LUMINARIES

FEATURES

Spec-Select™ Designer Strips feature adjustable wattage and color temperature for the perfect balance of light in any application.

- Energy efficient
- No flickering

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Wattage	38W / 46W / 54W
Voltage	120-277V
Current	0.45-0.19A
Power Factor	0.9
Total Harmonic Distortion (THD)	10

LIGHTING PERFORMANCE

Lumens	4940 / 5980 / 7020
Lumens Per Watt (LPW)	130
Color Temperature (CCT)	3500K / 4100K / 5000K
Color Rendering (CRI)	82
R9 (Red Value)	8
R13 (Skin Tones)	83
Beam Angle	130°
Light Distribution	Type II, Very Short
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4 ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Seoul 3528
Driver	SIP50-I1200

CONSTRUCTION

Housing	Aluminum
Lens	Frosted
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.



Item#: 21655

LED 8' SPEC-SELECT™ DESIGNER STRIP

ITEM INFORMATION

DIMENSIONS (Inches)

Length	94.2"
Width	3.4"
Height	3.6"
Net Weight (Lbs)	9



SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	**DOUBLE 4FT
LM79	VIEW
LM80	VIEW

PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	4	10811768028215	97.4" x 4.6" x 4.3"	55.1
Individual Box	1	811768028218	--	13.8
Country of Origin	China			
HS Tariff	-9405.11.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
21655	LED 8FT SPEC-SELECT™ DESIGNER STRIP/38-46-54W/35-50K/DIMM/120-277V - P5.1	4

ACCESSORIES

69845	LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30FT DIA, 8-40FT HEIGHT 800W/1200W • 120/277V	50
79845	LOW BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 48FT DIA, 8-20FT HEIGHT 800W/1200W • 120/277V	50
89845	360° HIGH BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 60FT DIA, 8-50FT HEIGHT 800W/1200W • 120/277V	50
49845	EXTENDER MOUNT FOR SENSOR 69845/79845/89845	100
65455	ROW ALIGNER FOR DESIGNER STRIP	100
09355	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN- SPLIT TYPE/L - T20C	1
19355	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN- SPLIT TYPE/L - T20C	1
29355	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN- SPLIT TYPE/L - T20C	1

ADDITIONAL INFORMATION:

**IES File for 8FT unavailable - IES files for #55610 can be doubled to approximative lighting results.

- Default settings; 54W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver. The color temperature and wattage should be selected prior to installation.

