

SAFETY DATA SHEET

Version 6.5 Revision Date 02/02/2021 Print Date 08/07/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : 2-Propanol

Product Number : 34863 Brand : SIGALD

Index-No. : 603-117-00-0 CAS-No. : 67-63-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

: +1 314 771-5765 : +1 800 325-5052

1.4 Emergency telephone

Telephone

Fax

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

SIGALD - 34863

Millipore Sigma

| Hazard statement(s) H225 H319 H336 | Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. |
|---|---|
| Precautionary statement(s) P210 | Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. |
| P233 P240 P241 | Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. |
| P242 P243 P261 | Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. |
| P264 P271 P280 P303 + P361 + P353 | Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection. IF ON SKIN (or hair): Take off immediately all contaminated |
| P304 + P340 + P312 | clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337 + P313 P370 + P378 | If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |
| P403 + P233 P403 + P235 P405 | Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. |
| P501 | Dispose of contents/ container to an approved waste disposal plant. |
| | |

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : sec-Propyl alcohol

Isopropyl alcohol Isopropanol

| Component | Classification | Concentration |
|------------|--|---------------|
| 2-Propanol | | |
| | Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, | <= 100 % |



Page 2 of 11

| H336 | |
|-----------------------|--|
| Concentration limits: | |
| >= 20 %: STOT SE 3, | |
| H336; | |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pav attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.



5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb \mathbb{R}). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Handle and store under inert gas. hygroscopic Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters



| Component | CAS-No. | Value | Control | Basis |
|------------|---------|--|--|---|
| 2-Propanol | 67-63-0 | TWA | 200 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | Remarks | Not classifiable as a human carcinogen | | |
| | | STEL | 400 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | | Not class | Not classifiable as a human carcinogen | |
| | | TWA | 400 ppm 980 mg/m ³ | USA. NIOSH Recommended Exposure Limits |
| | | ST | 500 ppm 1,225 mg/m ³ | USA. NIOSH Recommended Exposure Limits |
| | | TWA | 400 ppm 980 mg/m ³ | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| | | TWA | 400 ppm 980 mg/m ³ | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
| | | STEL | 500 ppm 1,225 mg/m ³ | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
| | | PEL | 400 ppm 980 mg/m ³ | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| | | STEL | 500 ppm 1,225 mg/m ³ | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |

Biological occupational exposure limits

| Component | CAS-No. | Parameters | Value | Biological specimen | Basis |
|------------|---------|---------------------------------|---------|---------------------|--|
| 2-Propanol | 67-63-0 | Acetone | 40 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | Remarks | End of shift at end of workweek | | | |

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact



Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Chloroprene

Minimum layer thickness: 0.65 mm Break through time: 120 min

Material tested: KCL 720 Camapren®

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor alcohol-like

c) Odor Threshold 1 ppm

d) pH at 20 °C (68 °F)neutral

e) Melting point/range: -89.5 °C (-129.1 °F)

point/freezing point

f) Initial boiling point and boiling range

82 °C 180 °F

g) Flash point 12.0 °C (53.6 °F) - closed cup

h) Evaporation rate 3.0

i) Flammability (solid,

gas)

No data available

j) Upper/lower Upper explosion limit: 13.4 %(V) flammability or Lower explosion limit: 2 %(V)

explosive limits

k) Vapor pressure 43 hPa at 20 °C (68 °F)

) Vapor density 2.07

m) Relative density 0.785 g/mL at 25 °C (77 °F)

n) Water solubility soluble

o) Partition coefficient: log Pow: 0.05 - Bioaccumulation is not expected.

n-octanol/water

p) Autoignition 425.0 °C (797.0 °F)

temperature

q) Decomposition Distillable in an undecomposed state at normal pressure.

temperature

r) Viscosity No data availables) Explosive properties No data availablet) Oxidizing properties No data available

9.2 Other safety information

Minimum ignition 0.65 mJ

energy

Conductivity $< 0.1 \mu S/cm$

Surface tension 20.8 mN/m at 25.0 °C (77.0 °F)

2.07

Relative vapor

density

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

Reacts with air to form peroxides.

The product is chemically stable under standard ambient conditions (room temperature) . Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year.

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

rubber, various plastics, oils

10.6 Hazardous decomposition products

In the event of fire: see section 5



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 5,840 mg/kg (OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 37.5 mg/l

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - 12,800 mg/kg

Remarks: (RTECS)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation

(OECD Test Guideline 405)

(Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Ames test

Salmonella typhimurium

Result: negative

In vitro mammalian cell gene mutation test

Chinese hamster ovary cells

Result: negative

OECD Test Guideline 474

Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation, Oral - May cause drowsiness or dizziness. - Central nervous system Remarks:

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Acute inhalation toxicity - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

RTECS: NT8050000

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects., Aspiration may lead to:, Lung edema, Pneumonia

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Headache Dizziness inebriation Unconsciousness narcosis

After uptake of large quantities:

Coma

Handle in accordance with good industrial hygiene and safety practice.

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

9,640 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic

invertebrates

EC50 - Daphnia magna (Water flea) - 13,299 mg/l - 48 h

Remarks: (IUCLID)

Toxicity to algae IC50 - Desmodesmus subspicatus (green algae) - > 1,000 mg/l - 72

h

Remarks: (IUCLID)

Toxicity to bacteria EC5 - Pseudomonas putida - 1,050 mg/l - 16 h



Remarks: (Lit.)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 5 d

Result: 53 % - Readily biodegradable. (Directive 67/548/EEC, Annex V, C.6)

Theoretical oxygen 2,400 mg/g demand Remarks: (Lit.)

Ratio BOD/ThBOD 49 %

Remarks: (IUCLID)

12.3 Bioaccumulative potential

No bioaccumulation is to be expected (log Pow \leq 4).

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and loc No mixing with other waste. Handle uncleaned containers like the product See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

DOT (US)

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 1219 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ISOPROPANOL

IATA

UN number: 1219 Class: 3 Packing group: II

Proper shipping name: Isopropanol

SECTION 15: Regulatory information

SIGALD - 34863

Millipore Sigma

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date 67-63-0 2007-03-01

2-Propanol

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.5 Revision Date: 02/02/2021 Print Date: 08/07/2021

