

# Ontology Adaptation upon Updates

Alessandro Solimando, Giovanna Guerrini

Dipartimento di Informatica, Bioingegneria, Robotica e Ingegneria dei Sistemi  
Università di Genova, Italy  
name.surname@unige.it

**Abstract.** Ontologies, like any other model, change over time due to modifications in the modeled domain, deeper understanding of the domain by the modeler, error corrections, simple refactoring or shift of modeling granularity level. Local changes usually impact the remainder of the ontology as well as any other data and metadata defined over it. The massive size of ontologies and their possible fast update rate requires automatic adaptation methods for relieving ontology engineers from a manual intervention, in order to allow them to focus mainly on high-level inspection. This paper, in spirit of the *Principle of minimal change*, proposes a fully automatic ontology adaptation approach that reacts to ontology updates and computes sound reformulations of ontological axioms triggered by the presence of certain preconditions. The rule-based adaptation algorithm covers up to *SRDQ* DL.

## 1 Introduction and Motivations

Ontologies, like any other model, change over time and a revalidation of all data and metadata defined on top of the modified ontology is needed upon updates. Massive ontology size and fast update rate<sup>1</sup> call for automated support and adaptation algorithms. Despite the great attention devoted in the last ten years to ontology evolution [1, 7], to the best of our knowledge there are no proposals in the literature coping with ontology adaptation upon updates. With similar motivations, an adaptation algorithm for a subset of *SPARQL* queries (with expressivity equivalent to union of Conjunctive Queries) in response to ontology updates is proposed in [6]. *Protégé*<sup>2</sup>, one of the most complete ontology frameworks, does not support any kind of adaptation w.r.t. ontology updates: when a concept or a role is deleted, all the axioms referring it are removed as well. Even if there are cases in which this behavior is acceptable (*e.g.*, error corrections), there are others for which it is detrimental, for instance a modification of the modeling granularity of the ontology. In this scenario, a sound reformulation of axioms by means of super/sub concepts or roles is not only desirable but usually manually performed by the modeler. Additionally, in Artificial Intelligence (*Belief Revision*), knowledge deletion usually follows the *Principle of Minimal*

<sup>1</sup> An example is the *Gene Ontology* (<http://www.geneontology.org/>), with  $\sim 416K$  axioms and  $\sim 40K$  entities, daily updated (statistics for data-version 2013-02-22).

<sup>2</sup> Available here: <http://protege.stanford.edu/>

*Change* [5], which suggests that the amount of lost information should be as minimal as possible. Given that ontologies do not necessarily (explicitly) include all their logical consequences, also the implicit knowledge should be taken into account, as well as explicit one (that is, ontology axioms).

While a set of basic ontology changes can be easily defined, it is impossible to identify a set of complex changes without fixing the granularity level, *i.e.*, updates expressed as arbitrarily complex graph patterns (see [10], Section 3.2.1). In this proposal we consider the basic updates proposed by [3]: addition, deletion and update of entities (concepts and roles). Given that adding or updating entities do not reduce knowledge, and that ontology consistency can be tested using ontology reasoners, our adaptation algorithm focuses only on entity deletions.

In this paper, we propose an algorithm that, given an ontology and an entity (concept or role) to delete, scans for an equivalent, a super and a sub-entity and tries to reformulate the axioms involving the entity in question, with a rule-based approach. Our reformulated axioms are a fraction of the *implicit knowledge* of the ontology under update that would be lost by deleting all of the axioms involving the removed entity. An alternative would be to compute the closure (that is, complete inference of implicit knowledge) for the ontology prior to entity deletion. Due to its high computational cost and possible non-finiteness of the result, a suboptimal but less expensive approach is preferable for our target scenario, that is interactive modeling.

Even if the adaptation algorithm is completely automatic, it may not always be aligned with the modeler’s intention. For this reason, the present proposal has to be intended as an optional feature. When activated, it provides a preview of the changes to show the automatic adaptation effects. On this basis, the modeler can accept or ignore the proposed changes. In addition, a straightforward extension could be the possibility, for the modeler, to select the equivalent (resp. sub/super) entity for the reformulation, when different alternatives are available.

The contribution of the present paper can be summarized as follows: an automatic adaptation algorithm supporting up to *SRQIQ* expressivity, its correctness proof, and temporal complexity analysis (Section 3), an experimental evaluation of the percentage of adaptable entities and axioms on a dataset of real ontologies (Section 4). First, DL basics are introduced (Section 2), and the paper concludes discussing future work (Section 5).

## 2 Preliminaries

Our proposal covers up to *SRQIQ* Description Logic (DL), on top of which the *Ontology Web Language* (OWL2) [11] is defined. The notations and definitions used in this section are borrowed from [4]. An ontology is defined by a set of axioms and a set of entity names (signature), composed by three disjoint subsets:  $N_{\mathcal{R}}$  for role names,  $N_{\mathcal{I}}$  for individual names,  $N_{\mathcal{C}}$  for concept names. These entities are defined by means of expressions. We have *Role expressions*  $\mathbf{R} ::= U \mid N_{\mathcal{R}} \mid N_{\mathcal{R}}^-$ , and *Concept expressions*  $\mathbf{C} ::= N_{\mathcal{C}} \mid (\mathbf{C} \sqcup \mathbf{C}) \mid (\mathbf{C} \sqcap \mathbf{C}) \mid \neg \mathbf{C} \mid \top \mid \perp \mid \exists \mathbf{R}.\mathbf{C} \mid \forall \mathbf{R}.\mathbf{C} \mid \geq_n \mathbf{R}.\mathbf{C} \mid \leq_n \mathbf{R}.\mathbf{C} \mid \exists \mathbf{R}.\textit{Self} \mid \{N_{\mathcal{I}}\}$ , with  $n \geq 0$ . For the

	Precondition	Rule
a.1	$C \equiv C'$ , $C \in \text{signature}(\text{axiom})$	$\text{axiom} \rightarrow \text{axiom}[C/C']$
a.2	$C \sqsubseteq D$	$E \equiv \exists R.C \rightarrow E \sqsubseteq \exists R.D$
a.3	$C \sqsubseteq D$	$E \equiv \geq_n R.C \rightarrow E \sqsubseteq \geq_n R.D$
a.4	$C \sqsubseteq D$	$E \equiv C \sqcup F \rightarrow E \sqsubseteq D \sqcup F$
a.5	$C \sqsubseteq D$	$E \equiv C \sqcap F \rightarrow E \sqsubseteq D \sqcap F$
a.6	$C \sqsubseteq D$	$E \equiv \neg C \rightarrow \neg D \sqsubseteq E$
a.7	$C \sqsubseteq D$	$C(a) \rightarrow D(a)$
a.8	$C \sqsubseteq D$	$E \equiv \forall R.C \rightarrow E \sqsubseteq \forall R.D$
a.9	$B \sqsubseteq C$	$E \equiv \leq_n R.C \rightarrow E \sqsubseteq \leq_n R.B$
a.10	$B \sqsubseteq C$	$E \equiv C \sqcup F \rightarrow B \sqcup F \sqsubseteq E$
a.11	$B \sqsubseteq C$	$E \equiv C \sqcap F \rightarrow B \sqcap F \sqsubseteq E$
a.12	$B \sqsubseteq C$	$E \equiv \neg C \rightarrow E \sqsubseteq \neg B$
a.13	$B \sqsubseteq C$	$C \sqsubseteq E \rightarrow B \sqsubseteq E$

**Table 1.** Adaptation rules for concept deletion  $DEL(C)$ , where  $B, C, C', D, E, F \in N_C$ ,  $R \in N_R$  and  $a \in N_I$ .

semantics associated with nominals, role and concept expressions the reader may refer to [4]. The set of axioms of an ontology, denoted with  $Axioms$ , is defined as  $Axiom ::= ABox \cup RBox \cup TBox$ . The reader may refer to [4] also for a detailed description of the different available axioms for  $SR\mathcal{OIQ}$  DL, and to [9] for the definitions of ontology *interpretation* and ontology *satisfiability*. W.l.o.g. in the paper we will consider normalized ontologies in *Negation Normal Form* (NNF), with an application of *Structural Reduction* (SR), as shown in [9] (Subsection 5.3). SR introduces fresh concept names for (complex) concept expressions, thus letting us to easily refer to each concept expression by means of its associated concept name. Neither the SR nor the NNF are required for the application of our method. NNF, however, may increase the ratio of adapted axioms.

### 3 Algorithm

This section introduces the adaptation rules (Section 3.1), the rule-based adaptation algorithm (Section 3.2), the correctness proof for the given rules (Section 3.3), and the temporal complexity of the algorithm (Section 3.4).

#### 3.1 Adaptation Rules

The adaptation rules are presented in Table 1 (rules for concepts) and Table 2 (rules for roles). We denote by  $\text{axiom}[A/B]$  the alpha renaming of an axiom of entity  $A$  by entity  $B$ . A rule  $r$  is composed by a left hand side,  $LHS(r)$ , a right hand side,  $RHS(r)$ , and a precondition  $\text{prec}(r)$ . A rule is defined **applicable** iff  $\text{prec}(r)$  is satisfied by at least one concept (resp. role). Given an ontology  $o$  and an entity  $e$  to delete, the  $LHS$  of a rule  $r$  is said to be **matching** iff an axiom in  $o$  exists that is equal to  $LHS(r)$  modulo alpha renaming of  $C$  (resp.  $R$ )

	Precondition	Rule
b.1	$R \equiv R'$ , $R \in \text{signature}(\text{axiom})$	$\text{axiom} \rightarrow \text{axiom}[R/R']$
b.2	$Q \sqsubseteq R$	$T_0 \circ \dots \circ T_m \circ R \circ T'_0 \circ \dots \circ T'_p \sqsubseteq T$ $\rightarrow T_0 \circ \dots \circ T_m \circ Q \circ T'_0 \circ \dots \circ T'_p \sqsubseteq T$
b.3	$Q \sqsubseteq R$	$E \equiv \forall R.C \rightarrow E \sqsubseteq \forall Q.C$
b.4	$Q \sqsubseteq R$	$E \equiv \leq_n R.C \rightarrow E \sqsubseteq \leq_n Q.C$
b.5	$Q \sqsubseteq R$	$T \equiv R^- \rightarrow Q^- \sqsubseteq T$
b.6	$Q \sqsubseteq R$	$\text{Disjoint}(R, T) \rightarrow \text{Disjoint}(Q, T)$
b.7	$R \sqsubseteq S$	$R(a, b) \rightarrow S(a, b)$
b.8	$R \sqsubseteq S$	$E \equiv \exists R.C \rightarrow E \sqsubseteq \exists S.C$
b.9	$R \sqsubseteq S$	$E \equiv \exists R.\text{Self} \rightarrow E \sqsubseteq \exists S.\text{Self}$
b.10	$R \sqsubseteq S$	$E \equiv \geq_n R.C \rightarrow E \sqsubseteq \geq_n S.C$
b.11	$R \sqsubseteq S$	$T \equiv R^- \rightarrow T \sqsubseteq S^-$
b.12	$R \sqsubseteq S$	$T_0 \circ \dots \circ T_q \sqsubseteq R \rightarrow T_0 \circ \dots \circ T_q \sqsubseteq S$

**Table 2.** Adaptation rules for role deletion  $DEL(R)$ , where  $E, C \in N_C$ ,  $Q, R, R', S, T, T_i, T'_j \in N_{\mathcal{R}}$ , with  $m, n, p, q \geq 0$ , and  $a, b \in N_{\mathcal{I}}$ .

with  $e$ , denoted with  $LHS(r)[e]$ . The **application** of an applicable rule  $r$  w.r.t.  $o$  and  $e$  rewrites any axiom of  $o$  matching  $LHS(r)[e]$  into  $RHS(r)[e']$ , where  $e'$  is the selected entity for reformulation. It is worth noting that if a DL less expressive than  $\mathcal{SROIQ}$  is adapted, only a subset of the rules will be applicable, depending on the axioms and constructors available. For instance, for basic  $\mathcal{ALC}$  with *General Concept Inclusion* (i.e.,  $C \sqsubseteq D$ ), rules a.3, a.9, b.2, b.4, b.5, b.9, b.10, b.11, b.12 are not applicable.

### 3.2 Adaptation Algorithm

Algorithm 1 presents the adaptation algorithm for ontology updates. It takes as input the entity  $e$  to be deleted and the ontology  $o$  it belongs to. By means of function *computePrec*, the set of axioms related to  $e$  is computed, as well as a triple  $p$  consisting of a (nondeterministically chosen) equivalent, a sub and a super entity, if any (line 3). For each axiom  $a$  having  $e$  in its signature (line 4), it tests if the axiom matches the left hand side of the rule (line 5). At this point, function *satisfies* (line 6) checks if the current axiom is compatible with rule  $r$  and if the required element in  $p$  is not null. The reformulated axiom is inserted in  $o$  (line 7). Finally, all the axioms involving entity  $e$  are removed from  $o$  (line 8). Even if a preliminar classification phase is not required, it may increase the algorithm effectiveness. In what follows we give a toy example of ontology update, comparing the result of adaptation to classical deletion approach.

*Example 1.* Consider an ontology  $o$  consisting of these axioms and the obvious associated signature:  $\text{Human} \equiv \exists \text{eats.Food}$ ,  $\text{Food}(\text{cheese})$ ,  $\text{Eater} \equiv \forall \text{eats.Food}$ ,  $\perp \equiv \text{Plastic} \sqcap \text{Food}$ ,  $\text{Uneatable} \equiv \neg \text{Eatable}$ ,  $\text{Pizza} \sqsubseteq \text{Food}$ ,  $\text{Food} \sqsubseteq \text{Eatable}$ . Deleting  $\text{Food}$  concept from  $o$  with adaptation we obtain:  $\text{Human} \sqsubseteq \exists \text{eats.Eatable}$ ,  $\text{Eatable}(\text{cheese})$ ,  $\text{Eater} \sqsubseteq \forall \text{eats.Eatable}$ ,  $\text{Plastic} \sqcap$

---

**Algorithm 1** Ontology Update Adaptation
 

---

```

1: function ONTOUPDATEADAPT(Entity  $e$ , Ontology  $o$ )
2:    $axioms = \emptyset$ 
3:    $p := \langle eq, sub, sup \rangle \leftarrow computePrec(e, axioms, o)$ 
4:   for  $a \in axioms$  do
5:     for  $r \in Rules$  .  $a = LHS(r)[e]$  do
6:       if  $satisfies(\langle a, e, e' \rangle, prec(r))$ ,  $e' \in \{eq, sub, sup\}$  then
7:          $Axioms(o) \leftarrow Axioms(o) \cup \{RHS(r)[e']\}$ 
8:       end if
9:     end for
10:  end for
11:   $Axioms(o) \leftarrow Axioms(o) \setminus axioms$ 
12: end function
13: function COMPUTEPREC(Entity  $e$ , Set  $axioms$ , Ontology  $o$ )
14:   $eq, sub, sup \leftarrow \epsilon$ 
15:  for  $a \in Axioms(o)$  .  $e \in signature(a)$  do
16:     $axioms \leftarrow axioms \cup \{a\}$ 
17:    if  $eq, sub, sup \neq \epsilon$  then
18:      break
19:    end if
20:    if  $a = e \equiv e'$  or  $a = e' \equiv e$  then
21:       $eq \leftarrow e'$ 
22:    else if  $a = e \sqsubseteq e'$  then
23:       $sup \leftarrow e'$ 
24:    else if  $a = e \sqsupseteq e'$  then
25:       $sub \leftarrow e'$ 
26:    end if
27:  end for
28:  return  $\langle eq, sub, sup \rangle$ 
29: end function

```

---

$Pizza \sqsubseteq \perp$ ,  $Pizza \sqsubseteq Eatable$ ,  $Uneatable \equiv \neg Eatable$  (using rule a.2, a.7, a.8, a.11 and a.13, respectively). Without adaptation, instead, only the last axiom would be present in  $o$  after concept deletion.

### 3.3 Rules Correctness Proof

Before stating the proposition about the correctness of the adaptation rules we introduce some definitions and lemmata. For sake of brevity we will interchangeably refer to the axioms and their semantics, according to [4].

**Definition 1.** An axiom  $A_1$  *entails* an axiom  $A_2$  iff, for any interpretation  $I$ ,  $I \models A_2 \implies I \models A_1$ , that is  $A_2^I \subseteq A_1^I$ .

**Definition 2.** An adaptation rule  $r$  is *sound* iff  $\{LHS(r), prec(r)\}$  entails  $RHS(r)$ .

**Lemma 1.**  $\forall C, D, F \in N_C$  .  $C \sqsubseteq D \implies C \sqcup F \sqsubseteq D \sqcup F$ .

*Proof.* By considering the associated semantics the Lemma can be restated as  $C^I \subseteq D^I \implies \underbrace{C^I \cup F^I}_{\alpha} \subseteq \underbrace{D^I \cup F^I}_{\beta}$ . Assume that the preceding formula does

not hold, that is  $\alpha \not\subseteq \beta$ . This means  $\exists x \in \beta$  .  $x \notin \alpha$ , and requires that at least one of the following conditions holds:

- $x \in F^I$ , but this implies  $x \in \alpha$ , resulting in a contradiction,
- $x \in C^I$ , and thus this implies  $C^I \subseteq D^I \implies x \in \alpha$ , contradicting the hypothesis.  $\square$

**Lemma 2.**  $\forall C, D, F \in N_C . C \sqsubseteq D \implies C \sqcap F \sqsubseteq D \sqcap F$ .

*Proof.* By considering the associated semantics the Lemma can be restated as  $C^I \subseteq D^I \implies \underbrace{C^I \cap F^I}_{\alpha} \subseteq \underbrace{D^I \cap F^I}_{\beta}$ . Assume that the preceding formula does not

hold, that is  $\alpha \not\subseteq \beta$ . This means  $\exists x \in \beta . x \notin \alpha$ . Note that  $x \in \beta$  is equivalent to requiring that  $x \in F^I \wedge x \in D^I$  holds. However,  $x \in F^I \wedge x \notin \alpha \implies x \notin C^I$ . Given that  $x \in D^I$  holds, this contradicts the premise  $C \sqsubseteq D$ .  $\square$

**Lemma 3.**  $\forall C, D \in N_C . C \sqsubseteq D \implies \exists R.C \sqsubseteq \exists R.D$ .

*Proof.* Assume that  $\{x \mid \exists y \in C^I . \langle x, y \rangle \in R^I\} \not\subseteq \{x \mid \exists y \in D^I . \langle x, y \rangle \in R^I\}$  holds, that is,  $\exists R.C \not\subseteq \exists R.D$ . This requires that the following condition holds:  $\exists \langle x, y \rangle \in R^I . y \in C^I \wedge y \notin D^I$ . But, if such condition holds, then  $C \not\subseteq D$ , contradicting the premise.  $\square$

**Lemma 4.**  $\forall C, D \in N_C . C \sqsubseteq D \implies \forall R.C \sqsubseteq \forall R.D$ .

*Proof.* Assume that  $\{x \mid \forall \langle x, y \rangle . \langle x, y \rangle \in R^I \implies y \in C^I\} \not\subseteq \{x \mid \forall \langle x, y \rangle . \langle x, y \rangle \in R^I \implies y \in D^I\}$  holds, that is,  $\forall R.C \not\subseteq \forall R.D$ . This requires that the following condition holds:  $(\exists x . \forall \langle x, y \rangle . \langle x, y \rangle \in R^I \implies y \in C^I) \wedge (\exists \bar{y} . \langle x, \bar{y} \rangle \in R^I \wedge \bar{y} \notin D^I)$ . But, if this condition holds, then an  $\bar{y}$  exists and  $R^I$  is not empty. Therefore, since the left operand of the implication holds, then right operand also does. From this, we obtain  $C^I \not\subseteq D^I$ , contradicting the premise.  $\square$

**Proposition 1.** *Adaptation rules application preserves ontology satisfiability.*

*Proof.* Ontology satisfiability is preserved because every adaptation rule is sound. We prove this for each rule separately:

- a.1 The proof directly follows from *Concept Equivalence* axiom definition.
- a.2  $E \equiv \exists R.C \rightarrow E \sqsubseteq \exists R.D$ .  $\exists R.C \sqsubseteq \exists R.D$  must hold: thanks to the rule precondition,  $C \sqsubseteq D$ , we can apply Lemma 3.
- a.3  $E \equiv_{\geq n} R.C \rightarrow E \sqsubseteq_{\geq n} R.D$ .  $\geq_n R.C \sqsubseteq_{\geq n} R.D$  must hold, but it is sufficient that  $\{x \mid \exists y \in C^I . \langle x, y \rangle \in R^I\} \subseteq \{x \mid \exists y \in D^I . \langle x, y \rangle \in R^I\}$  holds. Thanks to the rule precondition,  $C \sqsubseteq D$ , we can apply Lemma 3.
- a.4  $E \equiv C \sqcup F \rightarrow E \sqsubseteq D \sqcup F$ .  $C \sqcup F \sqsubseteq D \sqcup F$  holds for Lemma 1 because  $C \sqsubseteq D$  holds.
- a.5  $E \equiv C \sqcap F \rightarrow E \sqsubseteq D \sqcap F$ .  $C \sqcap F \sqsubseteq D \sqcap F$  holds for Lemma 2 because  $C \sqsubseteq D$  holds.
- a.6  $E \equiv \neg C \rightarrow \neg D \sqsubseteq E$ .  $\neg D \sqsubseteq \neg C$  must hold: the semantics is  $\Delta^I \setminus D^I \subseteq \Delta^I \setminus C^I$ , but this contradicts  $C \sqsubseteq D$ .
- a.7  $C(a) \rightarrow D(a)$ .  $C(a) \implies D(a)$  is guaranteed by the rule precondition.
- a.8  $E \equiv \forall R.C \rightarrow E \sqsubseteq \forall R.D$ .  $E \equiv \forall R.C \implies E \sqsubseteq \forall R.D$  holds for Lemma 4 because  $C \sqsubseteq D$  holds.

- a.9  $E \equiv \leq_n R.C \rightarrow E \sqsubseteq \leq_n R.B. \leq_n R.B \sqsubseteq \leq_n R.C$ , but it is sufficient that  $\{x \mid \exists y \in B^I . \langle x, y \rangle \in R^I\} \subseteq \{x \mid \exists y \in C^I . \langle x, y \rangle \in R^I\}$ . Thanks to the rule precondition,  $B \sqsubseteq C$ , we can apply Lemma 3.
- a.10  $E \equiv C \sqcup F \rightarrow B \sqcup F \sqsubseteq E$ . The proof for  $B \sqcup F \sqsubseteq C \sqcup F$  is the dual of the one given in item (a.4).
- a.11  $E \equiv C \sqcap F \rightarrow B \sqcap F \sqsubseteq E$ . The proof for  $B \sqcap F \sqsubseteq C \sqcap F$  is the dual of the one given in item (a.5).
- a.12  $E \equiv \neg C \rightarrow E \sqsubseteq \neg B$ . the proof for  $\neg C \sqsubseteq \neg B$  is the dual of the one given in item (a.6).
- a.13  $C \sqsubseteq E \rightarrow B \sqsubseteq E$ . The rule precondition,  $B \sqsubseteq C$ . By transitivity, this implies  $B \sqsubseteq E$ .
- b.1 The proof directly follows from *Role Equivalence* axiom definition.
- b.2  $\underbrace{T_0 \circ \dots \circ T_m \circ R \circ T'_0 \circ \dots \circ T'_p}_{\alpha} \sqsubseteq T \rightarrow \underbrace{T_0 \circ \dots \circ T_m \circ Q \circ T'_0 \circ \dots \circ T'_p}_{\beta} \sqsubseteq T$ . assume that  $\beta^I \not\subseteq \alpha^I$  holds. This requires that  $\exists x_0, \dots, x_{m+p+3} . \langle x_0, x_1 \rangle \in T_0^I \wedge \dots \wedge \langle x_{m+1}, x_{m+2} \rangle \in Q^I \wedge \langle x_{m+p+2}, x_{m+p+3} \rangle \in T_p^I \wedge \langle x_{m+1}, x_{m+2} \rangle \notin R^I$ . This contradicts  $Q \sqsubseteq R$ .
- b.3  $E \equiv \underbrace{\forall R.C}_{\alpha} \rightarrow E \sqsubseteq \underbrace{\forall Q.C}_{\beta}$ . Assume that  $\alpha^I \not\subseteq \beta^I$  holds. This requires that  $\exists x . x \in \alpha^I \wedge x \notin \beta^I$ , that is,  $\exists x . ((\forall y . \langle x, y \rangle \in R^I \implies y \in C^I) \wedge (\exists y' . \langle x, y' \rangle \in Q^I \wedge y' \notin C^I))$ . Given that  $Q \sqsubseteq R$ , if such  $y'$  exists,  $\alpha$  cannot hold, leading to a contradiction.
- b.4  $T \equiv \underbrace{\leq_n R.C}_{\alpha} \rightarrow T \sqsubseteq \underbrace{\leq_n Q.C}_{\beta}$ . Assume that  $\alpha^I \not\subseteq \beta^I$ . This requires that  $\exists x . |\{y \mid y \in C^I \wedge \langle x, y \rangle \in R^I\}| \leq n \wedge |\{y \mid y \in C^I \wedge \langle x, y \rangle \in Q^I\}| > n$ . This implies  $|Q^I| > |R^I|$ , contradicting  $Q \sqsubseteq R$ .
- b.5  $T \equiv R^- \rightarrow Q^- \sqsubseteq T$ . Assume that  $Q^{-I} \not\subseteq R^{-I}$ . This requires that  $\exists \langle x, y \rangle . \langle y, x \rangle \in Q^I \wedge \langle y, x \rangle \notin R^I$ . This contradicts  $Q^I \subseteq R^I$ .
- b.6  $Disjoint(R, T) \rightarrow Disjoint(Q, T)$ . Assume that  $R^I \cap T^I = \emptyset \implies Q^I \cap T^I = \emptyset$  does not hold. This requires that  $\exists \langle x, y \rangle \in Q^I \wedge \langle x, y \rangle \in T^I \wedge \langle x, y \rangle \notin R^I$  holds, but  $\langle x, y \rangle \in Q^I \wedge \langle x, y \rangle \notin R^I$  contradicts  $Q \sqsubseteq R$ .
- b.7  $R(a, b) \rightarrow S(a, b)$ . From  $R \sqsubseteq S$  we have that  $\forall \langle x, y \rangle . \langle x, y \rangle \in R \implies \langle x, y \rangle \in S$ .
- b.8  $E \equiv \underbrace{\exists R.C}_{\alpha} \rightarrow E \sqsubseteq \underbrace{\exists S.C}_{\beta}$ . Assume that  $\alpha^I \not\subseteq \beta^I$ . This requires that  $\exists x . \exists y \in C^I . \langle x, y \rangle \in S^I \wedge \langle x, y \rangle \notin R^I$  holds. This contradicts  $R \sqsubseteq S$ .
- b.9  $E \equiv \underbrace{\exists R.Self}_{\alpha} \rightarrow E \sqsubseteq \underbrace{\exists S.Self}_{\beta}$ . Assume that  $\alpha^I \not\subseteq \beta^I$ . This requires that  $\exists x . \langle x, x \rangle \in S^I \wedge \langle x, x \rangle \notin R^I$  holds. This contradicts  $R \sqsubseteq S$ .
- b.10  $E \equiv \underbrace{\geq_n R.C}_{\alpha} \rightarrow E \sqsubseteq \underbrace{\geq_n S.C}_{\beta}$ . Assume that  $\alpha^I \not\subseteq \beta^I$ . This requires that  $\exists x . |\{y \mid y \in C^I \wedge \langle x, y \rangle \in R^I\}| \geq n \wedge |\{y \mid y \in C^I \wedge \langle x, y \rangle \in S^I\}| < n$ . This implies  $|R^I| > |S^I|$ , contradicting  $R \sqsubseteq S$ .

- b.11  $T \equiv R^- \rightarrow T \sqsubseteq S^-$ . Assume that  $R^{-I} \not\subseteq S^{-I}$ . This requires that  $\exists \langle x, y \rangle . \langle y, x \rangle \in R^I \wedge \langle y, x \rangle \notin S^I$ , thus contradicting  $R \sqsubseteq S$ .
- b.12  $T_0 \circ \dots \circ T_q \sqsubseteq R \rightarrow T_0 \circ \dots \circ T_q \sqsubseteq S$ . This immediately follows, by transitivity, from  $R \sqsubseteq S$ .  $\square$

### 3.4 Temporal Complexity

**Proposition 2.** *The time complexity of the algorithm is in  $\mathcal{O}(n)$ , where  $n$  is the number of axioms of the input ontology  $o$ .*

*Proof.* *computePrecond* scans all the axioms of ontology  $o$ . For each of them it performs some comparison having a total cost of  $c_1$ , so it has a cost of  $n \cdot c_1$ . The *for* statement of line 4 in Algorithm 1 is executed  $n$  times in the worst case (each axiom of the ontology refers to the entity in question). The *for* statement of line 5 is executed  $c_2 = |\text{Rules}|$  times, where *Rules* is the set of adaptation rules. *satisfies* test requires a constant ( $c_3$ ) time for checking the required conditions. Axiom rewriting and its insertion requires constant ( $c_4$ ) time. The removal of old axioms requires constant time ( $c_5$ ) too. The overall complexity is therefore equal to  $n \cdot c_1 + c_2 \cdot c_3 \cdot c_4 \cdot n + c_5$ , that belongs to  $\mathcal{O}(n)$ .  $\square$

## 4 Experiments

In order to evaluate the practical applicability of our proposal we implemented a Java prototype based on the OWL API library<sup>3</sup>. In OWL API the axioms are immutable objects, and it supports only axiom addition and removal. Whenever possible, the rule application has been simulated with a pair of add and delete changes. In the other cases we employed Java Reflection for directly modifying the involved axiom. In addition to correctness, we also experimentally evaluated the coverage of OWL2 axioms and constructors of our set of rules. The dataset is presented in Table 3 (manual selection on the Web based on ontology size and DL expressivity).

*Correctness* The developed proof-of-concept prototype has been used for testing correctness of our adaptation rules, the experimental counterpart of the proofs given in Section 3.3. More precisely, the test consists in taking as input a satisfiable ontology composed by the precondition and an axiom corresponding to the LHS of a rule  $r$  (modulo alpha renaming of the entity to delete). At this point, using *Hermit* reasoner (v1.3.7)<sup>4</sup>, we check the entailment of  $RHS(r)[e']$ .

*Evaluation* An entity  $e$  is **adaptable** iff it satisfies at least one rule precondition, while an axiom  $a$  is **adaptable** iff it at least one rule  $r$  s.t.  $LHS(r)[e] = a$  exists, in case *prec*( $r$ ) holds w.r.t.  $e$ , the axiom is said **fully adaptable**. As an estimation of the practical effectiveness of our algorithm, we consider, for

<sup>3</sup> Available here: <http://owlapi.sourceforge.net/>

<sup>4</sup> Hermit and related information are available at <http://hermit-reasoner.com/>



ID	DL	URI	Axioms	Logical Axioms	(C.1)	(C.2)	(C.3)	(C.4)	(C.2)*	(C.4)*
1.	ALUQ(D)	<a href="http://omv.ontoware.org/2009/09/OWLChanges">http://omv.ontoware.org/2009/09/OWLChanges</a>	186	100	100.00	49.49	0.00	N/A	49.49	N/A
2.	SHIN(D)	<a href="http://ecdb.ucsd.edu/SAO/1.2">http://ecdb.ucsd.edu/SAO/1.2</a>	7767	2712	100.00	17.92	97.22	76.17	17.95	76.17
3.	ALEHI+(D)	<a href="http://swat.cse.lehigh.edu/onto/univ-bench.owl">http://swat.cse.lehigh.edu/onto/univ-bench.owl</a>	243	93	97.67	35.11	36.00	45.16	37.10	45.16
4.	SHOIN(D)	<a href="http://www.w3.org/TR/2003/CR-owl-guide-20030818/wine">http://www.w3.org/TR/2003/CR-owl-guide-20030818/wine</a>	747	657	94.81	67.88	84.62	66.96	88.29	66.96
5.	ALCO	<a href="http://purl.obolibrary.org/obo/ogms.owl">http://purl.obolibrary.org/obo/ogms.owl</a>	576	84	100.00	50.00	N/A	N/A	50.00	N/A
6.	ALQ(D)	<a href="http://owlodm.ontoware.org/OWL2">http://owlodm.ontoware.org/OWL2</a>	353	215	90.80	45.50	0.00	N/A	46.91	N/A
7.	SRIQ(D)	<a href="http://semanticscience.org/ontology/sio-core.owl">http://semanticscience.org/ontology/sio-core.owl</a>	5043	1747	100.00	48.07	100.00	93.55	48.43	93.55
8.	SHOIN	<a href="http://www.co-ode.org/ontologies/pizza/pizza.owl">http://www.co-ode.org/ontologies/pizza/pizza.owl</a>	939	712	100.00	22.14	75.00	100.00	22.15	100.00
9.	SHOIN(D)	<a href="http://sweet.jpl.nasa.gov/2.1/reprSciUnits.owl">http://sweet.jpl.nasa.gov/2.1/reprSciUnits.owl</a>	503	475	100.00	8.20	33.33	0.00	42.86	0.00
10.	SR	<a href="http://purl.obolibrary.org/obo/ido.owl">http://purl.obolibrary.org/obo/ido.owl</a>	20027	8493	96.22	38.53	0.00	N/A	50.47	N/A
11.	SROIF	<a href="http://purl.obolibrary.org/obo/ido.owl">http://purl.obolibrary.org/obo/ido.owl</a>	3499	1025	100.00	34.67	86.67	67.02	36.92	67.73
12.	SROIF	<a href="http://ontology.neuinfo.org/NIF/Dysfunction/NIF-Dysfunction.owl">http://ontology.neuinfo.org/NIF/Dysfunction/NIF-Dysfunction.owl</a>	5649	350	100.00	50.00	N/A	N/A	50.00	N/A
13.	SHIN(D)	<a href="http://aims.fao.org/aes/geopolitical.owl">http://aims.fao.org/aes/geopolitical.owl</a>	23527	22834	100.00	100.00	100.00	100.00	100.00	100.00
14.	S	<a href="http://human.owl">http://human.owl</a>	30364	11545	99.82	49.84	0.00	N/A	49.84	N/A
15.	ALE	<a href="http://mouse.owl">http://mouse.owl</a>	11043	4838	67.02	36.99	0.00	N/A	38.93	N/A
16.	ALCHOIN	<a href="http://owl.man.ac.uk/2005/07/sssw/people.owl">http://owl.man.ac.uk/2005/07/sssw/people.owl</a>	396	108	100.00	69.94	71.43	81.25	71.18	81.25
17.	SROIF	<a href="http://ontology.neuinfo.org/NIF/BiomaterialEntities/NIF-GrossAnatomy.owl">http://ontology.neuinfo.org/NIF/BiomaterialEntities/NIF-GrossAnatomy.owl</a>	19849	2930	99.75	39.62	18.18	100.00	39.62	100.00
18.	SROIN(D)	<a href="http://purl.obolibrary.org/obo/flu/dev/flu.owl">http://purl.obolibrary.org/obo/flu/dev/flu.owl</a>	874	204	100.00	100.00	100.00	100.00	100.00	100.00
19.	ALCOIF	<a href="http://www.owl-ontologies.com/generations.owl">http://www.owl-ontologies.com/generations.owl</a>	60	38	94.44	77.14	75.00	100.00	100.00	100.00
20.	AL(D)	<a href="http://protege.stanford.edu/plugins/owl/owl-library/ka.owl">http://protege.stanford.edu/plugins/owl/owl-library/ka.owl</a>	404	216	100.00	57.03	0.00	N/A	57.18	N/A
21.	SROIF	<a href="http://ontology.neuinfo.org/NIF/BiomaterialEntities/NIF-Cell.owl">http://ontology.neuinfo.org/NIF/BiomaterialEntities/NIF-Cell.owl</a>	3508	398	100.00	46.73	0.00	N/A	46.73	N/A
22.	SOIN(D)	<a href="http://www.owl-ontologies.com/travel.owl">http://www.owl-ontologies.com/travel.owl</a>	145	93	100.00	49.61	33.33	100.00	50.00	100.00
23.	ALUHN	<a href="http://www.hozo.jp/owl/YAMATO20120714.owl">http://www.hozo.jp/owl/YAMATO20120714.owl</a>	4428	2444	100.00	51.69	95.63	11.67	51.69	11.67
24.	ALHIF(D)	<a href="http://purl.org/net/ontology/beer.owl">http://purl.org/net/ontology/beer.owl</a>	165	81	84.48	42.86	22.22	100.00	42.86	100.00
25.	SH(D)	<a href="http://msi-ontology.sourceforge.net/ontology/NMR.owl">http://msi-ontology.sourceforge.net/ontology/NMR.owl</a>	1096	290	100.00	50.00	N/A	N/A	50.00	N/A
26.	SHIF(D)	<a href="http://www.nada.kth.se/~mehrana/Delegation.owl">http://www.nada.kth.se/~mehrana/Delegation.owl</a>	103	63	63.16	40.91	80.00	81.25	40.91	81.25
27.	ALCRIQ(D)	<a href="http://www.biomodels.net/kisao/KISAO">http://www.biomodels.net/kisao/KISAO</a>	2044	647	100.00	42.70	100.00	92.23	42.82	92.47
28.	ALCO	<a href="http://purl.obolibrary.org/obo/omrse.owl">http://purl.obolibrary.org/obo/omrse.owl</a>	99	25	100.00	50.00	0.00	N/A	50.00	N/A

**Table 3.** Dataset and coverage results presented in Section 4. Ontologies 14 and 15 are part of the dataset used by *Ontology Alignment Evaluation Initiative*, and are available at <http://oaei.ontologymatching.org/>. Coverage results are unaggregated and based on the data of Table 4. N/A means the ontology contains no roles/adaptable roles.

each ontology in our dataset, the following scenario: we simulate the deletion of each single entity, in isolation, and we take into account the percentage of adaptable ones (i.e., such that another entity suitable for reformulation exists). For each of these adaptable entities, we also inspect how many axioms involving them would be adapted instead of simply deleted. For this reference scenario we defined *Coverage* measure as: **(C.1)** the percentage of adaptable concepts (resp. roles **(C.3)**) out of the total number of concepts (resp. roles), and **(C.2)** the percentage of adaptable axioms w.r.t. the deleted concept (resp. role, **(C.4)**) out of the number of axioms to be deleted (that is, presenting the deleted entity in their signature). The (C.)<sup>\*</sup> variants count the fully adaptable axioms, and evaluate the completeness of our adaptation rules (the complement of the fully adaptable axioms is not supported by our rules).

In Table 3 the coverage for each ontology in isolation is reported (computed from the raw data of Table 4), while the result considering the dataset as a whole ontology is the following: (C.1) 93.247%, (C.2) 41.757%, (C.2<sup>\*</sup>) 44.185%, (C.3) 73.647%, (C.4) 79.63%, (C.4<sup>\*</sup>) 80.847%. Table 3 shows that 10 out of 12 of the worst performing ontologies w.r.t. role coverage ((C.3), (C.4) and (C.4<sup>\*</sup>)) are expressed in a DL missing role hierarchy constructs (identified by letter *H* in the DL name). Without role hierarchy constructs only role equality can be used for adaptation, thus reducing the number of adaptable roles. Concept coverage (C.1) presents, instead, high values (above 60%) for all the considered ontologies, independently from the DL they are expressed with. This is not surprising because concept hierarchy constructs are available for DLs at least as expressive as  $\mathcal{AL}$ . On the contrary, coverage results for concept rules w.r.t. OWL2 axioms and constructors seem to be unrelated to either the underpinning DL or the ontology size (in terms of number of axioms and/or entities). For instance, the ontologies with worst values for (C.2)<sup>\*</sup> are 2. ( $\mathit{SHIN}(\mathcal{D})$ ), 8. ( $\mathit{SHOIN}(\mathcal{D})$ ) 11. ( $\mathit{SROIF}$ ) 3. ( $\mathcal{AL}\mathcal{E}\mathcal{H}\mathcal{I} + (\mathcal{D})$ ) and 15. ( $\mathcal{AL}\mathcal{E}$ ), with very different number of concepts and axioms (Table 4). Similarly, among the best results for (C.2)<sup>\*</sup> the expressivity ranges from  $\mathcal{AL}(\mathcal{D})$  to  $\mathit{SROIN}(\mathcal{D})$ , again with varying number of axioms and concepts. Ideally the proposal should adapt all the axioms: (C.2)<sup>\*</sup>, in particular, is far from this result, but it is well known that OWL2, despite being based on  $\mathit{SROIQ}$ , adds new constructors and axioms, that are derivable from  $\mathit{SROIQ}$  ones (they do not add expressive power). For example, *Concept Disjointness* axiom (i.e.,  $\mathit{Disjoint}(C, D)$ , with  $C, D \in \mathcal{N}_C$ ) is only a shortcut for  $C \sqcap D \sqsubseteq \perp$ <sup>5</sup>. Our prototype strictly applies the rules of Table 1 and Table 2, so it cannot directly process the axioms and constructors not available in  $\mathit{SROIQ}$  DL, thus diminishing the number of adaptable axioms.

## 5 Future Work

The paper represents, to the best of our knowledge, the first proposal for ontology adaptation upon updates. In addition, the algorithm is totally automatic and supports ontology expressivity up to  $\mathit{SROIQ}$ , on top of which OWL2 is defined.

<sup>5</sup> Refer to [9], Chapter 9, for further examples and details.

The present paper could be extended in several directions. The set of adaptation rules is a preliminary proposal, we plan to further enrich it in order to increase the coverage rate reported in Section 4 and to consider reasonable alternatives for each single rule (*e.g.*, sound alternatives for a.8 could be  $C \sqsubseteq D, E \equiv \forall R.C \rightarrow \forall R.D \sqsubseteq E$  or  $B_0 \dots B_n \sqsubseteq C, E \equiv \forall R.C \rightarrow E \sqsubseteq \forall R. \bigsqcup_{i=0}^n B$ ). We also plan to consider the integration of anonymous entities (*e.g.*, using  $\top$  as superclass). Another possible extension is the integration of a complex update (*e.g.*, concept merge and split) proposals, such as [2]. The relationship between DL updates and *Belief Revision* has been investigated [8], we plan to further investigate it w.r.t. our proposal. We also intend to improve our prototype up to a full support of OWL2. Our final goal will be a *Protégé* plugin, from which we hope to receive feedbacks from the community of ontology engineers and practitioners. The experimental evaluation will also be strengthened with an extended ontology dataset and temporal profiling of the prototype.

## References

1. Flouris, G., Manakanatas, D., Kondylakis, H., Plexousakis, D., Antoniou, G.: Ontology change: Classification and survey. *Knowl. Eng. Rev.* 23(2), 117–152 (2008)
2. Hartung, M., Groß, A., Rahm, E.: COnto-Diff: Generation of Complex Evolution Mappings for Life Science Ontologies. *Journal of Biomedical Informatics* (2012)
3. Hartung, M., Groß, A., Rahm, E.: Rule-based Generation of Diff Evolution Mappings between Ontology Versions. *CoRR* abs/1010.0122 (2010)
4. Horrocks, I., Kutz, O., Sattler, U.: The Even More Irresistible SROIQ. In: *Principles of Knowledge Representation and Reasoning – KR 2006*. pp. 57–67 (2006)
5. Katsuno, H., Mendelzon, A.O.: Propositional Knowledge Base Revision and Minimal Change. *Artificial Intelligence* 52(3), 263–294 (1991)
6. Kondylakis, H., Plexousakis, D.: Ontology Evolution: Assisting Query Migration. *Conceptual Modeling – ER 2012* pp. 331–344 (2012)
7. Noy, N., Klein, M.: Ontology Evolution: Not the same as Schema Evolution. *Knowledge and Information Systems* 6(4), 428–440 (2004)
8. Ribeiro, M.M., Wassermann, R., Antoniou, G., Flouris, G., Pan, J.: Belief Contraction in Web-Ontology Languages. In: *Workshop on Ontology Dynamics, IWOD* (2009)
9. Rudolph, S.: Foundations of Description Logics. *Reasoning Web. Semantic Technologies for the Web of Data* pp. 76–136 (2011)
10. Stojanovic, L.: Methods and Tools for Ontology Evolution. Ph.D. thesis, University of Karlsruhe (2004)
11. W3C as Hitzler, P. and Krötzsch, M. and Parsia, B. Patel-Schneider, P.F. and Rudolph, S.: OWL 2 Web Ontology Language Primer. <http://www.w3.org/TR/owl2-primer/> (2009)

ID	Concepts	Adaptable Concepts	Concept Axioms	Adaptable Concept Axioms	Roles Adaptable Roles	Role Axioms	Adaptable Role Axioms	Unsatisfiable Concept Axioms	Unsatisfiable Role Axioms
1.	100	100	198	98	2	0	0	0	0
2.	736	736	5129	919	36	35	256	195	0
3.	43	42	131	46	25	9	31	14	0
4.	77	73	411	279	13	11	345	231	0
5.	92	92	168	84	0	0	0	0	0
6.	87	79	367	167	44	0	0	11	0
7.	1021	1021	2823	1357	184	184	946	885	0
8.	100	100	1477	327	8	6	180	180	0
9.	1930	12	183	15	6	2	137	0	136
10.	509	1857	9809	3779	4	0	0	2321	0
11.	509	509	2189	759	30	26	285	191	3
12.	352	352	700	350	0	0	0	0	0
13.	12	12	460	460	6	6	4888	4888	0
14.	3304	3298	10880	5423	2	0	0	0	0
15.	2744	1839	6256	2314	3	0	0	312	0
16.	60	60	173	121	14	10	48	39	0
17.	1628	1624	6116	2423	11	2	86	86	0
18.	213	213	447	447	19	19	83	83	0
19.	18	17	35	27	4	3	20	20	0
20.	96	96	377	215	60	0	0	0	0
21.	373	373	794	371	2	0	0	1	0
22.	35	35	129	64	6	2	11	11	0
23.	925	925	4589	2372	183	175	1542	180	0
24.	58	49	105	45	9	2	6	6	0
25.	301	301	580	290	9	0	0	0	0
26.	19	12	22	9	20	16	48	39	0
27.	202	202	1335	570	9	9	386	356	1
28.	27	27	50	25	2	0	0	0	0

**Table 4.** Raw data used for coverage analysis of Section 4. Unsatisfied axioms stands for axioms matching the LHS of a rule having a precondition not satisfied by the entity under deletion.