

L026AE

2x 1GbE RJ45, 1x SD/HD/3G-SDI, 1x LTC



PHYSICAL

Dimensions (W x H x D)	43.40 cm x 4.45 cm x 57.40 cm 17.09 in x 1.75 in x 22.60 in
Weight	12.61 kg (Unit) 18.2 kg (Gross)
ECCN	5A992
USHTS Code	8471.50.0150

ELECTRICAL

Max Potential Power	455 Watts (Max)
Heat Dissipation	1552.52 BTU/hr (Max)
AC Power Option	100 - 240 VAC (Input Voltage) 50 - 60 Hz (Line Frequency)

AC PSU Connector C14



DC Power Option Not qualified at this time

DC PSU Connector None available

ENVIRONMENTAL

Operating Conditions	10 to 35 °C (50 to 95 °F) 8% to 80% RH (non-condensing)
Storage Conditions	-40 to 65 °C (-40 to 149 °F) 5% to 95% RH (non-condensing)
Noise Level	58 dBA (Max)
Electromagnetic Compliance	EN 55024:2010, EN 55032:2015 EN 61000-3-2:2014 EN 61000-3-3:2013

Safety Compliance EN 60950-1:2006, EN 62368-1:2014
EN IEC 62368-1:2020, EN 62311:2008
IEC 60950-1:2005

SYSTEM

System Management	iDRAC9 Enterprise
Storage Capacity	480GB Redundant Storage
I/O Interfaces	2x 1GbE RJ45 1x SD/HD/3G-SDI 1x LTC

PORT CONFIGURATION

