

# L881AE

6x 1Gb, 2x 10Gb Multi-mode Fiber



## PHYSICAL

<b>Dimensions (W x H x D)</b>	43.40 cm x 4.28 cm x 75.83 cm 17.09 in x 1.69 in x 29.85 in
<b>Weight</b>	21.96 kg (Unit) 26.96 kg (Gross)
<b>ECCN</b>	5A992
<b>USHTS Code</b>	8471.50.0150

## ELECTRICAL

<b>Max Potential Power</b>	696 Watts (Max)
<b>Heat Dissipation</b>	2374.85 BTU/hr (Max)
<b>AC Power Option</b>	100 - 240 VAC (Input Voltage) 50 - 60 Hz (Line Frequency)

**AC PSU Connector** C14



**DC Power Option** -40 to -60 VDC (Input Voltage)

**DC PSU Connector** DC Terminal




## ENVIRONMENTAL

<b>Operating Conditions</b>	10 to 35 °C (50 to 95 °F) 8% to 80% RH (non-condensing)
<b>Storage Conditions</b>	-40 to 65 °C (-40 to 149 °F) 5% to 95% RH (non-condensing)
<b>Noise Level</b>	63 dBA (Max)
<b>Electromagnetic Compliance</b>	EN 55032, EN 55024, EN 61000 CISPR 32, CISPR 24 IEC 6100
<b>Safety Compliance</b>	EN 60950 IEC 60950 EN 62311

## SYSTEM

<b>System Management</b>	iDRAC9 Enterprise
<b>Storage Capacity</b>	480GB Redundant Storage
<b>I/O Interfaces</b>	6x 1Gb RJ45 2x 10Gb SFP+ slots installed with 10GbE Multi-mode Fiber Transceivers  See next page for qualified SFP add-ons

## PORT CONFIGURATION



# L881AE

6x 1Gb, 2x 10Gb Multi-mode Fiber

---

## QUALIFIED SFP ADD-ONS

Transceiver	Form Factor	Mode	Link Distance	Spare P/N	OEM	OEM Part Number
1000BASE-T RJ45	SFP	N/A	100 m	SP426	FS	SFP-GB-GE-T
10GBASE-LR Fiber Optic	SFP+	Single Mode	10 km	SP431	Intel	E10GSFPLR
10GBASE-SR Fiber Optic (Default)	SFP+	Multi-mode	300 m	SP412	Intel	E10GSFPSR

NOTE: Only qualified SFP add-ons denoted with \* require a minimum software version of AWS Elemental Live 2.21.1+