	4			3		2				<u>1</u>	
ITEM	CONNECTOR PART NO.		DESCRIPTION						TA	BLE 1	
1	See Table 1	ZR CONNECTOR	2				Ν	UMBER OF	CONNECTOR		TOTAL WI
2	UL1571, 28 AWG	GREY						CIRCUITS		ASSEMBLY PART NUMBER	
	,						1 2				304.8
							1 3		03ZR-8K-P	A03ZR03ZR28H152B	457.2
							1 4		04ZR-8K-P	A04ZR04ZR28H152B	609.6
							1 5		05ZR-8K-P		762.0
							1 6		06ZR-8K-P		914.4
							1 7		07ZR-8K-P		1,066.8
							1 8		08ZR-8K-P		1,219.2
							1 9	-	09ZR-8K-P		1,371.6
							1 1				1,524.0
							1 1				1,676.4
								2			1,828.8
								3	13ZR-8K-P	A13ZR13ZR28H152B	1,981.2
						\wedge		contact JS	т а Product	: Change Notice is require	: u.
						5.0)				J	
					152.4 ±	5.0					
			2IN 1								
		1:5-	<u>IN 1</u>	2					PIN 1		
			<u>IN 1</u>	2		SCALE 1: 1			PIN 1	Electrical Spe	
4	Revised description fro	1.5		6/17/2024	SP	1: 1 DIMENSIONS	MM with a		PIN 1	Electrical Spe 1 Current: 0.7A	ecification: AC/DC
43	Revised description fro	m overall to insid	e length	2 6/17/2024 6/17/2024	SP SP	1: 1		DESCRIPTION	<u>_</u>	Electrical Spe	ecification: AC/DC
-	Length tolerance revise	em overall to inside	e length 5.0	6/17/2024	SP	1: 1 DIMENSIONS All dimensions are in tolerance of ± 5.0 otherwise spec	0 unless	DESCRIPTION 1.5 mm	4 Pitch ZR Standard Ca	Electrical Spe 1 Current: 0.7A	AC/DC
3	Length tolerance revise Revised connector from	Im overall to insided from ± 3.0 to ± n Green (8M) to E	e length 5.0	6/17/2024 6/17/2024		1: 1 DIMENSIONS All dimensions are in tolerance of ± 5.0 otherwise spec	0 unless cified.	DESCRIPTION	4 Pitch ZR Standard Ca	Lectrical Spectrum Current: 0.7A Voltage: 50V A tatalog Assembly - 6" Inside Length – P	AC/DC
3	Length tolerance revise	Im overall to insided from ± 3.0 to ± n Green (8M) to E	e length 5.0 Black (8K) version	6/17/2024	SP SP	1: 1 DIMENSIONS All dimensions are in tolerance of ± 5.0 otherwise spec	0 unless cified. GTON	DESCRIPTION 1.5 mm	4 Pitch ZR Standard Ca RT NO.	1 Electrical Spectrum 1 Current: 0.7A Voltage: 50V A	AC/DC AC/DC AC/DC in out: 1 to N