

Lever Grease Gun 'V' Series

VI



Ideal combination of superior quality and value price

Aluminium die cast head fitted with automatic air bleeder valve

Black powder coated finish



Available in 2 choices

- a. 6" (150 mm) steel extension & coupler
- b. 12" (300 mm) x 0.33" (8.5 mm) flexible hose & coupler

SPECIFICATIONS

DEVELOPS	UPTO 6,000 PSI	UPTO 413 BAR
DELIVERS	UPTO 1 OZ. / 28 STROKES	UPTO 1 GM / STROKE

FILLING OPTIONS



ORDERING INFORMATION

CAT NR.	ORD NR.	CAT NR.	ORD NR.	CARTRIDGE CAPACITY		BULK CAPACITY	THREADS	BOX QTY.
				(OZ.)	(GMS)			
6" (150 MM) STEEL EXTENSION & COUPLER		12" (300 MM) FLEXIBLE HOSE & COUPLER						
* V1R/BL/B	42912	V1F/BL/B	42926	14	400	500	1/8" BSPT	16
* V1R/BL/M	42913	V1F/BL/M	42927	14	400	500	M10 x 1	16
V1R/BL/N	42914	V1F/BL/N	42928	14	400	500	1/8" NPT	16

* Best Seller