


VACUUM DRYING OVEN OVE077-913

<u>aa</u>aa

-



VACUUM DRYING OVEN OVE077-913

OVE077-913 VACUUM DRYING OVEN

Microprocessor controller

Dual layer tempered glass door for clear observation

Minimum heating time 50% less than traditional vacuum oven

Interior chamber made from stainless steel with a mirror polished finish making for easy cleaning

Standard with vacuum pump

Direct heating and control by shelves: Each shelf has a separate temperature sensor, can be independently displayed and controlled temperature in setting, monitoring and timing, more accurate and stable



SPECIFICATIONS

Model	OVE077-913
Capacity	913 L
Electrical requirement	AC 380 V 50 HZ
Controller	LED display
Power Consumption	5800 W
Temperature range	RT+10 - 200°C
Display Resolution	0.1
Temperature Stability	±1°C
Vacuum Degree	133 Pa
Ambient Temperature	+5 - 40°C
Interior Dimension	750Wx1160Dx1050H mm
Exterior Dimension	1400Wx1395Dx2010H mm
Shelves	5 pcs
Chamber Material	304 Stainless steel



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@labstac.com | Website: labstac.com