

BIOLOGICAL INDICATOR INCUBATOR



BIOLOGICAL INDICATOR INCUBATOR

Biological Indicator Incubator is supporting equipment for bio-indicator. It is small in size, less weight and is suitable for pressure steam sterilizer biological indicator, ethylene oxide sterilization biological indicator and other biological indicator sterilization, effect detection and cultivation.

Used in Environmental protection, Research institutes, University laboratories.

Also known as Laboratory Incubator.

INC51-100 BIOLOGICAL INDICATOR INCUBATOR

Unique designed. Small size, light weight, portable, and suits on various occasions.

LCD display. Temperature and time display simultaneously.

Auto fault detect and buzzer alarm. Temperature calibration function.

24V DC power supply input, low energy consumption. Built-in over-temperature protection device, safe and reliable.

Timer function. Time range from 0 to 999 min.

Variety of standard sample blocks for choice. Convenient for replacement. Block can be customized.



SPECIFICATIONS

| | |
|----------------------------|----------------------------|
| Model | INC51-100 |
| Temperature Control Range | RT+5°C~100°C |
| Temperature Setting Range | 5°C~100°C |
| Temperature Stability@56°C | ±0.5°C |
| Temp. Display Accuracy | 0.1°C |
| Heating Speed | <6min (20°C to 56°C) |
| Time Range | 1sec~999sec or 1min~999min |
| Voltage | DC 24V adapter |
| Power | 60W |
| Dimension (WxDxH) | 110x156x92 mm |
| Net Weight | 1kgs |

OPTIONAL ACCESSORIES

| Accessory Code | Name | Description |
|----------------|------------|-------------|
| 2805514005 | Block C | 6 x Φ15 mm |
| 2805514006 | Block D | 6 x Φ16mm |
| 2805514007 | Customized | Customized |

INC52 BIOLOGICAL INDICATOR INCUBATOR

- Designed for incubation of EO biological indicators
- Customized wells for placement of biological indicator vials
- Easy to set incubation temperature
- Aluminium blocks available to meet different experimental requirements



SPECIFICATIONS

| Model | INC52-080 | INC52-100 |
|------------------------|-----------------------|-------------------|
| Temperature Range | RT+5-80°C | RT+5-100°C |
| Temperature Accuracy | 0.35°C at 57°C | |
| Temperature Uniformity | 0.5°C | |
| Temperature Resolution | 0.1°C | |
| Time for Heating | ≤6 min (20°C to 57°C) | |
| Timer Range | 1 min-99h 59 min | |
| Exterior Dimension | 110Wx150Dx80H mm | 120Wx152Dx112H mm |
| Display | LCD | |
| Weight | 0.5/1 kg | 0.85/1.4 kg |
| Power | 120 W | |
| Power Supply | 240 V, 60 Hz | |



INC52-080



INC52-100

INC53-057 BIOLOGICAL INDICATOR INCUBATOR

Compact, fits in the palm of your hand
LCD display. It is easy to setup and use
Different kinds of aluminum blocks are available
Clear cover ensures temperature uniformity
Portable, Optional 24V adapter



SPECIFICATIONS

| | |
|------------------------------|-----------------------|
| Model | INC53-057 |
| Temperature Accuracy | 0.35°C at 57°C |
| Temperature Control Accuracy | ±0.5°C |
| Display Accuracy | 0.1°C |
| Time for Heating | ≤6 min (20°C to 57°C) |
| Timer Range | 1 min-99 h 59 min |
| Exterior Dimension | 120Wx152Dx112H mm |

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com