

GEL CARD INCUBATOR

÷

-

<u>aaaa</u>a

labstac.com

GEL CARD INCUBATOR

It can be suitable for many types of gel cards from different manufacturers. Feature like audible programmable alarm to notify end of incubation period makes it an ideal choice.

Used in Hospitals, Research, Laboratory.

Also known as Laboratory Gel Card Incubator.

INC31-24GC GEL CARD INCUBATOR

2 independent incubation zones with a capacity for 12 Gel cards Incubator for 24-Gel Cards in racks at 37°C Digital interface visor control and visualization of centrifuge speed and time remaining for processing



SPECIFICATIONS

| Model | INC31-24GC |
|----------------------------|--------------------------|
| Temperature Range | RT +5-60°C |
| Temperature Accuracy | ±1°C |
| Temperature Fluctuation | ±0.5% |
| CO2 Range | 0~20% |
| CO2 Recovery Time | ≤concentration x 1.2 min |
| Jacket Type | Air jacket type |
| Exterior Dimension (WxDxH) | 220x380x140 mm |
| Power | 300 W |
| Power Supply | AC220 V 3 A |

INC32-12GC GEL CARD INCUBATOR

Digital interface visor control and visualization of centrifuge speed and time remaining for processing

Automatic balance control

Pre-defined centrifugal parameters for optimum Gel cards processing; acceleration, speed, braking and time

Programmable audible alarms for end of centrifuge time periods



SPECIFICATIONS

| Model | INC32-12GC |
|--------------------|-------------------|
| Capacity | 12 Gel Cards |
| Speed Range | 800~1800 rpm |
| RCF. Range | 54~272 x g |
| Timer Range | 1~20 min |
| Exterior Dimension | 440Wx340Dx170H mm |
| Noise Level | ≤55 db |
| Weight | 7 kg |
| Power | 85 W |
| Power Supply | AC100-240 V |

INC33-24GC GEL CARD INCUBATOR

Digital interface visor control and visualization of centrifuge speed and time remaining for processing

Automatic balance control

Pre-defined centrifugal parameters for optimum Gel cards processing; acceleration, speed, braking and time

Programmable audible alarms for end of centrifuge time periods



SPECIFICATIONS

| Model | INC33-24GC |
|--------------------|-------------------|
| Capacity | 24 Gel Cards |
| Speed Range | 500~1500 rpm |
| RCF. Range | 33~294 x g |
| Timer Range | 1~20 min |
| Exterior Dimension | 530Wx410Dx180H mm |
| Noise Level | ≤55 db |
| Weight | 11.5 kg |
| Power | 85 W |
| Power Supply | AC100-240 V |



Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: contact@labstac.com | Website: labstac.com