



200116



Listed 84JM
ZMWV
E129884

Pressure Terminal
Connectors

NRTL Cat. No.

2S2/0

2/0-14 CU9AL | 90°C

Wire Size Copper (solid to semi-rigid stranded and metric mm ² , ##)	All Torque in in-lbs. For N-M divide by 8.85.			
	Rating °C	Wire Size FLEX Copper(##)	Wire Size aluminum	Torque (all drive means)
N/A	90°	1/0-1	N/A	75
N/A		1-4	N/A	55
2/0-3		4-8	2/0-3	50
4-6		8-10	4-6	45
8		10-14	8	40
10-14		N/A	10-12	35



ihconnectors.com/striplength

(#)



ihconnectors.com/flex

(#) FLEX - covers stranding classes within G, H, I/DLO, Metric class5 and K/MTW. (##) mm2 sizes within AWG/kcmil ranges are included. PARALLELING: Rated for PAIRS of wires.

All Torque in in-lbs. For N-M divide by 8.85.

Wire Size Copper (solid to semi-rigid stranded and metric mm ² , ##)	Rating °C	Wire Size aluminum	Torque (all drive means)
2/0-3	75°	2/0-3	120
4-6		4-6	120
8		8	120
10-14		10-12	120

(##) mm2 sizes within AWG/kcmil ranges are included. PARALLELING: Rated for PAIRS of wires.



ihconnectors.com/striplength



Listed 84JM
ZMWV
E129884

Pressure Terminal
Connectors

NRTL Cat. No.

2S2/0

2/0-14 CU7AL | 75°C