

# 1710W LED Lunar Lite®

Total LED Efficacy of 393,300 Lumens from a SINGLE light head

**"WE LEAVE OUR COMPETITORS IN THE DARK"**



**PATENTED TECHNOLOGY**

**ANTI-GLARE**



[www.LunarLighting.com](http://www.LunarLighting.com)



# 1710W LED Lunar Lite®

## 360° Anti-Glare Portable LED Light

Fully Directional lighting; 5x independent light segments of 72° per segment

### Features\*\*

- Dimmable
- Flicker Free
- LEDS rated for 50,000hrs
- Even and Uniform 360° Lighting
- Operating Temp range -40°C to 85°C
- Polymer Diffuser - Durable & Tough
- Daylight colour temperature 6000°Kelvin
- Adjustable from Visible light to Infrared light (Optional)
- Light head Dimensions: 57cm H x 43cm D Weight: 14kg
- Adjustable Wattages 342W – 684W – 1026W – 1368W – 1710W
- Area lit approximately 5027m<sup>2</sup> at 4m height and min lux of 1
- LED efficacy is 230 lm/W. 1710W LED efficacy is 393,300 lumens
- Input Voltage Options: 12VDC, 24VDC, 48VDC AND 90VAC to 305VAC
- HEAVY Duty Impact Resistant road-case for transportation and storage
- Total Luminous Flux of 266,266 lumens after diffuser and driver reductions
- Typical Amperage draw is 7.2 Amps @ 240V for 1710W; 1.4 Amps for 342W
- State of the Art LEDs which have Extreme Stability and high Thermal ability
- Innovative LED Thermal Management System with PURE Aluminium heat sink
- Can be Retrofitted to conventional lighting towers, poles, plant and machinery

\*\* Features and Figures may be subject to change at any time without notice © Lunar Lighting Pty Ltd 2024

\* Anti glare properties are dependent upon dimmer switch settings.



Lunar Lighting Pty Ltd  
www.LunarLighting.com  
PH: 1300 586 271 (1300 LUNAR1)

