

# 2550W LED Lunar Lite®

Total LED Efficacy of 586,500 Lumens from a SINGLE light head

**"WE LEAVE OUR COMPETITORS IN THE DARK"**



**PATENTED TECHNOLOGY**

**ANTI-GLARE**



[www.LunarLighting.com](http://www.LunarLighting.com)



# 2550W LED Lunar Lite®

## 360° Anti-Glare Mobile LED Lunar Light

Fully Directional lighting; 5x independent light segments of 72° per segment

### Features\*\*

- Dimmable
- Flicker Free
- LEDS rated for 50,000hrs
- Even and Uniform 360° Lighting
- Polymer Diffuser - Durable & Tough
- Operating Temp range -40°F to 185°F
- Daylight color temperature 5000°Kelvin
- Adjustable from Visible light to Infrared light (Optional)
- Adjustable Wattages 510W – 1020W – 1530W – 2040W – 2550W
- LED efficacy of 230 lm/W. 2550W LED efficacy of 586,500 lumens
- Light head Dimensions: 22 inches H x 17 inches D. Weight: 30lbs
- Input Voltage Options: 12VDC, 24VDC, 48VDC AND 90VAC to 305VAC
- Area lit approximately 10,956 sq. yds at 4.5 yds height and min lux of 1
- HEAVY Duty Impact Resistant road-case for transportation and storage
- Typical Amperage draw of 23Amps @ 110V for 2550W; 4.6 Amps for 510W
- Total Luminous Flux of 335,836 lumens after diffuser and driver reductions
- State of the Art LEDs which have Extreme Stability and high Thermal ability
- Innovative LED Thermal Management System with PURE Aluminium heat sink
- Can be Retrofitted to conventional lighting towers, poles, plant and machinery

\*\* Features and Figures may be subject to change at any time without notice © Lunar Lighting Innovations LLC 2024

\*Anti glare properties are dependent upon dimmer switch settings.



Lunar Lighting Innovations LLC  
www.LunarLighting.com  
Ph. +1 713 234 0270

