

4800W LED Lunar Lite®

Total LED Efficacy of 1,104,000 Lumens from a SINGLE light head

"WE LEAVE OUR COMPETITORS IN THE DARK"



PATENTED TECHNOLOGY

ANTI-GLARE



www.LunarLighting.com

4800W LED Lunar Lite®

360° Anti-Glare Mobile LED Lunar Light

Fully Directional lighting; 8x independent light segments of 45° per segment

Features**

- Dimmable
- Flicker Free
- LEDs rated for 50,000hrs
- Even and Uniform 360° Lighting
- Polymer Diffuser - Durable & Tough
- Light head Dimensions: 22" H x 34" D
- Operating Temp range -40°F to 185°F
- Daylight color temperature 5000°Kelvin
- Typical Amperage draw is 20A @ 240V for 4800W
- Can be Retro fitted to poles, plant and machinery
- Adjustable from Visible light to Infrared light (Optional)
- Area lit approximately 13,000yds² at 5.5yds height and min lux of 1
- LED efficacy of 230 lm/W. 4800W LED efficacy is 1,104,000 lumens
- Diesel fuel consumption of 0.45gal/Hr on a mechanical load of 3.58kW
- Input Voltage Options: 12VDC, 24VDC, 48VDC AND 90VAC to 305VAC
- Total Luminous Flux of 700,440 lumens after diffuser and driver reductions
- State of the Art LEDs which have Extreme Stability and high Thermal ability
- Innovative LED Thermal Management System with PURE Aluminum heat sink
- Adjustable Wattages 600W-1200W-1800W-2400W-3000W-3600W-4200W-4800W



** Features and Figures may be subject to change at any time without notice © Lunar Lighting Innovations LLC 2024

* Anti glare properties are dependent upon dimmer switch settings.



Lunar Lighting Innovations LLC
www.LunarLighting.com
Ph: +1 713 234 0270

