

Retail: \$9.99

Pattern: 1493CW


TEXAS

STITCHLESS APPLIQUE

CLASS WORKBOOK

Yellow Heart Rose

Includes two different size rose patterns
Large 6 1/2 in. or Small 3 1/2 in.



SKILL LEVEL: EZ BEGINNER



Mary Hugs!
tana

Basic Stitchless Applique Supplies and Instructions

Pattern: 1493CW

★ Basic Stitchless Applique Supplies and Definitions

Pattern: Yellow Heart Roses SKU: 1493CW


All patterns have a color photo, simplified basic instructions, black and white artwork patterns and color value chart.

Fabric kit: Kit includes background fabric and all fabrics for yellow heart rose. Yellow Heart Rose fabric kits are available SKU:1493K Note: Colors may vary.


Scotch® Magic Tape: Used for large formatted patterns only. To keep patterns affordable, we print on 11 in. H x 17 in. W, ledger paper. One page of the black and white artwork pattern must be trimmed, then it is matched up with second page. Use the Scotch® magic tape to tape the two pages together.

Sharpie® Permanent Markers: The black fine point is used to add numbers and notes on the large artwork patterns. The black and white large artwork pattern will need to be numbered. The first page of the black and white artwork pattern is pre-numbered and has the numbers, areas, and fabric colors listed with notes. Transfer the numbers, alpha characters and any notes. Sometimes patterns occasionally need to have a few lines re-traced, so they can be seen from the back while tracing.

The red fine point is used for centering lines. Place Scotch® tape over red marker.



Steam A Seam 2 Roll




Steam A Seam 2® (double sided fusible): Steam A Seam 2® is sold by the yard, roll or packages of five sheets (12 in. H x 9 in. W).


Steam A Seam 2® has two release papers. The top side has yellow graph lines, this is the side to trace on. The other side is plain white paper, do not trace on this side. The center is a woven fusible.



Front and back view



Center Woven Fusible Web



Wrinkled Steam A Seam 2® can be a problem when trying to trace. It can be lightly pressed with a hot dry iron on a low setting (Acetate 290 degrees). Place the Steam A Seam 2® on a ironing surface with the yellow graph side down. Press on the plain white paper side. Start from one end and press lightly gliding to the other end. Do not go back and forth while ironing. Pick up the iron and repeat. Allow to cool before using.

Steam A Seam 2® can also be used in an ink jet printer. Cut into 11 in. H x 8 1/2 in. W. It MUST be the exact size.

Recommended: designs by tana acrylic ruler, which is the exact size needed.



Basic Stitchless Applique Supplies and Instructions

Pattern: 1493CW

#2 Pencil or mechanical pencil 0.5mm or 0.7mm: A mechanical pencil is recommend for tracing applique pieces onto the Steam A Seam 2®. Choose a mechanical pencil lead size, that can be seen on the Steam A Seam2®. Tana recommends the Pentel Energize mechanical pencil 0.7mm. During classes we use a Bic® disposable pencil 0.7mm.



Pentel® Energize 0.5mm or 0.7mm



Bic® 0.7mm



Artograph LightTracer 12" x 10"



Artograph LightPad 940 LX - 17" x 12"

LightTracer® LED Lightbox: There are many brands of quality light-boxes or light pads. Tana recommends the LightTracer or LightPad 940, both are made by ArtoGraph. Sizes vary, pick a size between 12 in. x 10 in. or 17 in. x 12 in. Both have a Cool White 6500K color temperature.

Make sure the black and white artwork pattern can be seen through the Steam A Seam 2®. Some low priced lightbox will not work because they do not provide enough light to see through multiple layers. (pattern, background and applique)


Tim Holtz® 5" mini snip scissors: Designed and used by Tim Holtz! These mini snips feature Kushgrip® handles and micro-serrated, non-stick, titanium blades that make them the ideal craft tool. They can cut cardstock, chipboard, grunge board, craft wire, metals, ribbon and fabric. From handles to tip, these measure 5 inches (12.3cm).



Black & Decker® original iron: Easy to use and has a legible temperature setting guide. Temperature is the MAGIC in this "Stitchless Applique" technique. The iron is affordable and will out last most of the irons on the market today. Tana own's six of them. The first one was purchase in 1998 and it still works. Tana does not put water in any iron.



June Tailor portable ironing surface: Recommended for travel . It measure 18 in. x 24 in. Perfect amount of padding for great pressing. Tana recommends to cover it with a cotton pillow case for basic applique steps. For the final step cover the ironing surface with a cotton bath towel to keep ironing surface dry while finishing the applique block.



Mr. Clean® Magic Eraser® and gently used dish towel: Always clean the iron before beginning any project. Turn iron onto hottest setting (Linen 445 degrees). Place a knitted dish cloth or old wash cloth on ironing surface. Wet the Mr. Clean® Magic Eraser and ring it out. Place it on top of the dish cloth and glide hot dry iron across it until the entire soleplate is clean. Repeat as necessary.



The Mr. Clean® Magic Erasers are made with "Durafoam." Simply a
www.designsbytana.com

foam-like material made of formaldehyde-melamine-sodium bisulfate copolymer, a material that is commonly called melamine foam. This is an abrasive foam. There are no chemical cleaners in the eraser. This foam material has been used in a number of industries for over 20 years. MSDS #: FH/H/2003/TW Date: 05-2003

Bounce Gently Used Dryer Sheets: The Bounce® mega sheet, it is an oversized dryer sheet that measures 9 in. x 12 1/2 in. They are made out of polyester webbing also know as non-woven cloth.

The dryer sheet is used to place on top of applique pieces of Steam A Seam2® when pressing them onto the wrong side of the fabric. It will keep any excess fusible from getting onto the iron soleplate and pencil lead.

In the event an accident occurs while pressing the Steam A Seam 2® applique pieces with the hot dry iron, immediately glide the iron over the gently used dryer sheet to remove the fusible. Repeat until all fusible is removed.

DO NOT use a new dryer sheet for this. Only gently used dryer sheets. MSDS #: FH/F/2002/KHKT-5F2MTA Date: 10-2002

DISCLAIMER AND ALLERGY WARNING: These gently used dryer sheets may contain factory fragrance and chemicals, or pet hair.

Gently used dryer sheet means yes, it has been used with Tana’s regular weekly laundry. Yes, Tana also has two German Sheppard's.

For the purpose of this class, Tana laundries the gently used dryer sheets in hot water (130 degrees) with Tide® Hygienic Clean Heavy Duty 10X Liquid Detergent Original Scent and Clorox®. Rinsed with Lysol® Laundry Sanitizer and then they are dried (160 degrees) to ensure they are sanitized . NOTE: It is not necessary to laundry dryer sheets for personal use.

Pigma® Micron® pen black .05 mm: The Pigma® Micron® pens are used to add lettering and special details onto the applique pieces. The artwork should be done before placing the applique piece onto the block. The Steam A Seam 2® stabilizes the fabric so it may be written on. They are available in many sizes and colors.

Pigma® Micron® pens are permanent, fade resistant, chemically stable, pigment-based ink will not bleed or run if liquids are spilled on or applied to the fabrics or documents after the ink has dried.

General’s® Chalk pencil white: The General’s® Chalk pencils are used to mark the placement lines onto the fabric. Placement lines are the area another applique piece needs to be positioned.

General's® Chalk pencil are a smooth, blendable formula for use in fine arts, scrapbooks or mixed media artwork. The pencils are acid-free, pre-sharpened and made with sustained yield cedar wood to ensure strength. Chalk is not permanent and will wash out.

General's® Chalk pencil are available in many colors. Tana uses white, gray and sepia.



Basic Stitchless Applique Supplies and Instructions

Pattern: 1493CW

TIP: To sharpen, wet tip with water and dry with a paper towel. Using the General® all purpose sharpener, insert and rotate a few turns, remove and repeat.



Bear® Thread Applique pressing sheet: The Bear® Thread Applique pressing sheet is used to build the applique units. It is placed on top of the black and white pattern. To keep it from moving use two Prym Dritz® straight pins. One in the top and one in the bottom.



Tana's applique is built in units. What is a unit? One section or item is built on the Bear® Thread Applique pressing sheet. One rose is a unit after it is built. Allow it to cool and carefully remove.

The unit can be stored on a plastic sheet protector or a plain piece of paper, however do not press it onto the paper with a lot of pressure or while it is still warm because it will not be removable. DO NOT store on paper for long periods of time.

The Bear® Thread appliqué pressing sheet is double-sided sheet. It is made from an ultra high temperature fabric and is coated with non-stick Pylon. This release all sheet is guaranteed for 5 years and is available in three sizes: 13" x 17", 18" x 20" and 27" x 30".

Tana recommends size: 13 in. x 17 in.. Yes, the Bear® Thread The applique pressing sheet may be cut with a hot knife, as it is a woven product and will fray if cut with scissors.



Prym® Dritz® straight pins: Straight pins are used to pin the Bear® Thread Applique pressing sheet to the black and white artwork pattern. No more than two straight pins are needed. One on top and one on bottom or one on each side. Less is best.



Applique tweezers: Small applique pieces need to be handled carefully. The applique tweezers have a fine point with scored lines in the inside to help hold the grip on the applique piece., which makes easier to pick up small pieces.



While holding the applique piece with the applique tweezers, small pieces, circles and threads can carefully be trimmed.

Avery® Permanent Glue Stick: Small pieces sometimes need a small tab of glue to hold them in place. Use the applique tweezers to hold small piece and glide across the glue stick. Place the applique piece onto the unit, press hard and allow to dry. It will be permanent when dried.



Hefty® Storage Container: The small plastic container has a clear lid used to hold small applique pieces. The black bowl is used for applique trash after trimming.



Spray bottle: Any simple spray bottle that has a fine spray will work. Add tap water and use for pressing wrinkled fabric. After all of the applique pieces are in place on the foundation fabric, it must be sprayed heavily with water to activate the Steam A Seam2®.



Place the cotton towel on ironing surface. Place the foundation fabric with the applique pieces in place on the cotton towel. Spray heavily with water. Using the Black and Decker iron on the hottest setting (Linen 450 degrees) carefully press each area until dry. DO NOT apply a heavy pressure. Complete all areas until dry. Turn over and repeat.

Faultless® Spray Starch Luxe Finish Pro Grade: The finally step in the Tana’s applique process is to starch the final block to be squared.




Shake the can well. Spray the front of the applique block. Gently massage the starch into the block. Using the Black and Decker® iron on the hottest setting (Linen 450 degrees) carefully press each area until dry.

Using a pencil, make an asterisk “*” in the center of the back of the block. This will be the reminder all steps have been completed.

PROJECT FABRIC SUPPLY LIST

A: Tonal
Green Grass 1726918
2 1/2 in. H x 1 1/2 in. W



Background Fabric
Tossed Dots
White 1667 9524
6 in. H x 6 in. W



B: Marble
Medium 9881 Cosmo Yellow
3 in. H x 2 in. W



X: Solid Cotton
Medium 292417 Sun
3 1/2 in. H x 2 in. W



C: Splash Blender
Medium/Dark 3504-Gold
4 1/2 in. H x 2 in. W



Steam A Seam 2®: 4 1/4 in. H x 5 1/2 in. W

D: Blended
Light 45-Dandelion Yellow
1 1/2 in. H x 1 1/2 in. W



★ **Stitchless Applique Technique**

IMPORTANT READ ALL INSTRUCTIONS!

Note: Tana’s technique is easy to use if you follow the steps she is using when you apply the Steam A Seam 2®.



Understanding the Iron Settings

Setting	Fabric	Temperature
1	Acetate/Acrylic	275-290 F
2	Silk/Nylon	275-300 F
3	Rayon/Polyester	300-375 F
4	Blends of Cotton	300-375 F
5	Wool	300 F
6	Cotton	400 F
7	Linen	445 F



Tana only uses Steam A Seam 2®, if you are using a different brand of two sided fusible, test these steps.

Understanding the Steam A Seam 2® (SAS2) product.

SAS2 is made with two types of glue. One permanently bonds the fabrics and the other is tacky providing the repositionable benefit. The tacky glue is water soluble and must be completely steamed dissipating it and preventing resistance when sewing.

The yellow graph side is the side you will be tracing your applique pieces onto with a #2 pencil or .07mm mechanical pencil.

Tana’s applique fabric kits have 100% cotton fabric. Turn your iron on and place the setting on cotton to preheat. Do not use any water in the iron or steam.

Place fabric swatches on ironing surface, spray with a water bottle and press with hot dry iron, to remove any wrinkles and factory sizing. Turn fabric swatches over and repeat. The fabric swatches are ready for applique.



SAS2 has two release papers, the first one is the yellow graph side and the second is a plain piece of paper. Trace applique pieces onto the yellow graph side. Fussy cut between pieces. Remove the plain white release paper and place the fusible side to the wrong side of the fabric.

First Press onto Fabric: Wool Setting ~ No Steam

Hand press in place. Turn the iron setting to wool. Place a gently used dryer sheet over the piece and press with hot dry iron for four seconds. The small fusible dots in the center of the circles will melt. No steam, no water.



Steam A Seam 2®



First Pressing onto Fabric

Place the gently used dryer sheet over the applique pieces. This will allow you to see your SAS2 and fabric while pressing. The iron can be moved for pressing, without flipping pieces. Do not hold iron in one position because there will be dots in your SAS2 fusible that are not being heated.

Carefully build the unit on the pressing sheet.

Second Pressing onto Pressing Sheet: Wool Setting ~ No Steam

Using a Bear Thread® Applique Pressing Sheet, build the applique units. Place the gently used dryer sheet over the unit. Lightly press unit. Approximately three seconds. Allow to cool before removing from pressing sheet. No steam, no water.

Third Pressing onto Background Block: Wool Setting ~ No Steam

Place the gently used dryer sheet over the piece and press with hot dry iron for three seconds. No steam, no water.

Check position of the units. If everything is in place and does not need to be repositioned, turn the iron to the Linen (445 degrees) setting. Press block.

Forth Pressing onto Finishing Block: Linen Setting ~ No Steam

When you have reached this point, the tacky glue that is water soluble will need to be completely dissolved, so the permanent glue can be activate and completely melted.


Using a water bottle, spray the block heavily with water until the entire block is wet. The block will shrink when wet. Change the iron setting to Linen and press with hot dry iron until block is dry. Turn block over and repeat on back.

OPTIONAL: FINISH BLOCK

Using Faultless® Spray Starch, spray and hand massage into fabric. Press with hot dry iron on the Linen setting.

Turn block over, using a Pigma® Micron® Pen .05mm Black and place an asterisk (*) somewhere; so that you know the block has been completed and is ready to use. Store flat until ready to use.


DISCLAIMER AND WARNING: This is a "Tired and True" technique. If you are using the same products and following the directions, the finished project is "Stitchless." Tana strongly recommends for you to practice by building sample blocks and laundry them in a lingerie bag.



Unheated SAS2 Dots



Second Pressing onto Pressing Sheet



Third Pressing onto Background Block

Before Beginning READ ALL Instructions!

★ Foundation Background Fabric

Small Rose: Cut foundation fabric 6 in. H X 6 in. W.
Finished size: 5 1/2 in. H x 5 1/2 in. W.

Large Rose: Cut foundation fabric 9 in. H X 9 in. W.
Finished size: 8 1/2 in. H x 8 1/2 in. W.

★ Numbered Applique Pieces


Pattern: 1493B Yellow Heart Rose
See black and white artwork pattern with numbered pieces.

★ Centering the artwork


Place the black and white artwork pattern on the lightbox. Fold the top of the pattern matching the artwork edge to edge of the bottom of the pattern. Finger crease only an inch in the center.

Fold the left page of the pattern matching the artwork edge to edge of the right side of the pattern. Finger crease only an inch in the center.

Using a Sharpie® Fine Point Red, make a dot and lines. Place scotch tape over the red marker, so it does not bleed on your block.



Small Pattern Page 1
Numbered Applique Pieces,
Color Value Chart and Notes




Large Pattern Page 2

Color Value Chart: All patterns have a color value chart included. When this color value chart is printed the colors may vary.

The color value chart provides a information about the fabrics used. The fabric alpha character, name of fabric, how much fabric, any notes about directional, doubled or use wrong side and color photo.

Fabric letter: Alpha character's are used to identify fabric. A, B, C, D, etc. Tana does not use letter "I" and "O".

Directional: There are many fabrics that are directional, such as woodgrains and buffalo checks.



Color Value Chart

Basic Stitchless Applique Supplies and Instructions



Pattern: 1493CW

Wrong Side Fabric: There is a right side of the fabric and a wrong side (or back of fabric). Often times a lighter shade maybe needed, so Tana uses both sides of fabric.

TIP: When shopping for fabric look at both sides.

If a kit was purchased fabrics can be easily matched up using the color value chart.

If choosing fabrics, from a stash, chose a fabric as close as possible to the photo.



Doubled: Doubled fabric must be two layers, so the darker color behind it will not show through. There are notes on page 1 of the black and white artwork pattern, indicating which piece or pieces were doubled if necessary.

TIP: This is like making a sandwich.



Basic Doubling Instructions: Our kits have an “x” fabric for the doubling. Using the “x” fabric add a piece of Steam A Seam2® in the center of the wrong side of fabric “x”. The Steam A Seam 2® is pressed with a hot dry iron on wool setting. For 3 seconds. Allow to cool.

Applique pieces “5Cx” and “7Bx” need to be doubled. Cut fabric B, 1/2 in. H x 2 in. W. Cut fabric C, 2 in. H x 2 in. W.

Fabric “x”, remove the Steam A Seam2® release paper, place the wrong side of fabric “B” and “C” onto the fusible. It is okay if they are touching. Press with hot dry iron on wool setting for 3 seconds.


Using applique pieces “5cX” and “7bX”, remove the release paper and place onto the “x” fabric. Make sure they are on the color. Press with hot dry iron on wool setting for 3 seconds.

applique piece is now doubled and ready for use.



Doubling Fabric

SAS2 3 in. H x 1 1/2 in. W



Traced Doubling Pieces on Steam A Seam 2®

★ Basic Applique Instructions

1. This pattern is pre-numbered. If it were not, you would need to transfer the numbering.. Using a pencil or Sharpie® fine point marker, black, number each piece on the large pattern. Use numbered page enclosed in this pattern.

2. Black and white artwork pattern 1493B is NOT reversed. **Turn pattern over and place onto light box for tracing**

If you have trouble viewing the pattern lines, trace lines with a Sharpie® fine point black marker to make lines larger and darker.

3. Using a pencil, trace each piece onto the Steam A Seam 2® fusible, yellow graph side. Add 1/8 of an inch dashed line for over lapping pieces. When tracing leave 1/4 inch (width of pencil eraser) between pieces. Be sure to identify each piece by adding notes to include, number, part name, color and any directional notes.

Trace placement lines. Use Sharpie® black marker to trace over those lines.

Trace a square onto Steam A Seam 2® for each piece that needs to be doubled. Label each square.

4. Using scissors, rough cut out fusible pattern piece, in the 1/2 in. space between applique pieces. (do not cut on the line, cut between pieces).

5. Match fusible pieces to the correct fabric color. Use the color value chart for reference. Remove the release paper and place fusible pieces on the wrong side of fabric. Read the notes on the applique pieces for directional notes, etc.

Place the gently used dryer sheet over the applique pieces, press fusible pieces with hot dry iron onto fabric three seconds.

NOTE: Wool setting on iron. **High heat is not needed. DO NOT ADD ANY STEAM!**

6. Cut each piece out next to the traced line. If you cut on the line you will reduce the size of the applique piece.


7. Any piece that has placement lines or stitching lines, place on light box and transfer lines to the fabric. Use chalk pencil in dark areas and #2 pencil for all other placement areas.

8. For artwork details see black and white artwork pattern for instructions.

9. Some patterns have small sections of art. These small sections can be built as one unit and then applied to the foundation block.

10. Building small units, place black and white artwork pattern on-to lightbox. Use two straight pins to pin the applique pressing sheet to the paper. Build the unit on the pressing sheet.

Position the applique piece onto the applique pressing sheet by number. Using applique tweezers, carefully place each applique piece onto the pressing sheet in chronological order, finger press.



Traced Applique Pieces on Steam A Seam 2®



Cut Applique Pieces

Continue to match each piece onto the pattern until all pieces have been applied.

Press with hot dry iron. Approximately three seconds.

11. Find the center of the foundation fabric over the center of the pattern. Using a two straight pins, pin the top and bottom to the pattern.

12. Carefully remove the cooled rose unit from the pressing sheet. Place onto the center of the foundation fabric. Hand press.

13. Press with hot dry iron on wool setting for approximately three seconds.

★ Instructions for Finishing Permanent Stitchless Applique with no stitching

1. Press block with hot dry iron on Linen setting approximately three seconds.

2. Using a spray bottle with water, spray entire block from front until wet. Using a hot dry iron on linen setting press until dry. Turn over and repeat on back. NOTE: Linen is the hottest setting on iron.

3. Using Faultless® spray starch, shake well and spray front of block. Massage the starch into the block. Turn block over and press with hot dry iron on linen setting.

4. Using a pencil make an asterisk “*” on the back of the block in the center. This indicates you have heavily steamed and it is ready to use.

5. Store flat until ready to square to use in the project.

★ Test Block

If this is your “TEST” block, place it in a lingerie bag and wash with your regular laundry. Take out of washer, smooth out block and allow to dry on paper towel.

Check all the edges to make sure you followed the process. All pieces should be permanently attached. Press with hot dry iron.

“TIRED TRUE & TESTED”

★ Designer

If you need additional patterns, fabrics, supplies or a class please contact:

Tana Mueller, Designaholic


designs by tana

P. O. Box 208, Crowley, TX 76036-0208

Phone: 817-680-7220

Email: designsbytana@gmail.com

www.designsbytana.com




Stitchless Applique ~ Yellow Heart Rose

Pattern: 1493B

Small Artwork Size: 3 1/2 in. H x 3 in. W
 Background Fabric: 6 in. sq.
 Block Size: 5 1/2 in. sq.
 Applique Pieces: 10

This pattern is NOT reversed.
 Turn over on light box for tracing.

NUMBER	AREA	COLOR
1, 2	Leaf	A: Light/Medium Green
3, 4, 7	Petals	B: Medium Yellow
5, 6, 9, 10	Petals	C: Dark Yellow
8	Center	D: Light Yellow
5, 7	For doubling fabric	X: Medium Yellow



Notes: When pressing Steam A Seam 2® fusible onto the fabric, use the wool setting with no steam.



Double fabric definition: Fabric must be in two layers, so the darker fabric behind it will not show through.

Rose Petals are Doubled: Trace 5Cx and 7Bx. Fabric "x" Sun Cotton is used on the back for doubling. Cut one piece of fabric "x" 3 in. H x 2 in. W and cut one piece of Steam A Seam2, 3 in. H x 2 in. W. Remove release paper from Steam A Seam 2® and place on wrong side of fabric "X." Press with hot dry iron on wool setting. Cut in half, 1 1/2 in. H x 2 in. W for two pieces.

Remove release paper and place fabric "x" onto the wrong side of fabric "C" dark yellow, hand press. Repeat for fabric "B" medium yellow. Press with hot dry iron. Place applique pieces 5C and 7B on the sun cotton side. Heat press and carefully cut out each piece.

Micron Detail: Use Pigma® Micron .05 black for vein lines on leaves and lightly for petal vein lines.




Steam A Seam 2: 4 1/4 in. H x 5 1/2 in. W

NUMBER	AREA	COLOR
1, 2	Leaf	A: Light/Medium Green
3, 4, 7	Petals	B: Medium Yellow
5, 6, 9, 10	Petals	C: Dark Yellow
8	Center	D: Light Yellow
5, 7	Doubling	X: Medium Yellow

DO NOT TURN OVER FOR TRACING.

Steam A Seam 2 for doubling: 3 1/4 in. H x 1 3/4 in. W

Color Value Chart



This pattern is NOT reversed.
Turn over on light box for tracing.

Large Artwork Size: 5 1/2 in. H x 5 in. W
Background Fabric: 9 in. sq.
Block Size: 8 1/2 in. sq.
Applique Pieces: 10

