

## MARIN BIKES SUSPENSION FORK AXLE TO CROWN MEASUREMENT GUIDE - 2023

Marin Bikes mountain bike frames are engineered with a specific suspension fork axle to crown measurement for proper handling and safe use.

This document confirms the safe minimum and maximum fork axle to crown measurement for your bike model.

**Installing any fork with an axle to crown measurement that is outside the stated limits may result in an unsafe bicycle and will void the warranty.**

\*If your model/year is not on this list please reference the original specifications, then look up the axle to crown for that fork. The max and min are +/- 10mm of the originally specified fork's axle to crown measurement.



MODEL YEAR	MODEL	STOCK AXLE TO CROWN (mm)	MINIMUM AXLE TO CROWN (mm)	MAXIMUM AXLE TO CROWN (mm)
2018-2023	Alcatraz	491	481	501
2019-2023	Alpine Trail	571	561	581
2021-2023	Alpine Trail Carbon	571	561	581
2021-2023	Alpine Trail E	571	561	581
2015-2018	Attack Trail	544	534	554
2017	B-17	544	534	554
2021-2022	El Roy	551	541	561
2019-2022	Hawk Hill	520	510	530
2017-2018	Hawk Hill	509	499	519
2019-2020	Mount Vision	542	532	552
2015-2017	Mount Vision	534	524	544
2023	Rift Zone 27.5	532	522	542
2021-2022	Rift Zone 27.5	520	510	530
2023	Rift Zone 29 Alloy	551	541	561
2018-2019	Rift Zone 29 Alloy	531	521	541
2020-2022	Rift Zone 29 Carbon & Alloy	541	531	551
2020-2023	Rift Zone Carbon	544	534	554
2023	Rift Zone Jr (24" & 26")	534	524	544
2018-2022	Rift Zone Jr, Hawk Hill Jr	534	524	544
2021-2022	San Quentin 24	475	465	485
2019-2022	San Quentin 27.5	530	520	540
2023	San Quentin 27.5	542	532	552
2017-2020	Wolf Ridge	571	561	581