

www.testo.com/manuals



<https://qr.testo.com/ldtw8z>



	°C				
0560 1915 129 x 31 x 31 mm 5 x 1.2 x 1.2 in	-20 ... +50 °C -4 ... +122 °F	3 AAA Alkaline 150 hours	0.1 °C 0.1 °F	-60 ... +1000 °C -76 ... +1832 °F	±(0.5 °C + 0.3 % of mv) ±(0.9 °F + 0.3 % of mv)
0602 1093 ① Ø 5 mm / Ø 0.2 in ② 115 mm / 4.5 in	 -20 ... +60 °C -4 ... +140 °F			-50 ... +400 °C -58 ... +752 °F	±1.0 °C (-50 °C ... 100 °C) ±1 % of mv (others) ±1.8 °F (-58 °C ... 212 °F) ±1 % of mv (others)
0602 2093* ① Ø 5 mm / Ø 0.2 in ② 115 mm / 4.5 in	 -20 ... +60 °C -4 ... +140 °F			-50 ... +350 °C -58 ... +662 °F	±(1.0 + 1 % of mv) °C ±(1.8 + 1 % of mv) °F
0602 3093* ① Ø 5 mm / Ø 0.2 in ② 115 mm / 4.5 in				-50 ... +400 °C -58 ... +752 °F	±1.0 °C (-50 °C ... 100 °C) ±1 % of mv (others) ±1.8 °F (-58 °C ... 212 °F) ±1 % of mv (others)
0602 4093* ① Ø 5 mm / Ø 0.2 in ② 115 mm / 4.5 in				-50 ... +400 °C -58 ... +752 °F	±1.0 °C (-30 °C ... +80 °C) ±(0.7 + 1 % of mv)(-50 ... -30 °C) ±(0.2 + 1 % of mv)(+80 °C ... 400 °C) ±1.8 °F (-22 °F ... +186 °F) ±(1.3 + 1 % of mv)(-58 °F ... -22 °F) ±(0.4 + 1 % of mv)(+186 °F ... +752 °F)

* probe + handle

Approval and Certification

Product 产品名称	testo 915i
Mat.-No. 型号	0560 1915
Date 日期	13.06.2024

i The use of the wireless module is subject to the regulations and stipulations of the respective country of use, and the module may only be used in countries for which a country certification has been granted. The user and every owner has the obligation to adhere to these regulations and prerequisites for use, and acknowledges that the re-sale, export, import etc. in particular in countries without wireless permits, is his responsibility.

Country	Comments
Australia	 E 1561
Brazil	 14309-21-04701 See Brazil Information
Canada	IC ID: 6127B-05601915 See ISED Warnings
China	CMIIT ID: 2021DJ5252
Europa + EFTA	  Testo SE & Co. KGaA hereby declares that the testo 915i (0560 1915) complies with Directive 2014/53/EU. The full text of the EU Declaration of Conformity can be found on the following website: https://www.testo.com/eu-conformity . EU countries: Belgium (BE), Bulgaria (BG), Denmark (DK), Germany (DE), Estonia (EE), Finland (FI), France (FR), Greece (GR), Ireland (IE), Italy (IT), Latvia (LV), Lithuania (LT), Luxembourg (LU), Malta (MT), Netherlands (NL), Austria (AT), Poland (PL), Portugal (PT), Romania (RO), Sweden (SE), Slovakia (SK), Slovenia (SI), Spain (ES), Czech Republic (CZ), Hungary (HU), Republic of Cyprus (CY). EFTA countries: Iceland, Liechtenstein, Norway, Switzerland  WEEE Reg. no.: DE 75334352
Malaysia	Type Approval Code: RGOF/05A/0321/S(21-1025)
South Africa	TA-2020/8307
Türkiye	Authorized
United Kingdom (GB)	  The UK Declaration of Conformity can be found on the testo homepage www.testo.com under the product specific downloads.
USA	 FCC ID: WAF-05601915 See FCC Warnings

Bluetooth®-Information	Feature 特征与参数	Values 数值
	Bluetooth® range / 范围	up to 150m (490 feet) (free field / 无障碍场地)
	Radio type / 类型	Bluetooth® Low Energy (BLE) 4.2
	Company / 制造商	LSD Science & Technology Co., Ltd Lierda LSD4BT_S37
	RF Band / 射频频段	2402 – 2480MHz
	Power output / 输出功率	13.70dBm
Bluetooth® SIG Listing	Declaration ID	D043363
	Member company	Testo SE & Co. KGaA

	Comments
Hongkong	Authorized

EU SAR Information

The SAR limit of Europe is 2.0 W/kg. The highest SAR value reported for 0560 1915 under testing standard for use in hand is 0.275W/kg. This device and its antenna(s) must not be co-located or operating in conjunction with any other antenna or transmitter.

ISED Warnings

CAN ICES-003(B)/NMB-003(B):

This Class B digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe [B] est conforme à la norme NMB-003 du Canada.

RSS-Gen & RSS-247 statement:

This device complies with Industry Canada licence-exempt RSS standard(s).

Operation is subject to the following two conditions:

- (1) this device may not cause interference, and
- (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence.

L'exploitation est autorisée aux deux conditions suivantes :

- (1) l'appareil ne doit pas produire de brouillage, et
- (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

ISED SAR warning:

The highest SAR value reported under this standard during product certification for use in the hand is 0.450W/kg.

Co-Location:

This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter.

Avertissement DAS d'ISED:

La valeur DAS la plus élevée rapportée durant la prise en main pour utilisation selon la norme standard de certification de produit est de 0,450 W / kg.

Co-location

Ce transmetteur ne peut pas être installé en colocation ou être utilisé avec une autre antenne ou transmetteur, quel qu'en soit le type.

FCC warning statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. Shielded interface cable must be used in order to comply with the emission limits.

Warning

This device complies with Part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC SAR warning:

The SAR limit of USA (FCC) is 1.6 W/kg averaged over one gram of tissue. The highest SAR value reported under this standard during product certification of 0560 1915 (FCC ID:WAF-05601915) for use when properly worn in the hand is 0.450 W/kg.

Co-Location:



This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter.

Brazil Information

Este equipamento não tem direito à proteção contra interferência prejudicial e não pode causar interferência em sistemas devidamente autorizados. Este equipamento não é apropriado para uso em ambientes domésticos, pois poderá causar interferências eletromagnéticas que obrigam o usuário a tomar medidas necessárias para minimizar estas interferências.

Para maiores informações, consulte o site da Anatel – <https://www.gov.br/anatel/pt-br/>

Mat.-No.	0560 1915 08
-----------------	--------------

Country	Comments
Japan	Contains Lierda S37 BLE module  201-200983 See Japan Information
South Korea	 R-R-te2-05601915 See KCC Warning

Bluetooth® Information	Feature	Values
	Bluetooth® range	up to 100m (328 feet) (free field)
	Power output	9.37dBm

KCC Warning

해당 무선 설비는 운용 중 전파혼신 가능성이 있음.

Japan Information

当該機器には電波法に基づく、技術基準適合証明等を受けた特定無線設備を装着している。