accucold

ARG2PV-CRT



22.25" x 18.5" x 23.25" (H x W x D)

Performance series 2 cu.ft. countertop glass door controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

Highlights:

Adjustable operating control range from 68 to $77^{\circ}F$ (preset to $72^{\circ}F)$

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at $72^{\circ}F$

Intelligent microprocessor digital temperature controller

Product Features:

Controlled Room Temperature Cabinet	Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at 72°F	
Purpose-built design	Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products	
+/-1.5°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensol in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Stable operation	Designed to maintain a set temperature, even when ambient room temperature is as cold as 68° F or as high as 86° F	
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +68 to +77°F	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrect with adjustable evelo	Adjustable evelo defrect exercision ensures the unit eveld temperature spikes and ice buildup	

Automatic defrost with adjustable cycle
Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle
Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

Adjustable cycle defrost operation ensures the unit avoid temperature spikes avoid ensure


Adjustable cycle defrost o

accucold

ARG2PV-CRT Specifications:

Overview	
Height of Cabinet	22.25" (57 cm)
Width	18.5" (47 cm)
Width with Door Open	18.88" (48 cm)
Depth	23.25" (59 cm)
Depth with Handle	24.75" (63 cm)
Depth with door at 90°	42.5" (108 cm)
Capacity	1.94 cu.ft. (55 L)
Defrost Type	Automatic
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.6
Voltage/Frequency	115 V AC/60 Hz
Weight	80.0 lbs. (36 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101106960
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	2
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	0.84oz.
High Side PSI	280.0
Low Side PSI	90.0
Interior Light	Yes
Temperature Range	68 to 77ºF (preset to 72ºF)
Sound Level	42.4 dB
Dimensions	

Interior Height	16.5" (42 cm)
Interior Width	15.25" (39 cm)
Interior Depth	15.75" (40 cm)
Compressor Step Height	8.25" (21 cm)
Compressor Step Width	15.25" (39 cm)
Compressor Step Depth	4.25" (11 cm)



FRONT VIEW

