

3 Roll Plate Bending(Pre Pinching Type)



SPECIFICATION

MODEL NAME	WORKING ROLL LENGTH	BENDING THICKNESS	PRE-BENDING THICKNESS	TOP ROLL DIAMETER	BOTTOM ROLL DIAMETER	MOTOR H.P.	LENGTH	HEIGHT	WIDTH
MPBD-3R-0621	2100 mm	6 mm	4 mm	160 mm	140 mm	3	3950 mm	1160 mm	1080 mm
MPBD-3R-0821	2100 mm	8 mm	6 mm	190 mm	170 mm	5	3950 mm	1160 mm	1080 mm
MPBD-3R-1021	2100 mm	10 mm	8 mm	210 mm	190 mm	10	3950 mm	1160 mm	1080 mm
MPBD-3R-1221	2100 mm	12 mm	10 mm	230 mm	210 mm	10	4030 mm	1275 mm	1370 mm
MPBD-3R-1621	2100 mm	16 mm	12 mm	270 mm	250 mm	15	4180 mm	1385 mm	1440 mm
MPBD-3R-2021	2100 mm	20 mm	16 mm	300 mm	270 mm	20	4440 mm	1630 mm	1620 mm
MPBD-3R-2521	2100 mm	25 mm	20 mm	330 mm	300 mm	20	4250 mm	1850 mm	1800 mm
MPBD-3R-3021	2100 mm	30 mm	25 mm	360 mm	330 mm	25	4500 mm	2000 mm	1900 mm
MPBD-3R-4021	2100 mm	40 mm	30 mm	390 mm	360 mm	30	4900 mm	2200 mm	12000 mm
MPBD-3R-5021	2100 mm	50 mm	40 mm	430 mm	390 mm	40	5200 mm	2500 mm	2200 mm
MPBD-3R-0626	2600 mm	6 mm	4 mm	190 mm	170 mm	5	4450 mm	1160 mm	1080 mm
MPBD-3R-0826	2600 mm	8 mm	6 mm	210 mm	190 mm	10	4450 mm	1160 mm	1080 mm
MPBD-3R-1026	2600 mm	10 mm	8 mm	230 mm	210 mm	10	4530 mm	1300 mm	1370 mm
MPBD-3R-1226	2600 mm	12 mm	10 mm	270 mm	250 mm	15	4680 mm	1350 mm	1450 mm
MPBD-3R-1626	2600 mm	16 mm	12 mm	300 mm	270 mm		5000 mm	1650 mm	1650 mm
MPBD-3R-2026	2600 mm	20 mm	16 mm	330 mm	300 mm	20	5000 mm	1850 mm	1850 mm
MPBD-3R-2526	2600 mm	25 mm	20 mm	360 mm	330 mm	25	4900 mm	1950 mm	1850 mm
MPBD-3R-3026	2600 mm	30 mm	25 mm	390 mm	360 mm	30	5400 mm	2150 mm	2000 mm
MPBD-3R-4026	2600 mm	40 mm	30 mm	430 mm	390 mm	40	6000 mm	2250 mm	2200 mm
MPBD-3R-0631	3100 mm	6 mm	4 mm	210 mm	190 mm	7.5	5000 mm	1200 mm	1100 mm
MPBD-3R-0826	3100 mm	8 mm	6 mm	230 mm	210 mm	10	5100 mm	1300 mm	1400 mm
MPBD-3R-1026	3100 mm	10 mm	8 mm	270 mm	250 mm	10	5200 mm	1400 mm	1500 mm
MPBD-3R-1226	3100 mm	12 mm	10 mm	300 mm	270 mm	15	5500 mm	1700 mm	1700 mm
MPBD-3R-1626	3100 mm	16 mm	12 mm	330 mm	300 mm	20	5700 mm	1900 mm	1900 mm
MPBD-3R-2026	3100 mm	20 mm	16 mm	360 mm	330 mm	20	5700 mm	1900 mm	1900 mm
MPBD-3R-2526	3100 mm	25 mm	20 mm	390 mm	360 mm	25	5900 mm	2000 mm	2100 mm
MPBD-3R-3026	3100 mm	30 mm	25 mm	430 mm	390 mm	30	6000 mm	2200 mm	2300 mm
MPBD-3R-4026	3100 mm	40 mm	30 mm	460 mm	420 mm	40	6200 mm	2450 mm	2400 mm
MPBD-3R-5026	3100 mm	50 mm	40 mm	510 mm	460 mm	60	6400 mm	2800 mm	2500 mm
MPBD-3R-0641	4100 mm	6 mm	4 mm	270 mm	250 mm	7.5	6200 mm	1400 mm	1500 mm
MPBD-3R-0841	4100 mm	8 mm	6 mm	300 mm	270 mm	10	6300 mm	1700 mm	1700 mm
MPBD-3R-1041	4100 mm	10 mm	8 mm	330 mm	300 mm	10	6400 mm	1900 mm	1900 mm
MPBD-3R-1241	4100 mm	12 mm	10 mm	360 mm	330 mm	15	6500 mm	1900 mm	1900 mm
MPBD-3R-1641	4100 mm	16 mm	12 mm	390 mm	360 mm	20	7000 mm	2000 mm	2000 mm
MPBD-3R-2041	4100 mm	20 mm	16 mm	430 mm	390 mm	20	7200 mm	2200 mm	2200 mm
MPBD-3R-2541	4100 mm	25 mm	20 mm	460 mm	320 mm	25	7300 mm	2500 mm	2350 mm
MPBD-3R-3041	4100 mm	30 mm	25 mm	510 mm	460 mm	30	7500 mm	2800 mm	2500 mm