



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900
708-534-3957 (FAX)

Technical Data Sheet

Product series **PVC6YNA**
Product description **Non-adhesive vinyl tape**

General Description and Typical Applications

Non-adhesive vinyl tape is the ideal "wrap mask" for plating, anodizing, wet painting, fixture wrapping or abrasive blasting. Low-cost and conformable, this material can be used in a wide variety of applications where a lack of adhesive is a requirement. Sometimes called a "dry vinyl tape."

Product Construction

Color(s) **Yellow**
Total thickness **4.0 mils**
Backing thickness **4.0 mils**
Adhesive thickness **None**
Adhesive type **None**

Product Physical Characteristics

Maximum temperature **176°F**
Minimum temperature **Not available**
Adhesion to steel **Not applicable**
Tensile strength **2000 PSI MIN**
Elongation at break **225%**
Liner thickness (if applicable) **Not applicable**

Storage, Shelf Life and additional information

Store under normal conditions of 60° to 80°F and 40 to 60% relative humidity
For best performance, use this product within 24 months from date of sale

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believes this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.