







VULCRAFT ALABAMA

7205 Gault Avenue N Fort Payne, AL 35967 256.845.2460

VULCRAFT INDIANA

6610 County Road 60 St. Joe, IN 46875 260.337.1800

VULCRAFT NEBRASKA

1601 West Omaha Avenue Norfolk, NE 68701 402.644.8500

VULCRAFT NEW YORK

621 Main Street Chemung, NY 14825 607.529.9000

VULCRAFT SOUTH CAROLINA

1501 West Darlington Street Florence, SC 29501 843.662.0381

VULCRAFT TEXAS

175 County Road 2345 Grapeland, TX 75844 936.687.4665 **VULCRAFT UTAH** 1875 West Highway 13 South Brigham City, UT 84302 435.734.9433

VULCRAFT CANADA- WEST

1709 8th Street Nisku, AB T9E 7S8 780.955.3390

VULCRAFT CANADA- EAST

1362 Osprey Drive Ancaster, ON L9G 4V5 289.443.2000





04	ABOUT US	
00	PROJECTS	
80	BIM	
09	SUSTAINABILITY	
10	GENERAL JOIST & DECK INFORMATION	
JC	DIST	
12	SPECIAL PROFILES	
14	SEAT INFORMATION	
16	FLOOR VIBRATION	
18	DUCTWORK	
19	FIRE RESISTANCE	
D	ECK	
30	DOVETAIL DECK	
32	2 CELLULAR DECK	
34	ACOUSTIC INFORMATION	
44	FIRE RESISTANCE	
S	PECIAL PRODUCTS	
56	GRATING	
58	THE ECOSPAN® COMPOSITE FLOOR SYSTEM	





OUR MISSION: GROW THE CORE | EXPAND BEYOND | LIVE OUR CULTURE

Our challenge is TO BECOME THE WORDS SAFEST STEEL COMPANY.

We live each day with **GRATITUDE** for the families, customers and partners that make our work possible.

FOCUSING ON Relationships.

Vulcraft and Verco have invested a great deal of time and resources to build companies that focus on the relationship with our customers. As a result, our companies have the highest quality of products in the industry, the expertise to complete jobs correctly, and the goal to always seek out win-win solutions. Powerful partnerships get powerful results.





A WORD ABOUT QUALITY

In the manufacture of open web steel joists and Joist Girders, there can be no compromise on quality. Your business depends on it. Our reputation and success depends on it. As the largest manufacturer of open web steel joists and Joist Girders in North America, a lot of buildings and a lot of people depend on Vulcraft for consistently high standards of quality demonstrated through reliable performance.

In the manufacture of open web steel joists and Joist Girders, Vulcraft uses high quality steel. Welding to exact specifications is the key to making structurally sound joists and is the most critical step in the entire process. All Vulcraft welders are certified in accordance with the standards of the American Welding Society. All welds are in accordance with the welding criteria specified by the Steel Joist Institute and joists and Joist Girders are manufactured to meet the loading indicated by the specifying professional.

To further ensure the quality of every weld, every Vulcraft Quality Assurance Inspector is also certified to these same high standards. To further manage quality assurance in our manufacturing processes, Vulcraft employs an ongoing program of mechanical testing that includes full scale load tests at our facilities.

As the leading Manufacturer of open web steel joists and Joist Girders in North America, Vulcraft's reputation depends on successfully managed Quality Assurance programs. That is why Quality is important at Vulcraft. You have our word on it.

Vulcraft/Verco Products have a large variety of applications within all types of architectural projects. From our traditional products like steel bar joists, steel deck and grating, to our new product systems like the Ecospan Composite Floor System and the RediCor Modular Steel Form System.

Within this document we have provided all the data for our products that the specifying architect will need. This includes, Vibration Information, Acoustical Data, Fire Ratings, and BIM Information.

In addition, we have included in-depth information about our more architecturally focused products, Special Profile Joists, Dovetail Deck, and Cellular Deck.

For additional engineering and structural information please see our Steel Joist and Joists Girders Systems Manual, and our Steel Deck Solutions Manual available for download on our website:

www.vulcraft.com

BORREGO SPRINGS LIBRARY Borrego Springs, CA









BIM

Vulcraft is pairing their proven track record of quality and service with the future of 3D modeling to give fabricators, erectors, general contractors, engineers, and architects an edge over competitors in the market. Providing customers with a detailed model that can display a replica of their building, BIM leads to confidence and peace of mind for the life cycle of the project.

Vulcraft's distinct advantages include multiple platforms, including Revit®, Tekla, and SDS/2, designed web layouts, bridging, specialty joist profiles, and seat profiles with slots.

NUBIM[®] FOR REVIT

Our NuBIM for Revit add-in allows users to specify and model all parallel chord joists and Joist Girders available from Vulcraft as well as a number of common special profile joists, Ecospan, and composite joists. Users have the ability to apply a variety of common loading conditions to all joists, as well as create load tables and diagrams. All Vulcraft and Verco deck profiles can be added to standard Revit floor and roof components through the add-in. When your project is complete, a file can be exported containing all information related to our products, which can be sent to your Vulcraft sales rep to aid in the quoting and detailing process.

NUBIM[®] FOR TEKLA

With the NuBIM for Tekla Plug-In you can now build and manage projects more effectively within Tekla Structures. Vulcraft's Joist Plug-In for Tekla Structures enables you to specify Vulcraft joists during the creation of the building model. The joist parameters from the model can then be exported directly into Vulcraft's Detailing and Design Programs.

DESIGNED JOIST

When viewing the BIM provided by Vulcraft engineers, replicas of the steel joists are laid into each aspect of the project. Simple lines, and inexplicable renderings have been replaced with steel joists crafted by Vulcraft to represent the "as-built" product that will be delivered to job sites. Joists manufactured by Vulcraft can be supplied in BIM as they are actually built and put into the field. While viewing the joists in BIM, contractors and other parties have the advantage of reviewing the actual size of the members and panel layouts.

BRIDGING COMPONENTS

To further aid the design and construction of every aspect, Vulcraft has developed a bridging component for BIM to accurately depict all structural elements. Not only does the duct work, wiring and piping have to weave around the joists, but also around the bridging elements. Having these elements in place leads to decreased errors on the job site and saves valuable time and effort by specialty contractors.

SPECIALTY JOIST PROFILES

Vulcraft engineers and designers have taken joists to another level offering specialty joist profiles such as bowstrings, arches, scissors joists, double pitch, single pitch, and gable joists. Eliminating guesswork around specialty profiles reduces on-site error, saving money and valuable time and effort. Utilizing these specialty joists in BIM also enhances design review with customers.

LINKING COMPONENTS

Vulcraft can provide a number of things in BIM to benefit individual users. However, when used with an Integrated Project Delivery (IPD) system, BIM leverages the power of modeling to facilitate collaborative decision-making. IPD brings key construction management, fabricators and product manufacturing expertise together with design professionals and the owner earlier in the process. This produces a design that is optimized for quality, aesthetics, constructibility, affordability, timeliness, and seamless flow into lifecycle management.

To download Vulcraft's BIM tools and for additional information on Vulcraft's BIM capabilities, please visit: https://vulcraft.com/DesignTools/#bim-tools



SUSTAINABILITY



For more than 50 years, Nucor has been built on a sustainable model of recycling steel to produce new steel and steel products. Every Nucor steel mill uses an electric arc furnace (EAF) that melts recycled scrap and turns it into new steel products. EAFs are far less carbon-intensive and more energy-efficient than traditional blast furnace steelmaking, which makes steel by burning iron ore and coking coal.

Nucor is extending beyond its fence line to lower its carbon footprint and is committed to increasing the utilization of renewable energy. Nucor has invested in multiple virtual power purchase agreements to lower its carbon footprint and build partnerships to support the development of new clean energy infrastructure.

Nucor continues to develop product-specific Environmental Product Declarations and Health Product Declarations for all its steel products. Additionally, Nucor will work individually with any customer requiring product life cycle inventory data or other environmental footprint information

EMBODIED CARBON

Embodied carbon values for Vulcraft products can be found in the joists and deck Environmental Product Declarations (EPDs), available at https://www.nucor.com/sustainability/#resources. EPDs summarize the results of a cradle-to-gate life-cycle assessment, which includes the greenhouse gas emissions derived from raw material supply, transport, and manufacturing of steel joists and deck. The resulting global warming potential (GWP), along with other impact category indicators, can be found in the EPDs. Facility-specific GWP values are also available.

RECYCLED MATERIAL CONTENT

JOISTS/STRUCTURAL PRODUCTS - The bar steel for Vulcraft joists is typically obtained from one of the ten (10) Nucor bar mills. The average recycled content percentage for the Vulcraft joists is 97.0%. Specific project information is available from facility representatives.

DECK – Steel for decking produced by Vulcraft facilities is typically obtained from one of the seven (7) Nucor sheet mills. The Vulcraft deck products contain 56.5% recycled steel. Verco Decking, Inc. may obtain steel from sources outside of Nucor that may contain lower amounts of recycled content. Specific product information regarding Verco Decking, Inc. and individual Vulcraft locations is available from facility representatives.

All the steel produced by Nucor is 100% recyclable at the end of its useful life. Additional industry information is available online through the American Iron and Steel Institute at <u>https://www.steel.org/sustainability/.</u>

LEED INFORMATION

Nucor can provide a variety of documentation to help projects satisfy LEED credit requirements. Nucor publishes a Corporate Sustainability Report bi-annually which can be found here - <u>https://www.nucor.com/sustainability</u>. Additional LEED and/or other environmental information regarding specific Nucor Corporation products for a customer's specific order is available from facility representatives or the corporate office. A current contact list can be found here <u>https://www.nucor.com/locations/</u>.

REGIONAL MATERIALS - LEED 2009 Credit 5; LEED v4.1 Local Sourcing of Raw Materials

Nucor tracks the origin of scrap shipments to our mills. Nucor can approximate the amount of scrap recovered from any project site region. Nucor owns steel and steel products manufacturing facilities throughout the US that are often within 500 miles of the project site.

GENERAL JOIST INFORMATION

Standard Steel Joist Institute open web steel joists are designed for simple span uniform loads which result in a linearly sloped shear diagram for web forces and a parabolic moment diagram for chord forces. Projects often require that the open web joist support loads that are non-uniform or concentrated loads which alter the shape of the shear and moment diagrams. When specifying joists for these loads, the specifying professional should first attempt to specify a larger standard joist or possibly a KCS series joist (K-series Constant Shear). The interior webs for KCS joists are designed for 100% stress reversal and the chords are designed for a flat positive bending moment. The specified joist must have adequate moment and shear resistance throughout the entire length of the joist.



Current Series are K, KCS, LH, & DLH For Historic Joist Information please visti the publications section of <u>www.steeljoist.org</u> to find "90 Years of Open Web Steel Joist Construction"

As can be seen, this designation clearly provides the breakdown necessary for the proper application of the building code required load combinations. In addition, for LH and DLH joists it allows specification of depths not included in the standard load tables. The total load / live load format can also be used for specification of panel point loads on Joist Girders and for the specification of concentrated loads applied to the joists.

For complete joist loading specification information please see the Steel Joists & Joist Girder Systems Manual available in the literature section of www.vulcraft.com.

JOIST SEAT & CHORD WIDTHS

For maximum joist seat & chord widths please see the Economic Joist Guide in the Steel Joists & Joist Girder Systems Manual available in the literature section of <u>www.vulcraft.com</u>.



Steel roof and floor decks have long been recognized for their economy because of their light weight and high strength-to-weight ratio. They provide a durable and attractive roof or floor system for fast all-weather construction. Steel decks also provide excellent lateral diaphragm action thus reducing the necessity for structural bracing and their incombustible nature assures architects, engineers, and owners of excellent fire ratings.

ROOF DECK

		Long Span	Clean		Sound	Reconfigurable
Deck Profile	Standard Span	(≥10′)	Appearance	Fire Rated	Absorbing	Hangers
1.5B, 1.5BI, 1.5PLB	✓			\checkmark		
3N, 3NI, 3PLN		\checkmark		\checkmark		
1.5BA, 1.5BIA	✓			\checkmark	\checkmark	
3NA, 3NIA, 3PLNA		\checkmark		\checkmark	\checkmark	
2.0D		\checkmark	✓	✓		✓
3.5D		\checkmark	✓	✓		✓
2.0DA		\checkmark	\checkmark	\checkmark	\checkmark	✓
3.5DA		\checkmark	✓	\checkmark	\checkmark	✓

FLOOR DECK

			Clean		Reconfigurable
Deck Profile	Standard Span	Long Span (≥10′)	Appearance	Fire Rated	Hangers
1.5VL, 1.5VLI, 1.5VLR	✓			\checkmark	
2VLI		\checkmark		\checkmark	
3VLI		\checkmark		\checkmark	
2.0D FormLok®		\checkmark	\checkmark	\checkmark	\checkmark
3.5D FormLok®		\checkmark	\checkmark	\checkmark	\checkmark

NON-COMPOSITE FLOOR DECK

Non-Composite Floor Deck Profiles: 0.6C, 1.0C, 1.3C, 1.5C, 2C, 3C

FINISHES

Vulcraft offers a selection of finishes: primer painted over cold-rolled or galvanized, galvanized, or black (uncoated).

Primer painted: Prior to applying a baked-on acrylic medium gray or white primer, the cold-rolled or galvanized sheet is chemically cleaned and pre-treated.

Galvanized: Galvanized decks are supplied from mill coated sheets and are offered in two standard coated finishes.

NON-STANDARD CONFIGURATIONS

In addition to the standard configurations Vulcraft can also provide the following joist configurations:



In the fabrication of joists, a sufficient end depth must be provided. The appropriate end depth varies with the size, shape, and loading of the joist. The end depth is the distance between the top chord and the bottom chord or the projection of the bottom chord near the center line of the support. End depth requirements increase for bottom-chord-bearing joists and sloped joists. An absolute minimum end depth of 12" must be provided in all cases, with 18" minimum end depth recommended in most cases and for large joists it will increase. Contact Vulcraft for minimum end depth requirements.

Note that both Scissor and Arched Chord type joists require special attention for their supports due to the horizontal deflections. These joists can be designed with either pinned end restraints at both ends or pinned on one end with a roller on the other. The pinned/pinned condition may result in significant horizontal forces being applied to the structure. Analyzing the effect of increasing the stiffness of these joists shows little change in horizontal force magnitude with significant increase in stiffness. The pinned/roller condition requires that the roller bearing condition allow for horizontal movement. In this case increasing the joist stiffness does affect the horizontal displacement.

PLEASE <u>CONTACT</u> EITHER YOUR LOCAL DISTRICT SALES OFFICE OR THE NEAREST VULCRAFT MANUFACTURING FACILITY FOR LIMITATIONS IN DEPTH OR LENGTH.

12

SPECIAL PROFILES



SLOPED SEAT REQUIREMENTS FOR SLOPES 3/8":12 AND GREATER K-SERIES OPEN WEB STEEL JOISTS (VARIES FROM SJI CODE OF STANDARD PRACTICE)

Standard joist bearing seat depths (K=2.5" LH=5" JG=7.5") are based on typical chord sizes and not greater than 1/4":12 top chord slopes. Bearing length, in some cases, will also factor in to the joist seat depth. In general when slopes increase, so must the bearing seat depth. Special profile joists all require non-typical bearing seat depths due to the slope of the top chord. These tables were developed to clarify the bearing seat depth requirements of non-typical joists.

LOW END W/OUT TOP CHORD EXTENSIONS	HIGH END W/OUT TOP CHORD EXTENSIONS		MINIMUM HIGH END SEAT DEPTH "d"
END OF SEAT	END OF SEAT	SLOPE "X":12	VULCRAFT RECOMMENDED FOR SPECIAL CONDITIONS (8)
	CHART ⁽²⁾	3/8	5″
		1/2	5″
	4"	1	5″
4"-4"		1 1/2	5 1/2″
	& SUPPORT STRUCTURE	2	5 1/2″
LOW END W/ TOP CHORD EXTENSIONS	HIGH END W/ TOP CHORD EXTENSIONS	2 1/2	5 1/2″
		3	6"
	SLOPE 12" 21/2"(4)	3 1/2	6"
SLOPE 12"		4	6"
	SEE SEE	4 1/2	6 1/2"
		5	6 1/2"
		5 1/2	7"
	STD.	6	7"
	& SUPPORT STRUCTURE	> 6:12	SEE NOTE (9)

NOTES:

- 1. Depths shown are the minimum required for manufacturing of sloped seats. Depths may vary depending on actual bearing conditions.
- 2. $d = 1/2 + 2.5/\cos\theta + 4\tan\theta$ (Rounded up to the nearest 1/2")
- 3. Clearance must be checked on outer edge of support. Increase bearing depths as required to allow passage of 21/2" deep extension.
- 4. If extension depth greater than 2 1/2" is required, increase bearing depths accordingly.
- 5. If slope is 1/4:12 or less, sloped seats are not required.
- 6. Required bearing seat depth is determined at END OF SEAT.
- 7. Also, refer to SJI Specification 5.4 for special considerations of joist end reaction location.
- 8. For extensions greater than 1'-6" or when net uplift reactions exceed the values listed on page 14.
- 9. $d = 2 + 2.5/\cos\theta + 4\tan\theta$ (Rounded up to the nearest 1/2")
- 10. 4 1/2" for special conditions per Note 8
- 11. 3" for special conditions per Note 8



SLOPED SEAT REQUIREMENTS FOR SLOPES 3/8":12 AND GREATER LH- AND DLH-SERIES OPEN WEB STEEL JOISTS (VARIES FROM SJI CODE OF STANDARD PRACTICE)

Standard joist bearing seat depths (K=2.5" LH=5" JG=7.5") are based on typical chord sizes and not greater than 1/4":12 top chord slopes. Bearing length, in some cases, will also factor in to the joist seat depth. In general when slopes increase, so must the bearing seat depth. Special profile joists all require non-typical bearing seat depths due to the slope of the top chord. These tables were developed to clarify the bearing seat depth requirements of non-typical joists.

LOW END W/OUT TOP CHORD EXTENSIONS	HIGH END W/OUT TOP CHORD EXTENSIONS		MINIMUM HIGH END SEAT DEPTH "d"
END OF SEAT	END OF SEAT	SLOPE "X":12	VULCRAFT RECOMMENDED FOR SPECIAL CONDITIONS (9)
	CHẠRT ⁽²⁾	3/8	7 1/2"
5 " (12)		1/2	7 1/2"
	6"	1	8"
6"	STD.	11/2	8"
STD.	INSIDE EDGE OF BRG. SEAT & SUPPORT STRUCTURE	2	8 1/2″
LOW END W/ TOP CHORD EXTENSIONS	HIGH END W/ TOP CHORD EXTENSIONS	2 1/2	8 1/2"
		3	9"
	12" 5"(4)	3 1/2	9"
SLOPE 12"	SLOPE "X"	4	9 1/2″
"X"	e "d" SEE	4 1/2	10″
		5	10″
5" ⁽⁴⁾ 5 1/2" ⁽³⁾⁽¹⁾		5 1/2	10 1/2″
	$\left -\frac{6"}{\text{STD.}} \right $	6	11″
EDGE OF SUPPORT STRUCTURE (3)	INSIDE EDGE OF BRG. SEAT & SUPPORT STRUCTURE	> 6:12	SEE NOTE (10)

NOTES:

- 1. Depths shown are the minimum required for manufacturing of sloped seats. Depths may vary depending on actual bearing conditions.
- 2. $d = 1/2 + 5/\cos\theta + 6\tan\theta$ (Rounded up to the nearest 1/2'')
- 3. Clearance must be checked on outer edge of support. Increase bearing depths as required to allow passage of 5" deep extension.
- 4. If extension depth greater than 5" is required, increase bearing depths accordingly.
- 5. Add 2 1/2" to seat depth at 18 thru 25 chord section numbers. Consult with Vulcraft for information when TCXs are present.
- 6. If slope is 1/4:12 or less, sloped seats are not required.
- 7. Required bearing seat depth is determined at END OF SEAT.
- 8. Also, refer to SJI Specification 5.4 for special considerations of joist end reaction location.
- 9. For extensions greater than 2'-6".
- 10. $d = 2 + 5/\cos\theta + 6\tan\theta$ (Rounded up to the nearest 1/2")
- 11. 7" for special conditions per Note 9
- 12. 6" for special conditions per Note 9

FLOOR VIBRATION

Floor vibration due to human activity occurs, in varying degrees, in all types of building construction. Unlike steady state vibration due to machinery, which can be isolated, vibration due to human occupancy is inconsistent in both amplitude and frequency and must be controlled by proper design of the elements supporting the floor.

The Steel Joist Institute and Nucor Research and Development have been studying this phenomenon for years. Laboratory research continues to be performed along with gathering measurements on numerous buildings, exhibiting both good and bad characteristics, using seismic recording instruments. AISC Design Guide 11 "Vibrations of Steel-Framed Structural Systems Due to Human Activity" Second Edition and SJI Technical Digest 5 "Vibration of Steel Joist Concrete Floor Slabs" discuss in detail methods for calculating vibration characteristics of open web steel joist supported floors. Vibration of Vulcraft steel joist/steel deck supported concrete floors can easily be checked for walking excitation utilizing Vulcraft's new Vibration Analysis Tool, <u>https://www.vulcraft.com/design-tools/</u>.

The clear majority of floors, including those utilizing steel joists, do not exhibit floor vibrations severe enough to be considered objectionable. However, human sensitivity to vibratory motion varies, and a satisfactory framing solution is dependent upon the sound judgment of qualified design professionals.

Floor vibration is measured in terms of acceleration, displacement amplitude, and frequency. These factors are not objectionable to all people at the same level since human sensitivity and tolerance for vibration varies.

The following observations are recommended only as a guide to the design professional:

OPEN FLOOR AREAS are often subject to vibration issues. Modern "electronic offices" tend to have lower live loading and lower damping. Partitions, file cabinets, book stacks, heavy furnishings, and even crowds of people provide additional damping and reduce vibration levels.

PARTITIONS increase damping more than any other element and often eliminate vibration issues. They are effective either above or below a floor as long as they are full height partitions connected to the floor above and below the partition. Consideration should be given to potential changes in occupancy of the floor over the life of the building.

SUPPORT FRAMING BEAMS can contribute to floor vibration. The natural frequency and amplitude of both the joists and supporting Joist Girders or hot rolled girders must be calculated. In this manner, the resulting system acceleration, displacement, and frequency can be determined.

TYPE of STEEL JOIST END CONNECTION to a girder can significantly affect the natural frequency and the effective mass of floor framing systems subjected to walking motion. Joists fabricated with flush framed top chord bolted connections, Ecospan® flush joist seats, or stiffened top chord bearing seats have been shown to reduce floor vibration versus standard top chord bearing seats.

BRIDGING of all standard types provides equal floor vibrational characteristics.

THICKER FLOOR SLABS can be an economical solution for controlling floor vibrations. The additional thickness increases floor system stiffness transverse to the joists, often improving vibration characteristics. The additional mass of the system can also reduce vibration levels.



WIDER JOIST SPACINGS improve vibrational characteristics only when combined with thicker floor slabs. The resulting increase in joist size does not contribute significantly. When used with a thicker slab, greater resistance to vibration can be achieved, and, since fewer pieces must be installed, may be more economical.

NON-COMPOSITE JOISTS are considered to be fully composite joists in vibration analyses. Human-induced loads typically cause mid-bay displacement amplitudes smaller than 0.01 in. - implying very low horizontal shears between the joists and the slab. Also, deck fasteners, including spot welds and screws, provide enough slip resistance to warrant using the composite transformed moment of inertia in vibration analyses.

LONGER FLOOR SPANS have many advantages over shorter spans both in construction and vibrational response. There are many long spanning joist supported floors that have satisfactory vibration performance.

INCREASING JOIST STIFFNESS beyond that required to meet the live load deflection limitations can be beneficial when only a small decrease in predicted acceleration is needed. Increase the stiffness of the joist or Girder (whichever has the lowest frequency) until the criterion is met. When the joist and girder have the same frequency, increase the stiffness of both until the required vibration criteria is achieved.

PC - based software for the evaluation of joist supported floor systems subjected to walking, rhythmic, or sensitive equipment / occupants is available from: STRUCTURAL ENGINEERS, INC 537 Wisteria Drive Radford, VA 24141 Phone (540) 731-3330 www.floorvibe.com

CONCLUSIONS

Partitions will usually eliminate vibration issues. When a floor cannot have partitions, changing the type of joist end connection, increasing the slab thickness, increasing the joist spacing, and/or increasing the joist or girder stiffness can be economical and effective ways to reduce vibrations.

For more information refer to the Steel Joist Institute Technical Digest No. 5 "Vibration of Steel Joist-Concrete Slab Floors" and the AISC Steel Design Guide 11 "Vibrations of Steel-Framed Structural Systems Due to Human Activity" Second Edition.

DEFINITIONS

Acceleration - is the primary measure of vibration level used in the assessment of human comfort, and is usually expressed as a percentage of the acceleration due to gravity.

Frequency - is the number of cycles per second or Hz.

Damping - is the loss of energy over time in a vibrating system and is usually presented as a percent of critical damping.

Critical Damping - is the damping required to bring a displaced system to rest without oscillation.

DUCTWORK

Joist Depth (in.)	Panel Length (in.)	Round (in.)	Square (in.)	Rectangular (in. x in).
10	19*	5	4	3x6
12	19*	6	5	4x7
14	19*	7	6	5x7
16	19*	8	6	6x7
18	24*	9	7	6x9
20	24*	10	8	7x9
22	24*	10	9	8x9
24	24*	11	9	9x9
18	48	10	8	6x18
20	48	10	8	7x18
22	48	10	9	8x18
24	48	12	10	8x19
26	48	15	12	9x19
28	48	16	13	10x18
30	48	17	14	11x19
32	64	20	16	11x25
34	68	22	18	12x28
36	72	24	18	13x29
38	76	25	20	13x30
40	80	26	22	14x32
42	84	27	22	16x34
44	88	28	23	17x36
46	92	30	24	18x36
48	96	32	26	19x40
50	100	33	27	20x42

ALLOWABLE DUCTWORK

* rod joist

VIERENDEEL OPENINGS

For cases in which larger openings in joists are required, Vulcraft can provide Vierendeel Openings. Please contact your Vulcraft Sales Representative for more information about Vierendeel options.





18

The use of steel joists and Joist Girders in buildings frequently requires the use of fire rated systems of construction. The fire ratings of systems are expressed in hours ranging from one to four hours. The required rating for a roof-ceiling or floor-ceiling assembly in a building is established by the Building Code and is a function of the building's occupancy, area and height. The ratings are to be met using rated assemblies meeting or exceeding the required rating. Such assemblies typically consist of steel deck, structural members, fireproofing protection, and other appropriate materials. Assemblies are constructed and tested according to the methods and acceptance criteria described in ASTM Standard E119, "Standard Test Methods for Fire Tests of Building Construction and Materials" (ASTM, 2018).

The purpose of fire tests is to establish the relative performance of different assemblies under identical laboratory test conditions. Most fire tests over the years have been conducted by Underwriters Laboratories Inc. and descriptions of the rated assemblies are compiled in the UL "Fire Resistance Directory." It is important when applying rated assemblies to a project that all the features of the rated assembly be carried over into the design, or it will not be valid and can delay the issuance of a Building Permit.



			Built Up Roof		Maximum	Minimum			
Restrained Assembly Rating	Protection Material	Minimum Joist Size	Deck Material	Insulation	Joist Spacing (in.)	Primary Support Member	UL Design Number	Deck Types	
		12K1	22 MSG Min.	Fiber Board	84	W8 x 17	P201	1.5B,1.5BI	
		10K1	26 MSG Min.	Fiber Board	48	W6 x 12	P202	None	
		10K1	26 MSG Min.	Fiber Board	48	20G@13plf	P211	1.5B,1.5BI	
		12K3	28 MSG Min.	Fiber Board	72	20G@13plf W8 x 17	P214	1.5B,1.5BI	
	Evpaged Crid	12K1	26 MSG Min.	Fiber Board	72	20G@13plf W6 x 12	P225	1.5B,1.5BI,3N, 3NI	
I Ar.	Exposed Grid	12K3	24 MSG Min.	Building Units	48	NS	P227	1.5B,1.5BI	
		12K3	26 MSG Min.	Fiber Board	72	20G@13plf W6 x 12	P230	1.5B,1.5BI	
		12K1	26 MSG Min.	Insulating Concrete	48	20G@14plf* W8 x 15	P231	1.0C, 1.3C, 1.5C	
		12K3	24 MSG Min.	Foamed Plastic	72	W8 x 15	P235	1.5B,1.5BI	
		10K1	28 MSG Min.	Insulating Concrete	72	20G@13plf W8 x 15	P246	0.6C,1.0C, 1.3C, 1.5C	

			Built Up Roof		Maximum	Minimum		
Restrained Assembly Rating	Protection Material	Minimum Joist Size	Deck Material	Insulation	Joist Spacing (in.)	Primary Support Member	UL Design Number	Deck Types
		12K5	26 MSG Min.	Fiber Board	48	W6 x 12	P250	1.5B,1.5BI
		12K1	28 MSG Min.	Insulating Concrete	72	20G@13plf W6 x 12	P251	0.6C,1.0C, 1.3C, 1.5C
		10K1	22 MSG Min.	Fiber Board	72	W6 x 12	P254	1.5B,1.5BI
		10K1	28 MSG Min.	Insulating Concrete	72	W8 x 15	P255	0.6C,1.0C, 1.3C, 1.5C
		10K1	24 MSG Min.	Fiber Board	72	NS	P259	1.5B,1.5BI
		12K1	28 MSG Min.	Insulating Concrete	72	20G@13plf W6 x 12	P261	0.6C,1.0C, 1.3C, 1.5C
1 Hr.	Exposed Grid	12K1	26 MSG Min.	Insulating Concrete	72	W8 x 15	P264	1.0C, 1.3C, 1.5C
		10K1	Metal Roof Deck Panels	Batts and Blankets	60	NS	P265	Metal Roof Panels
		10K1	26 MSG Min.	Fiber Board	48	W6 x 16	P267	1.0C, 1.5C
		10K1	Metal Roof Deck Panels	Batts and Blankets	60	NS	P268	Metal Roof Panels
		12K1	26 MSG Min.	Insulating Concrete	72	20G@14plf* W8 x 15	P269	0.6C,1.0C, 1.3C, 1.5C
	Fiber Board	10K1	24 MSG Min.	Fiber Board	NS	W6 x 16	P301	1.5B,1.5BI
		10K1	22 MSG Min.	Fiber Board	48	NS	P302	1.5B,1.5BI
		10K1	22 MSG Min.	Fiber Board	NS	W6 x 16	P303	1.5B,1.5BI
1 Hr.	Gypsum Board	12K3	26 MSG Min.	Insulating Concrete	60	W8 x 24	P509	1.3C, 1.5C
	oypson board	12K3	24 MSG Min.	Fiber Board	72	20G@13plf W8 x 13	P510	1.5B,1.5BI
		10K1	22 MSG Min.	Fiber Board	72	20G@13plf	P514	1.5B,1.5BI
		10K1	20 MSG Min.	Fiber Board	48	NS	P519	1.5B,1.5BI
		12K1	26 MSG Min.	Fiber Board	72	20G@13plf W6 x 12	P225	1.5B,1.5BI,3N, 3NI
		12K3	24 MSG Min.	Building Units	48	NS	P227	1.5B,1.5BI
1 1/2 Hr.	Exposed Grid	12K3	26 MSG Min.	Fiber Board	48	20G@13plf W6 x 12	P230	1.5B,1.5BI
		12K1	26 MSG Min.	Insulating Concrete	48	20G@14plf* W8 x 24	P231	1.0C, 1.3C, 1.5C
		12K5	26 MSG Min.	Fiber Board	48	W6 x 12	P250	1.5B,1.5BI



FIRE RESISTANCE: ROOF

			Built Up Roof		Maximum	Minimum			
Restrained Assembly Rating	Protection Material	Minimum Joist Size	Deck Material	Insulation	Joist Spacing (in.)	Primary Support Member	UL Design Number	Deck Types	
		12K1	28 MSG Min.	Insulating Concrete	72	20G@13plf W6 x 12	P251	0.6C,1.0C, 1.3C, 1.5C	
1 1/2 Hr.		10K1	24 MSG Min.	Fiber Board	72	NS	P259	1.5B,1.5BI	
	Expand Crid	10K1	Metal Roof Deck Panels	Batts and Blankets	60	NS	P265	Metal Roof Panels	
	Exposed Grid	10K1	20 MSG Min.	Fiber Board	48	NS	P266	1.5B,1.5BI	
		10K1	Metal Roof Deck Panels	Batts and Blankets	60	NS	P268	Metal Roof Panels	
		12K1	26 MSG Min.	Insulating Concrete	72	20G@14plf* W8 x 24	P269	0.6C,1.0C, 1.3C, 1.5C	
	Fiber Board	10K1	24 MSG Min.	Fiber Board	NS	W6 x 16	P301	1.5B,1.5BI	
	Metal Lath	12K5	22 MSG Min.	22 MSG Min. Fiber Board		NS	P404	1.5B,1.5BI	
	Gypsum Board	12K3	24 MSG Min.	Fiber Board	72	20G@13plf W8 x 13	P510	1.5B,1.5BI,3N, 3NI	
		10K1	24 MSG Min.	Fiber Board	72	W6 x 12	P237	1.5B,1.5BI	
	Exposed Grid	12K1	28 MSG Min.	Insulating Concrete	72	20G@13plf W6 x 12	P251	0.6C,1.0C, 1.3C, 1.5C	
		10K1	20 MSG Min.	Fiber Board	48	NS	P266	1.5B,1.5BI	
2 Hr	Fiber Board	10K1	24 MSG Min.	Fiber Board	NS	W6 x 16	P301	1.5B,1.5BI	
2111.	Metal Lath	12K5	22 MSG Min.	Fiber Board	72	NS	P404	1.5B,1.5BI	
		10K1	22 MSG Min.	Fiber Board	72	20G@13plf	P514	1.5B,1.5BI	
	Gypsum Board	10K1	20 MSG Min.	Fiber Board	48	NS	P519	1.5B,1.5BI	
		14K1	26 MSG Min.	Insulating Concrete	66	NS	P520	1.0C, 1.3C, 1.5C	
3 Hr.	Metal Lath	10K1	28 MSG Min.	Insulating Concrete	48	NS	P405	0.6C,1.0C, 1.3C, 1.5C	
1 Hr	SAFRM	10K1	22 MSG Min.	Building Units	NS	NS	P822	NA	
	SPAT NIM	12K3	22 MSG Min.	Fiber Board	NS	W8 x 20	P824	1.5B,1.5BI	
1 Hr. and 1-1/2 Hr.	SAFRM	12K5	28 MSG Min.	Insulating Concrete	96	W6 x 16	P919	1.5B,1.5BI,3N, 3NI	
1-1/2 Hr. and 2 Hr.	SAFRM	10K1	22 MSG Min.	Building Units	NS	W6 x 16	P728	1.5B,1.5BI	

			Built Up Roof		Maximum	Minimum			
Restrained Assembly Rating	Protection Material	Minimum Joist Size	Deck Material	Insulation	Joist Spacing (in.)	Primary Support Member	UL Design Number	Deck Types	
		14K4	22 MSG Min.	Fiber Board	NS	20G@13plf W6 x 16	P701	1.5B,1.5BI,3N, 3NI	
		14K4	22 MSG Min.	Fiber Board	NS	20G@13plf W6 x 16	P711	1.5B,1.5BI,3N, 3NI	
		12K3	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P717	1.5B,1.5BI,3N, 3NI	
		10K1	22 MSG Min.	Foamed Plastic	NS	20G@13plf W8 x 28	P725	1.5B,1.5BI,3N, 3NI	
		10K1	22 MSG Min.	Fiber Board	NS	20G@13plf W6 x 16	P726	1.5B,1.5BI,3N, 3NI	
		14K4	22 MSG Min.	Fiber Board	NS	20G@13plf W6 x 16	P734	1.5B,1.5BI,3N, 3NI	
		14K4	22 MSG Min.	Fiber Board	NS	20G@13plf W6 x 16	P736	1.5B,1.5BI,3N, 3NI	
		10K1	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P739	1.5B,1.5BI,3N, 3NI	
		10K1	22 MSG Min.	Fiber Board	NS	W6 x 16	P740	1.5B,1.5BI,3N, 3NI	
		10K1	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P743	1.5B,1.5BI,3N, 3NI	
		12K3	22 MSG Min.	Fiber Board	NS	20G@13plf W6 x 16	P801	1.5B,1.5BI,3N, 3NI	
1 Hr., 1 1/2 Hr	SAEDM	10K1	22 MSG Min.	Fiber Board	NS	20G@13plf W6 x 16	P815	1.5B,1.5BI,3N, 3NI	
and 2 Hr.	SALIN	10K1	22 MSG Min.	Fiber Board	NS	W6 x 16	P816	1.5B,1.5BI,3N,3NI	
		10K1	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P819	1.5B,1.5BI,3N, 3NI	
		10K1	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P825	1.5B,1.5BI	
		10K1	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P827	1.5B,1.5BI,3N,3NI	
		12K1	22 MSG Min.	Fiber Board	NS	20G@13plf W8 x 20	P828	1.5B,1.5BI,3N,3NI	
		10K1	28 MSG Min.	Insulating Concrete	NS	20G@13plf W8 x 10	P902	1.5B,1.5BI,3N, 3NI	
		10K1	28 MSG Min.	Insulating Concrete	NS	W8 x 10	P907	1.5B,1.5BI,3N, 3NI	
		10K1	28 MSG Min.	Insulating Concrete	NS	20G@13plf W8 x 10	P908	1.5B,1.5BI,3N, 3NI, 2.0D, 3.5D	
		10K1	28 MSG Min.	Insulating Concrete	NS	W8 x 10	P920	1.5B,1.5BI,3N, 3NI	
		12K5	28 MSG Min.	Insulating Concrete	NS	20G@13plf W8 x 10	P921	1.5B,1.5BI,3N, 3NI, 2.0D, 3.5D	
		10K1	28 MSG Min.	Insulating Concrete	NS	W6 x 16	P922	1.5B,1.5BI,3N, 3NI	
		10K1	28 MSG Min.	Insulating Concrete	NS	20G@13plf W8 x 10	P923	1.5B,1.5BI,3N, 3NI	

FIRE RESISTANCE: ROOF

			Built Up Roof		Maximum	Minimum		
Restrained Assembly Rating	Protection Material	Minimum Joist Size	Deck Material	Insulation	Joist Spacing (in.)	Primary Support Member	UL Design Number	Deck Types
		10K1	28 MSG Min.	Insulating Concrete	NS	20G@13plf W8 x 10	P925	0.6C,1.0C,1.3C,1.5C,2C,3C,1.5B, 1.5BI,3N, 3NI
		12K5	28 MSG Min.	Insulating Concrete	NS	W8 x 10	P926	0.6C,1.0C,1.3C,1.5C,2C,3C,1.5B, 1.5BI,3N, 3NI
1 Hr.,		14K4	28 MSG Min.	Insulating Concrete	NS	20G@13plf W8 x 10	P927	0.6C,1.0C,1.3C,1.5C,2C,3C,1.5B, 1.5BI,3N, 3NI
and 2 Hr.	SAFRIM	12K5	28 MSG Min.	Insulating Concrete	NS	20G@13plf W8 x 10	P928	0.6C,1.0C,1.3C,1.5C,2C,3C,1.5B, 1.5BI,3N, 3NI
		12K3	28 MSG Min.	Insulating Concrete	NS	20G@13plf W8 x 10	P929	0.6C,1.0C,1.3C,1.5C,2C,3C,1.5B, 1.5BI,3N, 3NI
		10K1	28 MSG Min.	Insulating Concrete	NS	W6 x 16	P936	0.6C,1.0C,1.3C,1.5C,2C,3C,1.5B, 1.5BI,3N, 3NI
	SAFRM	12K3	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P718	1.5B,1.5BI
2 Hr.		12K3	22 MSG Min.	Foamed Plastic	NS	20G@13plf W6 x 16	P720	1.5B,1.5BI
		12K3	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P729	1.5B,1.5BI
		10K1	22 MSG Min.	Foamed Plastic	NS	20G@13plf W6 x 16	P719	1.5B,1.5BI,3N, 3NI
		10K1	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P722	1.5B,1.5BI
1 Hr., 1-1/2 Hr.	SAEDM	10K1	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P723	1.5B,1.5BI,3N, 3NI
2 Hr. and 3 Hr.	SAFRM	10K1	22 MSG Min.	Foamed Plastic	NS	W8 x 28	P732	1.5B,1.5BI,3N, 3NI
		10K1*,16K2	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P733	1.5B,1.5BI
		10K1*	22 MSG Min.	Foamed Plastic	NS	W6 x 16	P826	1.5B,1.5BI

			Concrete		Maximum	Minimum		
Restrained Assembly Rating	Protection Material	Minimum Joist Size	Minimum Thickness (in.)	Туре	Joist Spacing (in.)	Primary Support Member	UL Design Number	Deck Types
	Acoustical	12K1, 18LHO2	2.5	LW,NW	NL	20G@13plf W8 x 15	D216, D219	1.5VL, 1.5VLI, 2VL, 3VL, 2VLP, 3VLP
		10K1	2.5	NW	48*	20G@14plf W6 x 12	G205	0.6C, 1.0C, 1.3C, 1.5C
1 Hr.	Exposed Grid	10K1	2.0	NW	72	W6 x 12	G208	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	48*	20G@14plf W6 x 12	G256	0.6C, 1.0C, 1.3C, 1.5C
	Gypsum Board	10K1	2.5	NW	48	W8 x 24	G548	1.0C
	Acoustical	12K1 18LUO2	25		NI	20G@13plf	D216	1.5VLI, 2VL, 3VL, 2VLP, 3VLP
	ACOUSTICAL	IZKI, IOLHUZ	2.0		INL	W8 x 15	D219	1.5VL, 1.5VLI, 2VL, 3VL, 2VLP, 3VLP
- 11/2 Hr.	Gypsum Board	12K1, 18LHO2	2.5	NW	NL	20G@20plf W8 x 28	D502	1.5VL, 1.5VLI, 2VL, 3VL, 2VLP, 3VLP
		10K1	2.5	NW	24 (48)	20G@13plf W6 x 12	G2O3	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	48*	20G@14plf W6 x 12	G205	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.0	NW	72	W6 x 12	G208	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	24 (48)	W6 x 12	G213	0.6C, 1.0C, 1.3C, 1.5C
	Exposed Grid	10K1	2.5	NW	24 (48)	20G@13plf W8 x 31	G228	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.0	NW	24 (48)	20G@13plf W8 x 24	G229	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	24 (48)	20G@13plf W6 x 12	G243	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	24 (48)	20G@13plf W8 x 31	G268	0.6C, 1.0C, 1.3C, 1.5C
	Gypsum Board	12K1	2.0	NW	24 (48)	NS	G502	0.6C, 1.0C, 1.3C, 1.5C
	Acoustical	12K1 18I HO2	25	I W NW	NI	20G@13plf	D216	1.5VLI, 2VL, 3VL, 2VLP, 3VLP
	Accosticat		2.5			W8 x 15	D219	1.5VL, 1.5VLI, 2VL, 3VL, 2VLP, 3VLP
	Gypsum Board	12K1, 18LHO2	2.5	NW	NL	20G@20plf W8 x 28	D502	1.5VL, 1.5VLI, 2VL, 3VL, 2VLP, 3VLP
		10K1	2.25	NW	24 (48)	W6 x 25	G023	0.6C, 1.0C, 1.3C, 1.5C
2 Hr.	Concealed Grid	8K1	2.5	NW	24 (48)	20G@13plf W8 x 20	G031	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	30 (48)	20G@13plf W10 x 21	G036	0.6C, 1.0C, 1.3C, 1.5C
	Exposed Grid	10K1	2.5	NW	24 (48)	20G@13plf W6 x 12	G203	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	48*	20G@14plf W6 x 12	G205	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	72	W6 x 12	G208	0.6C, 1.0C, 1.3C, 1.5C



FIRE RESISTANCE: FLOOR

			Concre	ete	Maximum	Minimum		
Restrained Assembly Rating	Protection Material	Minimum Joist Size	Minimum Thickness (in.)	Туре	Joist Spacing (in.)	Primary Support Member	UL Design Number	Deck Types
		10K1	2.5		24 (48)		G213	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5		24 (48)	W8 x 31	G227	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5		24 (48)	20G@13plf W8 x 31	G228	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5		24 (48)	20G@13plf W8 x 24	G229	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5		24 (48)	20G@13plf W6 x 12	G243	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5		48*	20G@14plf W6 x 12	G256	0.6C, 1.0C, 1.3C, 1.5C
2 Hr.		10K1	2.5		24 (48)	20G@13plf W8 x 31	G268	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.0	NW	24 (48)	NS	G505	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	24 (48)	20G14plf W8 x 31	G514	0.6C, 1.0C, 1.3C, 1.5C
	Gypsum Board	10K1	2.5	NW	24 (48)	20G@13plf W10 x 21	G523	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	24 (48)	20G@13plf W8 x 24	G529	0.6C, 1.0C, 1.3C, 1.5C
		10K1	2.5	NW	24 (48)	20G@13plf W10 x 21	G547	1.5C
	Acquistical		3.25	IWNW	NI	20G@13plf	D216	1.5VLI, 2VL, 3VL, 2VLP, 3VLP
	ACOUSTICAL	12K1, 18LHUZ	3.25	LVV, IN VV	NL	W8 x 15	D219	1.5VL, 1.5VLI, 2VL, 3VL, 2VLP, 3VLP
	Consolad Crid	10K1	3.5	NW	24 (48)	20G@13plf W8 x 20	G033	0.6C, 1.0C, 1.3C, 1.5C
	conceated ond	10K1	3.25	NW	30 (48)	20G@13plf W10 x 21	G036	0.6C, 1.0C, 1.3C, 1.5C
		10K1	3.5	NW	48*	20G@14plf W6 x 12	G205	0.6C, 1.0C, 1.3C, 1.5C
		10K1	3.5	NW	24 (48)	W6 x 12	G213	0.6C, 1.0C, 1.3C, 1.5C
3 Hr.	Exposed Grid	10K1	3.25	NW	24 (48)	20G@13plf W8 x 24	G229	0.6C, 1.0C, 1.3C, 1.5C
		10K1	3.5	NW	48*	W6 x 12	G256	0.6C, 1.0C, 1.3C, 1.5C
_		10K1 (22 ksi max.)	2.63	NW	24 (48)	20G@13plf W8 x 31	G268	0.6C, 1.0C, 1.3C, 1.5C
		10K1	3.0	NW	24 (48)	20G@13plf W10 x 21	G523	1.5C
	Gypsum Board	10K1	2.75	NW	24 (48)	20G@13plf W8 x 24	G529	0.6C, 1.0C, 1.3C, 1.5C
		10K1	3.0	NW	24 (48)	20G@13plf W10 x 21	G547	1.5C

			Concre	ete	Maximum	Minimum		
Restrained Assembly Rating	Protection Material	Minimum Joist Size	Minimum Thickness (in.)	Туре	Joist Spacing (in.)	Primary Support Member	UL Design Number	Deck Types
		NS	2.5	LW,NW	NL	W8 x 28	D759	1.5VL,1.5VLI, 1.5VLP, 2VL, 3VL, 2VLP, 3VLP
		10K1	2.5	LW,NW	NL	W8 x 28	D779	1.5VLI, 2VL, 3VL
		10K1	2.5	LW,NW	NL	W8 x 28	D780	1.5VLI, 2VL, 3VL
		NS	3.25	LW	NL	W8 x 28	D782	1.5VLI, 2VL, 3VL
		101/1*	2.5	LW	NL	W8 x 28	DOOL	1.5VL,1.5VLI, 1.5VLP, 2VL, 3VL, 2VLP,
		IUKI	3.5	NW	NL	W8 x 28	D925	3VLP
		16K6*	NS	LW,NW	42	20G@20plf W8 x 28	G701	0.6C, 1.0C, 1.3C, 1.5C
		16K6	3.0	LW	50.5	NS	G702	1.5C
1 Hr.	SAFRM	16K6	3.75	NW	50.5	NS	G702	1.5C
		16K6*	2.5	LW,NW	42	NS	G705	0.6C, 1.0C, 1.3C, 1.5C
		16K6	3.0	LW	50.5	NS	G706	1.5C
		16K6	3.75	NW	50.5	NS	G706	1.5C
		16K6*	2.5	LW,NW	42	20G@20plf W8 x 28	G708	0.6C, 1.0C, 1.3C, 1.5C
		NS	2.5	LW,NW	42	W8 x 28	G709	0.6C, 1.0C, 1.3C, 1.5C
		16K6*	2.5	LW,NW	42	20g@20plf W8 x 24	G801	0.6C, 1.0C, 1.3C, 1.5C
		12K1	3.0	LW	50.5	NS	G802	0.6C, 1.0C, 1.3C, 1.5C
		12K1	3.75	NW	50.5	NS	G802	0.6C, 1.0C, 1.3C, 1.5C
		NS	2.5	LW,NW	NL	W8 x 28	D759	1.5VL,1.5VLI, 1.5VLP, 2VL, 3VL, 2VLP, 3VLP
		10K1	2.5	LW,NW	NL	W8 x 28	D779	1.5VLI, 2VL, 3VL
		10K1	2.5	LW,NW	NL	W8 x 28	D780	1.5VLI, 2VL, 3VL
		NS	3.25	LW	NL	W8 x 28	D782	1.5VLI, 2VL, 3VL
		10K1*	3.0	LW	NL	W8 x 28	D925	1.5VL,1.5VLI, 1.5VLP, 2VL, 3VL, 2VLP,
		10K1*	4.0	NW	NL	W8 x 28	0720	3VLP
		16K6*	2.5	LW,NW	42	20G@20plf W8 x 28	G701	0.6C, 1.0C, 1.3C, 1.5C
44/011	045014	16K6	3.5	LW	50.5	NS	G702	1.5C
11/2 Hr.	SAFRM	16K6	4.5	NW	50.5	NS	G702	1.5C
		16K6*	2.5	LW,NW	42	NS	G705	0.6C, 1.0C, 1.3C, 1.5C
		16K6	3.5	LW	50.5	NS	G706	1.5C
		16K6	4.5	NW	50.5	NS	G706	1.5C
		16K6*	2.5	LW,NW	42	20G@20plf W8 x 28	G708	0.6C, 1.0C, 1.3C, 1.5C
		NS	2.5	LW,NW	42	W8 x 28	G709	0.6C, 1.0C, 1.3C, 1.5C
		16K6*	2.5	LW,NW	42	20G@20plf W8 x 24	G801	0.6C, 1.0C, 1.3C, 1.5C
		12K5	3.5	LW	50.5	NS	G802	0.6C, 1.0C, 1.3C, 1.5C
		12K5	4.5	NW	50.5	NS	G802	0.6C, 1.0C, 1.3C, 1.5C



FIRE RESISTANCE: FLOOR

			Concr	ete	Maximum	Minimum		
Restrained Assembly Rating	Protection Material	Minimum Joist Size	Minimum Thickness (in.)	Туре	Joist Spacing (in.)	Primary Support Member	UL Design Number	Deck Types
		NS	2.5	LW,NW	NL	W8 x 28	D759	1.5VL,1.5VLI, 1.5VLP, 2VL, 3VL, 2VLP, 3VLP
		10K1	2.5	LW, NW	NL	W8 x 28	D779	1.5VLI, 2VL, 3VL
		10K1	2.5	LW, NW	NL	W8 x 28	D780	1.5VLI, 2VL, 3VL
		NS	3.25	LW	NL	W8 x 28	D782	1.5VLI, 2VL, 3VL
		101/1*	3.25	LW	NL	W8 x 28	DOJE	1.5VL,1.5VLI, 1.5VLP, 2VL, 3VL, 2VLP,
		IUNI	4.5	NW	NL	W8 x 28	D723	3VLP
		16K6*	2.5	LW,NW	42	20G@20plf W8 x 28	G701	0.6C, 1.0C, 1.3C, 1.5C
		16K6	4.0	LW	50.5	NS	G702	1.5C
2 Hr.	SAFRM	16K6	5.25	NW	50.5	NS	G702	1.5C
		16K6*	2.5	LW, NW	42	NS	G705	0.6C, 1.0C, 1.3C, 1.5C
		16K6	4.0	LW	50.5	NS	G706	1.5C
		16K6	5.25	NW	50.5	NS	G706	1.5C
		16K6*	2.5	LW,NW	42	20G@20plf W8 x 28	G708	0.6C, 1.0C, 1.3C, 1.5C
		NS	2.5	LW, NW	42	W8 x 28	G709	0.6C, 1.0C, 1.3C, 1.5C
		16K6*	2.5	LW,NW	42	20G@20plf W8 x 24	G801	0.6C, 1.0C, 1.3C, 1.5C
		12K5	4.0	LW	50.5	NS	G802	0.6C, 1.0C, 1.3C, 1.5C
		12K5	5.25	NW	50.5	NS	G802	0.6C, 1.0C, 1.3C, 1.5C
		NS	2.5	LW,NW	NL	W8 x 28	D759	1.5VL,1.5VLI, 1.5VLP, 2VL, 3VL, 2VLP, 3VLP
		10K1	2.5	LW, NW	NL	W8 x 28	D779	1.5VLI, 2VL, 3VL
		10K1	2.5	LW, NW	NL	W8 x 28	D780	1.5VLI, 2VL, 3VL
		NS	3.25	LW	NL	W8 x 28	D782	1.5VLI, 2VL, 3VL
		1∩⊮1*	4.19	LW	NL	W8 x 28	D925	1.5VL,1.5VLI, 1.5VLP, 2VL, 3VL, 2VLP,
0.11		IONI	5.25	NW	NL	W8 x 28	0723	3VLP
3 Hr.	SAFRM	16K6*	NS	LW,NW	42	20G@20plf W8 x 28	G701	0.6C, 1.0C, 1.3C, 1.5C
		16K6*	2.75	LW, NW	42	NS	G705	0.6C, 1.0C, 1.3C, 1.5C
		16K6*	2.75	LW,NW	42	20G@20plf W8 x 28	G708	0.6C, 1.0C, 1.3C, 1.5C
		NS	2.75	LW, NW	42	W8 x 28	G709	0.6C, 1.0C, 1.3C, 1.5C
		16K6*	2.75	LW,NW	42	20G@20plf W8 x 24	G801	0.6C, 1.0C, 1.3C, 1.5C
∕l Hr	SAEDM	10K1	2.5	LW,NW	NL	W8 x 28	D779	1.5VLI, 2VL, 3VL
		NS	3.25	LW	NL	W8 x 28	D782	1.5VLI, 2VL, 3VL

Restrained			Deck	Туре		
Assembly Ratings (hr.)	Type of Protection	Concrete Thickness & Type	UL Design No.	2D	3.5D	Unrestrained Beam Rating (hr.)
			D904	\checkmark		3⁄4
15	Unprotected	2" LW &	D961	\checkmark		3⁄4
I.	Deck	2¾" NW	D917	\checkmark		
			D928	\checkmark		3⁄4
			D947		\checkmark	
11⁄2	Unprotected Deck	2" LW & 2" NW	D964		\checkmark	
	Deek	Z INVV	D984		\checkmark	
			D904	\checkmark		1
		2½" LW,	D961	\checkmark		1
		3" SLW & 3¼" NW	D917	\checkmark		3⁄4
2	Unprotected	0/1 111	D928	\checkmark		1
	Deck		D947		\checkmark	3⁄4
		2" LW & 214" NW	D964		\checkmark	3⁄4
		Z /4 IN VV	D984		\checkmark	3⁄4
			D904	\checkmark		1
		3¼" LW,	D961	\checkmark		1
		4" SLW & 4%" NW	D917	\checkmark		3⁄4
3	Unprotected		D928	\checkmark		1
5	DECK		D947		\checkmark	11/2
		2¼" LW &	D964		\checkmark	11/2
		J /4 IN VV	D984		\checkmark	11/2

UL Fire Resistance Ratings

NOTES:

1. Refer to the UL "Fire Resistance Directory" for the necessary construction details.

- 2. Concrete thickness is thickness of slab above deck, in.
- 3. All Dovetail FormLok composite deck assemblies are subject to an upper live load limit of 130 psf.
- 4. Dramix[®] fibers may be used in UL or ULC fire rated assemblies in lieu of WWR. See UL file R19307 for additional information.
- 5. Restrained Assembly Rating is 1½ hr with listed NW concrete thickness.







DOVETAIL DECK

DOVETAIL DECK

If you need the best, you need Vulcraft's Dovetail steel roof deck. The innovative, high-quality decking system boasts a clean, sleek design with distinct shadow lines to provide texture to the ceiling surface.

The Dovetail acoustic steel deck uses pioneering soundreducing technology to deliver a calm, quiet interior environment – all while reducing overall design costs

Vulcraft's Dovetail deck delivers.

- Economical 2-inch-deep and long spanning 3.5-inch-deep products
- Excellent acoustic performance with Noise Reduction Coefficient (NRC) of 0.95 to 1.15
- Naturally hides unsightly roof system fasteners with the re-entrant shape of Dovetail Deck
- Factory painted options
- Proven performance listed with UL, FM and IAPMO-UES

For complete performance information, contact Vulcraft to get your Vulcraft Dovetail Roof Deck Catalog or download directly at <u>www.vulcraft.com/literature</u>.





The Vulcraft Structural Dovetail Ceiling/Deck is available in 2-inch-deep and 3.5-inch-deep profiles.





HANGING SOLUTIONS

HANGING SOLUTIONS





Sammy X-Press Hanger for Roof and Acoustical Roof Deck

Wedge Nut Hanger for Dovetail FormLok Deck

For more information on hanging solutions download the Vulcraft Deck Solutions Manual at <u>www.vulcraft.com/literature</u>







CELLULAR DECK

Combining functional structural and aesthetic design and affordability in one product, the Vulcraft 1.5BP Structural Cellular Ceiling/Deck is the best of all design options. By acting as both a ceiling and roof, this versatile product helps you achieve economies in construction, and it provides a clean and uncluttered appearance that is perfect for many different applications.

The expense and trouble of suspended ceilings is eliminated when you choose our acoustical option. Sound absorption is provided through inert, non-organic glass fiber sound absorbing batts placed in the panels. They are capable of absorbing up to 90% of the sound that strikes the ceiling. Whether in protected or harsh environments, the specially designed Vulcraft Structural Cellular Ceiling/Deck systems perform as expected. Use them for interior ceilings, soffits, and exterior metal ceilings. Economical and easy to use, our system requires no fasteners and gives you a flush look featuring an even, solid surface.

CELLULAR DECK PRODUCT OFFER



CELLULAR DECK

BOB EVANS HEADQUARTERS New Albany, OH



REDUCE INTERIOR NOISE WITH THE SOUND ABSORPTION CAPABILITIES OF VULCRAFT ACOUSTICAL ROOF DECK



2.0DA DOVETAIL

3.5DA DOVETAIL

Roof	AC Absorption Coefficients								RAL	
Insulation	Insulation	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SSA	NRC	Test. No.
2.0DA DOVETAIL										
Delvilse	Plain	0.19	0.54	1.15	1.07	1.01	0.79	0.95	0.95	A14-170
POLY-ISO	Encapsulated	0.35	0.82	1.15	0.99	0.97	0.72	0.96	1.00	A14-167
Fiberglass	Plain	0.74	1.40	1.25	1.03	0.98	0.80	1.14	1.15	A14-169
FIDEIGIASS	Encapsulated	0.62	1.18	1.08	0.93	0.97	0.77	1.02	1.05	A14-168
½" (13 mm) Roof	Plain	0.17	0.51	1.05	1.05	0.85	0.77	0.85	0.85	A19-101
Board	Encapsulated	0.30	0.56	1.02	0.99	0.92	0.78	0.86	0.85	A19-102
3.5DA DOVETAIL										
Delvilee	Plain	0.25	0.74	1.13	1.06	0.97	0.75	0.96	1.00	A14-186
POLY-ISO	Encapsulated	0.38	0.86	1.18	1.03	0.93	0.65	0.98	1.00	A14-189
Fiberglass	Plain	0.92	1.51	1.13	1.06	0.98	0.78	1.14	1.15	A14-187
Fiberglass	Encapsulated	0.97	1.50	1.09	1.00	0.91	0.67	1.10	1.15	A14-188
½" (13 mm) Roof Board	Plain	0.33	0.95	1.20	1.00	0.96	0.74	1.01	1.05	A19-220
	Encapsulated	0.56	1.10	1.13	0.91	0.94	0.64	1.02	1.00	A19-223

NOTE:

1. Plain 3.0 pcf (48 kg/m³) fiberglass acoustical insulation standard. Inquire regarding lead time for encapsulated insulation.







1.5BA-36 / 1.5BIA-36 / 1.5PLBA-36

Roof	AC	Absorption Coefficients								RAL	
Insulation	Insulation	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SSA	NRC	Test. No.	
1.5BA-36 / 1.5BIA-36 / 1.5PLBA-36											
Delvilee	Plain	0.09	0.20	0.47	0.86	0.55	0.32	0.55	0.55	A15-125	
POLY-ISO	Encapsulated	0.14	0.35	0.74	0.76	0.44	0.27	0.57	0.55	A15-124	
Fiberglass	Plain	0.68	1.16	1.17	0.96	0.52	0.31	0.95	0.95	A15-126	
	Encapsulated	0.75	0.83	0.78	0.68	0.42	0.28	0.67	0.70	A15-123	

NOTE:

1. Plain 0.75 pcf (12 kg/m³) fiberglass acoustical insulation standard for all BA decks. Inquire regarding lead time for encapsulated insulation.



3NLA-32 / 3NIA-32 / 3PLNA-32

Roof	AC	Absorption Coefficients							RAL	
Insulation	Insulation	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SSA	NRC	Test. No.
3NLA-32 / 3NIA-32 / 3PLNA-32										
Dahulaa	Plain	0.23	0.42	0.85	0.95	0.50	0.41	0.68	0.70	A19-032
Poly-ISO	Encapsulated	0.30	0.62	1.09	0.79	0.52	0.31	0.74	0.75	A19-111
Fiberglass	Plain	0.78	1.17	1.20	0.98	0.50	0.41	0.96	0.95	A19-031
Fiberglass	Encapsulated	0.89	1.08	1.09	0.74	0.46	0.30	0.83	0.85	A19-110
½" (13 mm)Roof Board	Plain	0.21	0.41	0.81	0.89	0.49	0.41	0.64	0.65	A19-033



3NA-24 / 3NIA-24

Roof	AC	Absorption Coefficients								RAL
Insulation	Insulation	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SSA	NRC	Test. No.
3NA-24 / 3NIA-24	4									
	Plain	0.19	0.33	0.73	0.83	0.48	0.33	0.59	0.60	A15-130
POLY-ISO	Encapsulated	0.17	0.39	0.94	0.86	0.48	0.27	0.67	0.65	A15-138
Fiberglass	Plain	0.81	1.16	1.15	0.91	0.47	0.27	0.92	0.90	A15-128
Fiberglass	Encapsulated	1.07	1.13	1.04	0.81	0.43	0.26	0.85	0.85	A15-137

NOTE:

1. Plain 0.75 pcf (12 kg/m³) fiberglass acoustical insulation standard for all NA decks. Inquire regarding lead time for encapsulated insulation.



DECK ACOUSTIC INFORMATION



1.5BPA-36 / 1.5PLBPA-36 ROOF DECK 1.5VLPA-36 / 1.5PLVLPA-36 COMPOSITE DECK

3NPA-32 / 3PLNPA-32 ROOF DECK



3NPA-24 / 3PLNPA-24 ROOF DECK

Roof	AC	Absorption Coefficients								RAL
Insulation	Insulation	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SSA	NRC	Test. No.
1.5BPA-36 / 1.5PLBPA-36 ROOF DECK or 1.5VLPA-36 / 1.5PLVLPA-36 COMPOSITE DECK										
Poly-Iso	Plain	0.27	0.32	0.70	1.02	0.80	0.52	0.69	0.70	A15-114
	Encapsulated	0.26	0.44	0.84	0.98	0.67	0.45	0.72	0.75	A15-115
3NPA-32 / 3PLNF	PA-32 ROOF DECK	(
Delvilee	Plain	0.47	0.61	1.08	1.03	0.83	0.67	0.90	0.90	A22-125
POLY-ISO	Encapsulated	0.52	0.71	1.12	0.80	0.62	0.45	0.83	0.80	A22-188
3NPA-24 / 3PLNPA-24 ROOF DECK										
Poly-Iso	Plain	0.25	0.47	0.92	0.75	0.62	0.54	0.69	0.70	A15-141
	Encapsulated	0.39	0.62	1.19	0.74	0.66	0.44	0.80	0.80	A15-231



2VLPA-36 / 2PLVLPA-36 COMPOSITE DECK



3VLPA-36 / 3PLVLPA-36 COMPOSITE DECK

AC Absorption Coefficients								RAL		
Floor	Insulation	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SSA	NRC	Test. No.
2VLPA-36 / 2PLVLPA-36 COMPOSITE DECK										
<u>Cara anata</u>	Plain	0.31	0.44	0.72	0.77	0.47	0.47	0.60	0.60	A15-120
Concrete	Encapsulated	0.39	0.45	0.87	0.66	0.31	0.19	0.58	0.55	A15-119
3VLPA-36 / 3PLVLPA-36 COMPOSITE DECK										
Conorata	Plain	0.48	0.56	1.00	0.75	0.49	0.49	0.69	0.70	A15-121
Concrete	Encapsulated	0.51	0.63	0.83	0.49	0.39	0.28	0.58	0.60	A15-122

NOTE:

1. Factory installed plain 3.0 pcf (48 kg/m³) fiberglass acoustical insulation standard for all cellular decks. Inquire regarding lead time for encapsulated insulation.

ACHIEVE QUIET SPACES WITH PREMIUM FINISHES BY USING THE SUPERIOR STC AND IIC RATINGS OF 2.0D FORMLOK DECK-SLABS

2.0D FORMLOK DECK-SLAB

- 2" (51 mm) Deep Composite Deck
- 5½" (140 mm) Total Slab Depth
- Normal Weight Concrete (145 pcf / 2235 kg/m³)
- Exposed Deck Ceiling



Exposed Deck (No Ceiling)

Floor Covering	Underlayment	STC	IIC	Intertek Test No.
Ceramic Tile	5 mm ECOsilence	51	41	<u>H7786.06</u>
Engineered Wood	5 mm ECOsilence	50	50	<u>H7786.05</u>
Fusion Hybrid Vinyl Plank	2 mm ECOsilence	46	51	<u>H7786.02</u>
Attain Luxury Vinyl Tile	5 mm ECOsilence	52	51	<u>H7786.03</u>
Forest Rx Rubber Backed Sheet Vinyl	None	51	51	<u>H7786.04</u>
Exposed Concrete	None	52	23	<u>H7786.01</u>

NOTES:

- 1. The acoustical test reports with complete assembly details are available from <u>www.dovetaildeck.com</u>.
- 2. The testing was performed in accordance with the following standards:
 - ASTM E90-09 (2016), Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions
 - ASTM E492-09(2016)e1, Standard Test Method for Laboratory Measurement of Impact Sound Transmission Through Floor-Ceiling Assemblies Using the Tapping Machine



DECK ACOUSTIC INFORMATION

2.0D FORMLOK DECK-SLAB

- 2" (51 mm) Deep Composite Deck
- 5½" (140 mm) Total Slab Depth
- Normal Weight Concrete (145 pcf / 2235 kg/m³)
- Gypsum Board Ceiling



Gypsum Board Ceiling on Furring Channels Directly Attached to Deck

Floor Covering	Underlayment	STC	IIC	Intertek Test No.
Ceramic Tile	5 mm ECOsilence	53	47	<u>H7786.12</u>
Engineered Wood	5 mm ECOsilence	50	50	<u>H7786.11</u>
Fusion Hybrid Vinyl Plank	2 mm ECOsilence	51	50	<u>H7786.08</u>
Attain Luxury Vinyl Tile	2 mm ECOsilence	52	50	<u>H7786.09</u>
Forest Rx Rubber Backed Sheet Vinyl	None	50	50	<u>H7786.10</u>
Exposed Concrete	None	52	32	<u>H7786.07</u>

NOTE:

 Values shown are for gypsum board on furring channels directly connected to the underside of the slab. Gypsum board ceilings attached to the deck by methods providing acoustical separation will provide improved STC and IIC values.

2.0D FORMLOK DECK-SLAB

- 2" (51 mm) Deep Composite Deck
- 5½" (140 mm) Total Slab Depth
- Normal Weight Concrete (145 pcf / 2235 kg/m³)
- Suspended Gypsum Board Ceiling



Suspended Gypsum Board Ceiling

Floor Covering	Underlayment	STC	IIC	Intertek Test No.
Ceramic Tile	5 mm ECOsilence	62	60	<u>15133.01</u>

NOTE:

1. Laboratory tests determining STC and IIC for DoveTail FormLok deck with a suspended ceiling were conducted with ceramic tile and underlayment. Adding a suspended ceiling to the ceramic tile assembly improved the STC rating by 11 and the IIC rating by 19 compared to an assembly with no ceiling. Other flooring types can expect similar improvement in performance.



ACHIEVE QUIET SPACES WITH PREMIUM FINISHES BY USING THE SUPERIOR STC AND IIC RATINGS OF 3.5D FORMLOK DECK-SLABS

3.5D FORMLOK DECK-SLAB

- 3¹/₂" (89 mm) Deep Composite Deck
- 6" (152 mm) Total Slab Depth
- Normal Weight Concrete (145 pcf / 2235 kg/m³)
- Exposed Deck Ceiling



Exposed Deck (No Ceiling)

Floor Covering	Underlayment	STC	IIC	Intertek Test No.
Ceramic Tile	5 mm ECOsilence	50	42	<u>H7787.06</u>
Engineered Wood	5 mm ECOsilence	45	46	<u>H7787.05</u>
Fusion Hybrid Vinyl Plank	2 mm ECOsilence	47	47	<u>H7787.02</u>
Attain Luxury Vinyl Tile	5 mm ECOsilence	50	50	<u>H7787.03</u>
Forest Rx Rubber Backed Sheet Vinyl	None	49	49	<u>H7787.04</u>
Exposed Concrete	None	50	24	<u>H7787.01</u>

3.5D FORMLOK DECK-SLAB

- 3¹/₂" (89 mm) Deep Composite Deck •
- 6" (152 mm) Total Slab Depth
- Normal Weight Concrete (145 pcf / 2235 kg/m³)
- Gypsum Board Ceiling



Gypsum Board Ceiling on Furring Channels Directly Attached to Deck

Floor Covering	Underlayment	STC	IIC	Intertek Test No.
Ceramic Tile	5 mm ECOsilence	56	49	<u>H7787.12</u>
Engineered Wood	5 mm ECOsilence	55	52	<u>H7787.11</u>
Fusion Hybrid Vinyl Plank	2 mm ECOsilence	55	53	<u>H7787.08</u>
Attain Luxury Vinyl Tile	5 mm ECOsilence	56	52	<u>H7787.09</u>
Forest Rx Rubber Backed Sheet Vinyl	None	55	52	<u>H7787.10</u>
Exposed Concrete	None	55	32	<u>H7787.07</u>

NOTE:

1. Values shown are for gypsum board on furring channels directly connected to the underside of the slab. Gypsum board ceilings attached to the deck by methods providing acoustical separation will provide improved STC and IIC values.



DECK ACOUSTIC INFORMATION

3.5D FORMLOK DECK-SLAB

- 3¹/₂" (89 mm) Deep Composite Deck
- 6" (152 mm) Total Slab Depth
- Normal Weight Concrete (145 pcf / 2235 kg/m³)
- Suspended Gypsum Board Ceiling



Suspended Gypsum Board Ceiling

Floor Covering	Underlayment	STC	IIC	Intertek Test No.
Ceramic Tile	5 mm ECOsilence	62	62	<u>15133.02</u>

NOTE:

 Laboratory tests determining STC and IIC for DoveTail FormLok deck with a suspended ceiling were conducted with ceramic tile and underlayment. Adding a suspended ceiling to the ceramic tile assembly improved the STC rating by 12 and the IIC rating by 20 compared to an assembly with no ceiling. Other flooring types can expect similar improvement in performance.

USE UL RECOGNIZED VULCRAFT ROOF DECKS FOR YOUR FIRE RATED ASSEMBLIES

Vulcraft steel decks may be used in assemblies which are required to meet hourly fire ratings. Approved hourly fire rated assemblies are a combination of specific proprietary materials as listed in UL fire resistance ratings.



REPRESENTATIVE FIRE RATED ASSEMBLY

Refer to the table on the following pages for a listing of UL fire-rated assemblies utilizing Vulcraft steel deck profiles. Refer to the particular UL assembly being considered for full details of construction, including specific information about fill or fireproofing thicknesses and span limitations.



UL Fire Resistance Ratings

Restrained	3								
Assembly Ratings (hr.)	Type of Protection	Type of Insulation	UL Design No.	В	32″ 3N	24″ 3N	2.0D	3.5D	Unrestrained Beam Rating (hr.)
			P211+	\checkmark					
			P214+	\checkmark					1
		Digid Inculation	P225+	\checkmark	\checkmark	\checkmark			1,1½
	Exposed Grid	Rigiu Insolation	P227+	\checkmark					
			P230+	\checkmark					1,11⁄2
			P235+	\checkmark					1
		Insulating Fill	P214+	\checkmark					1
		Disid Inculation	P510+	\checkmark	\checkmark	\checkmark			
	Gypsom Board	Rigid Insulation	P514	\checkmark					
			P701*	\checkmark	\checkmark	\checkmark			1,1½,2
	Cementitious	Rigid Insulation	P711*	\checkmark	\checkmark	\checkmark			1,1½,2
		5	P717*	\checkmark	\checkmark	\checkmark			1,1½,2
1			P801*	\checkmark	\checkmark	\checkmark			1,1½,2,3
	Sprayed Fiber	Rigid Insulation	P815*	\checkmark	\checkmark	\checkmark			1,1½,2,3
			P819*	\checkmark	\checkmark	\checkmark			1,1½,2
			P902	\checkmark	\checkmark	\checkmark			1,1½,2
			P907	\checkmark	\checkmark	\checkmark			1,1½,2
			P908	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2
			P919	\checkmark	\checkmark	\checkmark			1,1½
	Unprotected	la culatia a Fill	P920	\checkmark	\checkmark	\checkmark			1,1½,2
	Deck	Insulating Fill	P921	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2
			P922	\checkmark	\checkmark	\checkmark			1,1½,2
			P923	\checkmark	\checkmark	\checkmark			1,1½,2
			P937				\checkmark	\checkmark	
			P938				\checkmark	\checkmark	1,1½,2
			P225+	\checkmark	\checkmark	\checkmark			1,1½
	Exposed Grid	Rigid Insulation	P227+	\checkmark					1,1½
			P230+	\checkmark					1,1½
417	Metal Lath	Rigid Insulation	P404+	\checkmark					
1/2	Gypsum Board	Rigid Insulation	P510+	\checkmark	\checkmark	\checkmark			
			P701*	\checkmark	\checkmark	\checkmark			1,1½,2
	Cementitious	Rigid Insulation	P711*	\checkmark	\checkmark	\checkmark			1,1½,2
			P717*	\checkmark	\checkmark	\checkmark			1,1½,2

Restrained			Deck Type							
Assembly Ratings (hr.)	Type of Protection	Type of Insulation	UL Desian No.	в	32″ 3N	24″ 3N	2.0D	3.5D	Unrestrained Beam Rating (hr.)	
(,			P801*	✓	\checkmark	\checkmark			1,1½,2	
	Sprayed Fiber	Rigid Insulation	P815*	\checkmark	\checkmark	\checkmark			1,1½,2,3	
		5	P819*	\checkmark	\checkmark	\checkmark			1,1½,2,3	
			P902	\checkmark	\checkmark	✓			1,1½,2	
			P907	\checkmark	\checkmark	\checkmark			1,1½,2	
	Unprotected Deck		P908	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2	
11⁄2			P919	\checkmark	\checkmark	\checkmark			1,11/2	
			P920	\checkmark	\checkmark	\checkmark			1,1½,2	
		Insulating Fill	P921	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2	
			P922	\checkmark	\checkmark	~			1,1½,2	
			P923	\checkmark	\checkmark	\checkmark			1,1½,2	
			P937				\checkmark	\checkmark		
			P938				\checkmark	\checkmark	1,1½,2	
	Exposed Grid	Rigid Insulation	P237+	\checkmark					2	
	Metal Lath	Rigid Insulation	P404+	\checkmark						
	Gypsum Board	Rigid Insulation	P514+	\checkmark						
			P701*	\checkmark	\checkmark	\checkmark			1,1½,2	
	Cementitious	Rigid Insulation	P711*	\checkmark	\checkmark	\checkmark			1,1½,2	
			P717*	\checkmark	\checkmark	\checkmark			1,1½,2	
			P801*	\checkmark	\checkmark	\checkmark			1,1½,2	
	Sprayed Fiber	Rigid Insulation	P815*	\checkmark	\checkmark	\checkmark			1,1½,2	
2			P819*	✓	\checkmark	✓			1,1½,2,3	
2			P902	\checkmark	\checkmark	\checkmark			1,1½,2	
			P907	\checkmark	\checkmark	\checkmark			1,1½,2	
			P908	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2	
	Upprotected		P920	\checkmark	\checkmark	\checkmark			1,1½,2	
	Deck	Insulating Fill	P921	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2	
			P922	\checkmark	\checkmark	\checkmark			1,1½,2	
			P923	\checkmark	\checkmark	\checkmark			1,1½,2	
			P937				\checkmark	\checkmark		
			P938				\checkmark	\checkmark	1,1½,2	

UL Fire Resistance Ratings (continued)



NOTES:

- 1. Refer to the UL "Fire Resistance Directory" for the necessary construction details.
- 2. Deck finish shall be galvanized unless noted otherwise.
 - + Deck finish is not critical for fire resistance when used in P2--, P4--, & P5-- Series designs. Deck finish shall be galvanized or painted.

* Denotes deck finish is critical for fire resistance. Deck finish shall be galvanized or painted. This gray paint is a special type of paint and is compatible with the spray-applied fire protection and is U.L. approved for use in the denoted P7-- & P8-- Series designs.

3. B = 1.5B, 1.5BI, and 1.5PLB

32" 3N = 32" (813 mm) Wide 3NL, 3NI, and 3PLN

24" 3N = 24" (610 mm) Wide 3N and 3NI

USE UL RECOGNIZED COMPOSITE AND NON-COMPOSITE DECKS FOR YOUR FIRE RATED ASSEMBLIES WITH STRUCTURAL CONCRETE FILL

Vulcraft composite and non-composite slabs may be used to meet hourly fire ratings. The type and thickness of concrete specified will generally determine whether fireproofing will be required on the underside of the composite or non-composite deck.



REPRESENTATIVE FIRE RATED ASSEMBLY

The table on the following pages lists the UL fire rated assemblies that include Vulcraft composite and non-composite deckprofiles. This summary table is provided to assist in identification of assemblies to meet specific project requirements. Refer to the particular UL assembly for full details of construction, including specific information about concrete slab, framing, type of fire protection, deck types, and span limitations.

UL Fire Resistance Ratings

Restrained			Deck Type								
Assembly Ratings	Type of	Concrete								Unrestrained Beam Rating	
(hr.)	Protection	Thickness & Type	UL Design No.	1.5VL	2VL	3VL	1.5VLP	2VLP	3VLP	(hr.)	
3/_	Unprotected	21/2 1/11	D914 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1	
/4	Deck	Z72 LVV	D916 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
	Exposed Grid	21⁄2″ NW	D216 +	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	2,3	
		2" NW & LW	D743 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3	
			D703 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	11⁄2	
Cementitious	Comontitious		D712 *		\checkmark	\checkmark			\checkmark	2	
	Cementitious	21⁄2″ NW & LW	D722 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2	
		D739 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3,4		
			D759 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
		2" NW & LW	D859 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1.5,2,3	
			D832 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
1	Sprayed Fiber	2½" NW & LW	D847 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,3	
			D858 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3,4	
			D871 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3	
		01///	D902 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
			D914 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1	
		272" LVV	D916 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
	Unprotected		D919 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½	
	Deek		D902 #	✓	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
		31⁄2″ NW	D916 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
			D919 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½	
	Gypsum Board	21⁄2″ NW	D502 *	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	11⁄2,2	
		2" NW & LW	D743 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3	
			D703 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	11/2	
1 ½			D712 *		\checkmark	\checkmark			\checkmark	2	
	cementitious	21⁄2″ NW & LW	D722 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2	
			D739 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3,4	
			D759*	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	

✓⁺1.5VLI Only

	UL	Fire	Resistance	Ratings	(continued)
--	----	------	------------	---------	-------------

Restrained			Deck Type							
Assembly Ratings (hr.)	Type of Protection	Concrete Thickness & Type	UL Design No.	1.5VL	2VL	3VL	1.5VLP	2VLP	3VLP	Unrestrained Beam Rating (hr.)
		2" NW & LW	D859 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3
			D832 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Sprayed Fiber		D847 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,3
		Z72" IN VV & LVV	D858 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3,4
			D871 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3
1½ Unprot Dec			D902 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
		3" LW	D916 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Unprotected		D919 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½
	Deck		D902 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
		4" NW	D916 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
			D919 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½
Exposed Grid Gypsum Boar	Exposed Grid	21⁄2″ NW	D216 +	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	2,3
	Gypsum Board	21⁄2″ NW	D502 +	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	11⁄2,2
		2" NW & LW	D743 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3
		21⁄2″ LW	D746 *	\checkmark						1,1½,2,3
			D752 *	\checkmark	\checkmark	\checkmark	✓	\checkmark	✓	1,1½,2,
			D703 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	11⁄2
			D712 *		\checkmark	\checkmark			\checkmark	2
			D716 *	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	1½,2
2			D722 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2
	Cementitious	21/21/ NI/N/ 8, I/M/	D739 *		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3,4
		Z/2 INVV & LVV	D745 *		\checkmark	\checkmark				1,1½,2
			D750 *	\checkmark	\checkmark	\checkmark				1½,2
			D755*	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
			D759*	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
			D760 *	✓+	\checkmark	\checkmark				1,1½,2,3,4
		21/5" NI/M	D730 *		\checkmark	\checkmark		\checkmark	\checkmark	
		2/2 INVV	D742 *	\checkmark	\checkmark	\checkmark				1,1½

✓⁺1.5VLI Only

UL Fire Resistance Ratings (continued)

Restrained		Deck Type								
Assembly Ratings (hr.)	Type of Protection	Concrete Thickness & Type	UL Design No.	1.5VL	2VL	3VL	1.5VLP	2VLP	3VLP	Unrestrained Beam Rating (hr.)
		2" NW & LW	D859 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3
			D822 *		\checkmark	\checkmark		\checkmark	\checkmark	1
			D825 *	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2
		21⁄2" NW & LW	D831 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2
			D832 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Sprayed Fiber		D833 *	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	11⁄2
	Sprayeu Fiber		D847 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,3
			D858 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3,4
			D861 *		\checkmark	\checkmark				1,1½
			D871 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3
		21⁄2″ LW	D862 *		\checkmark	\checkmark				1
2		3¼″ LW	D860 *		\checkmark	\checkmark				1,1½,2
			D826 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2
			D840 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½
			D902 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
		21/ // 1 \\//	D907 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,2
		374 LVV	D913 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1
	Unprotected Deck		D916 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Doort		D919 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½
			D920 #		\checkmark	\checkmark		\checkmark	\checkmark	11⁄2
			D902 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,11/2,2,3
		4½″ NW	D916 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,11/2,2,3
			D919 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½

✓⁺1.5VLI Only

UL Fire Resistance Ratings (continued)

Restrained			Deck Type								
Assembly Ratings (hr.)	Type of Protection	Concrete Thickness & Type	UL Design No.	1.5VL	2VL	3VL	1.5VLP	2VLP	3VLP	Unrestrained Beam Rating (hr.)	
	Exposed Grid	3¼″ NW	D216 +	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	2,3	
		2" NW & LW	D743 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3	
		21⁄2″ LW	D746 *	\checkmark						1,1½,2,3	
			D703 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	11⁄2	
			D708 *	✓+	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1½,3	
	Comontitious		D739 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3,4	
	Cementitious	2½" NW & LW	D755	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
			D759	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
			D760 *	✓+	\checkmark	\checkmark				1,1½,2,3,4	
		3¼″ LW	D754 *	\checkmark	\checkmark	\checkmark				11⁄2,2	
		3¼″ NW	D742 *	✓	\checkmark	\checkmark				1,1½	
		2" NW & LW	D859 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3	
3			D816 *	\checkmark	\checkmark	\checkmark		\checkmark	✓	11⁄2,2	
			D831 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2	
	Sprayed Fiber	ayed Fiber 2½″ NW & LW	D832 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
			D833 *	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	11⁄2	
			D858*		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3,4	
			D871 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3	
		3¼″ LW	D860 *		\checkmark	\checkmark				1,1½,2	
			D902 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
		4 ³/16" LW	D916 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
	Unprotected		D919 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½	
	Deck		D902 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
		5¼″ NW	D916 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3	
			D919 #	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½	
		21/2 // NI/N/ 8. I/N/	D760 *	✓+	\checkmark	\checkmark				1,1½,2,3,4	
	Cementitious	$\angle /2$ IN VV \propto LVV	D739 *	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3,4	
4		3¼" LW	D754 *	~	\checkmark	\checkmark				11⁄2,2	
Sprayed Fiber	Sprayed Eiber	21⁄2″ NW & LW	D858 *		\checkmark	\checkmark		\checkmark	\checkmark	1,1½,2,3,4	
	3¼″ LW	D860 *		\checkmark	\checkmark				1,1½,2		

✓⁺ 1.5VLI Only

UL Fire Resistance Ratings

Restrained					Decl	к Туре		
Assembly Ratings (hr.)	Type of Protection	Concrete Thickness & Type	UL Design No.	0.6C	1.0C	1.3C	1.5C	Unrestrained Beam Rating (hr.)
	Exposed Grid	21⁄2″ NW	G256 +	\checkmark	\checkmark	✓	✓	1,2,3
1	Comontitious	21/2 // NI/N/ 8. I /M/	G701	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Cementitious	Z/2 INVV & LVV	G705	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Sprayed Fiber	2¾″ NW & LW G801 ✓				\checkmark	\checkmark	1,1½,2
	2" NW		G229 +	\checkmark	\checkmark	\checkmark	\checkmark	11⁄2,2,3
	Exposed Grid		G228 +	\checkmark	\checkmark	\checkmark	\checkmark	11⁄2,2
	Exposed ond	21⁄2″ NW	G243 +	\checkmark	\checkmark	\checkmark	\checkmark	1½,2
1 1/			G213 + ✓		\checkmark	\checkmark	\checkmark	1½,2,3
172	Gypsum Board	2" NW & LW	G502 +	\checkmark	\checkmark	\checkmark	\checkmark	
	Comontitious		G701	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Cementitious	Z_{2} IN VV \propto LVV	G705	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Sprayed Fiber	2¾" NW & LW	G801	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2
			G227 +	\checkmark	\checkmark	\checkmark	\checkmark	2,3
			G228 +	\checkmark	\checkmark	\checkmark	\checkmark	11⁄2,2
	Exposed Grid	01/ // NIM	G229 +	\checkmark	\checkmark	\checkmark	\checkmark	1½,2,3
		272" NW	G243 +	\checkmark	\checkmark	\checkmark	\checkmark	11⁄2,2
			G256 +	\checkmark	\checkmark	\checkmark	\checkmark	1,2,3
			G213 +	\checkmark	\checkmark	\checkmark	\checkmark	1½,2,3
2		2" NW	G505 +	\checkmark	\checkmark	\checkmark	\checkmark	
		21⁄2″ NW & LW	G529 +	\checkmark	\checkmark	\checkmark	\checkmark	2,3
	Gypsum Board	01/ // NUA/	G514 +	✓	✓	✓	\checkmark	3
		21⁄2″ NW	G523 +	\checkmark	\checkmark	\checkmark	\checkmark	2,3
	0		G701	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Cementitious	21⁄2" NW & LW	G705	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Sprayed Fiber	2¾" NW & LW	G801	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2
		3¼″ NW	G229 +	✓	\checkmark	~	\checkmark	11⁄2,2,3
	Exposed Grid	01/ // NDA/	G213 +	\checkmark	\checkmark	\checkmark	\checkmark	11⁄2,2,3
		31⁄2″ NW	G256 +	\checkmark	\checkmark	\checkmark	\checkmark	11⁄2,2,3
3 _	Gypsum Board	3¼″ NW & LW	G529 +	\checkmark	\checkmark	\checkmark	\checkmark	2,3
			G701	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	cementitious	2¾" NW & LW	G705	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2,3
	Sprayed Fiber	2¾" NW & LW	G801	\checkmark	\checkmark	\checkmark	\checkmark	1,1½,2

Restrained			Deck Type			
Assembly Ratings (hr.)	Type of Protection	Concrete Thickness & Type	UL Design No.	2D	3.5D	Unrestrained Beam Rating (hr.)
1 ¹⁰	Unprotected Deck	2" LW & 2¾" NW	D904	\checkmark		3/4
			D961	\checkmark		3/4
			D917	\checkmark		
			D928	\checkmark		3⁄4
1½	Unprotected Deck	2" LW & 2" NW	D947		\checkmark	
			D964		\checkmark	
			D984		\checkmark	
2	Unprotected Deck	2½" LW, 3" SLW & 3¼" NW	D904	\checkmark		1
			D961	\checkmark		1
			D917	\checkmark		3/4
			D928	\checkmark		1
		2" LW & 2¼" NW	D947		\checkmark	3⁄4
			D964		\checkmark	3⁄4
			D984		✓	3⁄4
3	Unprotected Deck	3¼" LW, 4" SLW & 4¾" NW	D904	\checkmark		1
			D961	\checkmark		1
			D917	\checkmark		3⁄4
			D928	\checkmark		1
		2¼" LW & 3¾" NW	D947		\checkmark	11⁄2
			D964		\checkmark	11⁄2
			D984		✓	11⁄2

UL Fire Resistance Ratings

Concrete Thickness				
(in.)	(mm)			
2	51			
21/2	64			
2¾	70			
31⁄4	83			
31/2	89			
4	102			
4 ³ / ₁₆	106			
41/2	114			
4¾	121			
5¼	133			

NOTES:

- 1. Refer to the UL "Fire Resistance Directory" for the necessary construction details.
- 1.5VL = 1.5VL, 1.5VLI, and 1.5PLVLI
 2VL = 2VLI, 2VLJ, and 2PLVLI
 3VL = 3VLI, 3VLJ, and 3PLVLI
 1.5VLP = 1.5VLP and 1.5PLVLP
 2VLP = 2VLP, and 2PLVLP
 3VLP = 3VLP, and 3PLVLP
- 3. Concrete thickness is thickness of slab above deck, in.
- 4. 1.5VLR may be used in designs D832, D902, and D916.
- 5. All Dovetail FormLok composite deck assemblies are subject to an upper live load limit of 130 psf.
- 6. Fluted deck finish shall be galvanized unless noted otherwise.

+ Denotes fluted deck finish is not critical when used in D2-- & D5-- Series designs. Deck finish shall be galvanized or phosphatized/painted.

* Fluted deck finish is critical for fire resistance. Fluted deck finish shall be galvanized or phosphatized/ painted. This gray paint is a special type of paint and is compatible with the spray-applied fire protection and is U.L. approved for use in the denoted D7-- & D8-- Series designs.

Denotes fluted deck finish is not critical for fire resistance. Fluted deck finish shall be galvanized or phosphatized/painted.

- 7. Vulcraft cellular deck used in the listed assemblies shall be galvanized.
- 8. Vulcraft cellular deck units are approved by UL for use as electrical raceways under UL Standard 209.
- 9. Dramix[®] fibers may be used in UL or ULC fire rated assemblies in lieu of WWR. See UL file R19307 for additional information.
- 10. Restrained Assembly Rating is 1½ hr with listed NW concrete thickness.

WHY GRATING?

- Easy Installation and Fabrication
- Adaptable to Complex Floor Layouts

APPLICATIONS

- Walkways
- Bridge Decks
- Trenches
- Wall Cladding
- Sun Shades
- Industrial Flooring

Standard



Close-Mesh



ADA-Compliant &

Heels-Friendly 🛓



- Allows Passage of Light and Air
- High Strength-to-Weight Ratio
- Durable and Long Lasting Surface

Heavy-Duty



HD Close-Mesh



Wide-Gap







56

GRATING



Vulcraft Grating offers both ADA compliant and Heels-Friendly Grating.







ECOSPAN®

The Ecospan® Structural Floor System by Nucor Vulcraft/Verco Group is an innovative, effective, and economical method of providing all steel structural components for elevated floor construction while incorporating the benefits of lighter weight composite design.



PRODUCT DESCRIPTION

- Joists: The Ecospan® Structural Floor System uses E-Series Vulcraft joists ranging from 10" to 30" deep and a maximum length of approximately 50'-0". Joists are typically spaced between 4'-0" o.c. and 6'-0" o.c. (For requirements outside this range please contact your Ecospan® Representative) The span is the distance from centerline to centerline of the supporting members. The design of The Ecospan® Structural Floor System joists is greatly affected by their spacing. The spacing is the distance to the adjacent joist or to the edge of the slab at exterior joists or joists next to slab openings.
- **2. Decking:** Ecospan[®] utilizes multi-span sheets of steel decking. Generally, form deck with a depth of 1" will be utilized for residential applications. 1-1/2" composite steel deck may be used for commercial applications or wider joist spaces.
- **3.** Shearflex[®] Screws: This screw is a self-drilling and self-tapping screw, ranging from 2 -1/2" to 3" in length (not including the threaded section). Screws are installed using the Vulcraft provided Shearset[®] Tool.
- **4. Concrete Slab Reinforcement (by Others):** Slab reinforcement shall be the responsibility of the design professional. Rebar or welded wire fabric is suggested for form deck applications while distributed fibers may be an acceptable alternate for projects utilizing composite decks. Refer to ANSI/SDI-C-2017 Standard for Composite Steel Floor Deck-Slabs paragraph 2.4.B.15 Items 2 & 3 for applicable dosage rates for distributed fibers.
- **5. Concrete slab (by Others):** The concrete topping slab (specified by the Design Professional) is typically 2-1/2" normal weight concrete having a minimum 28 day ultimate compressive strength (f'_c) of 3,000 psi, though thicker slabs may be designed for heavier duty uses or serviceability concerns. Light weight concrete may also be specified with The Ecospan[®] Structural Floor System.



CONSIDER THE ADVANTAGES

- The Ecospan® Structural Floor System is an effective and economical solution for constructing residential and commercial floor systems.
- Erection is safe, easy, and cost effective. Sub-trades can normally continue construction the day after the concrete is placed.
- Floor to floor heights can often be decreased due to the inherent ability to pass mechanical ducts, piping, conduit, etc. through the open web design.
- High strength-to-weight ratio of composite steel joists allow for greater spans and spacing with lighter members.
- Weight savings due to composite joist design reduces building weight and allows foundation and wall costs to be reduced.
- Constructed with non-combustible materials, achieving multiple UL listings with gypsum board, acoustical ceilings, or spray applied fire resistant materials.
- The Ecospan® Structural Floor System has a Sound Transmission Classification (STC) of 57, and meets or exceeds Impact Insulation Classification (IIC) requirements of the IBC for residential and commercial construction with commonly used sound attenuation materials.

INCORPORATING ECOSPAN® INTO A PROJECT

The Ecospan[®] Structural Floor System can be utilized for most commercial or residential projects. Ecospan[®] joists (E-series) are individually designed for the span, spacing, and loading specified on the Contract Documents.

In order for Vulcraft engineers and detailers to quickly and efficiently prepare each project with minimal shop drawing review time, some basic design criteria will be needed from the Design Professional.

1. DESIGN LOADS

Unfactored loads that should be specified are as follows:

- a. Non-composite dead load: Includes concrete, joists, deck, and bridging
- **b.** Construction live load: Indicates the required loading due to work crews and construction equipment before and during the placement of concrete (Ref. ASCE 37-14)
- **c. Composite dead load:** Includes non-moving partitions, mechanical, electrical, fireproofing, floor covering, and ceiling
- d. Composite live load: The design live load, including moving partitions, as specified.

2. CAMBER

E-series joists are designed with an Ecospan standard camber or cambered for 100% of the non-composite dead load. The Design Professional may indicate their preference for camber design, as well as any additional camber requirements.

3. DEFLECTION

The Design Professional shall indicate the maximum allowable live load deflection for each Ecospan[®] composite joist. In the absence of a specified live load or total load deflection limit, a L/360 live load deflection limit is assumed.

4. VIBRATION

Calculations for the predicted floor vibration of the Ecospan[®] Structural Floor System shall be completed by the Design Professional. Based on this analysis, the Design Professional can indicate a minimum moment of inertia (MOI), either as dynamic effective MOI or as chord MOI, required to meet the floor performance requirements.

5. ADDITIONAL CONSIDERATIONS

When specifying the Ecospan® Structural Floor System, the Design Professional should consider the following items:

- a. Parallel top and bottom chords are required
- b. Maximum steel floor deck depth is 1-1/2" inches
- c. Slab thickness above top flute of the deck must be a minimum of 2 -1/2" for fire rated assemblies
- d. Maintain a constant concrete thickness along the entire joist span

E-SERIES JOIST DESIGNATION

The image below illustrates the format used to designate an E-Series joist. Loading numbers are shown in pounds per lineal foot (PLF). Total load is the summation of the un-factored live load, non-composite dead load, and composite dead load.



Visit <u>www.vulcraft.com/Products/Ecospan</u> for additional information about the Ecospan Composite Floor System, including Case Studies of existing Ecospan Projects.

VULCRAFT SALES CORPORATION OFFICES

ATLANTA, GA 770.307.2111

BALTIMORE, MD 410.998.0800

BIRMINGHAM, AL 205.982.4394

BOARDMAN, OH 330.726.8833

CENTERVILLE, UT 801.292.0730

COLUMBIA, SC 803.358.1300

DALLAS, TX 214.340.1883

DENVER, CO 303.757.6323

EDISON, NJ 732.738.8188

FLOWOOD, MS 601.383.7807

GENEVA, NY 315.828.1730

GRAND RAPIDS, MI 616.949.2106

HINSDALE, IL 630.887.1400

HOUSTON, TX 281.251.8857

INDIANAPOLIS, IN 317.576.5399

KERNSVILLE, NC 336.497.5302

KNOXVILLE, TN 865.690.6388

LEXINGTON, KY 859.940.0152

LITTLE ROCK, AR 501.758.6424

MEMPHIS, TN 901.612.3481

MINNEAPOLIS, MN 763.425.4399

NASHVILLE, TN 615.871.9385

NEW HUDSON, MI 248.486.6166

NORRISTOWN, PA 610.539.6516

OKLAHOMA CITY, OK 405.715.2844

ORANGE, CA 714.957.5713

OVERLAND PARK, KS 913.341.9299

PHOENIX, AZ 623.385.1649

SACRAMENTO, CA 916.488.8180

SALEM, NH 603.894.1146

SAN ANTONIO, TX 210.655.9070

SEATTLE, WA 425.402.9011

SPRINGFIELD, OH 937.390.2300

ST. LOUIS, MO 636.266.1844

TAMPA, FL 813.621.0684



