



 **WARNING:** Before attempting to install or maintain this product, assure that your weapon is unloaded and the weapon safety is in the "safe" position

ASSEMBLING MAGNIFIER TO MOUNT

The 4xRDM will come pre-assembled with the smaller Absolute Cowitness Spacer. If you need to change your setup for Lower 1/3 Cowitness red dots, follow these steps.

- 1) Loosen and remove the 2 Tension Bolts on the far sides of the optic mount and remove the Magnifier
- 2) Remove the two small Spacer Bolts on the inside of the optic mount and remove the spacer.
- 3) Install the Large Spacer and Spacer Bolts the same way, applying even tension on both bolts
- 4) Insert the Magnifier with the Elevation Adjustment up, and the Windage Adjustment to the right.
- 5) Hand tighten Tension bolts to hold magnifier, plus ¼ turn. **Do not over-tighten.**

MOUNTING THE SIGHT

- 1) Loosen the Lock Nut using the included wrench, and release the Quick Detach Lever.
- 2) Position the magnifier behind your red dot optic.
 - a. Mount as close as possible, while still leaving room for operating your sight – about ¼"
- 3) Close the Quick Detach Lever and tighten the Lock Nut until optic doesn't move. **Do not over-tighten.**

OPERATION

To flip – Push the Release Button, and Flip to Side to engage and disengage.

- **To focus** - If the red dot is blurry, use the Diopter Adjustment and adjust until dot appears clear.

CENTERING THE DOT

After zeroing your optic, use the Windage and Elevation Adjustment Screws to center the red dot within your magnifier's sight picture. *Note – this step is optional, as it will not change the point of impact. It only centers the reticle in your magnifier.*

WARRANTY

AT3 Tactical products carry a lifetime warranty. Full details are available at at3tactical.com/warranty
If you have any issues or need a replacement, please contact us via email: support@at3tactical.com

