

## Cement Putty

Putty for smoothing interior and exterior plastering.

### Description:

- **CEMENT PUTTY** is a powder based on cement, specially formulated filler and chemical additives to improve its features.

### Fields of use:

- For smoothing plasters on walls and ceilings.
- For exterior and interior application.
- For filling small holes and fissures.

### Advantages:

- Ready to use after adding water.
- Resistant to weathering conditions.
- Good adhesion to concrete, cement and lime plaster surfaces.

### Technical Data: (at 25 ° C):

Color:	White – Gray (Other colors on demand)
Density (powder):	0.98 ± 0.05 kg / lt.
Density ( putty ) 28 day	1.75 ± 0.05 kg / lt.
Drying Time:	4 hours
Consumption Rate (Theoretical):	350 – 400 gm. / m <sup>2</sup> / coat Thickness 200-225 μ

### Directions for use:

- The surface should be clean and free from dust, oils, grease, etc.
- Add water to **CEMENT PUTTY** powder at a ratio 40 – 45 L water : 100 Kg powder and mix thoroughly.
- Apply one or more coats of **CEMENT PUTTY** by a putty knife, depending on roughness of the surface.
- Each layer could should be dried and sanded down before applying the next coat.
- Clean tools directly after use with water.

### Safety Precautions:

- Wear gloves, overalls and goggles during handling & application.
- In case of contact, rinse off thoroughly with water.

**Storage:** 12 months under proper and dry storing conditions.

**Packs:** Bags: 10, 25 kg.