

survitec

# SOLAS BOATS

SEARCH AND RESCUE BOAT SOLUTIONS ↓





# DSB INFLATABLE RESCUE BOATS

SEARCH AND RESCUE BOAT SOLUTIONS ↓

DSB part of the Survitec Group has a global presence with a worldwide reach. DSB pioneered the design and manufacture of Rescue Boats in 1931, making them the safest, most popular and widely used Rescue Boats in the international survival market. Designed for commercial and military applications and with broad adaptability we offer our customers' turnkey boat solutions. Our products meet the highest safety regulations in the industry and all of our rescue boats meet current SOLAS approvals. DSB offers two types of Rescue Boats; Inflatable and Semi Rigid.

DSB Inflatable Rescue Boats are available in several sizes including 420, 470 and 530. Exceptionally lightweight due to ultra-light Hypalon fabric and smaller outboard engine, our boats require smaller davits making transport and servicing easier, more efficient and economical. Built for a variety of end users including commercial and defence organisations, the DSB Rescue Boats couple operator friendly, advanced performance capabilities with durability and innovative design.

## FEATURES

- INFLATABLE DEEP V SHAPED KEEL FOR IMPROVED MANOEUVRABILITY
- FITTED WITH RADAR REFLECTOR, COMPASS AND ALL STANDARD SAFETY EQUIPMENT
- REINFORCED HYPALON SEAMS
- HYPALON FENDER TUBE IS UV AND ABRASION RESISTANT
- INFLATABLE KEEL RESULTING IN EXCELLENT MANOEUVRABILITY IN THE WATER
- ADVANCED BOW DESIGN INCREASES INTERNAL SPACE
- LIGHTWEIGHT RESULTING IN EASIER MANOEUVRABILITY



# DSB - INFLATABLE BOATS

RESCUE BOAT SOLUTIONS ↓

## TECHNICAL DATA

Product Name	DSB 420	DSB 470	DSB 530
Overall Length	4.20 m	4.70 m	5.30 m
Length Inside	2960 mm	3420 mm	3795 mm
Beam Overall	1800 mm	1980 mm	2135 mm
Beam Inside	890 mm	980 mm	1035 mm
Boat Weight	123 kg	149 kg	179 kg
Stowed Boat Dimensions on a palette	160 x 80 x 90 cm	160 x 80 x 110 cm	175 x 85 x 140 cm
Capacity	6 persons	7 persons	15 persons
Max Hoisting Weight (operational)	801 kg	910 kg	1610 kg
Tube Diameter	455 mm	500 mm	550 mm
Air Compartments	5 Chambers	5 Chambers	7 Chambers
Fabric	Hypalon/Neoprene	Hypalon/Neoprene	Hypalon/Neoprene
Min Motorisation	11.2/15 kW/PS	11.2/15 kW/PS	11.2/15 kW/PS
Max Motorisation	29.5/40 kW/HP	29.5/40 kW/HP	29.5/40 kW/HP
Key points	Inflatable Keel	Inflatable Keel	Inflatable Keel



## APPROVALS

EC MED

