





FEATURES

- · Thicker than most other duct wrapping films
- · Durable and flexible
- · Self-adhesive inner surface
- Excellent adhesion to duct & fittings
- Easily removable without leaving residue in most temperatures

SPECIFICATIONS

- Application: Galvanized Steel, Stainless Steel, Aluminum
- Tensile Strength: Minimum 10 psi
- Elongation: Twice its original length
- UV resistant and waterproof
- Color: Blue
- Disposal: Recyclable



<u>Item #</u>	Code	<u>Description</u>	Dimensions (cxw)	Weight per roll (lbs.)	<u>Packaging</u>
13380	DW24-200	Dyn-O-Wrap Roll 24'' x 200'	24'' x 200'	6.3	6 Rolls/Box
13384	DW36-200	Dyn-O-Wrap Roll 36'' x 200'	36'' x 200'	10	1 Roll/Box
13388	DW48-200	Dyn-O-Wrap Roll 48" x 200'	48'' x 200'	14	1 Roll/Box
13382	PRW24-200	Puncture Resistant Dyn-O-Wrap Roll 24" x 200'	24'' x 200'	6.3	1 Roll
13386	PRW36-200	Puncture Resistant Dyn-O-Wrap Roll 36" x 200'	36" x 200'	10	1 Roll
13389	PRW48-200	Puncture Resistant Dyn-O-Wrap Roll 48" x 200'	48" x 200'	14	1 Roll

Duro Dyne East Division, Bay Shore, NY
Duro Dyne Midwest Division, Hamilton, OH
Duro Dyne West Division, Fontana, CA
Duro Dyne Canada, Lachine, Quebec, Canada
www.durodynecanada.ca
E-mail: durodynecanada@durodyne.com

631-249-9000
Fax: 631-249-8346
Fax: 513-870-6005
Fax: 562-926-5778
Fax: 514-636-0328

