



DESIGNER

EXTERIOR

TIMBERSHADES
ACRYLIC-ALKYD SEMI-TRANSPARENT STAIN



GREAT PAINT GREAT PEOPLE



hallmanlindsay.com

TIMBERSHADES

TIMBERSHADES SEMI-TRANSPARENT STAIN is our finest exterior semi-transparent stain designed to help beautify and protect exterior wood surfaces. Formulated to meet the expectations of designers and architects, TIMBERSHADES SEMI-TRANSPARENT STAIN enhances the natural appearance and texture of wood surfaces while providing industry-leading color and weather protection. Hybrid alkyd-acrylic technology provides the penetration, durability, and repellency of an alkyd with the color retention and application of an acrylic.

TIMBERSHADES SEMI-TRANSPARENT STAIN provides a rich, semi-transparent finish that may be applied in multiple coats to increase opacity building a semi-opaque finish with a soft sheen. Best used on new wood surfaces and recoating properly prepared previously finished wood surfaces and can be used on decks, siding, logs, shingles, shake, furniture, and fencing.

FEATURES

- Waterborne Alkyd-Acrylic Technology
- Excellent Adhesion
- Outstanding Color Retention
- Mildew and Algae Resistant
- Hydrophobic Technology
- Light Sheen Build With Multiple Coats

BENEFITS

Enduring Wood Finish

TIMBERSHADES will hold color long after traditional coatings have worn away. Trans-oxide pigments provide the color retention needed for prolonged UV exposure.

Tenacious Weather Protection

TIMBERSHADES hydrophobic technology helps block moisture penetration adding years of life to your wood surfaces.

Mold and Mildew Resistant Coating

Exceptional resistance to mold and mildew provides a clean, attractive finish for years to come.



TECHNICAL INFORMATION

APPLICATION INFORMATION

Drying Time at 77° F 50% R.H.:

To Touch: 4 Hours*

Recoat: Same Day*

* Cooler temperatures and higher relative humidity will extend dry times

Application Temperature:

Apply Down to 50° F. Ask for details.

Recommended Spreading Rate:

200-400 sq.ft./Gal on most surfaces

Solids Content:

Volume: 34% ± 2 Weight: 46% ± 2

BASES: NATURAL CEDAR TONE - 198-51 · CUSTOM COLORS - 198 SERIES

EQUIPMENT RECOMMENDATIONS

Roller: 1/4" - 3/8" nap synthetic cover

Brush: 100% nylon or synthetic blend

Airless: 800-1500 psi with 0.011" - 0.015" tip

HVLP: Not recommended

SAFETY AND COMPLIANCE

VOC (EPA Method 24):

22 g/L 0.18 lbs./Gal

FINISHING RECOMMENDATIONS

New Wood Surfaces:

Cedar, Redwood, Pine, Treated Pine: Apply TIMBERSHADES SEMI-TRANSPARENT to achieve desired appearance.

Recoating Wood Surfaces:

Surface must be free of dirt, grime, previous stains, or other contaminants that prevent stain penetration. Apply TIMBERSHADES SEMI-TRANSPARENT to achieve desired appearance.