NOTES: UNLESS OTHERWISE SPECIFIED.

1. INTERPRET DRAWING PER MIL-STD-100.
2. INTERPRET DIMENSIONS AND TOLERANCES PER ANSI Y14.5M.
3. ABBREVIATIONS PER MIL-STD-12.
4. DIMENSIONS AND VALUES IN BRACKETS ARE METRIC.
5. MOUNT DIMENSIONS DO NOT REFLECT INSTALLED, LEVELED HEIGHT.

A10S

REVISIONS				
ZONE	LTR	DESCRIPTION	DATE	APPROVED
	A	SEE DCN-1082	12/2/95	SK
	B	SEE DCN-1323	4/18/96	GUY/SK
	C	SEE DCN-1499	10/24/96	SK
	D	SEE ECN-1547	11/13/96	SK
	E	SEE ECN-1606	4/14/97	



Specifications for EDWARDS multi-stage vacuum pump		
Model A10S		60 Hz
Pump Speed		1200 LPM, 42 CFM
Ultimate Press.		3 x 10^{-3} Torr
MOTOR	Power	2.2 kw
	Current Full Load	11.1 Amps
	Voltage	208 VAC
	RPM	3450
Pumping	Inlet	NW40
	Exhaust	NW40
GAS BALLAST	Inlet	.375-18 NPT
	Exhaust	.375-18 NPT
	Pressure	<4kgf/cm² (60psi) Differential: 1-2kgf/cm² (14-28psi)
	Quantity	3.5 l/min (0.9 GPM)
SEAL PURGE	Inlet	.250 tube connection
	Pressure	Primary: 1-7kgf/cm² (14-100psi) Secondary: 1atg/cm² (14psi)
	Quantity	10-12 l/min(0.3-0.4cfm) W/O Exh. Oil
Oil Capacity		0.4 (13.5oz)
Weight Approx.		230kg [485lbs]





PARTS LIST				
QTY. REQD.	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL AND/OR SPECIFICATION	ITEM NO.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCES
DECIMALS: X ±.1, X.X ±.03, X.XX ±.010
FRACTIONS ±1/64
ANGLES ±1°
DO NOT SCALE DRAWING
THIRD ANGLE PROJECTION

This drawing contains proprietary information and may not be copied, duplicated or used for any other purposes than for which furnished, without written permission of EDWARDS HIGH VACUUM INTERNATIONAL

EDWARDS TECHNOLOGIES INC.
DRYPUMP OPERATION

JOB NUMBER	STANDARD	
DRAWN	C THOMPSON	2/1/96
CHECK	S KELLEY	2/14/96
DESIGN	S KELLEY	2/14/96
PROJECT	S KELLEY	2/14/96

EDWARDS TECHNOLOGIES INCORPORATED
DRYPUMP OPERATION
EDWARDS Sacramento, CA 95838 U.S.A.

SIZE B | DWG NO. 110243 | REV E

SCALE 1/8 | WEIGHT | SHEET 1 OF 1

209