

Secure Start® Permeable

Breathable, Lightweight Synthetic Underlayment

Secure Start® Permeable synthetic underlayment is engineered for the ultimate defense from roof deck rot. Patented permeable technology removes moisture from a wet roof deck or poorly ventilated roof system, preventing premature roof deck decay and mold growth.

Secure Start® Permeable is an ultra thick but lightweight polypropylene underlayment that installs 25% faster than #30 traditional felt.

INSTALLED SECOND


When installing a complete 5-component system, underlayment is installed second, after the ice & water barrier, and prior to the starter shingles.

ONE WAY PERMEABLE BARRIER —

Permeable inner layer prevents water transfer through the membrane but allows water vapor from poor attic ventilation to escape from beneath.

3 LAYER CONSTRUCTION

Provides greater tear strength than conventional felt underlayments.



Bottom layer absorbs moisture from the roof deck and grips the surface for slip protection.

Top layer effectively sheds water and can withstand 90 days of UV exposure.

IMPROVED SAFETY

Raised shamrocks provide a slip resistant surface and make steep slope roofing installations safer in all weather conditions.



Secure Start® Permeable is mechanically fastened to the roof deck, and carries a UL Class A Fire Rating when installed with a fire-rated roof covering.

Test Compliance - ASTM D4869, ASTM D8257, ASTM E108 Class A Fire Rating, CAN/CSA A220.1, CCRR #0537, ICC-ES AC188, and FBC FL23186.

Secure Start® Permeable is eligible for expanded warranty coverages relative to its use as a single roofing accessory or in combination with others in a complete Malarkey Secure Choice $^{\mathtt{m}}$ roofing system. Installed separately, it carries a 10-year product warranty against manufacturing defects. For complete warranty information, please visit www.malarkevroofing.com/warranties

This version supersedes all previous versions. Rev. 07/24

LIGHTWEIGHT

5 SQ. ROLL

Only 19 lbs.