

# **Parker Steel Company**





## SAFETY DATA SHEET

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MATERIAL	, REVISION DATE	Identification / Rev. Number
Chrome-plated bar and tubing (Chromerod and Chromerod Extreme)	1/29/2016	2010-124 3_EI_Chrome_Rev7
SUPPLIERS'S ADDRESS	ENVIRONMENTAL, HEAL	TH, & SAFETY CONTACT PHONE NO.
1625 Indian Wood Circle Maumee Ohio 43537 P:800-333-4140 Email: sales@metricmetal.com		T: CHEMTREC 1.800.424.9300 utside US, dial 703.527.3887)
CHEMICAL FAMILY	FORM	13ide 00; upi 100.021.0001)
Metals		induction-hardened steel bars, ods, & tubes

## **SECTION 2: COMPOSITION / HAZARDOUS INGREDIENTS**

MATERIAL OR COMPONENT	CAS NUMBER	CARBON STEEL (% Wt.)	LOW ALLOY STEEL (% Wt.)	APPLICABLE E	XPOSURE LIMITS
Base Metal				OSHA PEL <sup>z</sup> (mg/m3)	ACGIH TLV <sup>3</sup> (mg/m3)
Iron (Fe)	7439-89-6	Balance	Balance	10 as Fe <sub>2</sub> O <sub>3</sub> Fume	50 as Fe <sub>2</sub> O <sub>3</sub> Fume
Elements					
Aluminum (AI)*	7429-90-5	0.1 MAX	0.1 MAX	5 as Respirable	5.0 as Welding Fume
Carbon (C)	7440-44-0	0.45 MAX	0.45 MAX	None Listed	None Listed
Chromium (Cr)*	7440-47-3	0.22 - 1.64	0.52 - 3.04	1.0 as Chrome	0.5 as Chrome
Copper (Cu)*	7440-50-8	0.35 MAX	0.6 MAX	0.2 as Copper	1.0 as Dust
Manganese (Mn)*	7439-96-5	0.2 - 1.7	0.2 -1.7	5 as Manganese (C)	5 as D <sub>i</sub> st; 1 as Fume 3 (C)
Molybdenum (Mo)	7439-98-7	0.1 MAX	0.65 MAX	15 as Insoluble Compd.	10 as Insoluble Compd.
Nickel (Ni)*	7440-02-0	0.25 MAX	0.7 MAX	1.0 as Nickel	1.0 as Nickel
Phosphorous (P)*	7723-14-0	0.035 MAX	0.04 MAX	0.1 as Phosphorous	0 as Phosphorous
Silicon (Si)	7440-21-3	1.0 MAX	1.0 MAX	5 as Respirable	10 as Total Dust
Sulfur (S)	7446-09-5	0.05 MAX	0.5 MAX	5.0 as Sulfur Dioxide	5.2 as Sulfur Dioxide
Tin (Sn)	7440-31-5	0.03 MAX	0.03 MAX	2.0 as Tin	2.0 as Tin
Vanadium (V)	1-314-62-1	0.15 MAX	0.15 MAX	0.5 as Dust; 0.1 Fume (C)	0.0 as Dust and Fume

- The above listing is a summary of elements commonly found in applicable steel grades. Various grades of steel may contain different combinations of these elements. Other trace elements, in minute quantities, may also be pe sent. Chrome plating chemistry considered in the above component percentages, although the product is not homogenous. MAX chrome concentration calculated using maximum surface area to volume ratio of normal product size ranges. Values shown within carbon steel and low alloy steel columns differ due to chemistries of substrate (base) steel.
  - (2) OSHA Permissible Exposure Limits (PELs) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A ("C") designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted.
  - (3) Threshold Limit Values (TLVs) established by the American Conference of Governmental Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded during any time during the workday.
  - \* SARA Title III Section 313 Chemical (See Section 15)
  - (5) Optional Light surface coating of rust preventative or polish may be used. SDS available upon request. Use gloves when handling to prevent skin irritation. Use adequate ventilation and / or appropriate personal protection when fumes or dust are generated

## **SECTION 3: PHYSICAL DATA**

Solid (at standard conditions)	Bright Silver & Odd		
OTHER PHYSICAL DATA			
Boiling Point: NA Vapor Pressure: NA Solubility in H <sub>2</sub> O: Insoluble	Specific Gravity: 7.5 to 8 % Volatile by Vol.: NA Evaporation Rate: NA	pH: NA Melting Point:	,2400 – 2800 °F

## **SECTION 4: FIRE & EXPOSION DATA**

Flash Point (°F)	Auto Ignition Temperature (°F)	Flammable Limits in Air (%)	Extinguishing Media	
NA	NA	Lower: NA Upper: NA	NA	
Fire and Explosion Hazards		Extinguishing Media Not to be Used		
NONE		NA		
	in the solid state do not present a fi by present a dust explosion hazard.	re or explosion hazard. Hov	vever, particulate generated	

**SECTION 5: REACTIVITY** 

REACTIVITY					
Stability		у	Incompatibility (Materials to Avoi	d)	
$\boxtimes$					
	Conditions to Avoid				
No	Non- ventilated areas when cutting, welding, burning, or brazing; avoid generation of airborne dusts and fumes.				
	Hazardous Decomposition Products				
Me	etallic oxide	es			

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### SPILL OR LEAK PROCEDURES

Special Precautions: Use good housekeeping practices to prevent accumulation of dust and to keep airborne dust to a minimum. No CERCLA RQ specified for the product as a whole.

SECTION 7: PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION	PROTECTIVE CLOTHING
NIOSH Approved dust/mist/fume respirator should be used during welding or burning if OSHA PEL or TLV is exceeded.	Use appropriate protective clothing such as welder's aprons & gloves when welding or burning. Depending on use, check local, state, and federal codes.
EYES AND FACE	VENTILATION
Safety glasses should always be worn when grinding or cutting; face shields should be worn when welding or burning.	As per welding requirements. Depending on use, check local, state, and federal codes.

### **SECTION 8: EMERGENCY MEDICAL PROCEDURES**

INHALATION	SKIN CONTACT
Remove to fresh air, if condition continues, consult physician.	If irritation develops, remove clothing and wash well with soap and water. If condition persists, seek medical attention.
EYE CONTACT	INGESTION
Immediately flush well with running water to remove particulate; seek medical attention.	If significant amounts of metal are ingested, seek medical attention.

## **SECTION 9: HEALTH/SAFETY INFORMATION**

#### HEALTH

- General: Steel products in the natural state do not present an inhalation, ingestion, or contact health hazard. However, operations such as welding, burning, sawing, brazing, grinding, and possibly machining, which results in elevating the temperature of the product to or above its melting point or results in the generation of airborne particulates may present hazards. The above operations should be preformed in well-ventilated areas.
- Occupational Exposure Limits: Refer to Section 1.
- Major Exposure Hazard: Inhalation
- Overexposure Effects:
  - 1. Acute: Excessive inhalation of metallic fumes and dusts may result in irritation of eyes, nose, and throat. High concentrations of oxide fumes and may result in metal fume fever. Typical symptoms consist of a metallic

taste in the mouth, dryness and irritation of the throat, chill and fever and usually last from 12 to 48 hours.

- 2. Chronic: Chronic and prolonged inhalation of high concentrations of fumes or dust of the following elements may lead to:
- Iron (iron oxide) Pulmonary effects, siderosis
- Manganese bronchitis, pneumonitis, effect on central nervous system
- Chromium Various forms of dermatitis, inflammation and/or ulceration of upper respiratory tract and
  possibly cancer of nasal passages and lungs. Based on available information, there does not
  appear to be evidence that exposure to welding fume induce human cancer.
- Nickel Same as chromium
- Copper Pulmonary effects
- Molybdenum Pain in joints hands knees and feet.
- Aluminum May initiate fibrotic changes to lung tissue
- Phosphorous Necrosis of the mandible
- Sulfur Edema of the lungs
- Tin Cumulative systemic toxicity, central nervous system effects

CARCINOGENICITY NOTE: The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP), and OSHA do not list steel products as carcinogens. IARC identifies welding fumes as a Group 2B Carcinogen, a mixture that is possibly carcinogenic to humans.

## **SECTION 10: HANDLING & STORAGE**

#### STORAGE TEMPERATURES

Stable under standard temperatures & pressures.

#### **HANDLING / STORAGE PRECAUTIONS:**

Store away from strong oxidizers. Dusts or powders may form explosive mixtures with air. Avoid breathing dusts or fumes.

## SECTION 11: TOXIOLOGICAL PROPERTIES

ACUTE TOXICITY DATA	LD <sub>50</sub> (mg/kg) – oral	
Iron (Fe)	No Data	
Aluminum (AI)*	No Data	
Carbon (C)	No Data	
Chromium (Cr)*	No Data	
Copper (Cu)*	No Data	
Manganese (Mn)*	9,000 (rat)	
Molybdenum (Mo)	No Data	
Nickel (Ni)*	No Data	
Phosphorous (P)*	No Data	
Silicon (Si)	No Data	
Sulfur (S)	No Data	
Tin (Sn)	No Data	
Vanadium (V)	10 (rat)	

NOTE: No LD<sub>50</sub> has been established for the mixture as a whole. Source for Acute Toxicity Data Shown Above: NIOSH Chemical Listing and Documentation of Revised IDLH Values.

## **SECTION 12: ECOLOGICAL INFORMATION**

#### **ECOTOXICITY**

No data available for the product as a whole. However, individual components of the product have been found to be toxic to the environment. Metal dusts have the potential migrate into soil and groundwater mediums if not managed properly.

#### ENVIRONMENTAL FATE

No data available on the product as a whole.

#### **ENVIRONMENTAL DEGRADATION**

No data available on the product as a whole.

#### SECTION 13: DISPOSAL / RECYCLING CONSIDERATIONS

## WASTE MANAGEMENT METHODS

Product should be recycled whenever possible, in accordance with federal, state, and local regulations. Steel scrap, when recycled, is not regulated as a hazardous or solid waste under RCRA (40 CFR 261). If product dusts and/or fumes from processing operations are not recycled, they are considered to be a solid waste and may be classified as a hazardous waste depending on the toxicity characteristics of the dust as defined within 40 CFR 261.24.

#### SECTION 14: TRANSPORT INFORMATION

#### **USDOT INFORMATION**

This product is not listed as a USDOT Hazardous Material as defined within 49 CFR 172.101. However, ensure that material loads are prepared and secured in accordance with all applicable USDOT Regulations.

#### SECTION 15: REGULATORY INFORMATION

#### **OSHA REGULATIONS**

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A: The product as a whole is not listed. However, individual components of the product are listed.

#### **ENVIRONMENTAL REGULATIONS**

- RCRA (40 CFR 261): Steel scrap, when recycled, is not regulated as a hazardous o solid waste under RCRA. If product dusts and/or fumes from processing operations are not recycled, they are considered to be a solid waste and may be classified as a hazardous waste depending on the toxi ty characteristics of the dust as defined within 40 CFR 261.24.
- CERCLA (40 CFR 302.4): No CERCLA RQ specified for the product as a whole.
- SARA 313 (40 CFR 372.65): Potential SARA Title III Section 313 Chemicals are denoted by an asterisk (\*) in Section I. Please note that if you prepackage or redistribute this product to industrial customers, SARA 313 may require a notice be sent to these customers.

NOTE: Information listed above is intended for use as guidance only and should not be solely relied upon for all regulatory compliance obligations / responsibilities. Neither state nor foreign regulations are addressed within the information listed above.

#### **SECTION 16: ADDITIONAL INFORMATION**

#### **MATERIAL CERTIFICATION**

- European Union Directive 2002/95/EC, Restriction of Hazardous Substances (RoHS)
- European Union Directive 2000/53/EC, End-of-Life Vehicles (ELV)
- GADSL, no declarable substances within supplied components at vehicle point-of-sale
- Free of mercury contamination and / or mercury compounds\*

\*As defined by GADSL V1.0 2005-01-25 and RoHS Directive (2002/95/EC)

#### DISCLAIMER

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard (29 CFR 1910.1200). The information in the SDS was obtained from sources that we believe are reliable, but are beyond our direct supervision or control. We make NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, with respect to such information, and we assume no liability resulting from its use. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or, disposal of the product. It is the obligation of each user of this product to determine the suitability of this product and comply with the requirements of all applicable laws regarding use and disposal of this product.



#### **WARNING:**

This product can expose you to a chemical or chemicals such as Chromium which is [are] known to the State of California to cause cancer or birth defects or other reproductive harm.

For more information go to: www.P65Warnings.ca.gov/product