



MAXI-TUFF® MF
PLASTIC
ELEVATOR BUCKET



TECHNICAL SPECIFICATION - MAXI-TUFF® MF PLASTIC ELEVATOR BUCKET

Type	A	B	H1	H1	T	HDP	PU	Nylon	Capacity (W-L)	holes	D	E	I	Max. buckets per meter
Dimensions	mm	mm	mm	mm	mm	kgs.	kgs.	kgs.	Ltr.	No.	mm	mm	mm	Pcs.
8 x 5 x 7	210	140	191	120	9,7	0,77	1,08	0,89	1,32	cust. spec.	cust. spec.	cust. spec.	cust. spec.	4,9
10 x 5 x 7	260	140	191	120	10,0	0,93	1,30	1,51	1,56	cust. spec.	cust. spec.	cust. spec.	cust. spec.	4,9
12 x 7 x 11	311	191	292	160	8,9	1,64	2,18	1,81	2,83	cust. spec.	cust. spec.	cust. spec.	cust. spec.	3,3
12 x 8 x 11	311	216	292	175	8,3	1,96	2,56	2,18	4,50	cust. spec.	cust. spec.	cust. spec.	cust. spec.	3,3
14 x 7 x 11	362	191	292	160	8,3	1,76	2,42	2,05	3,30	cust. spec.	cust. spec.	cust. spec.	cust. spec.	3,3
14 x 8 x 11	362	216	292	175	8,3	2,07	X	2,39	5,50	cust. spec.	cust. spec.	cust. spec.	cust. spec.	3,3
16 x 7 x 11	413	191	292	160	8,3	1,99	2,71	2,25	3,91	cust. spec.	cust. spec.	cust. spec.	cust. spec.	3,3
16 x 8 x 11	413	216	292	175	8,3	2,35	X	2,64	6,50	cust. spec.	cust. spec.	cust. spec.	cust. spec.	3,3
18 x 7 x 11	464	191	292	160	8,3	2,25	3,06	2,64	4,00	cust. spec.	cust. spec.	cust. spec.	cust. spec.	3,3
18 x 8 x 11	464	216	292	175	8,3	2,64	X	3,07	7,66	cust. spec.	cust. spec.	cust. spec.	cust. spec.	3,3

- Type MAXI-TUFF® MF elevator bucket has flat holes in the back of the bucket and on the inside of the bucket and needs to be fitted on the elevator belt by using a DIN15237 elevator bolt or Norway elevator bolt (metric) type STM in combination with a flat washer according to DIN9021 (Fig.1). Contact a Muller Beltex representative for advice on the recommended bolt hole pattern.

- Available in polyethylene color white (max. temp +80° C.), Polyurethane color green (max. temp +80° C. X = not available) and nylon color tan (max. temp +120° C.).

- FDA 1935/2004