

END-TO-END | Scooter Specifications

For more information visit pridemobility.com.au or call 03 8770 9600
20-24 Apollo Drive, Hallam VIC 3803 | ACN 088 609 661 | ABN 66 088 609 66



MODEL NAME	Quest®	Go-Go®Ultra X	Go-Go® Elite Traveller Plus	Go-Go® LX w/ CTS Suspension	Revo® 2.0	Zero Turn 8	Zero Turn 10	Pathrider® ES 10	Pathrider® 10	Pathrider® 10 DX	Gopher SV	Victory® LX w/ CTS Suspension	Celebrity® DX	Celebrity® XL DX	Pathrider® 130 XL	Pathrider® 140 XL	Outback®	Sport Rider
FRONT TYRES	4 cm x 18 cm (1.5" x 7") solid	3W: 5 cm x 20.3 cm (2" x 8") solid 4W: 5 cm x 17.8 cm (2" x 7") solid	5 cm x 20.3 cm (2" x 8") solid	5 cm x 17.8 cm (2" x 7") solid	6.3 cm x 22.8 cm (2.5" x 9") solid	5 cm x 17.8 cm (2" x 7") solid	22.8 cm x 7 cm (9" x 2.75") solid	9.1 cm x 26.4 cm (3.6" x 10.4")	9 cm x 25.4 cm (3.5" x 10")	9 cm x 25.4 cm (3.5" x 10")	7.62 cm x 25.4 cm (3" x 10")	9 cm x 25.4 cm (3.5" x 10")	9 cm x 25.4 cm (3.5" x 10")	10 cm x 33 cm (4" x 13")	10 cm x 33 cm (4" x 13")	10 cm x 33 cm (4" x 13")	37 cm x 15.2 cm (14.5" x 6")	6.9 cm x 48.2 cm (2.75" x 19") ¹⁷
REAR TYRES	5 cm x 20 cm (1.9" x 7.8") solid	6.35 cm x 20.3 cm (2.5" x 8") solid	7.6 cm x 22.9 cm (3" x 9") solid	6.35 cm x 20.3 cm (2.5" x 8") solid	6.3 cm x 22.8 cm (2.5" x 9") solid	6.35 cm x 22.9 cm (2.5" x 9") solid	27.3 cm x 8.25 cm (10.75" x 6") solid	9.1 cm x 27.3 cm (3.6" x 10.75") solid	9 cm x 25.4 cm (3.5" x 10")	10 cm x 25.4 cm (4" x 10")	7.62 cm x 25.4 cm (3" x 10")	9 cm x 25.4 cm (3.5" x 10")	10 cm x 25.4 cm (4" x 10")	10 cm x 25.4 cm (4" x 10")	10 cm x 33 cm (4" x 13")	10 cm x 33 cm (4" x 13")	37 cm x 15.2 cm (14.5" x 6")	6.9 cm x 48.2 cm (2.75" x 19") ¹⁷
MAXIMUM SPEED¹⁸	Up to 6 km/h (3.7 mph)	Up to 6.4 km/h (4 mph)	Up to 7.2 km/h (4.5 mph)	Up to 7 km/h (4.4 mph)	Up to 8 km/h (5 mph)	Up to 6.4 km/h (4 mph)	Up to 10 km/h (6.2 mph)	Up to 8.85 km/h (5.5 mph)	Up to 8.4 km/h (5.25 mph)	Up to 8.85 km/h (5.5 mph)	Up to 10 km/h (6.2 mph)	Up to 9 km/h (5.6 mph)	Up to 9.65 km/h (6 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)
GROUND CLEARANCE^{4,13,15}	5.8 cm (2.3") at frame	6.3 cm (2.5") at midframe 3.8 cm (1.5") at motor	7.62 cm (3") at frame	6.4 cm (2.5") at frame 3.8 cm (1.5") at motor	8.9 cm (3.5") at frame 3.2 cm (1.25") at motor	8.9 cm (3.5") at frame 3.2 cm (1.3") at motor	5 cm (2") at motor	8.8 cm (3.5") at frame	7.6 cm (3") at midframe	8.25 cm (3.25") at midframe	4 cm (1.5") at rear frame	5.6 cm (2.2") at motor	8.25 cm (3.25")	10.8 cm (4.25")	19.7 cm (3.8")	13.3 cm (5.25") at midframe	14 cm (5.5") at motor	12.7 cm (5") at shroud
TURING RADIUS⁴	82 cm (32")	3W: 83.8 cm (33") 4W: 112 cm (44")	116.2 cm (45.72")	116.2 cm (45.72")	132.1 cm (52")	97.2 cm (38.25")	109 cm (43")	132 cm (51.9")	137 cm (53.9")	133.3 cm (52.5")	143 cm (56.2")	152 cm (59.9")	3W: 105.4 cm (41.5") 4W: 149.8 cm (59")	168.2 cm (66.2")	170 cm (67")	210 cm (83") right 208 cm (82") left	243 cm (95.6")	3W: 158 cm (62.2")
LENGTH & WIDTH^{4,12}	92.7 cm/49.5 cm (36.5"/19.5")	3W: 94 cm/49.5 cm (37"/19.5") 4W: 100.3 cm/49.5 cm (39.5"/19.5")	102.3 cm/54 cm (40.25"/21.25")	104 cm/52.1 cm (41"/20.5")	119.4 cm/52.7 cm (47"/20.75")	116 cm/50.8 cm (45.75"/20")	122 cm/61.6 cm (48"/24.25")	115.6 cm/57.1 cm (45.5"/22.5")	115 cm/56.5 cm (45.25"/22.25")	119.4 cm/56.2 cm (47"/22.13")	119 cm/59 cm (46.8"/23.2")	119.4 cm/56.5 cm (47"/22.25")	3W: 116.8 cm/61 cm (46"/24") 4W: 118.7 cm/61 cm (46.75"/24")	130.2 cm/64.1 cm (51.25"/25.25")	136 cm/63.6 cm (53.5"/25")	142.8 cm/69.2 cm (56.25"/27.25")	156 cm/83 cm (61.4"/32.6")	3W: 165 cm/78 cm (65"/30.7")
SEAT-TO-GROUND HEIGHT RANGE	51 cm (20") Fixed	55 cm - 60 cm (21.6" - 23.6")	52 cm - 55.88 cm (20.5" - 22")	52.7 cm - 56.5 cm (20.75" - 22.25")	53.3 cm - 60 cm (21" - 23.5")	53.3 cm - 60 cm (21" - 23.5")	58.4 cm - 63.5 cm (23" - 25")	51.4 cm - 55.2 cm (20.25" - 21.75")	52 cm - 55.8 cm (20.5" - 22")	60 cm - 63.8 cm (23.6" - 25.1")	61 cm - 64 cm (24" - 25.2")	60 cm - 64.8 cm (23.5" - 25.5")	58.5 cm - 61.5 cm (23" - 24.25")	54 cm - 64 cm (21.25" - 25.25")	56.7 cm (22.3")	66.7 cm - 70.5 cm (26.25" - 27.75")	76 cm - 80 cm (30" - 31.5")	63 cm (24.8")
SEAT TYPE (STANDARD)⁶	Compact, Foldable, Molded Plastic 41 cm x 33 cm (16" x 13")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5" x 17.5")	Foldable Molded Plastic 46 cm x 43 cm (18" x 17")	Foldable Molded Plastic 46 cm x 43 cm (18" x 17")	CRS Junior Seat 44.25 cm x 43 cm (17.5" x 17")	Foldable Molded Plastic 48 cm x 42 cm (19" x 16.5")	Reclining H/B w/ Sliders & Headrest 46 cm x 46 cm (18" x 18")	Deluxe Reclining H-B w/ Sliders & Headrest 46 cm x 46 cm (18" x 18")	Deluxe Reclining H-B w/ Sliders & Headrest 46 cm x 46 cm (18" x 18")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5" x 17.5")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5" x 17.5")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5" x 17.5")	Captains High-Back Adjustable Seat 51 cm x 56 cm (20" x 22")
WEIGHT^{3,4,14}	4W: 23.5 kg (51.8 lbs)	3W: 34.5 kg (76 lbs) 4W: 36.3 kg (80 lbs)	4W: 39.4 kg (87 lbs)	4W: 39.4 kg (87 lbs)	4W: 60 kg (132 lbs)	4W: 53.9 kg (119 lbs)	4W: 82.1 kg (180 lbs)	4W: 59.4 kg (130.9 lbs)	4W: 62.4 kg (137.5 lbs)	4W: 84.8 kg (186.9 lbs)	4W: 68.9 kg (151.8 lbs)	4W: 81.2 kg (179 lbs)	3W: 70.7 kg (156 lbs) 4W: 75 kg (165 lbs)	4W: 112 kg (246.9 lbs)	4W: 99.8 kg (220 lbs)	4W: 117.7 kg (259 lbs)	4W: 124 kg (273 lbs)	3W: 115 kg (253.5 lbs)
SEAT-TO-DECK HEIGHT RANGE	31 cm (12.2") Fixed	40 cm - 43.8 cm (15.75" - 17.25")	41.3 cm - 45 cm (16.25" - 17.75")	41.3 cm - 43.8 cm (16.25" - 17.25")	38.1 cm - 45.7 cm (15" - 18")	40.6 cm - 45.6 cm (15.9" - 17.9")	47.5 cm - 52.5 cm (18.7" - 20.6")	37 cm - 42 cm (14.5" - 16.5")	43.8 cm - 47.6 cm (17.2" - 18.75")	44.5 cm - 48.3 cm (17.5" - 19")	46 cm - 49 cm (18.1" - 19.3")	42 cm - 47 cm (16.5" - 18.5")	41 cm - 44.5 cm (16.2" - 17.5")	43.2 cm - 53.3 cm (17" - 21")	47 cm (18.5")	53.3 cm - 57 cm (21" - 22.5")	50 cm - 53 cm (19.6" - 21")	47.5 cm (18.7")
BATTERY WEIGHT¹¹	2.3 kg (5 lbs)	4.08 kg (9 lbs) ea ²	6.05 kg (13.3 lbs) ea ²	6.05 kg (13.3 lbs) ea ²	11 kg (24.2 lbs) ea	6.05 kg (13.3 lbs) ea	14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	16.8 kg (37 lbs) ea	23.45 kg (51.6 lbs) ea	27.9 kg (61.5 lbs) ea	23.75 kg (52.3 lbs) ea
BATTERY REQUIREMENTS⁷	(1) Lithium 11.5 AH	(2) 12AH	(2) 18AH	(2) 18AH	(2) 31AH	(2) 22AH	(2) 40AH	(2) 31AH	(2) 31AH or (2) 40AH	(2) 31AH or (2) 40AH	(2) 40AH	(2) 40 AH	(2) 31AH or (2) 40AH	(2) 40 AH	(2) 55 AH	(2) 70 AH	(2) 100 AH	(2) 70 AH
PER CHARGE RANGE (MAX)^{2,9}	Up to 19.3 km (12 miles)	3W: Up to 11 km (6.9 miles) 4W: Up to 11.5 km (7.2 miles)	Up to 20.9 km (13 miles) ¹⁰	Up to 16.9 km (10.5 miles) ¹⁰	Up to 21 km (13 miles)	Up to 16 km (10 miles)	Up to 28.8 km (17.8 miles)	Up to 17.9 km (11 miles)	Up to 25 km (15.5 miles)	Up to 25 km (15.5 miles) with 40 AH batteries	Up to 30 km (18.6 miles)	Up to 26 km (16 miles)	Up to 20.6 km (12.8 miles)	Up to 40.2 km (24.9 miles) ¹⁶	Up to 25 km (15.5 miles)	Up to 35 km (21.7 miles)	Up to 35 km (21.7 miles)	Up to 35 km (21.7 miles)
BATTERY CHARGER	Lithium Off-Board 2.5A	Off-Board, 2A	Off-Board, 2A	Off-Board, 2A	Off-Board, 3.5A	Off-Board, 3.5A	Off-Board, 3.5A	Off-Board, 3A	Off-Board, 3A (32AH) Off-Board, 5A (40AH)	Off-Board, 3A (32AH) Off-Board, 5A (40AH)	Off-Board, 5A	Off-Board, 5A	Off-Board, 5A	Off-Board, 5A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A
SUSPENSION	N/A	N/A	N/A	Front & Rear	Front & Rear	Front & Rear	Front & Rear	N/A	N/A	Front & Rear	Front & Rear	Front & Rear	3W: Rear 4W: Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear
MAXIMUM WEIGHT CAPACITY	113.3 kg (250 lbs)	118 kg (260 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	170 kg (374.7 lbs)	136 kg (300 lbs)	170 kg (374.7 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	160 kg (352 lbs)	181.4 kg (400 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	181.4 kg (400 lbs)	158.7 kg (350 lbs)	181.4 kg (400 lbs)
STANDARD BODY COLOURS	White	Red	Red, Blue ¹	Red, Blue ¹	Grey Street, True Blue	Fire Opal, Pearl White, Sapphire Blue	Candy Apple Red	Red	Viper Blue	Viper Blue	Red	Candy Apple Red	Candy Apple Red	Candy Apple Red, Silver	Candy Apple Red, Mercury Silver	Candy Apple Red, Yellow, Silver	Stone Grey	Black
WEIGHT OF HEAVIEST PIECE⁴	23.5 kg (56.2 lbs) (does not disassemble)	3W: 13.4 kg (29.5 lbs) 4W: 15.4 kg (34 lbs) (front sections)	15.4 kg (34 lbs) (front section)	16.6 kg (36.6 lbs) (front section)	25.9 kg (57 lbs) (front section)	21.8 kg (48 lbs) (rear section)	34 kg (75 lbs) (rear section)	25.8 kg (57 lbs) (front section)	27.7 kg (61 lbs) (rear section)	29.5 kg (65 lbs) (front section)	50.8 kg (112 lbs) (does not disassemble)	35.2 kg (77.6 lbs) (rear section)	3W: 27.5 kg (60.5 lbs) 4W: 32 kg (70.5 lbs) (front section)	37.6 kg (83 lbs) (front section)	34 kg (74.9 lbs) (rear section)	93 kg (205 lbs) (main frame)	99 kg (218.2 lbs) (main frame)	3W: 92.3 kg (203.4 lbs) (main frame)
3W/4W OPTION	4W	4W & 3W	4W	4W	4W	4W	4W	4W	4W	4W	4W	4W	4W & 3W	4W	4W	4W	4W	3W

TRAVEL MOBILITY

ZERO TURN SERIES

MID-SIZED LUXURY

FULL-SIZED LUXURY

1 All shroud panels included. 2 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%. 3 Battery weight not included. 4 Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%. 5 12 AH battery pack weighs 8.8 kg (19.5 lbs.). 6 Durable solid plastic. 7 Deep cycle (AGM or gel cell type recommended) excluding Lithium-ion models. 8 18 AH battery pack weighs 13.4 kg (29.5 lbs.). 9 Tested in accordance with ANSI/RENSA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. 10 Up to 14 miles per charge on 18 AH batteries. 11 Battery weight may vary based on manufacturer. 12 Width of base (not including seat). 13 Does not account for anti-tip clearance. 14 Includes standard seat weight. 15 At midframe 16 Range tested with 31-36 AH Batteries. Standard larger battery size would increase range. 17 6.9 cm x 35.5 cm (2.75" x 14") Rim Only 18 Varies with user weight, terrain type, battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%. NOTE The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.





MODEL NAME	Jazzy® Passport	Go Chair NG®	Jazzy® Select 6	Jazzy® Air 2	Jazzy® 623 2.0	Jazzy® Elite HD	Jazzy® 1450	R-40
WEIGHT CAPACITY	113.3 kg (250 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	204.1 kg (450 lbs) ⁶	273.1 kg (600 lbs)	136 kg (300 lbs)
TURNING RADIUS ¹	61.5 cm (24.25")	64.5 cm (25.4")	55.5 cm (21.87")	61.5 cm (24.25")	50.8 cm (20")	61.9 cm (24.3")	67.3 cm (26.5")	96.5 cm (38") with foot riggings
WIDTH ¹	59.6 cm (23.5")	57.1 cm (22.6")	59.6 cm (23.5")	64.1 cm (25.25")	60.9 cm (24")	61.5 cm (24.2")	74.2 cm (29.25")	63.5 cm (25") at rear wheels
LENGTH ^{1,2}	101.6 cm (40")	83.8 cm (33")	90.1 cm (35.5")	106 cm (42")	90.1 cm (35.5")	90.1 cm (35.5")	97.1 cm (38.25")	88.9 cm (35")
MAXIMUM SPEED ³	Up to 5.7 km/h (3.6 mph)	5.9 km/h (3.7 mph)	Up to 6.4 km/h (4 mph)	Up to 6.4 km/h (4 mph)	Up to 9.6 km/h (6 mph)	Up to 6.4 km/h (4 mph)	Up to 7.2 km/h (4.5 mph)	Up to 9.6 km/h (6 mph)
GROUND CLEARANCE ¹	7.6 cm (3") at motor	4.5 cm (1.8") at frame	4.4 cm (1.75") at motors & at centre frame	7.3 cm (2.9") 2.5 cm (1") at motor bracket	7.6 cm (3") at rear castor	7.6 cm (3")	3.8 cm (1.5")	7.2 cm (2.87")
FRONT WHEELS	20.3 cm (8") solid front castors	15.2 cm (6") solid castors	15.24 cm (6") solid castors	15.2 cm (6") solid castors	15.2 cm (6") solid castors	7.6 cm (3") solid anti-tips	10.6 cm (4") solid anti-tips	22.8 cm (9") pneumatic castors
DRIVE WHEELS	30.4 cm (12") pneumatic	22.8 cm (9") solid	25.4 cm (10") solid	25.4 cm (10") solid	35.5 cm (14") pneumatic	35.5 cm (14") solid	35.5 cm (14") solid	35.5 cm (14") pneumatic
REAR WHEELS	N/A	7.6 cm (3") solid anti-tips	15.2 cm (6") solid castors	15.2 cm (6") solid castor	15.2 cm (6") solid castors	15.2 cm (6") solid castors	22.8 cm (9") castors	7.6 cm (3") solid rear anti-tips
DRIVE TRAIN	2x 180W brushed motors	Two-motor, rear-wheel drive	Two-motor, in-line, mid-wheel drive	Two-motor, in-line, mid-wheel drive	Two-motor, in-line, mid-wheel 6 [®]	Two-motor, front-wheel drive	Two-motor, front-wheel drive	Two-motor, rear-wheel drive
BRAKING SYSTEM	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical
SUSPENSION TYPE	Limited	Limited	Active-Trac [®] (ATX)	Active-Trac [®] with Mid-Wheel 6 technology	Active-Trac [®] (ATX)	Limited	Swing Arm	Adjustable
HIGH-BACK SEAT-TO-FLOOR RANGE	N/A	N/A	53.9 cm - 59 cm (21.25" - 23.25")	53.9 cm - 84 cm (21.25" - 33.1")	52 cm - 59.6 cm (20.5" - 23.5")	50.8 cm - 55.8 cm (20" - 22")	52 cm - 57.1 cm (20.5" - 22.5")	N/A
SPECIALITY SEATING OPTIONS	N/A	N/A	N/A	N/A	Synergy [®] Seating ^A Tru-Balance ^B	N/A	Synergy [®] Seating ^A	N/A
SPECIALTY CONTROLS	N/A	N/A	N/A	N/A	Yes	N/A	Yes	N/A
STANDARD ELECTRONICS	50A, PG VSI	40A, PG GC3	40A, PG GC3	40A, VR2	90A, PG VR2	90A, PG VR2	90A, PG VR2	70A, PG VR2
BATTERY SIZE	24 V, 18 AH Lithium-ion (1)	12 V, 18 AH (2)	12 V, 35 AH (2)	12 V, 40 AH (2)	12 V, 55 AH (2)	12 V, 55 AH (2)	12 V, 70 AH (2)	12 V, 50 AH (2)
STANDARD BATTERY CHARGER	2A, off-board, Lithium	2A, off-board	3.5A, off-board	5A, off-board	8A, off-board	5A, off-board	8A, off-board	5A, off-board
PER-CHARGE RANGE ^{9,5}	Up to 15.4 km (9.6 miles)	Up to 14km (8.7 miles)	Up to 24.1 km (15 miles)	Up to 27 km (16.8 miles)	Up to 24.9 km (15.5 miles)	Up to 15.7 km (9.8 miles)	Up to 25.2 km (15.7 miles)	Up to 24.9 km (15.5 miles)
BATTERY WEIGHT ⁷	3.9 kg (8.81 lbs) each	14 kg (31 lbs) battery box	10.5 kg (23.3 lbs) each	14.1 kg (31.2 lbs) each	16.8 kg (37 lbs) each	16.8 kg (37 lbs) each	23.4 kg (51.6 lbs) each	16.8 kg (37 lbs) each
WEIGHT OF HEAVIEST PIECE ⁴	24.4 kg (54 lbs)	16.3 kg (36 lbs)	44.1 kg (97.4 lbs)	91.6 kg (202 lbs) ⁸	62.3 kg (137.5 lbs)	44.9 kg (99 lbs)	88.4 kg (195 lbs)	47.6 kg (105 lbs)
STANDARD SEAT WEIGHT	N/A (seat is integrated with the base) (sling)	13.6 kg (30 lbs)	19.9 kg (44 lbs) (comfort, high-back)	23 kg (50.7 lbs) (high-back)	19.9 kg (44 lbs) (high-back)	23.5 kg (52 lbs) (high-back)	25.8 kg (57 lbs) (high-back)	N/A (seat is integrated with the base) (sling with power tilt)
STANDARD SEAT SIZE	41.9 cm x 44.4 cm (16.5" x 17.5")	43.1 cm x 45.7 cm (17" x 18")	45.7 cm x 45.7 cm (18" x 18")	40.6 cm x 45.7 cm (16" x 18") 45.7 cm x 45.7 cm (18" x 18") 50.8 cm x 45.7 cm (20" x 18")	45.7 cm x 45.7 cm (18" x 18") 50.8 cm x 45.7 cm (20" x 18")	45.7 cm x 45.7 cm (18" x 18") 50.8 cm x 50.8 cm (20" x 20") 55.8 cm x 50.8 cm (22" x 20")	60.9 cm to 81.2 cm (24" to 32")	40.6 cm x 45.7 cm (16" x 18")
COLOUR OPTIONS	Pewter	Ruby Red, Pearl White	Ruby Red	Black Oynx, Pearl White, Pink Topaz, Garnet Red	Candy Apple Red	Jazzy Red, Jazzy Blue	Candy Apple Red, Viper Blue	Silver
	FOLDABLE	NEW GENERATION				JAZZY POWER CHAIRS		FUSION

¹ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections. ² Without front riggings. ³ Varies with user weight, terrain, battery condition and tire pressure. ⁴ Does not include seat or battery weights. ⁵ Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, - 5%. ⁶ Maximum weight capacity is reduced to 400 lbs. (181 kg) on 46 cm (18") deep seat configurations. ⁷ Battery weight may vary based on manufacturer. ⁸ Seat weight included (because tools are required to remove the seat). Battery weight not included. ⁹ Varies with user weight, terrain, battery type, battery condition and tire pressure. *International configuration shown SEATING: A For Synergy[®] Seating. Contact your nearest Pride[®] stocklist for more information B Quantum[®] dealers only NOTE The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

PRIDE POWER RECLINER COLLECTION



MODEL NAME	C1	C5	C6	C-101	LC-101 Euro Leather	LC-107	D30	560	660	T-3	LC-358XL
POSITION	3-Position Lift Chair 163 cm & below (5'4" & below)	3-Position Chaise Lounger with fully removable upholstery components 163 cm-183 cm (5'4" - 6'0")	Infinite-Position Chaise Lounger with fully removable upholstery components 163cm-183 cm (5'4" - 6'0")	3-Position Chaise Lounger 163 cm-183 cm (5'4" - 6'0")	3-Position Chaise Lounger with European style rounded arm design 163 cm -183 cm (5'4" - 6'0")	Infinite-Position Chaise Lounger with extended length on footrest 163 cm -183 cm (5'4" - 6'0")	3-Position Chaise Lounger 163 cm-183 cm (5'4" - 6'0")	3-Position Chaise Lounger 163 cm-183cm (5'4" - 6'0")	Infinite-Position Chaise Lounger 163 cm-183cm (5'4" - 6'0")	Infinite-Position Chaise Lounger featuring Trendelenburg position (elevates legs above head for greater relaxation) & zero-gravity position 163 cm-183 cm (5'4" - 6'0")	3-Position Chaise Lounger 163 cm-183 cm (5'4" - 6'0")
WEIGHT CAPACITY	113 kg (250 lbs)	170 kg (375 lbs)	136 kg (300 lbs)	147 kg (325 lbs)	147 kg (325 lbs)	147 kg (325 lbs)	170 kg (375 lbs)	170 kg (375 lbs)	170 kg (375 lbs)	170 kg (375 lbs)	227 kg (500 lbs)
BACK WIDTH	51 cm (20")	71 cm (28")	71 cm (28")	72 cm (28.5")	58 cm (23")	74 cm (29")	74 cm (29")	71 cm (28")	71 cm (28")	69 cm (27")	91 cm (36")
SEAT-TO-FLOOR	41 cm (16")	46 cm (18")	48 cm (19")	47 cm (18.5")	47 cm (18.5")	51 cm (20")	48 cm (19")	48 cm (19")	48 cm (19")	48 cm (19")	51 cm (20")
SEAT DEPTH	51 cm (20")	46 cm-51 cm (18" - 20")*	53 cm (21")	51 cm (20")	51 cm (20")	53 cm (21")	56 cm (22")	48 cm (19")	51 cm (20")	51 cm (20")	56 cm (22")
SEAT WIDTH	46 cm (18")	56 cm (22")	56 cm (22")	51 cm (20")	51 cm (20")	51 cm (20")	56 cm (22")	48 cm (19")	48 cm (19")	51 cm (20")	66 cm (26")
TOP OF BACK TO SEAT	66 cm (26")	66 cm-71 cm (26" - 28")*	66 cm-71 cm (26" - 28")*	70 cm (27.5")	70 cm (27.5")	70 cm (27.5")	66 cm (26")	63 cm (25")	63 cm (25")	68.5 cm (27")	74 cm (29")
BACK STYLE	Blown Fibre Accented Pillow-Back	Blown Fibre Sewn Pillow-Back	Blown Fibre Sewn Pillow-Back	Blown Fibre Button-Back	Blown Fibre Split-Back	Blown Fibre Sewn Split-Back	Blown Fibre Sewn Split-Back	Blown Fibre Pillow-Back	Blown Fibre Pillow-Back	Blown Fibre Mongolian-Back	Blown Fibre Button-Back
FULLY PADDED CHAISE	Yes	Yes ²	Yes ²	Yes	Yes	Yes	Yes ¹	Yes ¹	Yes ¹	Yes	Yes
INTEGRATED BATTERY BACKUP³	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
RECLINE POSITIONS	3	3	Infinite	3	3	Infinite	3	3	Infinite	Infinite	3
STANDARD ARM COVERS	No	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
STANDARD HEAD COVERS	No	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
FABRIC SELECTION GUIDE	<p>FABRIC</p> <p>Arctic Blue Chocolate Faun</p>	<p>FABRIC</p> <p>Arctic Blue Chocolate Faun</p>	<p>FABRIC</p> <p>Arctic Blue Chocolate Faun</p> <p>LEVANTE (VINYL)</p> <p>Royal Blue</p>	<p>FABRIC</p> <p>Cocoa Fern Sandal</p>	<p>LEATHER</p> <p>Beige Brown Black Red</p>	<p>FABRIC</p> <p>Pecan Burgundy Ocean</p>	<p>FABRIC</p> <p>Burgundy Ocean</p> <p>LEVANTE (VINYL)</p> <p>Royal Blue</p>	<p>FABRIC</p> <p>Burgundy Ocean</p>	<p>FABRIC</p> <p>Latte</p>	<p>LEATHER</p> <p>Black</p>	<p>FABRIC</p> <p>Latte Burgundy</p> <p>LEVANTE (VINYL)</p> <p>Burgundy</p>

3 - POSITION	The 3-position full recline is available on most Pride® Power Lift Recliner models and puts you in a position ideal for napping or relaxing
TRUE INFINITE-POSITION	The true infinite-position recline is perfect for taking a nap. Infinite-position Pride® Power Lift Recliners enable the backrest and footrest to move independently from one another so that a variety of positions can be reached.
TRENDELENBURG	The Trendelenburg position, elevates one's feet higher than his or her heart for increased comfort and relaxation.
ZERO GRAVITY	The zero gravity position, which can be reached on infinite-position Pride® Power Lift Recliner models, positions one's thighs and lower legs higher than his or her torso



NOTE The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Measurements may vary +/- 2.5cm (1") Specifications subject to change without prior notice. ¹ Removable fully padded chaise. ² All upholstery compounds on C5 and C6 are fully removable. ³ Batteries are not included. *Frame Adjustment

AVAILABLE WITH
30.4 CM iLEVEL®



AVAILABLE WITH
30.4 CM iLEVEL®



AVAILABLE WITH
30.4 CM iLEVEL®



AVAILABLE WITH
25.4 CM ELEVATION



AVAILABLE WITH
30.4 CM iLEVEL®



AVAILABLE WITH
25.4 CM ELEVATION



AVAILABLE WITH
25.4 CM ELEVATION



AVAILABLE WITH
25.4 CM ELEVATION



	EDGE 3 STRETTO®	EDGE® 3	Q6 EDGE® 2.0	4FRONT®	Q6 EDGE® Z	Q6 EDGE® HD		QUANTUM® 1450	J623 2.0	QUANTUM® R44 RIVAL®	
DRIVE CONFIGURATION	Mid-wheel Drive	Mid-wheel Drive	Mid-wheel Drive	Front-wheel Drive	Mid-wheel Drive	Mid-wheel Drive		Front-wheel Drive	Mid-wheel Drive	Rear-wheel Drive	
DRIVE WHEELS	35.5 cm (14") or 31.7 cm (12.5") Pneumatic or Flat Free Tyres	35.5 cm (14") Flat Free/ 35.5 cm (14") Pneumatic	35.5 cm (14") Flat Free/ 35.5 cm (14") Pneumatic	35.5 cm (14") Flat Free/ 35.5 cm (14") Pneumatic	35.5 cm (14") Flat Free/ 35.5 cm (14") Pneumatic	35.5 cm (14") Flat Free/ 35.5 cm (14") Pneumatic		35.5 cm (14") Flat Free	35.5 cm (14") Flat Free/ 35.5 cm (14") Pneumatic	35.5 cm (14") Flat Free/ 35.5 cm (14") Pneumatic	
CASTOR WHEELS	Front: 12.7 cm (5") Flat Free Rear: 15.2 cm (6") Flat Free	Front: 15.2 cm (6") Solid Rear: 15.2 cm (6") Solid	Front: 15.2 cm (6") Solid ¹ 20.3 cm (8") Solid ² Rear: 15.2 cm (6") Solid ¹ 20.3 cm (8") Solid ²	Rear: 22.8 cm (9") Flat Free	Front: 15.2 cm (6") Solid Rear: 15.2 cm (6") Solid	Front: 15.2 cm (6") Solid Rear: 15.2 cm (6") Solid		22.8 cm (9") Solid	Front: 15.2 cm (6") Solid ¹ 20.3 cm (8") Solid ² Rear: 15.2 cm (6") Solid ¹ 20.3 cm (8") Solid ²	Front: 22.8 cm (9") Solid/Pneumatic 25.4 (10") Solid/Pneumatic	
ANTI-TIP WHEELS	N/A	N/A	N/A	Front: 10.1 cm (4")	N/A	N/A		Front: 10.1 cm (4") Solid	N/A	Rear: 7.6 cm (3") Solid	
MAXIMUM SPEED⁴	Up to 10 km/h (6.2 mph) (5.6 km/h (3.5 mph) w/iLevel) ¹³	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 7.5 km/h (4.6 mph)		Up to 7.2 km/h (4.4 mph)	Up to 10 km/h (6.2 mph)	Up to 9.6 km/h (6 mph)	
GROUND CLEARANCE	7.3 cm (2.9")	6.8 cm (2.7") (battery tray)	6.8 cm (2.7") (battery tray)	7.6 cm (3") (motor pivot)	7.6 cm (3") (frame base)	7.6 cm (3") (frame centre)		5 cm (2") (anti-tips)	6.9 cm (2.7") (battery tray)	8.1 cm (3.2") (frame base)	
TURNING RADIUS⁵	53.3 cm (21")	52 cm (20.5")	52 cm (20.5") w/15.2 cm (6") castors 59 cm (23.2") w/20.3 cm (8") castors	62.2 cm (24.5")	50 cm (19.7")	50 cm (19.7")		67.3 cm (26.5")	52.1 cm (20.5")	90.6 cm (35.7)	
OVERALL LENGTH¹¹	82.5 cm (32.5")	81.8 cm (32.2") (without foot riggings)	90.1 cm (35.5") w/15.2 cm (6") castors 102.6 cm (40.4") w/20.3 cm (8") castors	116 cm (45.7")	90.4 cm (35.6")	90.4 cm (35.6")		90.4 cm (35.6")	90.2 cm (35.5") without foot riggings	91.4 cm (36")	
BASE WIDTH	55.2 cm (21.75") (35.5 cm (14") drive wheels) 51.9 cm (20.47") (31.5 cm (12.5") drive wheels)	61.9 cm (24.4")	61.9 cm (24.4")	60.9 cm (24")	66.5 cm (26.2")	66.5 cm (26.2")		74.1 cm (29.2")	61.9 cm (24.4")	63.5 cm (25")	
SEAT SIZES	TRU-Balance® 3	TRU-Balance® 3	TRU-Balance® 3	TRU-Balance® 3	TRU-Balance® 3	TB2 HD	TB3 HD	TRU-Balance® 2 HD Tilt	TRU-Balance® 3	TB2 HD	TB3 HD
SYNERGY®	N/A	N/A	W: 12-22" D: 12-22"	N/A	W: 12-24" D: 10-24"	W: 16-28" D: 20-28"	W: 16-32" D: 20-28"	W: 20-32" D: 20-28"	W: 12-22" D: 12-22"	W: 12-22" D: 10-20"	W: 12-22" D: 12-22"
STATIC	W: 12-20" D: 12-20"	W: 12-22" D: 10-22"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-24" D: 12-24"	W: 16-28" D: 20-28"	W: 16-32" D: 20-28"	W: 20-32" D: 20-28"	W: 12-22" D: 12-22"	W: 12-22" D: 10-20"	W: 12-22" D: 12-22"
POWER TILT	W: 12-20" D: 12-20"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-24" D: 14-24"	W: 16-28" D: 20-28"	W: 16-28" D: 20-25"	W: 20-32" D: 20-28"	W: 12-22" D: 12-22"	W: 14-22" D: 14-20"	W: 12-22" D: 12-22"
LIFT & TILT	W: 12-20" D: 12-20"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-24" D: 12-24"	N/A	W: 16-24" D: 20-25"	N/A	N/A	N/A	W: 12-22" D: 12-22"
SEAT-TO-FLOOR HEIGHTS^{16,17}	TRU-Balance® 3	TRU-Balance® 3	TRU-Balance® 3	TRU-Balance® 3	TRU-Balance® 3	TB2 HD	TB3 HD	TRU-Balance® 2 HD Tilt	TRU-Balance® 3	TB2 HD	TB3 HD
SYNERGY®/STATIC	16"-18" (Static only)	16.5-18.5"	16.5-18.5"	15.2-17.2" ³	16.5-18.5"	16.5-18.5"	17.5-19.5"	16.5-18.5"	16.5-18.5"	16.5-18"	16.5-18.1"
POWER TILT⁸	17.5-19.5"	17.5-19.5"	17.5-19.5"	17.5-19.5"	17.5-19.5"	18.2-20.9"	18.5-20.5"	18.1-20.1"	17.5-19.5"	16.5-18"	18-19.6"
LIFT & TILT⁸	17.5-19.5"	17.5-19.5"	17.5-19.5"	17.5-19.5"	18-20"	N/A	17.7-19.7"	N/A	17.5-19.5"	N/A	18.5-20.1"
MANUAL RECLINE	Yes	Yes	Yes	Yes	Yes	No		No	Yes	Yes	
BATTERY SIZE⁶	40AH (2) or NF-22 (55AH) (2)	NF-22 (55AH) (2)	NF-22 (55AH) (2)	Group 24: (74AH) (2)	Group 24: (74AH) (2)	Group 24: (74AH) (2)		Group 24: (74AH) (2)	NF-22 (55AH) (2)	Group 24: (74AH) (2)	
BATTERY WEIGHT¹⁴	40 AH: 14 kgs (31 lbs. each) 55 AH: 18.1 kgs (40 lbs. each)	17.2 kgs (37.9 lbs.) (each)	17.2 kgs (37.9 lbs.) (each)	23.5 kgs (51.8 lbs.) (each)	23.5 kgs (51.8 lbs.) (each)	23.5 kgs (51.8 lbs.) (each)		23.5 kgs (51.8 lbs.) (each)	17.2 kgs (37.9 lbs.) (each)	23.5 kgs (51.8 lbs.) (each)	
AVAILABLE ELECTRONICS¹²	120A Q-Logic 3 EX	120A Q-Logic 3 EX	120A Q-Logic 3 EX	120A Q-Logic 3 EX	120A Q-Logic 3 EX	120A Q-Logic 3 EX		90A VR2 6-key 100A Q-Logic 2 EX	90A VR2 6-key	100A Q-Logic 2 EX	
BATTERY CHARGER	8A Off-board	8A Off-board	8A Off-board	8A Off-board	8A Off-board	8A Off-board		8A Off-board	8A Off-board	8A Off-board	
MOTOR PACKAGES	2-Pole Mid-Wheel 6®	2-Pole Mid-Wheel 6®	2-Pole Mid-Wheel 6®	2-Pole, Front-wheel Drive	4-Pole, Mid-Wheel 6®	4-Pole, Mid-Wheel 6® ¹		4-Pole, Front-wheel Drive	2-Pole Mid-Wheel 6®	4-Pole, Rear-wheel Drive ¹	
WEIGHT CAPACITY⁷	136 kgs (300 lbs.)	136 kgs (300 lbs.)	136 kgs (300 lbs.)	136 kgs (300 lbs.)	136 kgs (300 lbs.)	204.1 kgs (450 lbs.) ¹⁵		272 kgs (600 lbs.)	136 kgs (300 lbs.)	136 kgs (300 lbs.)	
BASE WEIGHT	57.3 kgs (126.4 lbs.)	62.8 kgs (138.6 lbs.)	62.8 kgs (138.6 lbs) w/15.2 cm (6") castors 67.1 kgs (148 lbs) w/20.3 cm (8") castors	63.5 kgs (140 lbs.)	65 kgs (143.3 lbs.)	65 kgs (143.3 lbs.)		88.4 kgs (194.8 lbs.)	62.8 kgs (138.6 lbs.)	58.5 kgs (128.9 lbs.)	

1 Standard. 2 Optional. 3 Not available with Synergy®. 4 Speed varies with user weight, terrain type, battery charge, battery condition and tyre pressure. 5 Without front riggings. 6 Battery capacity may change when adding power positioning systems. 7 Weight capacity is dictated by the selection of seating. 8 All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 136 kg weight capacity and solid tyres (add 3/8" with pneumatic tyres). Depths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in their lowest position; does not include elevating system unless specified. 9 113 kg weight capacity with TRU-Balance® Systems. 10 A minimum seating size of 20" x 20" is required with iLevel® on the Q6 Edge® HD; maximum seating size is 24" x 25". 11 Without foot riggings. 12 All Quantum units can be ordered with speciality controls. 13 10 km/h speed available only with Q-Logic 3. 14 Battery weight may vary +/- 1.3 kgs based on manufacturer. 15 Weight capacity is reduced to 181 kgs with iLevel® power adjustable seat height. 16 Seat-to-floor heights are measured with the unit unloaded. Due to the 4Front's suspension system, seat-to-floor heights are approximately 0.6 cm lower when the unit is loaded. 17 41.9 cm seat-to-floor height is not available with power tilt or iLevel®, 49.5 cm seat-to-floor height is not available with static seat or power recline. **NOTE: The information contained herein is correct at the time of publication. We reserve the right to alter specifications without prior notice.**