

## Description

The IMX585-AAQJ1 is a diagonal 12.84 mm (Type 1/1.2) CMOS active pixel type solid-state image sensor with a square pixel array and 8.40 M effective pixels. This chip operates with analog 3.3 V, digital 1.1 V, and interface 1.8 V triple power supply, and has low power consumption. High sensitivity, low dark current and no smear are achieved through the adoption of R, G and B primary color mosaic filters. This chip features an electronic shutter with variable charge-integration time.

(Applications: Security cameras)

## Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Input frequency: 24 MHz / 27 MHz / 37.125 MHz / 72 MHz / 74.25 MHz
- ◆ Number of recommended recording pixels: 3840 (H) × 2160 (V) approx. 8.29M pixel
- ◆ Readout mode
  - All-pixel scan mode
  - Horizontal / Vertical 2/2-line binning mode
  - Window cropping mode
  - Horizontal / Vertical direction - Normal / Inverted readout mode
- ◆ Readout rate
  - Maximum frame rate in All-pixel scan mode: 12 bit: 60 frame/s, 10 bit: 90 frame/s
- ◆ High dynamic range (HDR) function
  - Digital overlap HDR
  - Clear HDR
- ◆ Synchronizing sensors function
- ◆ Variable-speed shutter function (resolution 2H units)
- ◆ 10-bit / 12-bit A/D converter
- ◆ CDS / PGA function
  - 0 dB to 30 dB : Analog Gain 30 dB (step pitch 0.3 dB)
  - 30.3 dB to 72 dB : Analog Gain 30 dB + Digital Gain 0.3 dB to 42 dB (step pitch 0.3 dB)
- ◆ Supports I/O
  - CSI-2 serial data output (2 Lane / 4 Lane / 8Lane / 4Lane × 2ch)
  - RAW10 / RAW12 / RAW16 (Clear HDR) output

## STARVIS 2

\* STARVIS 2 is a registered trademark or trademark of Sony Group Corporation or its affiliates. The STARVIS 2 is back-illuminated pixel technology used in CMOS image sensors for security camera applications. It features a sensitivity of 2000 mV or more per 1  $\mu\text{m}^2$  (color product, when imaging with a 706 cd/m<sup>2</sup> light source, F5.6 in 1 s accumulation equivalent). It also has a wide dynamic range (AD 12 bit) of more than 8 dB compared to STARVIS for the same pixel size in a single exposure, and achieves high picture quality in the visible-light and near infrared light regions.

Sony reserves the right to change products and specifications without prior notice.

"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

**Device Structure**

- ◆ CMOS image sensor
- ◆ Image size Diagonal 12.84 mm (Type 1/1.2) approx. 8.40 M pixels, All pixels
- ◆ Total number of pixels 3856 (H) × 2220 (V) approx. 8.56 M pixels
- ◆ Number of effective pixels 3856 (H) × 2180 (V) approx. 8.40 M pixels
- ◆ Number of active pixels 3856 (H) × 2176 (V) approx. 8.39 M pixels
- ◆ Number of recommended recording pixels 3840 (H) × 2160 (V) approx. 8.29 M pixels
- ◆ Unit cell size 2.9 μm (H) × 2.9 μm (V)
- ◆ Optical black  
Horizontal (H) direction: Front 0 pixels, rear 0 pixels  
Vertical (V) direction: Front 20 pixels, rear 0 pixels
- ◆ Dummy  
Horizontal (H) direction: Front 0 pixels, rear 0 pixels  
Vertical (V) direction: Front 0 pixels, rear 0 pixels
- ◆ Package 122 pin LGA

**Image Sensor Characteristics**

(Tj = 60 °C)


Item		Value	Remarks
Sensitivity (F5.6)	Typ.	19556 Digit/lx/s	12 bit converted value
Saturation signal	Min.	3895 Digit	12 bit converted value

**Basic Drive Mode**


Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All-pixel	3840 (H) × 2160 (V) approx. 8.29 M pixels	90	CSI-2	10
Horizontal/ Vertical 2/2-line binning	1920 (H) × 1080 (V) approx. 2.07 M pixels	90	CSI-2	10

### Comparison Image under Complex Lighting Environment


IMX585 has a wider dynamic range than conventional type. Also, when shooting a fast-moving target the image taken with Clear HDR does not have chromatic aberration compared to DOL HDR.




Conventional: One shot



IMX585: One shot



Conventional: DOL HDR



IMX585: Clear HDR

