

# RCU15 Remote Control Unit

A small **compact remote control** connected to acoustic warning devices in small systems, either using a wired link or wirelessly. It enables the user to **control a siren, group of sirens, and the aSCADA systems** in small warning systems.



# Versions



## RCU15 Basic

- 4 simple resistant push-buttons for immediate alarm activation or deactivation
- LED indicator to display the operational status of a warning device
- Each push-button capable of activating an alarm pre-defined by the user



## RCU15 Professional

- Clearly-arranged back-lit LCD display for working in adverse lighting conditions
- Rotary encoder for convenient navigation even in protective gloves
- More alarms and other functionalities

Both RCU15 remote control unit versions have a built-in microphone and, depending on the type of connection, they allow or do not allow live voice announcement broadcasting. As standard, there is port for connecting an external microphone.



## Basic functions

- Alarm activation in warning devices
- Alarm deactivation in warning devices
- Complete monitoring of controlled devices (the RCU15 Professional version only)



## Technical parameters

<b>Power Supply</b>	12 V from aBUS®-E interface (for wired connection)
<b>LiPol Battery Charging</b>	LiPol battery 3,7 V / 1000 mAh (for wireless connection) 5 V using a USB connector 12-30 V from the mains using an adapter
<b>Dimensions</b>	150 × 90 × 25 mm
<b>Weight</b>	200 g
<b>Range of Working Temperatures</b>	from -25°C to +65°C
<b>Display (RCU15 Professional)</b>	LCD 128 × 64 px. orange/black

 telegrafia®



**Telegrafia a.s.**

Lomená 7, 040 01 Košic

sales@telegrafia.sk

www.telegrafia.eu