



# JMST2.MH49032 - Gasket Materials - Component

*Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.*

## Gasket Materials - Component

**TRIM-LOK INC**

MH49032

6855 HERMOSA CIR  
PO BOX 6180  
BUENA PARK, CA 90622-6180 United States

Marking: Company name and model designation.

Note: For additional marking information, refer to the [Guide Information Page](#).

***Closed cell EPDM sponge material***

Rubber Seal C1280CM

***Closed cell sponge type material***

Trim-Seal VY0101 and EPDM Sponge Tubing C1505CM

***Co-Extruded closed cell EPDM sponge and dense material***

Co-Extruded Trim Seal 17123CM Dense and C1200CM Sponge

Trim Seal 17151CM Dense and C1200CM Sponge

Trim Seal 17151CM Dense and C1324CM Sponge

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.

Last Updated on 2022-01-11

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"



# Rubber Seal C1280CM - Gasket Materials - Component

## Gasket Materials - Component

File Number: MH49032

### COMPANY

TRIM-LOK INC  
6855 HERMOSA CIR  
PO BOX 6180  
BUENA PARK, CA 90622-6180 United States

### MODEL INFO

Rubber Seal C1280CM

ATTRIBUTES	VALUE
Material Type	Closed cell EPDM sponge material
Enclosure Standards ANSI/UL50 and 50E	Yes
Enclosure Ratings	2, 3, 3R, 3RX, 3S, 3SX, 4, 4X, 5, 6, 6P, 12, 12K, 13
Compression Ratings	Continuous and Periodic Recompression
Oil Rating	Yes
LP Gas	No

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.

Report Date: 2012-05-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-

Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"



# Trim-Seal VY0101 and EPDM Sponge Tubing C1505CM - Gasket Materials - Component

## Gasket Materials - Component

File Number: MH49032

### COMPANY

TRIM-LOK INC  
6855 HERMOSA CIR  
PO BOX 6180  
BUENA PARK, CA 90622-6180 United States

### MODEL INFO

Trim-Seal VY0101 and EPDM Sponge Tubing C1505CM

ATTRIBUTES	VALUE
Material Type	Closed cell sponge type material
Enclosure Standards ANSI/UL50 and 50E	Yes
Enclosure Ratings	2, 3, 3R, 3RX, 3S, 3SX, 4, 4X, 5, 6, 6P
Compression Ratings	Continuous Compression and Periodic Recompression
Oil Rating	No
LP Gas	No

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.

Report Date: 2012-09-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-

Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"



# Co-Extruded Trim Seal 17123CM Dense and C1200CM Sponge - Gasket Materials - Component

## Gasket Materials - Component

File Number: MH49032

### COMPANY

TRIM-LOK INC  
6855 HERMOSA CIR  
PO BOX 6180  
BUENA PARK, CA 90622-6180 United States

### MODEL INFO

Co-Extruded Trim Seal 17123CM Dense and C1200CM Sponge

ATTRIBUTES	VALUE
Material Type	Co-Extruded closed cell EPDM sponge and dense material
Enclosure Standards ANSI/UL50 and 50E	Yes
Enclosure Ratings	2, 3, 3R, 3RX, 3S, 3SX, 4, 4X, 5, 6, 6P
Oil Rating	No
LP Gas	No
Minimum Ambient Service Temperature	-29 °C
Maximum Ambient Service Temperature	75 °C
Other Considerations	Suitable for the published ratings/conditions when evaluated to UL 157
Standards	UL 157

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.

---

Report Date: 2012-06-20

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"



# Trim Seal 17151CM Dense and C1200CM Sponge - Gasket Materials - Component

## Gasket Materials - Component

File Number: MH49032

### COMPANY

TRIM-LOK INC  
6855 HERMOSA CIR  
PO BOX 6180  
BUENA PARK, CA 90622-6180 United States

### MODEL INFO

Trim Seal 17151CM Dense and C1200CM Sponge

ATTRIBUTES	VALUE
Material Type	Co-Extruded closed cell EPDM sponge and dense material
Enclosure Standards ANSI/UL50 and 50E	Yes
Enclosure Ratings	2, 3, 3R, 3RX, 3S, 3SX, 4, 4X, 5, 6, 6P
Compression Ratings	Continuous and Periodic Recompression
Oil Rating	No
LP Gas	No
Minimum Ambient Service Temperature	-29 °C
Maximum Ambient Service Temperature	75 °C
Other Considerations	Suitable for the published ratings/conditions when evaluated to UL 157

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.



---

Report Date: 2012-06-20

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"



# Trim Seal 17151CM Dense and C1324CM Sponge - Gasket Materials - Component

## Gasket Materials - Component

File Number: MH49032

### COMPANY

TRIM-LOK INC  
6855 HERMOSA CIR  
PO BOX 6180  
BUENA PARK, CA 90622-6180 United States

### MODEL INFO

Trim Seal 17151CM Dense and C1324CM Sponge

ATTRIBUTES	VALUE
Material Type	Co-Extruded closed cell EPDM sponge and dense material
Enclosure Standards ANSI/UL50 and 50E	Yes
Enclosure Ratings	2, 3, 3R, 3RX, 3S, 3SX, 4, 4X, 5, 6, 6P
Compression Ratings	Continuous and Periodic Recompression
Oil Rating	No
LP Gas	No
Minimum Ambient Service Temperature	-29 °C
Maximum Ambient Service Temperature	75 °C
Other Considerations	Suitable for the published ratings/conditions when evaluated to UL 157

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.

---

Report Date: 2012-06-20

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"