
Wilsonart®

ADHESIVES

SPRAY EQUIPMENT GUIDE



Coating Atomization Technologies: 337 S. Arthur Ave. Louisville, CO 80027
Phone: 888.820.4498, Fax: 303.438.5708
www.spraycat.com

Material Set-Up Recommendations

WILSONART CONTACT ADHESIVES (800/801, 810/811, 860/861, 844, 950/951, 981) **GUN / TECHNOLOGY** SYSTEM TIP / AIR CAP AIR PRESS. FLUID PRESS. FLUID REG.PRESS. Pressure Pot 1.5 X 2266-3T 80 PSI 10 PSI Panther 1.5 X 2266-3T 80 PSI 20 PSI 10 PSI Double Diaphragm Pressure Pot 1.5 X 2266-3 80 PSI 10 PSI Tomcat Double Diaphragm 1.5 X 2266-3 80 PSI 20 PSI 10 PSI

800/801 - Postforming Spray Grade Contact Adhesive

810/811 - Postforming Spray Grade Contact Adhesive

860/861 - Postforming Spray Grade Contact Adhesive

844 - Premium Postforming Spray Grade Contact Adhesive

950/951 - Flatwork Spray Grade Contact Adhesive

981 - Reduced Reflection Spray Grade Contact Adhesive







WILSONART CONTACT ADHESIVES (1700/1701, 1730/1731)							
GUN / TECHNOLOGY	SYSTEM	TIP / AIR CAP	AIR PRESS.	FLUID PRESS.	FLUID REG.PRESS.		
Panther	Pressure Pot	1.5 X 2266-3T	40 PSI	14 PSI	-		
	Double Diaphragm	1.5 X 2266-3T	40 PSI	30 PSI	14 PSI		
Tomcat	Pressure Pot	1.5 X 2266-3	40 PSI	14 PSI	-		
	Double Diaphragm	1.5 X 2266-3	40 PSI	30 PSI	14 PSI		

1700/1701 - Low VOC Contact Adhesive

1730/1731 - California Compliant Bulk Contact Adhesive





* Tip size may be changed based on the user's speed of application

For best results please use the recommended air and fluid pressures listed

Material Set-Up Recommendations

WILSONART POLYVINYL ACETATE (PVA) ADHESIVE (3000)							
GUN / TECHNOLOGY	SYSTEM	TIP / AIR CAP	AIR PRESS.	FLUID PRESS.	FLUID REG.PRESS.		
Panther	Pressure Pot	2.8 X 2268	60 PSI	30 PSI	-		
	Double Diaphragm	1.8 X 2266-3T	60 PSI	60 PSI	30 PSI		
Tomcat	Pressure Pot	2.8 X 2268	60 PSI	30 PSI	-		
	Double Diaphragm	1.8 X 2266-3	60 PSI	60 PSI	30 PSI		
AutoCAT 100C*	Pressure Pot	2.8 X 2268	60 PSI	30 PSI	-		
	Double Diaphragm	1.8 X 2266-3	60 PSI	60 PSI	30 PSI		

^{*} For flat line operations:

- 2.8 mm setup recommended for 1-2 gun operation.
- 1.8 mm setup recommended for 3+ gun operation.

3000 - Postforming and Pinch Roller PVA Adhesive



WILSONART CONTACT ADHESIVES (H2O)								
GUN / TECHNOLOGY	SYSTEM	TIP / AIR CAP	AIR PRESS.	FLUID PRESS.	FLUID REG.PRESS.			
Panther	Pressure Pot	1.2 X 2266-3T	12 PSI	4 - 6 PSI	-			
	Double Diaphragm	1.2 X 2266-3T	12 PSI	12 PSI	4 - 6 PSI			
CAT SLP (HVLP - California Compliant)	Pressure Pot	1.3 X 1313	18 PSI	4 PSI	-			
	Double Diaphragm	1.3 X 1313	18 PSI	10 PSI	4 PSI			

H2O - Water-based Contact Adhesive





- * Tip size may be changed based on the user's speed of application
- For best results please use the recommended air and fluid pressures listed

Recommended Products



Panther P100G "The Laminator"

- The P100G is CAT's premier air spray gun ideal for any glue/ adhesive application.
- The gun body/air cap are teflon anodized for easy clean up.
- Stainless steel fluid passages.
- * Self cleaning needle.
- The teflon coated air cap is designed to reduce "face loading".



Tomcat

General Purpose

- The Tomcat/Tomahawk are general purpose conventional air spray_ guns.
- Rugged and designed for production use, these spray guns are perfect for all coatings thick and



CP-CSLP CSLP CAT Pack

- The CSLP is an all stainless steel pressure feed spray gun.
- Comes in a kit which incorporates 3 needles/nozzles and 2 air caps.
- California compliant HVLP.



Double Diaphragm Pumps

C.A. Technologies double diaphragm pumps are the answer for spraying virtually any type of adhesives, including "sheer sensitive" products. They're perfect for single, multi-hand gun and automatic spray systems. Available with optional fluid regulator (52-203) to provide pulse free operation and multi-gun setups. Stainless steel construction, teflon diaphragms and stainless steel balls and seats, these units are rated at 12 gallons per minute at maximum of 100 psi fluid pressure.



70-1101-5 5 Gallon Wall Mount

70-1101-55 55 Gallon **Wall Mount**



70-1102-55 5 Gallon 55 Gallon Cart Mount **Cart Mount**



70-1105 55 Gallon **Drum Mount**



70-1103 5 Gallon **Pail Mount**

Pressure Tanks - Solvent Based





5 Gallon Tank



Pressure Tanks - Water Based

2.5 Gallon Stainless Steel Tank



5 Gallon Stainless Steel Tank



Semi Ridged Liners 2.5 Gallon Disposable Semi Ridged Liners





- * Semi ridged liners for the 51-200/800 series 2.5 gal tanks. Part Number: 51-261-12 (12 pack) 51-261-60 (60 pack)
- *Please note that standard 5 gallon pails will fit into our 5 gallon pressure pots.