

ARGUS

ADVANTA®

XCOMP MT

TIRES®

MUD TERRAIN LIGHT TRUCK TIRES

- Aggressive is an understatement. This tire is a beast!
- Maximum traction and grip on the shoulder area of the tire when it's needed most.
- Self-cleaning tread and shoulder area to prevent mud, rock and snow build up.
- The tire casing has three full plies of polyester with a high turn up on the sidewall. This gives the tire excellent strength and durability.
- The tread area has two full steel belts and two full nylon belts. The result is a very stable tread and shoulder area for aggressive and proven performance.
- The end result is a tire that is strong, stable, durable and surprisingly quiet.
- Enthusiast Approved, Race Proven!
- M & S Rated



ECOSAFE

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	Tread Depth 32nds	Sidewall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
1952467553	35X12.50R17LT	126	Q	E	20	BSW	8.5-11.0	12.5	34.5	3750	72
1952468533	33X12.50R18LT	118	Q	E	20	BSW	8.5-11.0	12.5	32.5	2910	68
1952468352	35X12.50R18LT	123	Q	E	20	BSW	8.5-11.0	12.5	34.5	3415	70
1952460333	33X12.50R20LT	114	Q	E	20	BSW	8.5-11.0	12.5	32.5	2600	68
1952460352	35X12.50R20LT	121	Q	E	20	BSW	8.5-11.0	12.5	34.5	3195	75
1952460373	37X13.50R20LT	127	Q	E	20	BSW	8.5-11.0	13.6	36.5	3860	85
1952462332	33X12.50R22LT	109	Q	E	20	BSW	8.5-11.0	12.5	32.5	2270	68
1952462353	35X12.50R22LT	117	Q	E	20	BSW	8.5-11.0	12.5	34.5	2835	73
1952462373	37X13.50R22LT	123	Q	E	20	BSW	8.5-11.0	13.6	36.5	3415	85
1952464353	35X12.50R24LT	117	Q	E	20	BSW	8.5-11.0	12.5	34.5	2835	70
1952464374	37X13.50R24LT	120	Q	E	20	BSW	8.5-11.0	13.6	36.5	3085	81
1952466373	37X13.50R26LT	117	Q	E	20	BSW	8.5-11.0	13.6	36.5	2835	75



ARGUS **ADVANTA**[®]

ER-700

ECONOMY RADIAL TIRES

Superior Traction:

- Symmetrical tread design provides increased dry, wet and light snow traction.

Solid Center Rib:

- Improves on-line steering feel, stability and tread wear.

High-Speed Maneuverability:

- High angle tread blocks designed to extend the contact patch combined with symmetrical tread design enhance high speed cornering and stability.
- 45,000-mile limited treadwear warranty.



ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.

ER-700

ADVANTA[®]

Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
ER700215	225/60R17	99	T	STD	460AB	10	BLK	6.0-8.0	8.98	27.64	1709	26.4
ER700105	175/65R14	82	H	STD	420AA	10	BLK	5.0-6.0	6.97	22.99	1047	15.2
ER700100	185/60R14	82	H	STD	420AA	10	BLK	5.0-6.5	7.44	22.76	1047	15.7
ER700125	185/60R15	84	H	STD	420AA	10	BLK	5.0-6.5	7.44	23.74	1102	17.2
ER700110	185/65R14	82	H	STD	420AA	10	BLK	5.0-6.5	7.44	23.46	1047	16.1
ER700135	185/65R15	88	H	STD	420AA	10	BLK	5.0-6.5	7.44	24.45	1235	17.0
ER700115	185/70R14	88	T	STD	460AB	10	BLK	4.5-6.0	7.44	24.25	1235	17.2
ER700130	195/60R15	88	H	STD	420AA	10	BLK	5.5-7.0	7.91	24.21	1235	18.3
ER700140	195/65R15	91	H	STD	420AA	10	BLK	5.5-7.0	7.91	25.00	1356	19.4
ER700120	195/70R14	91	T	STD	460AB	10	BLK	5.0-6.5	7.91	24.80	1356	19.0
ER700160	205/55R16	91	V	STD	420AA	10	BLK	5.5-7.5	8.43	24.88	1356	20.7
ER700170	205/60R16	92	V	STD	420AA	10	BLK	5.5-7.5	8.23	25.67	1389	20.9
ER700145	205/65R15	94	H	STD	420AA	10	BLK	5.5-7.5	8.23	25.47	1477	21.2
ER700165	215/55R16	97	H	XL	420AA	10	BLK	6.0-7.5	8.90	25.28	1609	22.0
ER700200	215/55R17	94	V	STD	420AA	10	BLK	6.0-7.5	8.90	26.30	1477	22.4
ER700175	215/60R16	95	V	STD	420AA	10	BLK	6.0-7.5	8.70	26.14	1521	22.9
ER700210	215/60R17	96	T	STD	460AB	10	BLK	5.5-7.5	8.70	27.17	1565	24.4
ER700185	215/65R16	98	T	STD	420AA	10	BLK	6.0-7.5	8.70	27.01	1653	24.9
ER700220	215/65R17	99	T	STD	460AB	10	BLK	6.0-8.0	8.70	28.04	1709	25.3
ER700195	225/50R17	94	V	STD	420AA	10	BLK	6.0-8.0	9.17	25.91	1477	23.5
ER700205	225/55R17	97	V	STD	420AA	10	BLK	6.0-8.0	9.17	26.78	1609	24.6
ER700180	225/60R16	98	H	STD	420AA	10	BLK	6.0-8.0	8.98	26.61	1653	24.5
ER700225	225/65R17	102	T	STD	460AB	10	BLK	6.0-7.5	8.98	28.51	1874	26.6



ARGUS ADVANTA[®]

HPZ-01

HIGH PERFORMANCE TIRES

- Outstanding Ride Control:
Tread designed for stability with a large contact patch
- Noise treated tread design for an exceptionally quiet ride
- All season design and M&S rated for all driving conditions
- Exceptional wet and dry performance in all weather conditions
- 40,000-mile limited treadwear warranty



ECOSAFE

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range	Overall Width (in.)	Overall Diameter (in.)	Max Load	
											Single/Dual (lbs.)	Tire Weight (lbs.)
1951357400	205/40ZR17 XL	84	W	XL	420 AA A	10	BLK	7-8	9	23.5	1102	19.8
1951357500	205/50ZR17 XL	93	W	XL	420 AA A	10	BLK	5.5-7.5	9	25.1	1433	22.9
1951357401	215/40ZR17 XL	87	W	XL	420 AA A	10	BLK	7-8.5	9	23.8	1201	21.4
1951357451	215/45ZR17 XL	91	W	XL	420 AA A	10	BLK	7-8	9	24.7	1356	22.5
1951357501	215/50ZR17 XL	95	V	XL	420 AA A	10	BLK	6-7.5	9	25.5	1521	23.7
1951357551	215/55ZR17 XL	98	W	XL	420 AA A	10	BLK	6-7.5	9	26.3	1653	22.5
1951357452	225/45ZR17 XL	94	W	XL	420 AA A	10	BLK	7-8	9	25	1477	23.2
1951357502	225/50ZR17 XL	98	V	XL	420 AA A	10	BLK	6-8	10	25.9	1653	24.3
1951357552	225/55R17 XL	101	V	XL	420 AA A	10	BLK	6-8	10	26.8	1819	25
1951357453	235/45ZR17 XL	97	W	XL	420 AA A	10	BLK	7.5-9	10	25.4	1609	23.8
1951357553	235/55R17 XL	103	V	XL	420 AA A	10	BLK	6.5-8.5	10	27.2	1929	26
1951357404	245/40ZR17 XL	95	W	XL	420 AA A	10	BLK	8-9.5	10	24.7	1521	24.3
1951357454	245/45ZR17 XL	99	W	XL	420 AA A	10	BLK	7.5-9	10	25.7	1709	24.5
1951358351	215/35ZR18 XL	84	W	XL	420 AA A	10	BLK	7-8.5	9	23.9	1102	22.1
1951358401	215/40ZR18 XL	89	W	XL	420 AA A	10	BLK	7-8.5	9	24.8	1279	21.2
1951358402	225/40ZR18 XL	92	W	XL	420 AA A	10	BLK	7.5-9	9	25.1	1389	23.3
1951358452	225/45ZR18 XL	95	W	XL	420 AA A	10	BLK	7-8.5	9	25.9	1521	24.7
1951358403	235/40ZR18 XL	95	W	XL	420 AA A	10	BLK	8-9.5	10	25.4	1521	23.8
1951358503	235/50ZR18 XL	101	W	XL	420 AA A	10	BLK	6.5-8.5	10	27.3	1819	26
1951358553	235/55ZR18 XL	104	W	XL	420 AA A	10	BLK	6.5-8.5	10	28.2	1984	29.1
1951358404	245/40ZR18 XL	97	W	XL	420 AA A	10	BLK	8-9.5	10	25.7	1609	26.4
1951358454	245/45ZR18 XL	100	W	XL	420 AA A	10	BLK	7.5-9	10	26.7	1764	26.2
1951358355	255/35ZR18 XL	94	W	XL	420 AA A	10	BLK	8.5-10	11	25	1477	24.9
1951358455	255/45ZR18 XL	103	W	XL	420 AA A	10	BLK	8-9.5	10	27.1	1930	28.2
1951358555	255/55ZR18 XL	109	W	XL	420 AA A	10	BLK	7-9	10	29	2270	33.1
1951359352	225/35ZR19 XL	88	W	XL	420 AA A	10	BLK	7-8.5	9	25.2	1235	23.9
1951359402	225/40ZR19 XL	93	W	XL	420 AA A	10	BLK	8-9.5	9	26.1	1433	23.7
1951359552	225/55R19 SL	99	H	SL	420 AA A	10	BLK	6-8	10	28.8	1709	27.1
1951359353	235/35ZR19 XL	91	W	XL	420 AA A	10	BLK	7-8.5	9	25.5	1356	23.9
1951359354	245/35ZR19 XL	93	W	XL	420 AA A	10	BLK	8-9.5	10	25.8	1433	24.6
1951359404	245/40ZR19 XL	98	W	XL	420 AA A	10	BLK	8-9.5	10	26.7	1653	25.9
1951359454	245/45ZR19 XL	102	W	XL	420 AA A	10	BLK	7.50-9	10	27.7	1875	27.1
1951359355	255/35ZR19 XL	96	W	XL	420 AA A	10	BLK	8-9.5	11	26	1565	25.5
1951359306	265/30ZR19 XL	93	W	XL	420 AA A	10	BLK		11	25.3	1433	25.3
1951359307	275/30ZR19 XL	96	W	XL	420 AA A	10	BLK	9-10	11	25.6	1565	26.1
1951350302	225/30ZR20 XL	85	W	XL	420 AA A	10	BLK	7.5-9	9	25.4	1135	21.9
1951350352	225/35ZR20 XL	90	W	XL	420 AA A	10	BLK	7.5-9	9	26.2	1323	21.9
1951350304	245/30ZR20 XL	90	W	XL	420 AA A	10	BLK		10	25.8	1323	24.7
1951350354	245/35ZR20 XL	95	W	XL	420 AA A	10	BLK	8.5-10	10	26.8	1521	25.7
1951350404	245/40ZR20 XL	99	W	XL	420 AA A	10	BLK	8-9.5	10	27.7	1709	27.1
1951350454	245/45ZR20 SL	99	W	SL	420 AA A	10	BLK	8-9.5	10	28.7	1709	28
1951350355	255/35ZR20 XL	97	W	XL	420 AA A	10	BLK	8.5-10	11	27	1609	26.4
1951350455	255/45ZR20 XL	105	W	XL	420 AA A	10	BLK	8-9.5	10	29.1	2039	29.4
1951350307	275/30ZR20 XL	97	W	XL	420 AA A	10	BLK	9-10	11	26.5	1609	27.4
1951352407	275/40ZR20 XL	106	W	XL	420 AA A	10	BLK	9-11	11	28.7	2094	30.9
1951350457	275/45R20 XL	110	V	XL	420 AA A	10	BLK	8.5-10.5	11	29.8	2337	32.2
1951350557	275/55R20 XL	117	V	XL	420 AA A	10	BLK	7.5-9.5	12	31.9	2833	36.6
1951350258	285/25ZR20 XL	93	W	XL	420 AA A	10	BLK		12	25.6	1433	28.6
1951352303	235/30ZR22 XL	90	W	XL	420 AA A	10	BLK		10	27.6	1323	21.9
1951352304	245/30ZR22 XL	92	W	XL	420 AA A	10	BLK		10	27.8	1389	26.5
1951352305	255/30ZR22 XL	95	W	XL	420 AA A	10	BLK		11	28.1	1521	25.6
1951352306	265/30ZR22 XL	97	W	XL	420 AA A	10	BLK		11	28.3	1609	29.3
1951352355	265/35ZR22 XL	102	W	XL	420 AA A	10	BLK	9.5-10.5	11	29.3	1874	30.3
1951352258	285/25ZR22 XL	95	W	XL	420 AA A	10	BLK		12	27.6	1521	30.2
1951352458	285/45ZR22 XL	114	W	XL	420 AA A	10	BLK	9-10.5	12	32.1	2601	35.3
1951352259	295/25ZR22 XL	97	W	XL	420 AA A	10	BLK		12	27.8	1609	31.8
1951352400	305/40ZR22 XL	114	W	XL	420 AA A	10	BLK	10-12	13	31.6	2601	40.1
1951352450	305/45R22 XL	118	V	XL	420 AA A	10	BLK	9.5-11.5	12	32.8	2910	40.4
1951354305	255/30ZR24 XL	97	W	XL	420 AA A	10	BLK	8.5-9.5	11	30.1	1609	30.4
1951354257	275/25ZR24 XL	96	W	XL	420 AA A	10	BLK	9.5-10.5	11	29.5	1565	30.9
1951354450	305/35R24 XL	112	V	XL	420 AA A	10	BLK	10-12	13	32.4	2469	41
1951356257	275/25ZR26 XL	98	W	XL	420 AA A	10	BLK	9.5-10.5	11	31.4	1653	34.1
1951356309	295/30ZR26 XL	107	W	XL	420 AA A	10	BLK		12	33	2149	38.3
1951356300	305/30R26 XL	109	V	XL	420 AA A	10	BLK		13	33.2	2271	41.6

ARGUS **ADVANTA**[®]



HTR-700

LIGHT TRUCK HIGHWAY TERRAIN

- LT rated 10 ply tires designed for carrying heavy cargo and towing large trailers.
- Wide 5-rib highway tread offers combination of superb handling and braking on wet and dry surfaces.
- Designed for a quiet, comfortable ride and maximum performance for highway applications in all weather conditions.
- Strong steel belted construction ensures exceptional stability, durability and long tread life.
- M & S Rated



ECOSAFE

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



HTR-700



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	Ply Rating	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
1932401863	LT215/85R16	115/112	Q	E	10	15	BLK	5.5 - 7.0	8.5	30.4	2680/2470	37.0
1932402763	LT225/75R16	115/112	Q	E	10	15	BLK	6.0 - 8.0	8.8	29.3	2680/2470	38.6
1932403863	LT235/85R16	120/116	Q	E	10	15	BLK	6.0 - 7.5	9.3	31.7	3042/2778	42.7
1932404763	LT245/75R16	120/116	Q	E	10	15	BLK	6.5 - 8.0	9.8	30.5	3042/2778	43.3
1932406763	LT265/75R16	123/120	Q	E	10	15	BLK	7.0 - 8.0	10.5	31.7	3415/3085	47.6
1932404773	LT245/75R17	121/118	Q	E	10	15	BLK	6.5 - 7.5	9.8	31.5	3195/2910	43.2
1932407763	LT265/70R17	121/118	Q	E	10	15	BLK	7.0 - 8.5	10.7	31.7	3195/2910	47.4



ARGUS **ADVANTA**[®]

SVT-01

RADIAL SUV TIRES

- Designed for maximum performance for all sport utility vehicle applications.
- Tread design is noise treated to ensure smooth, quiet ride on all road surfaces.
- Designed for exceptional handling, braking and acceleration.
- Sturdy steel belt construction to ensure stability, durability and long tread life.
- M & S Rated
- 60,000-mile limited treadwear warranty.



ECOSAFE

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



SVT-01



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
1932436715	P215/70R16	99	T	SL	520 A A	11	BLK	5.5 - 7.0	8.7	27.9	1709	27.6
1932436735	P235/70R16	104	T	SL	520 A A	11	BLK	6.0 - 8.0	9.5	29.0	1984	30.7
1932437615	P215/60R17	95	V	SL	520 A A	11	BLK	6.0 - 7.5	8.7	27.2	1521	27.6
1932437625	P225/65R17	100	T	SL	520 A A	11	BLK	6.5 - 8.0	9.0	28.5	1764	29.1
1932437635	P235/65R17	103	T	SL	520 A A	11	BLK	6.5 - 8.0	9.5	29.1	1929	30.9
1932437645	P245/65R17	105	T	SL	520 A A	11	BLK	7.0 - 8.5	9.8	29.5	2039	32.3
1932437745	P245/70R17	108	T	SL	520 A A	11	BLK	6.5 - 8.0	9.8	30.6	2205	33.7
1932437665	P265/65R17	110	T	SL	520 A A	11	BLK	7.5 - 9.5	10.7	30.6	2337	35.8
1932437765	P265/70R17	113	T	SL	520 A A	11	BLK	7.0 - 9.0	10.7	31.7	2535	37.3
1932438255	P225/55R18	97	H	SL	520 A A	11	BLK	6.0 - 8.0	9.2	27.8	1609	28.4
1932438635	P235/60R18	102	T	SL	520 A A	11	BLK	6.5 - 8.5	9.5	29.1	1874	31.6
1932438355	P235/65R18	104	H	SL	520 A A	11	BLK	6.5 - 8.5	9.5	30.0	1984	32.7
1932438645	P245/60R18	104	T	SL	520 A A	11	BLK	7.0 - 8.5	9.8	29.6	1984	32.6
1932438555	P255/65R18	109	H	SL	520 A A	11	BLK	7.0 - 9.0	10.2	31.1	2271	34.5
1932438765	P265/70R18	114	T	SL	520 A A	11	BLK	7.0 - 9.0	10.7	32.6	2601	39.0
1932438755	P275/65R18	114	H	SL	520 A A	11	BLK	7.5 - 9.5	11.0	32.1	2601	39.8
1932439355	P235/55R19XL	105	V	XL	520 A A	11	BLK	6.5 - 8.5	9.7	29.2	2039	31.6
1932439455	P245/55R19	103	H	SL	520 A A	11	BLK	7.0 - 8.5	10.0	29.7	1929	33.0
1932432575	P275/55R20	117	T	SL	520 A A	11	BLK	7.5 - 9.5	11.2	31.9	2833	43.0
1932432675	P275/60R20	115	T	SL	520 A A	11	BLK	7.5 - 9.5	11.0	33.0	2679	46.0



ARGUS ADVANTA[®]

TRG-750

PASSENGER TOURING TIRES

- Fits Broadline sedans, coupes, compacts and vans with speed rated sizing for today's popular vehicle fitments
- Technology-driven tread design for superior all-weather performance
- Precision engineered for even wear and long tread life
- Full-depth siping for long lasting wet and snow traction
- Notched center rib with multi-element blading for improved handling and steering response
- 60,000 mile treadwear warranty T rated
- 50,000 mile treadwear warranty H/V rated

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



TRG-750



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
TRG750100	185/65R14	86	T	STD	500AB	10	SBL	5.0-6.5	7.44	23.46	1168	16.8
TRG750105	185/60R15	84	T	STD	500AB	10	SBL	5.0-6.5	7.44	23.74	1102	18.5
TRG750110	195/60R15	88	H	STD	460AA	10	SBL	5.5-7.0	7.91	24.21	1235	18.4
TRG750115	185/65R15	88	T	STD	500AB	10	SBL	5.0-6.5	7.44	24.45	1235	17.6
TRG750120	195/65R15	91	T	STD	500AB	10	SBL	5.5-7.0	7.91	25.00	1356	20.3
TRG750125	205/65R15	94	T	STD	500AB	10	SBL	5.5-7.5	8.23	26.46	1477	21.7
TRG750130	215/65R16	98	T	STD	500AB	10	SBL	6.0-7.5	8.23	25.47	1653	25.0
TRG750135	205/70R15	96	T	STD	500AB	10	SBL	5.0-7.0	8.70	26.89	1565	23.7
TRG750140	215/70R15	98	T	STD	500AB	10	SBL	5.5-7.0	8.23	26.34	1653	25.2
TRG750145	205/55R16	91	H	STD	460AA	10	SBL	5.5-7.5	8.43	24.88	1356	21.3
TRG750150	215/55R16	97	H	STD	460AA	10	SBL	6.0-7.5	8.90	25.28	1609	23.4
TRG750155	205/60R16	92	H	STD	460AA	10	SBL	5.5-7.5	8.70	25.16	1389	21.6
TRG750160	215/60R16	95	T	STD	500AB	10	SBL	6.0-7.5	8.70	26.14	1521	24.3
TRG750165	225/60R16	98	T	STD	500AB	10	SBL	6.0-8.0	8.70	27.17	1653	25.4
TRG750175	205/65R16	95	H	STD	460AA	10	SBL	5.5-7.5	8.70	27.01	1521	21.5
TRG750180	225/65R16	100	T	STD	500AB	10	SBL	6.0-8.0	8.98	27.48	1764	25.9
TRG750185	235/65R16	103	T	STD	500AB	10	SBL	6.5-8.5	9.45	28.03	1929	26.7
TRG750190	205/50R17	89	V	STD	380AA	10	SBL	5.5-7.5	8.43	25.12	1279	21.3
TRG750200	225/50R17	94	V	STD	380AA	10	SBL	6.0-8.0	9.17	25.91	1477	25.4
TRG750205	215/55R17	94	V	STD	380AA	10	SBL	6.0-7.5	8.90	26.30	1477	24.6
TRG750210	225/55R17	97	T	STD	500AB	10	SBL	6.0-8.0	9.17	26.77	1609	25.8
TRG750215	215/60R17	96	T	STD	500AB	10	SBL	6.0-7.5	8.98	27.64	1565	25.3
TRG750220	225/60R17	99	T	STD	500AB	10	SBL	6.0-8.0	8.98	26.61	1709	26.4
TRG750225	225/65R17	102	T	STD	500AB	10	SBL	6.0-8.0	8.98	28.50	1653	30.0



ARGUS **ADVANTA**®

ATX-750

ALL TERRAIN LIGHT TRUCK TIRES

- 3 Peak Mountain Snowflake Certified (3PMS) for severe snow performance.
- Aggressive open shoulder design increases stability and traction in all weather conditions.
- Stone ejectors withstand harsh road conditions.
- Trapezoidal claw design on the shoulder edge increases traction in snow and mud, dissipates heat and enhances durability.
- Jagged edge tread blocks improve grip on ice and in the mud providing superior traction.
- Zig zag grooves and continuous center block provide outstanding grip and superior handling.
- 50,000 mile limited treadwear warranty P metric rated
- 50,000 mile limited treadwear warranty LT rated.

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



ATX-750



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
ATX750100	235/75R15	109	S	SL	500AB	13	OWL	6.0-8.0	9.25	28.86	2271	31.5
ATX750105	235/70R16	106	S	SL	500AB	13	OWL	6.0-8.0	9.45	28.98	2094	31.2
ATX750110	245/75R16	111	S	SL	500AB	13	OWL	6.5-8.0	9.76	30.47	2403	35.2
ATX750115	265/75R16	116	S	SL	500AB	13	OWL	7.0-9.0	10.51	31.65	2756	38.1
ATX750120	265/70R16	112	T	SL	500AB	13	OWL	7.0-9.0	10.71	30.63	2469	37.1
ATX750125	245/65R17	107	S	SL	500AB	13	OWL	7.0-8.5	9.76	29.53	2149	33.3
ATX750130	265/65R17	112	S	SL	500AB	13	OWL	7.5-9.5	10.71	30.55	2469	37.2
ATX750135	265/70R17	115	S	SL	500AB	13	OWL	7.0-9.0	10.71	31.65	2679	39.0
ATX750140	275/65R18	116	T	SL	500AB	13	OWL	7.5-9.5	10.98	32.09	2756	39.9
ATX750145	275/60R20	115	T	SL	500AB	13	BSW	7.5-9.5	10.98	32.99	2679	40.8
ATX750150	275/55R20	117	T	XL	500AB	13	BSW	7.5-9.5	11.18	31.89	2833	40.1
ATX750155	LT225/75R16	115/112	S	10/E	-	16	BSW	6.0-7.0	8.78	29.29	2680/2470	36.6
ATX750160	LT285/75R16	126/123	R	10/E	-	16	OWL	7.5-9.5	11.26	32.83	3750/3415	49.3
ATX750165	LT245/75R16	120/116	S	10/E	-	16	BSW	6.5-8.0	9.76	30.47	3042/2778	41.3
ATX750170	LT265/75R16	123/120	S	10/E	-	16	OWL	7.0-8.0	10.51	31.65	3415/3085	45.2
ATX750175	LT235/85R16	120/116	R	10/E	-	16	BSW	6.0-7.5	9.25	31.73	3042/2778	41.7
ATX750180	LT235/80R17	120/117	R	10/E	-	16	OWL	6.0-7.5	9.25	31.81	3085/2835	41.5
ATX750185	LT245/70R17	119/116	S	10/E	-	16	OWL	6.5-8.0	9.76	30.55	3000/2755	41.6
ATX750190	LT245/75R17	121/118	S	10/E	-	16	OWL	6.5-7.5	9.76	31.50	3195/2910	42.9
ATX750195	LT265/70R17	121/118	S	10/E	-	16	OWL	7.0-8.5	10.71	31.65	3195/2910	45.6
ATX750200	LT285/70R17	121/118	R	10/E	-	16	OWL	7.5-9.0	11.50	32.76	3195/2910	49.6
ATX750205	LT265/70R18	124/121	R	10/E	-	16	BSW	7.0-9.0	10.71	32.64	3525/3195	47.0
ATX750210	LT275/70R18	125/122	R	10/E	-	16	OWL	7.0-8.5	10.98	33.19	3640/3305	49.4
ATX750215	LT275/65R18	123/120	R	10/E	-	16	OWL	7.5-9.0	10.98	32.09	3415/3085	47.5
ATX750220	LT275/65R20	126/123	R	10/E	-	16	BSW	7.5-9.5	10.98	34.09	3750/3415	50.7
ATX750225	31x10.50R15LT	109	S	6/C	-	16	OWL	7.0-9.0	10.54	30.52	2270	40.0