

HARVEST KING[®]

HARDWORKING, JUST LIKE YOU

AG TIRES 2018

FARM TIRES

TABLE OF CONTENTS

REAR FARM		
RADIAL REAR FARM R-1W	HARVEST KING FIELD PRO R-1W	3
	BKT AGRIMAX RT 945	3
	BKT AGRIMAX RT 855	4
	BKT AGRIMAX RT 765/657	5
REAR FARM G-1	HARVEST KING FIELD PRO ALL PURPOSE G-1	5
	BKT TR-126 / TR-144	5
REAR FARM R-1	HARVEST KING FIELD PRO ALL PURPOSE R-1	6
	BKT TR-137 HARVESTER BIAS	6
	BKT TR-135 / AS 2001	7
IRRIGATION R-1	HARVEST KING R-GATOR II	8
	HARVEST KING R-GATOR ND	8
	BKT TR-117	8
DEEP TREAD R-2	BKT TR-171	9
TURF R-3	BKT TR-390/387/391	9
REAR FARM R-4	HARVEST KING INDUSTRIAL TRACTOR R-4	9
	BKT AT-621	10
	BKT TR-459	10
TRACTION IMPLEMENT I-3/R-4	HARVEST KING POWER LUG 4WD II	10
	BKT AT-603	11
	BKT AS-504	11
FRONT FARM		
FRONT FARM F-2M	HARVEST KING FRONT FARM 4R	11
	BKT PRO RIB	12
FRONT FARM F-2	HARVEST KING FRONT TRACTOR II	12
	BKT TF-9090	13
INDUSTRIAL FRONT F-3	HARVEST KING PREMIUM BACKHOE F-3	13
	BKT RIB F-3	14
FLOTATION AND IMPLEMENT		
IMPLEMENT I-1	HARVEST KING RIB IMPLEMENT	14
	BKT IMPLEMENT I-1	15
INTERMITTENT HIGHWAY SERVICE FI	HARVEST KING FIELD PRO HIGHWAY SERVICE FI	15
SPECIALTY IMPLEMENT AND TRAILER	BKT AW-702	16
FLOTATION HF-2	BKT FLOTATION 648	16

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.

FARM TIRES

REAR FARM



HARVEST KING
FIELD PRO
R-1W



BKT
AGRIMAX RT



HARVEST KING
FIELD PRO ALL PURPOSE G-1
(APR)



BKT
TR-144



HARVEST KING
FIELD PRO ALL PURPOSE R-1
(APR)



BKT
TR-137
HARVESTER BIAS



BKT
TR-135



HARVEST KING
R-GATOR II
(GHD)



BKT
TR-117



BKT
TR-171



BKT
TR-390



HARVEST KING
INDUSTRIAL
TRACTOR-4 (HRT)



BKT
AT-621



BKT
TR-459



HARVEST KING
POWER LUG
4WD II (PLW)



BKT
AT-603



BKT
AS-504

FRONT FARM



HARVEST KING
FRONT FARM 4R
(HK4R)



BKT
PRO RIB



HARVEST
KING FRT
TRACTOR II



BKT
TF-9090



HARVEST KING
PREMIUM
BACKHOE F-3 (HBH)



BKT
RIB F-3

FLOTATION AND IMPLEMENT



HARVEST KING
RIB IMPLEMENT (HK)



BKT
IMPLEMENT I-1



HARVEST KING
FIELD PRO HIGHWAY
SERVICE FI (HSL)



BKT
AW-702
(HSL)



BKT
FLOTATION 648

RADIAL REAR FARM R-1W

HARVEST KING FIELD PRO R-1W

- Less slippage and lower fuel consumption
- Up to 25% deeper tread than conventional R-1 tires
- Mud breakers for enhanced self-cleaning and superior traction
- Designed for applications in heavy, wet soil conditions



ARTICLE NO.	SIZE	REPLACES SIZE	LOAD INDEX	TREAD DEPTH (32NDS)	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
HR38824	380/85R24	14.9R24	131A8/B	57	12.0	49	15.0	153	4300@23
HR38828	380/85R28	14.9R28	133A8/B	57	12.0	53.4	15.0	175	4540@23
HR42828	420/85R28	16.9R28	139A8/B	60	13.0	56.1	16.5	211	5360@23
HR38830	380/85R30	14.9R30	135A8/B	52	12.0	55.4	15.0	184	4800@23
HR42830	420/85R30	16.9R30	140A8/B	53	13.0	58.1	16.5	220	5520@23
HR38834	380/85R34	14.9R34	137A8/B	57	12.0	59.5	15.0	211	5080@23
HR46838	460/85R38	18.4R38	149A8/B	64	14.0	68.8	17.9	300	7150@23
HR52838	520/85R38	20.8R38	155A8/B	67	16.0	72.8	20.3	381	8550@23
HR48842	480/80R42	18.4R42	151A8/B	62	15.0	72.2	18.9	351	7600@23
HR52842	520/85R42	20.8R42	157A8/B	67	16.0	76.8	20.3	425	9100@23
HR38946	380/90R46	14.9R46	159A8/B	57	12.0	72.9	15.0	276	9650@58
HR48846	480/80R46	18.4R46	158A8/B	62	16.0	76.2	18.9	390	9350@35

RADIAL REAR FARM R-1W

BKT AGRIMAX RT945

- Specially designed with round shoulders to protect crops and soil from damage
- Deep tread for excellent traction and continuous ground contact
- High speed with nylon casing and rigid polyester belt for enhanced stability
- Capable of sustained high speeds to handle the road and field



ARTICLE NO.	SIZE	REPLACES SIZE	LOAD INDEX	TREAD DEPTH (32NDS)	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94021833	380/90R46	14.9R46	159A8/B	57	12.0	72.9	15.0	310	9640@58

RADIAL REAR FARM R-1W

BKT AGRIMAX RT855

- Combines excellent traction and self-cleaning features to increase tread life
- Designed to provide higher load capacities
- Provides maximum driving comfort both on and off road
- Excellent flotation characteristics for minimum impact on soil fertility



ARTICLE NO.	SIZE	REPLACES SIZE	LOAD INDEX	TREAD DEPTH (32NDS)	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94021536	280/85R24	11.2R24	115A8/B	51	10.0	42.8	11.5	95	2680@23
94021550	320/85R24	12.4R24	122A8/B	52	11.0	45.4	13.0	118	3300@23
94021635	380/85R24	14.9R24	131A8/B	56	12.0	49.4	15.0	163	4300@23
94021611	340/85R28	13.6R24	127A8/B	55	12.0	50.7	13.9	151	3860@23
94021666	380/85R28	14.9R28	133A8/B	56	12.0	53.4	15.0	185	4540@23
94021710	420/85R28	16.9R28	139A8/B	61	15.0	56.1	17.2	229	5360@23
94021680	380/85R30	14.9R30	135A8/B	56	12.0	55.4	15.0	200	4800@23
94021734	420/85R30	16.9R30	140A8/B	61	15.0	58.1	17.2	237	5500@23
94021765	460/85R30	18.4R30	145A8/B	65	16.0	60.8	18.7	287	6390@23
94021697	380/85R34	14.9R34	137A8/B	56	12.0	59.4	15.0	216	5080@23
94021741	420/85R34	16.9R34	142A8/B	61	15.0	62.1	17.2	259	5840@23
94021772	460/85R34	18.4R34	147A8/B	65	16.0	64.8	18.7	300	6780@23
94021758	420/85R38	16.9R38	144A8/B	64	15.0	66.1	17.2	280	6150@23
94021789	460/85R38	18.4R38	149A8/B	67	16.0	68.8	18.7	328	7160@23
94021802	520/85R38	20.8R38	155A8/B	71	16.0	72.8	20.3	430	8540@23
94021796	480/80R42	18.4R42	151A8/B	67	16.0	72.2	18.9	385	7600@23
94021819	520/85R42	20.8R42	157A8/B	71	16.0	76.8	20.3	435	9100@23
94021826	480/80R46	18.4R46	158A8/B	67	16.0	76.2	18.9	420	9350@35
94030569	520/85R46	20.8R46	158A8/B	71	16.0	80.8	20.3	498	9370@23
94029914	480/80R50	18.4R50	159A8/B	67	16.0	80.2	19.3	470	9640@35

RADIAL REAR FARM R-1W

BKT AGRIMAX RT765/657

- Excellent flotation characteristics for minimum impact on soil fertility
- Combines excellent traction and self-cleaning features for increased tread life
- Designed to provide higher load capacities



ARTICLE NO.	SIZE	REPLACES SIZE	LOAD INDEX	TREAD DEPTH (32NDS)	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94021901	280/70R18	7.50R18	114A8/B	40	9.0	33.4	11.1	62	2600@35
94021970	280/70R20	7.50R20	116A8/B	40	9.0	35.4	11.1	66	2760@35
94021482	480/70R34	16.9R34	149A8/B	62	15.0	62.2	18.9	285	7150@35
94021383*	650/65R38	-	163D/166A8	74	20.0	71.3	25.4	498	11680@35

* Branded RT657

REAR FARM G-1

HARVEST KING FIELD PRO ALL PURPOSE G-1

- Long Bar / Long Bar for excellent traction and roadability
- Ideally suited for compact tractors
- Heavy duty construction to resist damage
- Competitively priced for the best value on the farm or homestead



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
APR714A	7-14	C/6	20	TL	6.0	27.2	7.2	19	990@36
APR716	7-16	C/6	31	TT	6.0	29.2	7.2	25	1100@36
APR816	8-16	C/6	34	TT	6.0	31.1	8.3	29	1360@28

REAR FARM G-1

BKT TR-126 / TR-144

- Designed for small tractors
- Deep lugs for excellent traction
- Suitable for wet soil



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (20 MPH)
94004522	6-14	B/4	33	TT	5.0	25.8	6.2	21	660@28
94004539	7-14	B/4	33	TT	5.0	27.2	6.7	22	785@24
94004706*	7-16	B/4	31	TT	6.0	29.1	7.2	26	855@24
94004720*	8-16	C/6	33	TT	6.0	30.9	7.9	32	1360@28
94004737	8-18	C/6	33	TT	6.0	33.1	7.9	37	1480@28
94004744	9.5-22	C/6	35	TT	7.0	39.4	9.3	52	1760@32

* Branded as TR-144

REAR FARM R-1

HARVEST KING FIELD PRO ALL PURPOSE R-1

- Long Bar / Long Bar design for traction and roadability
- Tough enough for even the most demanding environments
- Tapered lugs for support where you need it
- Deep size lineup with the most popular sizes in the market
- Best value in competitive rear farm segment



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
APR8324A	8.3-24	D/8	35	TT	7.0	39.1	8.3	49	2095@28
APR9524A*	9.5-24	D/8	38	TT	8.0	41.3	9.5	75	2270@40
APR11224A	11.2-24	D/8	40	TT	10.0	43.4	11.2	72	2540@36
APR12424A	12.4-24	D/8	44	TT	11.0	45.6	12.4	89	2830@32
APR14924A	14.9-24	D/8	47	TT	13.0	49.8	14.9	118	3520@26
APR16924A	16.9-24	D/8	50	TT	15.0	52.5	16.9	148	4080@24
APR11228A	11.2-28	D/8	40	TT	10.0	47.4	11.2	94	2680@36
APR12428A	12.4-28	D/8	44	TT	11.0	49.6	12.4	104	3000@32
APR13628A	13.6-28	D/8	47	TT	12.0	51.6	13.6	113	3300@28
APR14928A	14.9-28	D/8	47	TT	13.0	53.8	14.9	136	3740@26
APR16930A	16.9-30	D/8	48	TT	15.0	58.5	16.9	167	4400@24
APR18430A	18.4-30	D/8	48	TT	16.0	61.1	18.4	205	4800@20
APR18434A	18.4-34	D/8	38	TT	16.0	65.1	18.4	231	5080@20
APR13638A	13.6-38	D/8	50	TT	12.0	61.6	13.6	161	3860@28
APR15538A	15.5-38	D/8	43	TT	14.0	61.8	15.5	172	4540@26
APR18438A	18.4-38	D/8	50	TT	16.0	69.1	18.4	251	5360@20
APR20838A	20.8-38	D/8	53	TT	18.0	72.2	20.8	305	6150@18

* Slightly Different Tread Pattern

REAR FARM R-1

BKT TR-137 HARVESTER BIAS

- Dual-angled lugs for increased traction
- Strong casing for heavy loads
- More lugs for uniform distribution of load
- Optimum tread depth and special tread compound for higher mileage



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94004317	24.5-32	F/12	52	TL	21.0	71.1	24.5	489	8800@24
94004331	30.5L-32	F/12	60	TL	27.0	73.4	30.3	626	9350@20

REAR FARM R-1

BKT TR-135

- Dual-angled tread lugs for high traction and long life in both field and on-the-road operations
- Reinforced shoulders for extra durability
- Strong casing for excellent stability and safety
- Use in farm, industrial and construction applications



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94004621	9.5-20	C/6	35	TT	8.0	37.6	9.4	51	1710@32
94028818	11.2-20	D/8	41	TT	10.0	40.2	11.5	58	2150@35
94004584	8.3-24	C/6	35	TT	7.0	39.2	8.3	44	1570@36
94004669	9.5-24	D/8	38	TT	8.0	41.6	9.1	58	2200@42
94003044	11.2-24	D/8	41	TT	10.0	43.5	11.2	71	2540@36
94003129	12.4-24	D/8	42	TT	11.0	45.7	12.4	88	2830@32
94003303	13.6-24	D/8	45	TT	12.0	47.6	13.6	105	3080@28
94003457	14.9-24	D/8	45	TT	13.0	49.8	14.9	120	3520@26
94003570	16.9-24	D/8	47	TT	15.0	52.6	16.9	150	4080@24
94028382	14.9-26	D/8	45	TT	13.0	51.8	14.8	129	3640@26
94028375	16.9-26	E/10	47	TT	15.0	54.3	16.9	168	4540@28
94002795*	18.4-26	F/12	47	TT	16.0	58.1	18.4	197	5840@32
94004027	23.1-26	H/16	54	TL	20.0	62.4	23.1	346	8540@34
94003075	11.2-28	D/8	41	TT	10.0	47.4	11.2	80	2600@36
94003198	12.4-28	D/8	42	TT	11.0	49.6	12.8	100	3090@34
94003341	13.6-28	D/8	45	TT	12.0	51.6	13.6	118	3300@28
94003501	14.9-28	D/8	45	TT	13.0	53.7	14.9	139	3740@26
94002689*	16.9-28	D/8	50	TT	15.0	55.9	16.9	180	4300@24
94003617	16.9-30	D/8	47	TT	15.0	58.5	16.9	174	4400@24
94003761	18.4-30	D/8	48	TT	16.0	60.8	18.1	198	4800@20
94003686	16.9-34	D/8	47	TT	15.0	62.4	16.9	208	4680@24
94003839	18.4-34	D/8	48	TT	16.0	65.0	18.4	224	5080@20
94003266	12.4-36	D/8	42	TT	11.0	57.7	12.8	121	3420@34
94003372	13.6-36	D/8	45	TT	12.0	59.6	13.6	144	3640@30
94003419	13.6-38	D/8	45	TT	12.0	61.6	13.6	149	3860@30
94003549	15.5-38	D/8	42	TT	14.0	62.4	15.6	171	4080@26
94003730	16.9-38	D/8	47	TT	15.0	66.3	16.9	225	4940@24
94003907	18.4-38	D/8	48	TT	16.0	68.9	18.4	254	5360@20

* Branded as AS 2001

IRRIGATION R-1

HARVEST KING R-GATOR II

- Designed for mobile irrigation equipment
- Open tread center for improved cleaning
- Rounded cavity shape reduces crop and soil disturbance
- Anti-ozone compound extends the life of the tire
- Tube type - includes tire only



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
GHD22	11.2-24	C/6	35	TT	10.0	43.4	11.2	59	2090@26
GHD62	14.9-24	C/6	39	TT	13.0	49.8	14.9	105	3000@20
GHD30	11.2-28	C/6	40	TT	10.0	57.4	11.2	91	2540@26

IRRIGATION CROSS BAR

HARVEST KING R-GATOR ND

- Designed for mobile irrigation equipment
- Flat degree bar angle for less slippage and rutting
- Anti-ozone compound extends the life of the tire
- Tubeless Construction



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
GND22	11.2-24	C/6	43	TL	10.0	43.4	11.2	68	2090@26
GND62	14.9-24	C/6	47	TL	12.0	49.8	14.9	122	3000@20
GND30	11.2-38	C/6	43	TL	10.0	57.4	11.2	116	2540@26

IRRIGATION R-1

BKT TR-117

- Designed for mobile irrigation equipment
- Rounded tire shape for reduced crop and soil disturbance
- Tread designed for added traction and self-cleaning properties
- Tube type - includes tire only



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94028368	11.2-24	C/6	31	TT	10.0	42.9	11.2	60	2090@26
94003006	14.9-24	C/6	35	TT	13.0	49.0	14.9	99	3000@20
94028801	11.2-38	B/4	31	TT	10.0	56.9	11.2	88	2090@18

DEEP TREAD R-2

BKT TR-171

- Designed to provide excellent traction and extraordinary durability
- Outstanding self-cleaning properties
- Ideal for wet soil in the harshest operating conditions
- Tube type - includes tire only



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (20 MPH)
94040506	9.5-16	C/6	56	TT	8.0	33.3	9.5	53	1390@30
94035168	8-18	C/6	49	TT	6.0	33.3	7.5	42	1480@28
94034246	9.5-18	D/8	56	TT	8.0	35.4	9.5	61	1820@44
94004768	8.3-20	C/6	56	TT	7.0	35.2	7.9	48	1390@36
94004799	9.5-20	C/6	56	TT	8.0	37.4	9.3	65	1650@30
94004751	11.2-20	D/8	60	TT	10.0	39.6	11.2	82	2270@38
94034574	8.3-22	D/8	56	TT	7.0	37.2	8.1	54	1760@46
94034567	9.5-22	D/8	56	TT	8.0	39.6	9.3	71	2090@44
94004775	8.3-24	C/6	56	TT	7.0	39.0	7.9	57	1570@34
94004805	9.5-24	C/6	56	TT	8.0	41.5	9.3	74	1807@30
94004379	12.4-24	D/8	64	TT	11.0	45.9	12.4	112	2830@32
94025626	14.9-24	C/6	70	TT	13.0	49.8	15.4	150	3000@20

TURF R-3

BKT TR-387/390/391

- Ideal for use on soft soil, orchards and similar applications
- Specially-engineered tread design provides high flotation
- Increased tread depth and strong casing ensure long service life
- Suitable for industrial and construction applications



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94005277*	14.9-24	D/8	24	TL	13.0	49.4	15.9	132	3520@26
94004980*	18.4-26	E/10	30	TL	16.0	56.3	18.7	209	5200@26
94005185	23.1-26	F/12	34	TL	20.0	61.4	23.1	313	7150@24
94005246	28L-26	H/16	34	TL	25.0	61.4	28.1	402	9100@28

* Branded TR391 + Branded TR387

REAR FARM R-4

HARVEST KING INDUSTRIAL TRACTOR R4

- Rim guard strip to protect wheel flange in rough service areas
- Lug pattern designed for smoother roading between jobsites
- Large lugs for puncture and wear resistance
- Designed for maximum service at a competitive price



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (5 MPH)
HRT66	14.9-24	D/8	35	TL	12.0	49.6	15.4	135	5080@30
HRT03	16.9-24	E/10	33	TL	15.0	51.5	16.9	154	6400@32
HRT06	17.5L-24	E/10	32	TL	15.0	48.8	17.5	147	6150@32
HRT10	19.5L-24	F/12	37	TL	17.0	51.7	19.5	197	7600@34
HRT50	21L-24	F/12	37	TL	18.0	53.9	21.0	243	8550@32
HRT78	16.9-28	E/10	37	TL	15.0	55.5	16.9	170	6800@32

REAR FARM R-4

BKT AT-621

- Tread designed to provide excellent traction to drive wheels
- Designed for on and off-the-road use in all weather conditions
- Suitable for implement, industrial and construction applications
- Tubeless construction



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (5 MPH)
94028542	15.5/60-18	E/10	28	TL	13.0	37.4	15.7	99	5290@38
94028559	17.5/65-20	E/10	31	TL	14.0	42.9	17.7	141	7040@36

REAR FARM R-4

BKT TR-459

- Designed for drive wheel on industrial tractors
- Wide lugs and extensive lug overlapping at center provide resistance to buckling, tearing and cracking
- Special compound and durable casing provide long life



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94016457	14.9-24	F/12	33	TL	13.0	49.0	15.4	139	6400@42
94016495	16.9-24	F/12	35	TL	15.0	51.6	17.3	179	7150@38
94016617	18.4-24	F/12	36	TL	16.0	54.1	18.6	211	8550@36
94016662	19.5L-24	E/10	35	TL	16.0	52.2	19.3	200	6800@25
94016686	19.5L-24	F/12	35	TL	16.0	52.2	19.3	203	7600@34
94016709	21L-24	F/12	36	TL	18.0	54.3	21.0	245	8550@32
94016556	16.9-28	F/12	35	TL	15.0	55.5	17.3	202	7850@38
94016648	18.4-28	F/12	37	TL	16.0	58.1	18.6	239	9100@36

TRACTION IMPLEMENT I-3

HARVEST KING POWER LUG 4WD II

- Modern tread design provides outstanding performance
- Wide, sturdy overlapping lugs for long wear and good traction
- Strong nylon plies for strength and durability on 4WD backhoes
- Designed for 4WD backhoes and rough terrain forklifts



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
DS5013*	10.5/80-18	E/10	27	TL	9.0	34.8	10.8	60	4299@53
PLW44	12.5/80-18	F/12	27	TL	9.0	38.0	12.1	88	5840@53

* Branded D303

TRACTION IMPLEMENT I-3

BKT AT-603

- Excellent traction for drive wheels
- Designed for backhoe loaders, compact loaders and dumpers
- Engineered to provide the best performance on and off the road



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94019526	10.5/80-18	E/10	27	TL	9.0	35.7	10.8	68	4300@54
94019595	12.5/80-18	F/12	35	TL	9.0	38.9	12.1	91	5840@54

TRACTION IMPLEMENT I-3

BKT AS-504

- Excellent traction for drive wheels
- Straight lugs provide grip with even, steady pull
- Designed for implement, industrial and construction applications
- On and off-the-road use in all weather conditions



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94019151	5.00-15	C/6	20	TT	3.5	25.9	5.5	13	1230@51
94019168	6.00-16	C/6	22	TT	4.0	28.9	6.5	20	1520@41
94019373	7.50-20	D/8	27	TT	5.5	35.6	8.2	35	2760@46

FRONT FARM F-2M

HARVEST KING FRONT FARM 4R

- Excellent flotation and mobility from 4-rib design
- Excellent roadability
- Self-cleaning tread for superior traction
- Tubeless construction



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
HK4R31	9.5L-15	D/8	25	TL	7.0	30.8	9.5	35	1870@48
HK4R33	11L-15	D/8	25	TL	8.0	32.0	11.0	43	2090@44
HK4R51	10.00-16	D/8	27	TL	8.0	35.2	10.8	50	2340@44
HK4R55	11.00-16	D/8	30	TL	10.0	38.1	12.4	64	2600@40
HK4R84	14L-16.1	F/12	35	TL	11.0	38.8	14.0	78	3860@52

FRONT FARM F-2M

BKT PRO RIB

- Specifically designed for front fitment on tractors working on hard surfaces
- Steers easily and offers excellent load distribution and flotation
- Excellent scuff resistance



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94020492	9.5L-15	D/8	22	TL	7.0	30.7	9.4	41	1870@48
94020461	11L-15	D/8	26	TL	8.0	31.3	11.0	50	2090@44
94020447	10.00-16	D/8	26	TT	8.0	34.6	11.0	48	2340@44
94020454	11.00-16	D/8	30	TT	10.0	37.4	13.2	64	2600@40
94020485	14L-16.1	F/12	33	TL	11.0	38.6	14.0	105	3860@52

FRONT FARM F-2

HARVEST KING FRONT TRACTOR

- Nylon cord and tube type construction
- Wide selection of sizes and ply ratings for market coverage
- 3-rib design for improved steering and good flotation
- Center and shoulder ribs provide even load distribution and wear



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
FRT18	4.00-12	B/4	8	TT	3.0	21.2	4.4	8	495@52
FRT415A	4.00-15	B/4	15	TT	3.0	24.1	4.4	11	585@52
FRT22	5.00-15	B/4	21	TT	3.0	26.1	5.1	14	715@44
FRT7515A	7.5L-15	C/6	19	TT	6.0	29.4	8.2	24	1430@44
FRT9515A	9.5L-15	D/8	32	TL	7.0	29.4	9.5	32	1870@48
FRT1115A	11L-15	D/8	35	TT	8.0	32.0	11.0	48	2090@44
FRT39	5.50-16	C/6	18	TT	4.0	28.1	5.9	19	1050@56
FRT41	6.00-16	C/6	25	TT	4.0	29.1	6.3	21	1140@52
FRT42	6.50-16	C/6	25	TT	4.5	30.0	6.8	27	1230@48
FRT48	7.50-16	D/8	30	TT	5.5	31.8	8.0	35	1710@56
FRT53	10.00-16	E/10	34	TT	8.0	35.2	10.8	53	3000@50
FRT56	11.00-16	E/10	38	TT	10.0	38.1	12.4	71	3305@45
FRT72	7.50-18	D/8	24	TT	5.5	33.8	8.0	41	1870@56
FRT80	4.00-19	B/4	13	TT	3.0	28.2	4.4	14	715@52

FRONT FARM F-2

BKT TF-9090

- 3-rib front tire designed for easy steering
- Wide center and shoulder ribs
- Increased resistance toward stubble damage
- Tube type, nylon cord body



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94020843	5.00-15	B/4	14	TT	4.0	25.8	5.5	14	715@44
94020874	5.50-16	C/6	17	TT	4.0	28.0	5.9	19	1050@56
94020928	6.00-16	C/6	23	TT	4.5	28.9	6.7	20	1140@52
94021024	6.50-16	C/6	23	TT	4.5	30.1	7.1	24	1230@48
94021123	7.50-16	D/8	26	TT	5.5	31.9	8.1	35	1710@56
94020720	10.00-16	D/8	35	TT	8.0	35.4	10.8	54	2340@44
94020775	11.00-16	D/8	37	TT	10.0	38.2	12.6	71	2600@40
94020805	4.00-19	B/4	14	TT	3.0	28.1	4.5	13	715@52
94021260	7.50-20	D/8	26	TT	5.5	36.0	8.1	41	2040@56

INDUSTRIAL FRONT F-3

HARVEST KING PREMIUM BACKHOE F-3

- Tubeless nylon cord body
- Multi-rib design for improved handling and roadability
- Large footprint and deep grooves for long, even wear
- Designed for backhoes, forklifts and mowing equipment



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
HBH33	11L-15	E/10	16	TL	8.0	31.0	10.5	44	2340@52
HBH56	11L-16	E/10	16	TL	8.0	31.2	10.4	43	2470@52
HBH57	11L-16	F/12	16	TL	8.0	31.2	10.4	43	2760@64

INDUSTRIAL FRONT F-3

BKT RIB-F3

- Highway tread designed for agricultural and industrial applications
- Multi-rib design for improved handling and road-ability
- Tubeless nylon cord body
- Designed for backhoes, agricultural implements and trailers



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TYPIE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94000111	11L-15	E/10	16	TL	8.0	32.0	11.0	51	2340@52
94000142	11L-16	E/10	16	TL	8.0	32.7	11.0	53	2470@52
94000173	11L-16	F/12	16	TL	8.0	32.7	11.0	54	2760@64

IMPLEMENT I - 1

HARVEST KING RIB IMPLEMENT

- Wide tread for good flotation, tracking and steering
- Extra-wide shoulder ribs for long service life
- Tube type and tubeless sizes available
- Nylon cord construction



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TYPIE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (30 MPH)
HKT18	9.5L-14	D/8	8	TT	8.0	29.0	9.5	29	2400@44
HKT19	11L-14	C/6	11	TT	8.0	29.6	11.0	33	2040@28
HKT20	11L-14	D/8	11	TT	8.0	29.6	11.0	33	2470@36
HKT23	5.90-15	B/4	7	TT	4.5	26.2	6.1	17	1140@36
HKT24	6.70-15	C/6	7	TT	4.5	27.7	6.7	20	1610@44
HKT44	7.60-15	D/8	8	TT	5.5	28.9	7.6	25	2090@52
HKT31	9.5L-15	D/8	11	TT	7.0	30.1	9.5	30	2470@44
HKT33	11L-15	D/8	11	TT	8.0	30.5	11.0	34	2540@36
HKT68	12.5L-15	F/12	11	TT	10.0	32.1	12.2	43	3860@52
HKT37	11L-16	D/8	11	TT	8.0	31.3	10.8	35	2680@36
HKL44	7.60-15	D/8	8	TL	5.5	28.9	7.6	25	2090@52
HKL31	9.5L-15	D/8	11	TL	7.0	30.1	9.5	30	2470@44
HKL33	11L-15	D/8	11	TL	8.0	30.5	11.0	34	2540@36
HKL36	11L-15	F/12	11	TL	8.0	30.5	11.0	35	3200@52
HKL68	12.5L-15	F/12	11	TL	10.0	32.1	12.2	43	3860@52
HKL70	31x13.50-15	E/10	12	TL	10.0	30.8	13.8	60	3080@60
HKL73	12.5L-16	F/12	11	TL	10.0	33.4	12.5	43	3970@52
HKL84	14L-16.1	D/8	12	TL	11.0	37.0	14.0	72	3860@32
HKL80	16.5L-16.1	E/10	13	TL	14.0	40.3	16.5	87	5680@40

IMPLEMENT I - 1

BKT IMPLEMENT I-1

- Designed for high flotation, high capacity at low PSIs
- Suitable for on and off-the-road service
- Nylon cord construction



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (40 MPH)
94006113	9.5L-14	D/8	9	TT	7.0	28.9	9.4	26	2400@44
94006083	6.70-15	C/6	7	TT	4.5	28.0	6.8	17	1610@44
94006144	9.5L-15	D/8	9	TT	7.0	30.1	9.5	29	2470@44
94005864	11L-15	D/8	10	TT	8.0	30.3	10.6	31	2540@36
94006106	9.00-16	E/10	9	TT	6.0	33.3	9.2	39	3300@52
94005925	11L-16	D/8	10	TT	8.0	31.3	10.6	32	2680@36
94006151	9.5L-15	D/8	9	TL	7.0	30.1	9.5	31	2470@44
94006175	9.5L-15	F/12	9	TL	7.0	30.1	9.5	34	3200@64
94005871	11L-15	D/8	10	TL	8.0	30.3	10.6	34	2540@36
94005901	11L-15	E/10	10	TL	8.0	30.3	10.6	36	2910@44
94026197	11L-15	F/12	10	TL	8.0	30.3	10.6	36	3200@52
94006038	12.5L-15	F/12	11	TL	10.0	32.3	12.2	47	3860@52
94031337	16.5L-16.1	E/10	14	TL	14.0	40.4	17.1	108	5200@36

INTERMITTENT HIGHWAY SERVICE FI

HARVEST KING FIELD PRO HIGHWAY SERVICE FI

- Designed for use on farm implements transported intermittently at highway speeds; DOT-rated for highway use
- Extra-wide shoulder ribs for long service life
- Superior load capacity over comparable I-1 tires at field speeds
- Tubeless construction



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (60 MPH)
HSL9515A	9.5L-15	E/10	12	TL	7.0	30.2	9.5	40	3080@75
HSL1115A	11L-15	F/12	12	TL	8.0	30.6	11.0	54	3960@90
HSL1215A	12.5L-15	F/12	12	TL	10.0	32.4	12.5	61	4680@90

SPECIALTY IMPLEMENT & TRAILER

BKT AW-702

- Designed for heavy-duty service in free-rolling applications
- Special cut and chip resistant compound
- Superior durability



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94009633	12.5/80-18	F/12	14	TL	9.0	38.0	12.1	68	5840@54

FLOTATION HF-2

BKT FLOTATION 558/648

- Specially designed for high load capacities at low PSIs
- Minimizes soil compaction and crop damage
- Ideally suited for heavy implements, balers and trailer uses both on and off-the-road



ARTICLE NO.	SIZE	LR/PR	TREAD DEPTH (32NDS)	TTYPE	RIM WIDTH (INCH)	O.D. (INCH)	S.W (INCH)	WGT	SINGLE MAX. LOAD @ PSI (25 MPH)
94006403	600/50-22.5	H/16	33	TL	20.0	46.1	23.6	214	11350@38
94006489	700/40-22.5	H/16	33	TL	24.0	46.1	27.6	245	11680@32
94025596	700/50-22.5	H/16	33	TL	24.0	50.0	27.6	284	14770@35

HARVEST KING®

HARDWORKING, JUST LIKE YOU

harvestkingtires.com • tbcbrands.com • treadxpress.com • 1-866-822-4968

TBCBrands
4300 TBC Way, Palm Beach Gardens, FL 33410