

FULL LINE PRODUCT CATALOG



Hercules is widely recognized as the industry's premier value brand. Since 1952, independent tire dealers and distributors have trusted Hercules to deliver outstanding quality, a comprehensive line of passenger, light truck and commercial products, and industry leading warranty coverage. And with exceptional fill rates, high profit potential, and first rate service and support, Hercules is helping many dealers move their businesses to the next level.

Exceptional Tires. Extraordinary Value.



PERFORMANCE	
Raptis R-T5	4-5
H/P 4000	6-7
TOURING	
Roadtour 855 SPE.....	8-9
Roadtour 655	10-11
Tour 4.0 plus.....	12-13
MRX Plus IV	14-15
MRX Plus V.....	16-17
SUV/LIGHT TRUCK	
SUV/CROSSOVER	
Roadtour XUV	18-19
HIGHWAY	
Terra Trac Cross-V	20-21
Terra Trac HTS.....	22-23
ON/OFF ROAD ALL TERRAIN	
Terra Trac AT II	24-27
OFF ROAD TRACTION	
Trail Digger M/T.....	28-29
COMMERCIAL TRACTION	
Terra Trac D/T.....	30-31
Terra Trac Radial Rib	32
SPECIAL APPLICATIONS	
Bias Trailer LPT • Power STR Radial Trailer	33
WINTER	
Avalanche R G2.....	34-35
Avalanche X-Treme Passenger.....	36-37
Avalanche X-Treme SUV.....	38
Avalanche X-Treme LT.....	37
MEDIUM TRUCK	
H-804 • H-801	39
H-502 • H-309	41
H-902 • H-601	42
H-901 • H-704	43
H-903 • H-933	44
H-702 • H-703.....	45
H-803 • H-402	46
H-301 • H-307	47
H-302	48
WARRANTY	
Limited Warranty	49-52
Hercules Brand Medium Truck Warranty	53
Hercules Brand Casing Warranty	54
Buffing Guidelines.....	55
POP	
POP Materials	56
Notes	57

Tire sizes, data specifications and product availability change frequently. While every effort has been made to verify the accuracy of this information, it should be considered as approximate and subject to change. Please check with your sales representative for the most recent updates.



FEATURES AND BENEFITS

- High-grade silica tread compound and Hercules EvacuTrack™ grooves create better wet traction.
- 3D UltraWave™ siping and an asymmetric tread design deliver greater control and tighter handling.
- CoolCourse™ temperature control system optimizes performance and enhances tire life.
- 500 AA A UTQG – the highest traction grading possible.

The Hercules Raptis R-T5 - made to move.

With top-tier technologies, innovative design and advanced materials, the bold new Hercules® Raptis® R-T5 all-season UHP tire is changing the very landscape of performance tires. Marrying the year-round versatility of premium touring tires with the confident control of ultra high performance tires, the Raptis R-T5 delivers the traction, control and longer wear today's performance cars and high-end sport sedans demand.

The Raptis R-T5 features a 45,000 mile/75,000 km mileage warranty that includes road hazard protection and the exclusive 30-day "Trust Our Ride" test drive. Mileage warranty and road hazard are valid in the U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules Raptis® R-T5
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
W-Speed Rated											
91406	215/55ZR17 XL 98W	XL	BSW	500 AA A	7.0	1653	50	26.30	8.90	9.5	24.9
91407	225/55ZR17 XL 101W	XL	BSW	500 AA A	7.0	1819	50	26.80	9.17	9.5	27.1
91409	235/55ZR17 99W	STD	BSW	500 AA A	7.5	1709	51	27.20	9.65	9.5	28.3
91410	205/50ZR17 XL 93W	XL	BSW	500 AA A	6.5	1433	50	25.10	8.43	9.5	23.1
91411	215/50ZR17 XL 95W	XL	BSW	500 AA A	7.0	1521	50	25.50	8.90	9.5	24.4
91412	225/50ZR17 XL 98W	XL	BSW	500 AA A	7.0	1653	50	25.90	9.17	9.5	25.6
91413	235/50ZR17 XL 100W	XL	BSW	500 AA A	7.5	1764	50	26.30	9.65	9.5	27.3
91414	215/45ZR17 XL 91W	XL	BSW	500 AA A	7.0	1356	50	24.60	8.39	9.5	22.4
91415	225/45ZR17 XL 94W	XL	BSW	500 AA A	7.5	1477	50	25.00	8.86	9.5	24.3
91416	235/45ZR17 XL 97W	XL	BSW	500 AA A	8.0	1609	50	25.40	9.29	9.5	25.1
91417	245/45ZR17 XL 99W	XL	BSW	500 AA A	8.0	1709	50	25.70	9.57	9.5	26.8
91418	205/40ZR17 XL 84W	XL	BSW	500 AA A	7.5	1102	50	23.50	8.35	9.5	19.8
91419	245/40ZR17 XL 95W	XL	BSW	500 AA A	8.5	1521	50	24.70	9.76	9.5	24.9
91420	255/40ZR17 XL 98W	XL	BSW	500 AA A	9.0	1653	50	25.00	10.24	9.5	26.7
91408	235/55ZR18 XL 104W	XL	BSW	500 AA A	7.5	1984	50	28.10	9.65	9.5	29.7
91421	225/50ZR18 95W	STD	BSW	500 AA A	7.0	1521	51	26.90	9.17	9.5	26.8
91422	235/50ZR18 XL 101W	XL	BSW	500 AA A	7.5	1819	50	27.30	9.65	9.5	29.0
91423	215/45ZR18 XL 93W	XL	BSW	500 AA A	7.0	1433	50	25.60	8.39	9.5	23.8
91424	225/45ZR18 XL 95W	XL	BSW	500 AA A	7.5	1521	50	25.90	8.86	9.5	24.9
91425	235/45ZR18 XL 98W	XL	BSW	500 AA A	8.0	1653	50	26.30	9.29	9.5	26.5
91426	245/45ZR18 XL 100W	XL	BSW	500 AA A	8.0	1764	50	26.70	9.57	9.5	28.4
91427	255/45ZR18 XL 103W	XL	BSW	500 AA A	8.5	1929	50	27.00	10.04	9.5	29.5
91428	225/40ZR18 XL 92W	XL	BSW	500 AA A	8.0	1389	50	25.10	9.06	9.5	23.6
91429	235/40ZR18 XL 95W	XL	BSW	500 AA A	8.5	1521	50	25.40	9.49	9.5	25.0
91430	245/40ZR18 XL 97W	XL	BSW	500 AA A	8.5	1609	50	25.70	9.76	9.5	26.3
91431	255/35ZR18 90W	STD	BSW	500 AA A	9.0	1323	51	25.00	10.24	9.5	25.9
91432	225/45ZR19 XL 96W	XL	BSW	500 AA A	7.5	1565	50	27.00	8.86	9.5	26.1
91433	245/45ZR19 98W	STD	BSW	500 AA A	8.0	1653	51	27.70	9.57	9.5	29.1
91434	245/40ZR19 94W	STD	BSW	500 AA A	8.5	1477	51	26.70	9.76	9.5	27.5
91435	255/40ZR19 XL 100W	XL	BSW	500 AA A	9.0	1764	50	27.00	10.24	9.5	28.6
91436	235/35ZR19 XL 91W	XL	BSW	500 AA A	8.5	1356	50	25.50	9.49	9.5	24.2
91437	245/35ZR19 XL 93W	XL	BSW	500 AA A	8.5	1433	50	25.80	9.76	9.5	25.8
91438	255/35ZR19 XL 96W	XL	BSW	500 AA A	9.0	1565	50	26.00	10.24	9.5	26.8
91439	245/45ZR20 XL 103W	XL	BSW	500 AA A	8.0	1929	50	28.70	9.57	9.5	30.0
91440	255/45ZR20 101W	STD	BSW	500 AA A	8.5	1819	51	29.10	10.04	9.5	32.6
91441	245/40ZR20 XL 99W	XL	BSW	500 AA A	8.5	1709	50	27.70	9.76	9.5	28.9
91442	255/35ZR20 XL 97W	XL	BSW	500 AA A	9.0	1609	50	27.00	10.24	9.5	28.2
91443	275/35ZR20 XL 102W	XL	BSW	500 AA A	9.5	1874	50	27.60	10.94	9.5	30.7



FEATURES AND BENEFITS

- Performance enhanced tread design for cutting-edge traction in all conditions.
- Raised white lettering.
- Looks as good as it performs.

The Hercules H/P 4000 – the classic.

Developed for dependable performance, the H/P 4000 demonstrates our dedication to producing high quality, affordable performance tires. Available with a smooth raised white lettered sidewall in all the right sizes for your vintage and/or modern muscle car. Large multi-siped tread blocks taper into a rounded shoulder to provide sure-footed traction under all conditions. A wide solid center rib helps to deliver straight line stability at higher speeds as well as ensuring constant rubber to road contact. Put us to the test and stand out in the crowd with the H/P 4000.

The H/P 4000 features a limited 40,000 mile/ 65,000 km mileage warranty that includes road hazard protection. Mileage warranty and road hazard are valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules H/P 4000
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
T, S-Speed Rated											
02824	P215/70R14 96T	STD	RWL	440 A B	6.5	1554	44	25.76	8.66	10.5	22.0
02826	P225/70R14 98T	STD	RWL	440 A B	6.5	1675	44	26.27	8.92	10.5	24.0
02808	P185/60R14 82T	STD	BSW	440 A B	5.5	1047	44	22.80	7.15	10.5	16.0
02782	P235/60R14 96T	STD	RWL	440 A B	7.0	1565	44	25.06	9.11	10.5	23.0
02828	P215/70R15 97T	STD	RWL	440 A B	6.5	1620	44	26.71	8.71	10.5	23.0
02830	P225/70R15 100T	STD	RWL	440 A B	6.5	1753	44	27.37	9.10	10.5	26.0
02832	P235/70R15 102T	STD	RWL	440 A B	7.0	1896	44	27.90	9.46	10.5	27.0
02834	P255/70R15 108T	STD	RWL	440 A B	7.5	2183	44	28.95	10.40	10.5	32.0
02798	P215/65R15 95T	STD	RWL	440 A B	6.5	1510	44	26.00	8.38	10.5	23.0
02790	P235/60R15 98T	STD	RWL	440 A B	7.0	1642	44	26.11	9.15	10.5	25.0
02792	P245/60R15 100T	STD	RWL	440 A B	7.0	1753	44	26.55	9.47	10.5	26.0
02794	P255/60R15 102T	STD	RWL	440 A B	7.5	1885	44	27.01	10.24	10.5	28.0
02796	P275/60R15 107T	STD	RWL	440 A B	8.0	2149	44	28.06	10.70	10.5	30.0
02770	P295/50R15 105S	STD	RWL	440 A C	9.5	2061	35	26.80	12.22	10.5	32.0
02806	P235/55R16 96T	STD	BSW	440 A B	7.5	1565	44	26.15	9.65	10.5	24.0

FEATURES AND BENEFITS

- Full-depth siping ensures consistent, lasting traction for the life of the tire.
- Solid shoulder with offset grooves promotes greater stability when cornering and reduces road surface noise for a quiet, comfortable ride.
- 3D siping facilitates greater contact with the road and increases the amount of biting edges for improved grip on wet roads and in light snow.
- Advanced silica tread compound provides even wear, low-rolling resistance and enhanced wet traction.
- Asymmetric tread pattern incorporates larger blocks on the outside of the tire for stability and dry traction, and smaller inside elements with dense siping for added traction.
- Semi-solid center rib promotes crisp handling and driver comfort while maintaining traction and water evacuation.



Hercules® Roadtour® 855 SPE
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
V, H, T-Speed Rated											
06010	195/65R15 91H	STD	BSW	620 A A	6.0	1356	44	25.00	7.90	11.0	20.0
06145	205/65R15 94H	STD	BSW	620 A A	6.0	1477	44	25.47	8.20	11.0	22.0
06015	195/60R15 88H	STD	BSW	620 A A	6.0	1235	44	24.21	7.90	11.0	20.5
06135	205/65R16 95H	STD	BSW	620 A A	6.0	1521	44	26.46	8.20	11.0	21.7
06155	215/65R16 98H	STD	BSW	620 A A	6.5	1653	44	27.01	8.70	11.5	24.6
06085	225/65R16 100T	STD	BSW	780 A A	6.5	1764	44	27.48	9.00	11.5	27.9
06120	205/60R16 92V	STD	BSW	580 A A	6.0	1389	44	25.67	8.20	11.0	22.7
06025	215/60R16 95H	STD	BSW	620 A A	6.5	1521	44	26.14	8.70	11.0	24.9
06030	225/60R16 98H	STD	BSW	620 A A	6.5	1653	44	26.61	9.00	11.0	24.9
06090	235/60R16 100T	STD	BSW	780 A A	7.0	1764	44	27.09	9.40	11.0	27.0
06075	205/55R16 91V	STD	BSW	580 A A	6.5	1356	44	24.88	8.40	11.0	22.0
06020	215/55R16 93H	STD	BSW	620 A A	7.0	1433	44	25.28	8.90	11.0	23.4
06080	225/55R16 95V	STD	BSW	580 A A	7.0	1521	44	25.75	9.20	11.0	24.9
06110	215/65R17 99T	STD	BSW	780 A A	6.5	1709	44	28.03	8.70	11.5	26.6
06115	225/65R17 102T	STD	BSW	780 A A	6.5	1874	44	28.50	9.00	11.5	27.5
06095	235/65R17 104T	STD	BSW	780 A A	7.0	1984	44	29.06	9.40	11.5	28.8
06150	215/60R17 96H	STD	BSW	620 A A	6.5	1565	44	27.17	8.70	11.0	25.9
06160	225/60R17 99H	STD	BSW	620 A A	6.5	1709	44	27.64	9.00	11.0	28.9
06105	235/60R17 102T	STD	BSW	780 A A	7.0	1874	44	28.11	9.40	11.0	28.1
06055	215/55R17 94V	STD	BSW	580 A A	7.0	1477	44	26.30	8.90	11.0	25.1
06060	225/55R17 97V	STD	BSW	580 A A	7.0	1609	44	26.77	9.20	11.0	26.9
06065	235/55R17 99H	STD	BSW	620 A A	7.5	1709	44	27.17	9.60	11.0	29.9
06165	205/50R17 93V	XL	BSW	580 A A	6.5	1433	50	25.12	8.40	11.0	24.3
06170	215/50R17 95V	XL	BSW	580 A A	7.0	1521	50	25.51	8.90	11.0	25.9
06045	225/50R17 94V	STD	BSW	580 A A	7.0	1477	44	25.91	9.20	11.0	25.3
06050	235/50R17 96V	STD	BSW	580 A A	7.5	1565	44	26.30	9.60	11.0	27.9
06140	245/50R17 99V	STD	BSW	580 A A	7.5	1709	44	26.69	10.00	11.0	29.9
06040	225/60R18 100H	STD	BSW	620 A A	6.5	1764	44	28.62	9.00	11.0	27.9
06130	215/55R18 95H	STD	BSW	620 A A	7.0	1521	44	27.28	8.90	11.0	27.9
06035	225/55R18 98H	STD	BSW	620 A A	7.0	1653	44	27.76	9.20	11.0	26.9
06180	235/55R18 104V	XL	BSW	580 A A	7.5	1984	50	28.15	9.60	11.0	31.7
06100	225/50R18 95T	STD	BSW	780 A A	7.0	1521	44	26.89	9.20	11.0	26.4
06070	235/50R18 97V	STD	BSW	580 A A	7.5	1609	44	27.28	9.60	11.0	29.0
06185	225/45R18 95V	XL	BSW	580 A A	7.5	1521	50	25.94	8.90	11.0	27.4
06125	235/45R18 94V	STD	BSW	580 A A	8.0	1477	44	26.34	9.60	11.0	26.8
06175	245/45R18 100V	XL	BSW	580 A A	8.0	1764	50	26.65	9.60	11.0	27.9

Available in March 2016.

The Hercules Roadtour 855 SPE - luxury-touring.

Tires are extensions of your vehicle — key contributors to performance, security and appearance. You're looking for a high quality, great-looking tire that does more than simply get you from point A to point B; you need one that gets you there safely, comfortably, and quietly. The Hercules Roadtour 855 SPE is the perfect all-in-one solution, giving you the all-season traction, crisp handling, quiet ride and high mileage you're looking for — all at a great value.

The Roadtour 855 SPE features a limited 85,000 mile/135,000 km for T-rated, 70,000 mile/112,000 km for V/H-rated mileage warranty that includes road hazard protection and the exclusive 30 day "Trust Our Ride" test drive. Mileage warranty and road hazard are valid in U.S. and Canada only.

* ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD



FEATURES AND BENEFITS

- The most fuel efficient tire in the Hercules passenger lineup with LRR compounding (low rolling resistance).
- Computer optimized tread design greatly reduces road noise and vibrations.
- Touring tread design and siping result in superior all-season performance.
- Nylon overwrap added in the green tire aids in the stability and longevity of the Roadtour 655.
- Profile design and center rib result in crisp steering response and enhance overall road handling characteristics.



The Hercules Roadtour 655 – the intelligent choice.

With options ranging from 14"-17" and speed ratings of V, H and T, the Roadtour 655 has all the bases covered. The computer aided tread design emphasizes the most desirable tire characteristics of today: low rolling resistance tread compounding, noise and vibration suppression, all-season traction, enhanced handling qualities and longevity. The Hercules Roadtour 655 — your silent partner for safe, comfortable and effortless driving.

The Roadtour 655 features a limited 50,000 mile/80,000 km for V/H-rated, 60,000 mile/100,000 km for T-rated mileage warranty that includes road hazard protection and the exclusive 30 day "Trust Our Ride" test drive. Mileage warranty and road hazard are valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules Roadtour® 655
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
V, H, T, S-Speed Rated											
01105	185/70R14 88T	STD	BSW	540 A B	5.5	1235	44	24.23	7.40	10.0	18.1
01115	195/70R14 91T	STD	BSW	540 A B	6.0	1356	44	24.78	7.80	10.0	19.0
01125	175/65R14 82T	STD	BSW	540 A B	5.0	1047	44	22.95	6.85	10.0	16.0
01135	185/65R14 86T	STD	BSW	540 A B	5.5	1168	44	23.40	7.35	10.0	17.3
01133	235/75R15 109S	XL	WSW	540 A B	6.5	2271	50	28.85	9.40	11.0	29.0
01185	205/70R15 96T	STD	BSW	540 A B	6.0	1565	44	26.18	8.11	10.5	20.0
01123	205/70R15 96T	STD	WSW	540 A B	6.0	1565	44	26.18	8.11	10.5	20.0
01195	215/70R15 98T	STD	BSW	540 A B	6.5	1653	44	26.68	8.58	10.5	21.0
01127	215/70R15 98T	STD	WSW	540 A B	6.5	1653	44	26.68	8.58	10.5	22.0
01145	185/65R15 88T	STD	BSW	540 A B	5.5	1235	44	24.40	7.35	10.0	18.6
01110	195/65R15 91H	STD	BSW	440 A A	6.0	1356	44	24.96	8.09	10.5	20.0
01155	195/65R15 91T	STD	BSW	540 A B	6.0	1356	44	24.80	7.80	10.0	20.0
01120	205/65R15 94H	STD	BSW	440 A A	6.0	1477	44	25.40	8.42	10.5	22.0
01165	205/65R15 94T	STD	BSW	540 A B	6.0	1477	44	25.26	8.16	10.5	20.0
01175	215/65R15 96T	STD	BSW	540 A B	6.5	1565	44	25.81	8.65	10.5	23.0
01131	185/60R15 84T	STD	BSW	540 A B	5.5	1102	44	23.59	7.18	10.0	18.0
01130	195/60R15 88H	STD	BSW	440 A A	6.0	1235	44	24.16	8.10	10.5	19.0
01140	205/60R15 91H	STD	BSW	440 A A	6.0	1356	44	24.64	8.40	10.5	21.0
01129	205/65R16 95H	STD	BSW	440 A A	6.0	1521	44	26.46	8.20	9.5	22.0
01113	215/65R16 98T	STD	BSW	540 A B	6.5	1653	44	26.81	8.65	10.5	24.0
01141	225/65R16 100T	STD	BSW	540 A B	6.5	1764	44	25.63	9.00	9.5	23.0
01122	205/60R16 92V	STD	BSW	440 A A	6.0	1389	44	25.65	8.22	10.5	24.2
01128	215/60R16 95V	STD	BSW	440 A A	6.5	1521	44	26.11	8.82	10.5	26.0
01117	215/60R16 95T	STD	BSW	540 A B	6.5	1521	44	25.93	8.55	10.5	24.0
01150	225/60R16 98H	STD	BSW	440 A A	6.5	1653	44	26.55	9.11	10.5	25.4
01119	225/60R16 98T	STD	BSW	540 A B	6.5	1653	44	26.50	8.80	10.5	23.0
01142	195/55R16 87V	STD	BSW	440 A A	6.0	1201	44	24.41	7.90	9.5	19.0
01160	205/55R16 91H	STD	BSW	440 A A	6.5	1356	44	24.85	8.59	10.5	22.0
01121	205/55R16 91T	STD	BSW	540 A B	6.5	1356	44	24.64	8.30	10.0	21.0
01170	215/55R16 93H	STD	BSW	440 A A	7.0	1433	44	25.24	8.92	10.5	23.0
01114	225/55R16 95H	STD	BSW	440 A A	7.0	1521	44	25.76	8.88	10.5	26.0
01164	215/65R17 99T	STD	BSW	540 A B	6.5	1709	44	27.82	8.70	11.0	26.0
01162	215/60R17 96T	STD	BSW	540 A B	6.5	1565	44	26.94	8.73	11.0	26.0
01132	225/60R17 99T	STD	BSW	540 A B	6.5	1709	44	27.38	8.81	10.5	25.0
01126	215/55R17 94V	STD	BSW	440 A A	7.0	1356	44	26.25	8.75	10.5	27.5
01178	225/55R17 97T	STD	BSW	540 A B	7.0	1609	44	26.79	9.31	11.0	26.0
01124	215/50R17 95V	XL	BSW	440 A A	7.0	1521	50	25.46	8.72	10.5	25.0
01118	225/50R17 94V	STD	BSW	440 A A	7.0	1477	44	25.83	8.99	10.5	27.2

FEATURES AND BENEFITS

- Silica-enhanced compound provides superior traction in wet conditions without tread life reduction.
- Criss-cross grooves create biting edges to deliver wet and light snow traction.
- Provides all-season capability on wet, dry and light snow.
- Cross-block siping delivers crisp handling in inclement weather for 4.0 seasons of superior handling.
- Nylon overwrap enhances construction by adding uniformity and increasing ride stability.
- High void to tread ratio with groove curvature improves water evacuation for outstanding wet handling.



Hercules Tour 4.0[®] plus
M+S Rated

The Hercules Tour 4.0 plus – style and performance for all.

Welcome to the stylish Tour 4.0 plus, a versatile, all-season tire designed to take on anything Mother Nature might put forth. The sleek asymmetric tread combines large, solid outer shoulder blocks and two wide channels for stable handling while the inner tread design incorporates deep water channels and extra siping for excellent traction in inclement weather conditions. Performance tire look with all-season capabilities makes the Tour 4.0 plus an attractive choice for your vehicle.

The Tour 4.0 plus features a limited 55,000 mile/90,000 km mileage warranty that includes road hazard protection and the exclusive 30 day “Trust Our Ride” test drive. Mileage warranty and road hazard are valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
V, H, T-Speed Rated											
84660	175/70R13 82T	STD	BSW	620 A A	5.0	1047	44	22.60	7.09	10.0	15.0
84675	195/75R14 92T	STD	BSW	620 A A	5.5	1390	44	25.51	7.72	10.0	19.3
84676	205/75R14 95T	STD	BSW	620 A A	5.5	1521	44	26.14	7.99	10.0	20.7
84661	185/70R14 88H	STD	BSW	520 A A	5.5	1234	44	24.25	7.44	10.0	18.7
84662	195/70R14 91T	STD	BSW	620 A A	6.0	1356	44	24.72	8.03	10.0	22.0
84665	175/65R14 82H	STD	BSW	520 A A	5.0	1047	44	22.99	6.97	10.0	15.9
84666	185/65R14 86H	STD	BSW	520 A A	5.5	1168	44	23.47	7.44	10.0	18.1
84677	205/75R15 97T	STD	BSW	620 A A	5.5	1610	44	27.13	7.99	10.0	23.0
84678	215/75R15 100T	STD	BSW	620 A A	6.0	1765	44	27.68	8.50	10.0	25.5
84659	235/75R15 105T	STD	BSW	620 A A	6.5	2040	44	28.82	9.21	11.0	28.0
84663	205/70R15 96H	STD	BSW	520 A A	6.0	1565	44	26.34	8.23	10.0	25.4
84664	215/70R15 98H	STD	BSW	520 A A	6.5	1653	44	26.89	8.70	10.0	27.8
84667	185/65R15 88H	STD	BSW	520 A A	5.5	1234	44	24.45	7.44	10.0	19.2
84668	195/65R15 91H	STD	BSW	520 A A	6.0	1355	44	25.00	7.91	10.0	22.3
84669	205/65R15 94H	STD	BSW	520 A A	6.0	1477	44	25.47	8.23	10.0	23.1
84680	215/65R15 96H	STD	BSW	520 A A	6.5	1565	44	26.02	8.70	10.0	22.0
84682	185/60R15 84H	STD	BSW	520 A A	5.5	1100	44	23.74	7.44	10.0	18.1
84673	195/60R15 88H	STD	BSW	520 A A	6.0	1230	44	24.17	8.07	10.0	18.5
84683	205/60R15 91H	STD	BSW	520 A A	6.0	1356	44	24.69	8.23	10.0	21.6
84684	215/60R15 94H	STD	BSW	520 A A	6.5	1477	44	25.16	8.70	10.0	22.7
84679	215/70R16 100T	STD	BSW	620 A A	6.5	1765	44	27.87	8.70	10.0	28.0
84672	215/65R16 98T	STD	BSW	620 A A	6.5	1655	44	26.93	8.94	10.0	24.0
84681	235/65R16 103H	STD	BSW	520 A A	7.0	1930	44	28.03	9.45	10.0	27.0
84686	205/60R16 92T	STD	BSW	620 A A	6.0	1390	44	25.67	8.23	10.0	21.6
84670	215/60R16 95H	STD	BSW	520 A A	6.5	1521	44	26.14	8.70	10.0	24.9
84671	225/60R16 98H	STD	BSW	520 A A	6.5	1653	44	26.61	8.98	10.0	26.0
84674	205/55R16 91H	STD	BSW	520 A A	6.5	1356	44	24.80	8.66	10.0	23.0
84691	235/65R17 104T	STD	BSW	620 A A	7.0	1985	44	29.06	9.45	11.0	31.4
84685	225/60R17 99H	STD	BSW	520 A A	6.5	1710	44	27.64	8.98	10.0	22.0
84689	215/55R17 94H	STD	BSW	520 A A	7.0	1480	44	26.30	8.90	10.0	25.6
84690	225/55R17 97V	STD	BSW	520 A A	7.0	1610	44	26.77	9.17	10.0	27.1
91504	235/55R17 99H	STD	BSW	520 A A	7.5	1710	44	27.16	9.65	10.5	30.7
84687	215/50R17 XL 95V	XL	BSW	520 A A	7.0	1520	50	25.51	8.90	10.0	24.4
84688	225/50R17 94V	STD	BSW	520 A A	7.0	1480	44	25.91	9.17	10.0	25.6
84693	225/60R18 100H	STD	BSW	520 A A	6.5	1765	44	28.62	8.98	10.0	28.8
84692	235/55R18 100H	STD	BSW	520 A A	7.5	1765	44	28.15	9.65	11.0	29.7
91503	235/50R18 97V	STD	BSW	520 A A	7.5	1610	44	27.28	9.65	10.5	29.7
84694	255/45R19 100V	STD	BSW	520 A A	8.5	1765	44	28.07	10.04	10.0	32.0



FEATURES AND BENEFITS

- Two full-width belts stabilize tread for control and even wear.
- Tread elements form an effective tread pattern of distinct gripping edges for year-round traction.
- Slotted shoulders and wide grooves provide all-season traction and hydroplaning resistance.
- Variable pitch tread design for a quiet ride.



The Hercules MRX Plus IV – proven all-season performer.

With its simple yet effective 5-rib tread design, the MRX Plus IV provides five full rows of staggered biting blocks engineered to ensure flexibility and afford excellent traction. The variable pitch design helps to keep the ride smooth and minimize vibrations before they reach the interior of your vehicle. Available in a traditional white sidewall design in select sizes. An affordable, all-season tire that will impress with its effectiveness.

The MRX Plus IV features a limited 40,000 mile/ 65,000 km mileage warranty that includes road hazard protection. Mileage warranty and road hazard valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules MRX Plus IV M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
S-Speed Rated											
01652	P155/80R13 79S	STD	BSW	440 A B	4.5	959	44	22.75	6.10	9.5	13.8
01610	P175/70R13 82S	STD	BSW	440 A B	5.0	1036	35	22.68	6.89	10.0	16.0
04902	P185/75R14 89S	STD	BSW	440 A B	5.0	1290	44	24.80	7.20	10.0	17.0
04904	P195/75R14 92S	STD	BSW	440 A B	5.5	1400	44	25.40	7.60	10.0	19.8
04906	P205/75R14 95S	STD	BSW	440 A B	5.5	1532	35	25.95	7.95	10.5	21.3
01620	P175/70R14 84S	STD	BSW	440 A B	5.0	1102	35	23.18	6.89	10.0	16.3
01614	P185/70R14 87S	STD	BSW	440 A B	5.5	1201	35	24.23	7.40	10.0	18.1
01616	P195/70R14 90S	STD	BSW	440 A B	6.0	1312	35	24.78	7.80	10.0	20.0
01629	P215/70R14 96S	STD	BSW	440 A B	6.5	1554	44	25.78	8.58	10.0	20.0
01622	P175/65R14 81S	STD	BSW	440 A B	5.0	1019	35	22.90	6.85	10.0	16.0
01623	P185/65R14 85S	STD	BSW	440 A B	5.5	1124	35	23.40	7.35	10.0	17.3
01674	P205/75R15 97S	STD	WSW	440 A B	5.5	1598	35	26.98	8.03	10.5	20.0
01677	P215/75R15 100S	STD	WSW	440 A B	6.0	1742	35	27.55	8.40	10.5	22.0
04908	P225/75R15 102S	STD	BSW	440 A B	6.0	1874	44	28.05	8.70	10.5	22.0
01683	P235/75R15 105S	STD	WSW	440 A B	6.5	2028	35	28.65	9.10	11.0	25.0
01606	P205/70R15 95S	STD	WSW	440 A B	6.0	1499	35	26.28	8.10	10.0	20.0
01618	P205/70R15 95S	STD	BSW	440 A B	6.0	1499	35	26.28	8.11	10.0	20.0
01608	P215/70R15 97S	STD	WSW	440 A B	6.5	1620	35	26.78	8.58	10.0	22.0
01631	P225/70R15 100S	STD	BSW	440 A B	6.5	1753	35	27.28	8.85	10.0	22.0
01611	P195/65R15 89S	STD	BSW	440 A B	6.0	1279	35	24.90	7.80	10.0	19.0
01619	P205/65R15 92S	STD	BSW	440 A B	6.0	1400	35	25.25	8.26	10.0	20.0
01613	P215/65R15 95S	STD	BSW	440 A B	6.5	1510	35	25.88	8.65	10.0	22.0
01615	P215/60R16 94S	STD	BSW	440 A B	6.5	1477	35	25.99	8.55	10.0	22.0
01617	P225/60R16 97S	STD	BSW	440 A B	6.5	1609	35	26.52	8.80	10.0	24.0
01625	P205/55R16 89S	STD	BSW	440 A B	6.5	1279	35	24.75	8.30	10.0	21.0

FEATURES AND BENEFITS

- Two full-width belts stabilize tread for control and even wear.
- Unique center rib design provides cross slot for all-weather traction while maintaining on-center feel.
- Slotted shoulders and wide grooves provide all-season traction and hydroplaning resistance.
- Variable pitch tread design for a quiet ride.
- T-rated.



The Hercules MRX Plus V – an evolution of design.

The symmetric tread of the MRX Plus V incorporates cross-flowing sipes in its handsome 5-rib design to enhance road contact under all-season conditions, ensuring ultimate grip. The attractive sidewall treatment lends an original equipment appearance to your vehicle.

The MRX Plus IV features a limited 40,000 mile/65,000 km mileage warranty that includes road hazard protection. Mileage warranty and road hazard are valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules MRX Plus V
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
T-Speed Rated											
02163	185/65R15 88T	STD	BSW	440 A B	5.5	1235	44	24.35	7.35	10.0	18.6
02161	185/60R15 84T	STD	BSW	440 A B	5.5	1102	44	23.53	7.21	10.0	18.0
02158	195/60R15 88T	STD	BSW	440 A B	6.0	1235	44	24.21	7.91	10.0	21.0
02156	215/65R16 98T	STD	BSW	440 A B	6.5	1653	44	26.78	8.79	10.0	22.0
02159	205/60R16 92T	STD	BSW	440 A B	6.0	1389	44	25.67	8.23	10.0	24.0

FEATURES AND BENEFITS

- Specifically designed for crossover and SUV applications to provide a smooth ride, long life and excellent traction under all conditions.
- Unique compounding results in a lower rolling resistance for improved fuel economy.
- Computer optimized tread design greatly reduces road noise and vibrations.

The Hercules Roadtour XUV – modern efficiency.

Engineered to complement today’s crossovers and SUVs, the Roadtour XUV delivers polished motoring in an effortless fashion. The clean overall design exhibits a stylish sidewall and an uncomplicated 5-rib tread pattern that effectively provides a comfortable ride, excellent traction and impeccable road manners. The special compounding helps contribute to a lower rolling resistance, improving efficiency and ensuring a long tread life. When it comes time to replace the original equipment tires on your CUV, the Roadtour XUV is a brilliant choice.



Hercules Roadtour® XUV
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
H, T-Speed Rated											
01347	235/65R16 103T	STD	BSW	680 A A	7.0	1929	44	27.87	9.56	11.0	28.0
01379	235/70R17 XL 111T	XL	BSW	600 A B	7.0	2403	50	30.01	9.47	13.0	35.0
01463	225/65R17 102T	STD	BSW	680 A A	6.5	1874	44	28.34	8.98	11.0	27.0
01469	235/65R17 104H	STD	BSW	540 A A	7.0	1984	44	29.10	9.65	11.0	29.0
01424	255/65R17 110T	STD	OWL	600 A B	7.5	2337	44	30.11	10.09	12.5	37.0
01422	265/65R17 112T	STD	OWL	600 A B	8.0	2469	44	30.58	10.60	12.5	39.0
01342	235/60R17 102T	STD	BSW	680 A A	7.0	1874	44	28.00	10.07	11.0	28.0
01429	265/70R18 116T	STD	OWL	600 A B	8.0	2756	44	32.63	10.72	13.0	43.0
01465	235/65R18 106T	STD	BSW	680 A A	7.0	2094	44	29.87	10.06	11.0	30.0
01410	P255/65R18 109T	STD	BSW	680 A A	7.5	2271	44	31.02	10.20	11.0	37.0
01345	235/60R18 XL 107H	XL	BSW	600 A B	7.0	2149	50	29.29	9.40	12.0	34.0
01467	245/60R18 105H	STD	BSW	600 A B	7.0	2039	44	29.68	9.55	12.0	34.0
01344	265/60R18 110T	STD	OWL	600 A B	8.0	2337	44	30.55	10.50	12.5	39.0
01346	255/55R18 XL 109H	XL	BSW	600 A B	8.0	2271	50	29.13	10.30	12.0	36.0
01343	235/55R19 XL 105H	XL	BSW	540 A A	7.5	2039	50	29.41	10.10	11.0	32.0

The Roadtour XUV features a limited 50,000 mile/80,000 km for H-rated, 60,000 mile/100,000 km for T-rated mileage warranty that includes road hazard protection and the exclusive 30 day “Trust Our Ride” test drive. Mileage warranty and road hazard are valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**

FEATURES AND BENEFITS

- High-grade compound materials and a sophisticated tread design work in tandem to deliver outstanding wear resistance and durability.
- Micro-wave siping, open shoulder design and a unique water guard in the tire's footprint help maintain contact with the road surface for all-weather, all-road traction.
- Advanced silica compound provides exceptional grip in wet conditions, promotes wear resistance and produces lower rolling resistance.
- Exceptional stability and excellent feedback are achieved through innovative tread design and premium construction, resulting in highly-responsive handling.
- A debossed sidewall and modern symmetric design lends a high-end, luxury appearance while quality design and construction creates quiet comfort.



LT Sidewall

CUV/SUV Sidewall

Terra Trac Cross-V—All-Around Performance. One-Of-A-Kind Tire.

Citywide to countryside. Main Street shops to mountaintops. The Hercules Terra Trac Cross-V makes driving fun. With its premium construction and serious all-road capability, the Terra Trac Cross-V offers the versatility and performance you need—wherever the road takes you. Simply put, the Cross-V was engineered to perform.

The Terra Trac Cross-V features a limited 70,000 mile/112,000 km (CUV/SUV sizes) or 65,000 mile/105,000 km (LT sizes) mileage warranty that includes road hazard protection and the exclusive 30-day "Trust Our Ride" test drive. Mileage warranty and road hazard are valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules Terra Trac® Cross-V™
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (In)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
SUV: V, H, T-Speed Rated													
88355	LT215/85R16 115/112Q	E	BSW	-	6.0	2680	80	2470	80	30.39	8.50	14.0	36.4
88358	LT235/85R16 120/116Q	E	BSW	-	6.5	3042	80	2778	80	31.73	9.25	14.0	41.0
88356	LT225/75R16 115/112R	E	BSW	-	6.0	2680	80	2470	80	29.29	8.78	14.0	35.9
88331	245/75R16 111T	STD	BSW	600 A A	7.0	2403	51	-	-	30.47	9.76	12.5	34.4
88359	LT245/75R16 120/116R	E	BSW	-	7.0	3042	80	2778	80	30.47	9.76	14.0	40.8
88362	LT265/75R16 123/120Q	E	BSW	-	7.5	3415	80	3085	80	31.65	10.51	14.0	44.8
88332	235/70R16 106T	STD	BSW	600 A A	7.0	2094	51	-	-	28.98	9.45	12.5	31.3
88333	245/70R16 107T	STD	BSW	600 A A	7.0	2149	51	-	-	29.53	9.76	12.5	32.7
88334	255/70R16 111T	STD	BSW	600 A A	7.5	2403	51	-	-	30.08	10.24	12.5	34.8
88335	265/70R16 112T	STD	BSW	600 A A	8.0	2469	51	-	-	30.63	10.71	12.5	36.6
88357	LT235/80R17 120/117R	E	BSW	-	6.5	3085	80	2835	80	31.81	9.25	14.0	41.7
88360	LT245/75R17 121/118S	E	BSW	-	7.0	3195	80	2910	80	31.50	9.76	14.0	42.5
88336	235/70R17 111T	XL	BSW	600 A A	7.0	2403	50	-	-	30.00	9.45	12.5	33.1
88337	245/70R17 110T	STD	BSW	600 A A	7.0	2337	51	-	-	30.55	9.76	12.5	34.6
88338	265/70R17 115T	STD	BSW	600 A A	8.0	2679	51	-	-	31.65	10.71	12.5	38.8
88361	LT265/70R17 121/118R	E	BSW	-	8.0	3195	80	2910	80	31.65	10.71	14.0	45.2
88339	225/65R17 102H	STD	BSW	600 A A	6.5	1874	51	-	-	28.50	8.98	12.5	28.4
88340	235/65R17 104H	STD	BSW	600 A A	7.0	1984	51	-	-	29.06	9.45	12.5	31.1
88341	245/65R17 107T	STD	BSW	600 A A	7.0	2149	51	-	-	29.53	9.76	12.5	32.4
88342	265/65R17 112T	STD	BSW	600 A A	8.0	2469	51	-	-	30.55	10.71	12.5	36.6
88343	255/70R18 113T	STD	BSW	600 A A	7.5	2535	51	-	-	32.09	10.24	12.5	37.3
88344	235/65R18 106H	STD	BSW	600 A A	7.0	2094	51	-	-	30.04	9.45	12.5	32.0
88345	255/65R18 111T	STD	BSW	600 A A	7.5	2403	51	-	-	31.06	10.24	12.5	35.4
88346	265/65R18 114T	STD	BSW	600 A A	8.0	2601	51	-	-	31.54	10.71	12.5	37.5
88347	275/65R18 116T	STD	BSW	600 A A	8.0	2756	51	-	-	32.09	10.98	12.5	39.7
88348	235/60R18 107H	XL	BSW	600 A A	7.0	2150	50	-	-	29.10	9.40	12.5	30.4
88349	245/60R18 105H	STD	BSW	600 A A	7.0	2039	51	-	-	29.57	9.76	12.5	32.0
88350	255/60R19 109H	STD	BSW	600 A A	7.5	2271	51	-	-	31.10	10.20	12.5	35.3
88351	245/55R19 103T	STD	BSW	600 A A	7.5	1929	51	-	-	29.60	10.00	12.0	33.0
88352	275/60R20 115T	STD	BSW	600 A A	8.0	2679	51	-	-	32.99	10.98	12.5	40.8
88353	275/55R20 117T	XL	BSW	600 A A	8.5	2833	50	-	-	32.00	11.20	12.0	39.7
88354	265/50R20 107V	STD	BSW	600 A A	8.5	2149	51	-	-	30.50	11.00	12.0	35.8

FEATURES AND BENEFITS

- Closed inner shoulder design reduces noise, maximizes stability, resists irregular wear and delivers excellent handling at highway speeds.
- Notched and siped solid center rib offers highly responsive steering and maneuverability.
- Four wide circumferential channel grooves maximize water evacuation to protect against hydroplaning.
- Laterally connected wave siping minimizes irregular wear, creates a quieter ride and enhances water evacuation to boost traction.
- Tread construction features full depth siping and optimized pitch design for a quieter ride.
- Innovative tread profile creates an optimum contact patch area, promoting even wear and prolonged tread life, while a wide footprint delivers high traction and mileage.



The Terra Trac HTS delivers the traction, wear-resistance and ride comfort that you demand for highway driving. Full-depth wave siping leads the list of intelligent design features, ensuring all-season traction and lasting cosmetic appeal. The tread design also boasts features that deliver highly responsive steering and maneuverability, excellent water evacuation and a quiet ride. The Terra Trac HTS is a stand-out example of the value Hercules offers!

The Terra Trac HTS features a limited 50,000 mile/ 80,000 km (SUV sizes) or 45,000 mile/75,000 km (LT and floatation sizes) mileage warranty that includes road hazard protection.

** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD*



Hercules Terra Trac® HTS
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (In)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
SUV: T, S-Speed Rated													
85450	235/75R15 105T	STD	OWL	500 A B	6.5	2039	44	-	-	28.86	9.25	11.0	30.9
85439	31X10.50R15LT 109S	C	OWL	-	8.5	2270	50	-	-	30.51	10.55	14.5	41.3
85441	LT215/85R16 115/112S	E	BSW	-	6.0	2680	80	2470	80	30.39	8.50	14.5	38.9
85437	LT235/85R16 120/116S	E	BSW	-	6.5	3042	80	2778	80	31.73	9.25	14.5	42.3
85455	225/75R16 104T	STD	OWL	500 A B	6.0	1984	44	-	-	29.29	8.78	11.0	33.7
85435	LT225/75R16 115/112S	E	BSW	-	6.0	2680	80	2470	80	29.29	8.78	14.5	37.4
85451	245/75R16 111T	STD	OWL	500 A B	7.0	2403	44	-	-	30.47	9.76	11.0	35.5
85434	LT245/75R16 120/116S	E	BSW	-	7.0	3042	80	2778	80	30.47	9.76	14.5	42.5
85453	265/75R16 116T	STD	OWL	500 A B	7.5	2756	44	-	-	31.65	10.51	11.0	39.2
85440	LT265/75R16 123/120S	E	BSW	-	7.5	3415	80	3085	80	31.65	10.51	14.5	46.7
85449	215/70R16 100T	STD	OWL	500 A B	6.5	1764	44	-	-	27.87	8.70	11.0	28.8
85458	225/70R16 103T	STD	OWL	500 A B	6.5	1929	44	-	-	28.43	8.98	11.0	29.9
85443	235/70R16 106T	STD	OWL	500 A B	7.0	2094	44	-	-	28.98	9.45	11.0	31.9
85448	245/70R16 107 T	STD	OWL	500 A B	7.0	2149	44	-	-	29.53	9.76	11.0	33.1
85456	255/70R16 111T	STD	OWL	500 A B	7.5	2403	44	-	-	30.08	10.24	11.0	35.8
85447	265/70R16 112T	STD	OWL	500 A B	8.0	2469	44	-	-	30.63	10.71	11.0	37.7
85436	LT235/80R17 120/117S	E	BSW	-	6.5	3085	80	2835	80	31.81	9.25	14.5	40.4
85442	LT245/75R17 121/118S	E	BSW	-	7.0	3195	80	2910	80	31.50	9.76	14.5	41.9
85444	245/70R17 110T	STD	OWL	500 A B	7.0	2337	44	-	-	30.55	9.76	11.0	35.7
85438	LT245/70R17 119/116S	E	BSW	-	7.0	3000	80	2755	80	30.55	9.76	14.5	39.3
85445	265/70R17 115T	STD	OWL	500 A B	8.0	2679	44	-	-	31.65	10.71	11.0	39.7
85433	LT265/70R17 121/118S	E	BSW	-	8.0	3195	80	2910	80	31.65	10.71	14.5	48.4
85454	225/65R17 102T	STD	BSW	500 A B	6.5	1874i	44	-	-	28.50	8.98	11.0	31.8
85452	235/65R17 104T	STD	OWL	500 A B	7.0	1984	44	-	-	29.06	9.45	11.0	31.7
85446	245/65R17 107T	STD	OWL	500 A B	7.0	2149	44	-	-	29.53	9.76	11.0	34.1
85457	265/65R17 112T	STD	OWL	500 A B	8.0	2469	44	-	-	30.55	10.71	11.0	37.9

FEATURES AND BENEFITS

- 12% more lateral grooves and 29% more sipes** around the circumference of the tire boost traction in adverse weather conditions.
- Deep areas in the siping ensure traction performance for the life of the tire and provide lasting aesthetic appeal.
- Tough tread design with silica-infused AT-C tread compound delivers superior wet and off-road traction.
- Pitch sequence approximates a more comfortable “grey noise” by spreading the sound energy over a broad range of frequencies.
- Latest generation mold profile shape creates a more stable contact patch for controlled and balanced “on-and-off-road performance, all-weather traction and” even tread wear.



Terra Trac AT II – The Next Generation Of Tough And Tested.

This premium, all-terrain tire raises the bar on performance and versatility. It is the next generation of on-and-off-road strength, durability, versatility, quiet and design. From rough weather tenacity to stone ejection, Terra Trac AT II delivers the total package – rugged looks with good manners and absolute performance.

The Terra Trac AT II features a limited 60,000 mile/100,000 km mileage warranty that includes road hazard protection and the exclusive 30 day “Trust Our Ride” test drive. Mileage warranty and road hazard valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules’ exclusive AT-C tread compound is formulated to deliver enhanced wet traction and prolonged wear. Chemically engineered with silica, AT-C tread technology delivers ultimate year-round traction without sacrificing tread life.

**Compared to Terra Trac A/T



Hercules Terra Trac® AT II
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (In)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
SUV: T, S-Speed Rated													
04379	235/75R15 105T	STD	OWL	500 A B	6.5	2039	44	-	-	28.66	9.30	13.0	29.9
04137	235/75R15 XL 109S	XL	OWL	500 A B	6.5	2271	41	-	-	28.90	9.20	13.0	31.0
04130	LT235/75R15/6 104/101R	C	OWL	-	6.5	1985	50	1820	50	28.90	9.10	16.0	34.9
04115	30X9.50R15LT/6 104R	C	OWL	-	7.5	1985	50	-	-	29.29	9.60	16.5	36.9
04114	31X10.50R15LT/6 109R	C	OWL	-	8.5	2270	50	-	-	30.20	10.60	16.5	40.9
04112	LT215/85R16/10 115/112R	E	BSW	-	6.0	2680	80	2470	80	30.31	8.40	16.5	35.9
04113	LT235/85R16/10 120/116R	E	BSW	-	6.5	3042	80	2778	80	31.77	9.40	16.5	39.9
04378	225/75R16 104T	STD	OWL	500 A B	6.0	1984	44	-	-	29.09	8.60	13.0	28.9
04111	LT225/75R16/10 115/112R	E	BSW	-	6.0	2680	80	2470	80	29.33	8.50	16.5	35.9
04380	235/75R16 108T	STD	OWL	500 A B	6.5	2205	44	-	-	29.65	9.30	13.0	32.9
04377	245/75R16 111T	STD	OWL	500 A B	7.0	2403	44	-	-	30.24	9.60	13.0	34.9
04125	LT245/75R16/6 108/104R	C	OWL	-	7.0	2205	50	2006	50	30.51	9.60	16.5	38.9
04124	LT245/75R16/10 120/116R	E	OWL	-	7.0	3042	80	2778	80	30.35	9.70	16.5	40.9
04381	265/75R16 116T	STD	OWL	500 A B	7.5	2756	44	-	-	31.50	10.60	13.0	38.9
04128	LT265/75R16/6 112/109R	C	OWL	-	7.5	2470	50	2270	50	31.61	10.50	16.5	44.9
04127	LT265/75R16/10 123/120R	E	OWL	-	7.5	3415	80	3085	80	31.61	10.60	16.5	47.9
04129	LT285/75R16/10 126/123R	E	OWL	-	8.0	3750	80	3415	80	32.60	11.50	17.0	52.9
04133	LT315/75R16/10 127/124R	E	OWL	-	8.5	3195	50	2910	50	34.49	12.40	17.0	60.0
04369	215/70R16 100T	STD	OWL	500 A B	6.5	1764	44	-	-	27.72	8.70	13.0	27.9
04370	225/70R16 103T	STD	OWL	500 A B	6.5	1929	44	-	-	28.62	9.00	13.0	30.9
04371	235/70R16 106T	STD	OWL	500 A B	7.0	2094	44	-	-	28.82	9.40	13.0	31.9
04367	245/70R16 107T	STD	OWL	500 A B	7.0	2149	44	-	-	29.41	9.80	13.0	33.9
04375	255/70R16 111T	STD	OWL	500 A B	7.5	2403	44	-	-	29.96	10.20	13.0	34.9
04372	265/70R16 112T	STD	OWL	500 A B	8.0	2469	44	-	-	30.35	10.80	13.0	36.9
04120	LT305/70R16/10 124/121R	E	OWL	-	9.0	3525	65	3195	65	32.95	12.20	17.0	55.9

Continued on next page.



Hercules Terra Trac® AT II
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
SUV: T, S-Speed Rated													
04131	LT235/80R17/10 120/117R	E	OWL	-	6.5	3085	80	2835	80	31.77	9.20	16.5	41.9
04126	LT245/75R17/10 121/118S	E	OWL	-	7.0	3195	80	2910	80	31.50	10.00	16.0	44.9
04359	235/70R17 XL 111T	XL	BSW	500 A B	7.0	2403	50	-	-	29.96	9.50	13.0	34.9
04368	245/70R17 110T	STD	OWL	500 A B	7.0	2337	44	-	-	30.43	9.70	13.0	36.9
04117	LT245/70R17/10 119/116R	E	OWL	-	7.0	3000	80	2755	80	30.55	9.80	16.5	42.9
04376	255/70R17 112T	STD	OWL	500 A B	7.5	2469	44	-	-	31.10	10.20	13.0	37.9
04373	265/70R17 115T	STD	OWL	500 A B	8.0	2679	44	-	-	31.38	10.70	13.0	39.9
04119	LT265/70R17/6 112/109R	C	OWL	-	8.0	2470	50	2270	50	31.57	10.60	16.5	45.9
04118	LT265/70R17/10 121/118R	E	OWL	-	8.0	3195	80	2910	80	31.65	10.90	16.5	47.9
04122	LT275/70R17/6 114/110R	C	OWL	-	8.0	2600	50	2335	50	32.20	11.10	16.5	46.9
04134	P285/70R17 117T	STD	OWL	500 A B	8.5	2833	44	-	-	32.76	11.30	12.5	44.0
04110	LT285/70R17/10 121/118S	E	BSW	-	8.5	3195	80	2910	80	32.76	11.70	17.0	51.9
04121	LT315/70R17/8 121/118R	D	OWL	-	9.5	3195	50	2910	50	34.33	12.60	17.0	59.9
04362	235/65R17 104T	STD	OWL	500 A B	7.0	1984	44	-	-	29.17	9.40	12.5	32.9
04361	245/65R17 107T	STD	OWL	500 A B	7.0	2149	44	-	-	29.53	9.50	12.5	33.9
04365	255/65R17 110T	STD	OWL	500 A B	7.5	2337	44	-	-	30.12	10.10	12.5	36.9
04363	265/65R17 112T	STD	OWL	500 A B	8.0	2469	44	-	-	30.59	10.60	12.5	38.9
04374	265/70R18 116T	STD	OWL	500 A B	8.0	2756	44	-	-	32.56	10.70	13.0	41.9
04123	LT275/70R18/10 125/122S	E	OWL	-	8.0	3640	80	3305	80	33.23	11.10	16.0	52.9
04364	265/65R18 114T	STD	OWL	500 A B	8.0	2601	44	-	-	31.50	10.70	12.5	39.9
04366	275/65R18 116T	STD	OWL	500 A B	8.0	2756	44	-	-	32.13	11.00	12.5	41.9
04116	LT275/65R18/10 123/120S	E	OWL	-	8.0	3415	80	3085	80	32.09	11.10	16.0	50.9
04135	LT285/65R18/10 125/122S	E	OWL	-	8.5	3640	80	3305	80	32.56	11.60	16.0	54.0
04360	265/60R18 110T	STD	OWL	500 A B	8.0	2337	44	-	-	30.55	10.50	12.5	38.9
04107	LT275/65R20/10 126/123S	E	BSW	-	8.0	3750	80	3415	80	34.21	11.10	16.0	54.0
04108	275/60R20 115T	STD	BSW	500 A B	8.0	2679	44	-	-	33.03	11.10	12.5	43.0
04358	275/55R20 RE 117T	RE	BSW	500 A B	8.5	2833	50	-	-	31.93	10.90	12.5	40.9
04136	LT285/55R20/10 122/119R	E	BSW	-	9.0	3305	80	3000	80	32.36	11.70	16.0	55.0
04109	LT305/55R20/10 121/118S	E	BSW	-	9.5	3195	65	2910	65	33.19	12.40	16.0	59.0
04132	305/50R20 XL 120S	XL	BSW	500 A B	9.5	3086	50	-	-	32.17	12.10	13.0	51.0



FEATURES AND BENEFITS

- Designed with “stone-blockers” to increase puncture resistance and cut/chip performance.
- XXL scooping tread lugs give the Trail Digger maximum traction in mud, gravel and sand.
- Pinned for studs.
- Scalloped shoulder lugs provide superb traction in soft surface applications.



The Hercules Trail Digger M/T – absolute traction.

Mud, sand, gravel and rocks, bring them on. With its huge staggered tread blocks and aggressively notched shoulder lugs, the Trail Digger M/T was designed to deliver maximum traction under the most treacherous conditions, all while providing good on-road manners. The Trail Digger M/T is also studdable for use in winter climates. The size range includes 15"- 20" with select sizes featuring our tough 3-ply sidewall technology for even more resistance to punctures and cutting. When superlative traction is your desire, look no further than the Trail Digger M/T.



AS SEEN ON TV



Hercules Trail Digger® M/T
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (In)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)	Stud Size (in)
01238	LT235/75R15/6 104/101Q	C	OWL	-	6.5	1985	50	1820	50	28.90	9.00	18.0	32.0	15
01204	3 0X9.50R15LT/6 104Q	C	OWL	-	7.5	1985	50	-	-	29.30	9.75	19.5	37.0	17
01202	31X10.50R15LT/6 109Q	C	OWL	-	8.5	2270	50	-	-	30.50	10.50	20.0	41.0	17
01206	33X12.50R15LT/6 108Q	C	OWL	-	10.0	2205	35	-	-	32.50	12.80	20.5	52.0	17
01219	LT235/85R16/10 120/116Q	E	BSW	-	6.5	3042	80	2778	80	31.81	9.30	18.0	44.0	15
*01263	LT225/75R16/10 115/112Q	E	OWL	-	6.0	2680	80	2470	80	29.53	8.70	17.5	43.0	15
01217	LT245/75R16/10 120/116Q	E	BSW	-	7.0	3042	80	2778	80	30.71	9.40	17.5	39.0	15
01218	LT265/75R16/10 123/120Q	E	OWL	-	7.5	3415	80	3085	80	32.01	10.10	18.5	49.0	15
01220	LT285/75R16/8 122/119Q	D	OWL	-	8.0	3305	65	3000	65	33.10	11.30	18.5	53.0	15
01221	LT315/75R16/8 121/118Q	D	OWL	-	8.5	3195	50	2910	50	34.76	12.50	20.0	63.0	17
*01260	LT245/70R17/10 119/116Q	E	BSW	-	7.0	3000	80	2755	80	30.70	9.60	18.0	47.0	15
01230	LT265/70R17/10 121/118Q	E	OWL	-	8.0	3195	80	2910	80	31.65	11.03	18.5	50.0	15
*01265	LT285/70R17/10 121/118Q	E	OWL	-	8.5	3195	80	2910	80	33.00	11.50	18.5	58.0	15
01228	33X12.50R17LT/8 114Q	D	OWL	-	10.0	2600	50	-	-	32.50	12.80	20.5	57.0	17
01226	35X12.50R17LT/8 119Q	D	OWL	-	10.0	3000	50	-	-	34.85	12.67	20.5	62.0	17
*01203	LT275/70R18/10 125/122Q	E	BSW	-	8.0	3640	80	3305	80	33.35	11.00	20.5	62.0	17
*01264	LT275/65R18/10 123/120Q	E	OWL	-	8.0	3415	80	3085	80	32.32	10.98	18.0	56.0	15
*01205	35X12.50R20LT/10 121Q	E	BSW	-	10.0	3195	65	-	-	34.66	12.50	20.5	71.0	17

*Denotes 3-Ply sizes

FEATURES AND BENEFITS

- Lateral channel grooves evacuate mud and snow for uncompromised traction.
- Beveled tread block edges promote traction and uniform wear.
- Aggressive shoulder design maximizes traction and rugged appearance.
- Deep tread provides versatile all-season, all-surface performance.
- Pinned for studs.



The Hercules Terra Trac D/T – uncompromised traction

Aggressive and uncompromising, the deep tread Terra Trac D/T is a premium, multi-purpose traction tire designed for a range of on and off-road applications. The versatile Terra Trac D/T not only excels on any surface like an all-terrain tire, but digs in to maximize power and efficiency in extreme conditions or tough commercial applications. Built for all-season performance, the Terra Trac D/T also features enhanced stud-hole placements for solid winter traction.

AS SEEN IN



The Terra Trac D/T features a road hazard protection warranty. Road hazard warranty is valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules Terra Trac® D/T
M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)	Stud Size (in)
04013	31X10.50R15LT/6 109Q	C	OWL	-	8.5	2270	50	-	-	30.47	10.71	18.0	43.0	15
04009	35X12.50R15LT/6 113Q	C	OWL	-	10.0	2535	35	-	-	34.88	12.90	20.0	64.0	17
04026	35X12.50R17LT/8 119Q	D	OWL	-	10.0	3000	50	-	-	34.88	12.90	20.0	67.0	17
04025	LT235/85R16/10 120/116Q	E	BSW	-	6.5	3042	80	2778	80	31.89	9.30	18.0	44.0	15
04020	LT225/75R16/10 115/112Q	E	BSW	-	6.0	2680	80	2470	80	29.33	8.50	18.0	38.0	15
04022	LT245/75R16/10 120/116Q	E	BSW	-	7.0	3042	80	2778	80	30.51	9.80	18.0	43.0	15
04023	LT265/75R16/10 123/120Q	E	OWL	-	7.5	3415	80	3085	80	31.77	10.60	18.0	48.0	15
04024	LT285/75R16/8 122/119Q	D	OWL	-	8.0	3305	65	3000	65	32.80	11.30	20.0	54.0	17
04021	LT315/75R16/8 121/118Q	D	OWL	-	8.5	3195	50	2910	50	34.61	12.90	20.0	65.0	17
04016	LT235/80R17/10 120/117Q	E	OWL	-	6.5	3085	80	2835	80	31.85	9.40	18.0	45.0	15
04027	LT245/75R17/10 121/118Q	E	OWL	-	7.0	3195	80	2910	80	31.73	9.60	18.0	49.0	15
04017	LT265/70R17/10 121/118Q	E	OWL	-	8.0	3195	80	2910	80	31.65	11.03	18.0	50.0	15
04018	LT285/70R17/8 121/118Q	D	OWL	-	8.5	3195	65	2910	65	32.80	11.35	18.0	53.0	15
04019	LT275/70R18/10 125/122Q	E	OWL	-	8.0	3640	80	3305	80	33.30	10.95	18.0	54.0	15
04008	LT275/65R18/10 123/120Q	E	OWL	-	8.0	3415	80	3085	80	32.28	10.90	18.0	55.0	15

FEATURES AND BENEFITS

- Five-rib design for smooth running performance and exceptionally long mileage.
- Aggressive center rib gives great all-season performance and outstanding road traction.
- Wide tread arc provides traction and long, even treadwear.
- Closed shoulder design promotes balanced treadwear and good steering control.
- Commercial grade compound features excellent handling and long mileage.



The Terra Trac Radial Rib features a limited 40,000 miles/65,000 km mileage warranty. Mileage warranty valid in U.S. and Canada only.

Hercules Terra Trac® Radial Rib

M+S Rated

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
03767	7.50R16/8 112/107N	D	BSW	-	6.0	2470	65	2150	65	31.80	8.35	14.0	38.0
03775	LT215/85R16/10 115/112Q	E	BSW	-	6.0	2680	80	2470	80	30.28	8.20	14.0	38.0
03777	LT235/85R16/10 120/116Q	E	BSW	-	6.5	3042	80	2778	80	31.69	9.20	14.0	42.0
03779	LT225/75R16/10 115/112Q	E	BSW	-	6.0	2680	80	2470	80	29.17	8.60	14.0	38.0
03773	LT245/75R16/10 120/116Q	E	BSW	-	7.0	3042	80	2778	80	30.47	9.30	14.0	43.0



Hercules Bias Trailer LPT

- Designed for high speed mobile home applications and slower speed overloaded hauler applications.
- Reinforced heavy duty nylon cord construction.
- Reinforced steel bead to carry heavy loads.

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
58200	7-14.5/12 TL	F	BSW	-	6.0	2304	102	2017	102	26.65	7.30	8.0	26.5
58202	8-14.5/14 TL	G	BSW	-	6.0	3086	116	2712	116	27.83	8.00	8.0	31.9



Hercules Power STR Radial Trailer

- Engineered specifically for trailer applications.
- Advanced tread compound reduces rolling resistance, improves fuel economy and promotes long lasting wear.

Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
63958	ST175/80R13/6 91/87L	C	BSW	-	5.0	1360	50	1200	50	24.02	6.97	9.5	18.3
63959	ST205/75R14/6 100/96L	C	BSW	-	5.5	1760	50	1570	50	26.14	7.99	10.5	22.5
63960	ST215/75R14/6 102/98L	C	BSW	-	6.0	1870	50	1650	50	26.69	8.50	10.5	25.6
63962	ST205/75R15/8 107/102L	D	BSW	-	5.5	2150	65	1870	65	27.13	7.99	10.5	25.4
68146	ST225/75R15/10 117/112L	E	BSW	-	6.0	2830	80	2470	80	28.31	8.78	10.5	29.8
72985	ST235/85R16/12 128/124L	F	BSW	-	6.5	3960	95	3520	95	31.73	9.25	10.5	46.3
91161	ST235/80R16/10 124/120L	E	BSW	-	6.5	3520	80	3080	80	30.79	9.25	10.5	38.1

Please note: Sizes ST205/75R15/6 and ST225/75R15/8 available for special order. Minimum quantities apply.

FEATURES AND BENEFITS

- ‘Vacuum’ siping on shoulders draws in water to facilitate direct contact with the road surface, releasing it as the tread block rolls upward.
- Hercules’ exclusive, new AWC² compound uses silica and clean oils to provide superior lateral and linear grip at low temperatures, while offering outstanding performance in all weather conditions.
- Advanced siping uses the interaction of wide and narrow sipes to maintain a firm grip on quickly changing winter surface conditions.
- Tread blocks feature a jagged edge to aid in deceleration and create bite for efficient braking on slippery surfaces.
- Precise tread block geometry and overall structural design create responsive steering and confident handling.



An environmentally friendly tire, the Hercules Avalanche R G2 has very low rolling resistance and is manufactured using purified oils for cleaner, non-harmful use. The Hercules Eco FT logo signifies that the Hercules Avalanche® R G2 is an environmentally conscious option.



The Avalanche R G2 features a road hazard protection warranty. Road hazard warranty is valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules Avalanche® R G2



Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Max Load (lbs)	Max PSI	Overall Diam. (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)
Passenger Sizes: R-Speed Rated											
87007	185/65R14 XL 90R	XL	BSW	-	5.5	1323	51	23.46	7.28	12.0	15.4
87006	175/65R15 XL 88R	XL	BSW	-	5.0	1235	51	24.00	6.89	12.0	15.4
87008	185/65R15 XL 92R	XL	BSW	-	5.5	1389	51	24.45	7.28	12.0	16.1
87009	195/65R15 XL 95R	XL	BSW	-	6.0	1521	51	25.00	7.68	12.0	17.9
87010	205/65R15 XL 99R	XL	BSW	-	6.0	1709	51	25.47	8.07	12.0	20.1
87012	185/60R15 XL 88R	XL	BSW	-	5.5	1235	51	23.74	7.28	12.0	15.4
87013	195/60R15 XL 92R	XL	BSW	-	6.0	1389	51	24.21	7.68	12.0	17.2
87011	215/65R16 XL 102R	XL	BSW	-	6.5	1874	51	27.01	8.46	12.0	25.1
87014	205/60R16 XL 96R	XL	BSW	-	6.0	1565	51	25.70	8.07	12.0	20.1
87015	215/60R16 XL 99R	XL	BSW	-	6.5	1709	51	26.14	8.46	12.0	22.9
87016	225/60R16 XL 102R	XL	BSW	-	6.5	1874	51	26.61	8.86	12.0	25.6
87017	205/55R16 XL 94R	XL	BSW	-	6.5	1477	51	24.88	8.07	12.0	19.2
87018	215/55R17 XL 98R	XL	BSW	-	7.0	1653	51	26.30	8.46	12.0	24.7
87019	225/55R17 XL 101R	XL	BSW	-	7.0	1819	51	26.77	8.86	12.0	25.6
87020	205/50R17 XL 93R	XL	BSW	-	6.5	1433	51	25.12	8.07	12.0	20.9
87021	225/50R17 XL 98R	XL	BSW	-	7.0	1653	51	25.91	8.86	12.0	24.3
87022	215/45R17 XL 91R	XL	BSW	-	7.0	1356	51	24.65	8.46	12.0	19.4
87023	225/45R17 XL 94R	XL	BSW	-	7.5	1477	51	24.96	8.86	12.0	24.0
87025	235/45R17 XL 97R	XL	BSW	-	8.0	1609	51	25.35	9.25	12.0	26.7
87024	225/45R18 XL 95R	XL	BSW	-	7.5	1521	51	25.94	8.86	12.0	21.4
87026	225/40R18 XL 92R	XL	BSW	-	8.0	1389	51	25.08	8.86	12.0	23.6
SUV Sizes: R-Speed Rated											
87027	235/75R15 105R	STD	BSW	-	6.5	2039	47	28.90	9.25	12.0	30.0
87028	215/70R16 100R	STD	BSW	-	6.5	1764	47	27.87	8.46	12.0	25.6
87029	225/70R16 XL 107R	XL	BSW	-	6.5	2149	51	28.43	8.86	12.0	29.3
87030	235/70R16 106R	STD	BSW	-	7.0	2094	47	28.98	9.25	12.0	30.9
87031	245/70R16 XL 111R	XL	BSW	-	7.0	2403	51	29.53	9.65	12.0	31.7
87032	265/70R16 112R	STD	BSW	-	8.0	2469	47	30.60	10.43	12.0	35.7
87033	265/70R17 115R	STD	BSW	-	8.0	2679	47	31.65	10.43	12.0	37.3
87034	225/65R17 XL 106R	XL	BSW	-	6.5	2094	51	28.50	8.86	12.0	27.1
87035	235/65R17 XL 108R	XL	BSW	-	7.0	2205	51	30.00	9.25	12.0	30.9
87037	245/65R17 XL 111R	XL	BSW	-	7.0	2403	51	29.53	9.65	12.0	31.3
87038	215/60R17 XL 100R	XL	BSW	-	6.5	1764	51	27.17	8.46	12.0	25.4
87039	225/60R17 XL 103R	XL	BSW	-	6.5	1929	51	27.64	8.86	12.0	26.7
87036	235/65R18 XL 110R	XL	BSW	-	7.0	2337	51	30.04	9.25	12.0	33.1
87040	225/60R18 XL 104R	XL	BSW	-	6.5	1984	51	28.62	8.86	12.0	28.2
87041	235/60R18 XL 107R	XL	BSW	-	7.0	2149	51	29.09	9.25	12.0	30.9
87042	235/55R18 XL 104R	XL	BSW	-	7.5	1984	51	28.15	9.25	12.0	28.9
87043	255/55R18 XL 109R	XL	BSW	-	8.0	2271	51	29.02	10.04	12.0	33.3



Hercules Avalanche X-Treme® Passenger

- Built for maximum traction in icy conditions.
- Formulated with microfilament grip material that stays pliable in the coldest temperatures.
- Designed for driving in severe winter and harsh driving conditions.
- Features a winter specific compound to enhance traction on snow and ice.
- Studdable.



Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Max Load	Max PSI	Overall Diam. (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)	Stud Size
--------	---------------------------------	------------	----------	------	----------------	----------	---------	--------------------	--------------------	---------------------	--------------	-----------

T,S-Speed Rated

01090	185/75R14 89S	STD	BSW	-	5.0	1279	44	25.10	7.20	13.5	17.0	12
01091	195/75R14 92S	STD	BSW	-	5.5	1389	44	25.65	7.60	13.5	20.0	12
01092	205/75R14 95S	STD	BSW	-	5.5	1521	44	26.20	7.95	14.0	21.0	13
01001	185/70R14 88S	STD	BSW	-	5.5	1235	44	24.45	7.45	13.0	18.1	12
01003	195/70R14 91S	STD	BSW	-	6.0	1356	44	25.00	7.75	13.0	19.0	12
01005	175/65R14 82T	STD	BSW	-	5.0	1047	44	23.10	6.85	13.0	16.0	12
01007	185/65R14 86T	STD	BSW	-	5.5	1168	44	23.55	7.35	13.0	17.3	12
01093	205/75R15 97S	STD	BSW	-	5.5	1609	44	27.20	7.95	14.0	22.0	13
01096	215/75R15 100S	STD	BSW	-	6.0	1764	44	27.80	8.40	14.0	25.0	13
01094	225/75R15 102S	STD	BSW	-	6.0	1874	44	28.30	8.70	14.0	25.0	13
01097	235/75R15 105S	STD	BSW	-	6.5	2039	44	28.90	9.10	14.5	29.0	13
01099	205/70R15 96S	STD	BSW	-	6.0	1565	44	26.40	8.00	13.0	23.0	12
01101	215/70R15 98S	STD	BSW	-	6.5	1653	44	26.90	8.40	13.0	25.0	12
01095	225/70R15 100S	STD	BSW	-	6.5	1764	44	27.40	8.70	13.0	24.0	12
01009	185/65R15 88T	STD	BSW	-	5.5	1235	44	24.51	7.55	13.0	19.0	12
01011	195/65R15 91T	STD	BSW	-	6.0	1356	44	25.00	7.85	13.0	20.0	12
01013	205/65R15 94T	STD	BSW	-	6.0	1477	44	25.45	8.02	13.0	22.0	12
01017	215/65R15 96T	STD	BSW	-	6.5	1565	44	25.98	8.55	13.0	24.0	12
01019	185/60R15 84T	STD	BSW	-	5.5	1102	44	23.88	7.44	13.0	19.0	12
01021	195/60R15 88T	STD	BSW	-	6.0	1235	44	24.30	7.80	13.0	21.0	12
01023	205/60R15 91T	STD	BSW	-	6.0	1356	44	24.75	8.15	13.0	22.0	12
01027	215/60R15 94T	STD	BSW	-	6.5	1477	44	25.21	8.60	13.0	24.0	12
01000	195/55R15 85T	STD	BSW	-	6.0	1135	44	23.75	7.91	13.0	20.0	12
01004	205/65R16 95T	STD	BSW	-	6.0	1521	44	26.45	8.02	13.0	23.0	12
01029	215/65R16 98T	STD	BSW	-	6.5	1653	44	26.98	8.55	13.0	25.0	12
01085	235/65R16 103T	STD	BSW	-	7.0	1929	44	27.94	9.56	13.0	27.0	12
01031	205/60R16 92T	STD	BSW	-	6.0	1389	44	25.77	8.33	13.0	23.0	12
01033	215/60R16 95T	STD	BSW	-	6.5	1521	44	26.15	8.50	13.0	24.0	12
01035	225/60R16 98T	STD	BSW	-	6.5	1653	44	26.57	8.75	13.0	25.0	12

Continued on next page



Hercules Avalanche X-Treme® Passenger

- Built for maximum traction in icy conditions.
- Formulated with microfilament grip material that stays pliable in the coldest temperatures.
- Designed for driving in severe winter and harsh driving conditions.
- Features a winter specific compound to enhance traction on snow and ice.
- Studdable.



Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Max Load	Max PSI	Overall Diam. (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)	Stud Size
--------	---------------------------------	------------	----------	------	----------------	----------	---------	--------------------	--------------------	---------------------	--------------	-----------

T,S-Speed Rated

01006	235/60R16 100T	STD	BSW	-	7.0	1764	44	26.96	9.45	13.0	28.0	12
01037	205/55R16 91T	STD	BSW	-	6.5	1356	44	24.80	8.35	12.0	22.0	12
01008	215/55R16 RE 97T	XL	BSW	-	7.0	1609	50	25.35	8.90	13.0	25.0	12
01010	205/50R16 87T	STD	BSW	-	6.5	1201	44	24.27	8.34	13.0	21.0	12
01012	225/50R16 92T	STD	BSW	-	7.0	1389	44	25.10	9.17	13.0	25.0	12
01053	215/65R17 99T	STD	BSW	-	6.5	1709	44	28.11	8.93	13.0	26.0	12
01082	225/65R17 102T	STD	BSW	-	6.5	1874	44	28.50	8.84	13.0	27.0	12
01081	215/60R17 96T	STD	BSW	-	6.5	1565	44	27.24	9.03	13.0	26.0	12
01075	225/60R17 99T	STD	BSW	-	6.5	1709	44	27.72	9.14	13.0	27.0	12
01073	215/55R17 94T	STD	BSW	-	7.0	1477	44	26.36	9.46	13.0	26.0	12
01039	225/55R17 97T	STD	BSW	-	7.0	1609	44	26.88	9.20	13.0	28.0	12
01045	235/55R17 99T	STD	BSW	-	7.5	1709	44	27.22	9.79	13.0	30.0	12
01112	205/50R17 XL 93T	XL	BSW	-	6.5	1433	50	25.29	8.29	13.0	25.0	12
01014	215/50R17 91T	STD	BSW	-	7.0	1356	44	25.69	8.82	13.0	25.0	12
01084	225/50R17 94T	STD	BSW	-	7.0	1477	44	26.00	8.99	13.0	26.0	12
01016	225/45R17 RE 94T	RE	BSW	-	7.5	1477	50	25.09	9.03	13.0	24.0	12
01047	235/45R17 94T	STD	BSW	-	8.0	1477	44	25.53	9.30	13.0	26.0	12
01048	225/60R18 100T	STD	BSW	-	6.5	1764	44	28.70	9.01	13.0	29.0	12


The Avalanche X-Treme features a road hazard protection warranty. Road hazard warranty is valid in U.S. and Canada only.

*** ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD**



Hercules Avalanche X-Treme® SUV

- Built for maximum traction in snow/ice conditions.
- Formulated with microfilament grip material that stays pliable in the coldest temperatures.
- Designed for driving in severe winter and harsh driving conditions.
- Features a winter specific compound to enhance traction on snow and ice.
- The Avalanche X-Treme has stud pin holes, providing a biting grip.



Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Max Load	Max PSI	Overall Diam. (in)	Section Width (in)	Tread Depth (32nds)	Weight (lbs)	Stud Size
--------	---------------------------------	------------	----------	------	----------------	----------	---------	--------------------	--------------------	---------------------	--------------	-----------

S-Speed Rated

01090	185/75R14 89S	STD	BSW	-	5.0	1279	44	25.10	7.20	13.5	17.0	12
01018	265/70R15 112S	STD	BSW	-	8.0	2469	44	29.43	10.45	15.0	36.0	13
01103	225/75R16 104S	STD	BSW	-	6.0	1984	44	29.18	8.65	15.0	31.0	13
01025	235/75R16 108S	STD	BSW	-	6.5	2205	44	29.85	9.30	15.0	33.0	13
01050	245/75R16 111S	STD	BSW	-	7.0	2403	44	30.40	9.60	15.0	34.0	13
01052	265/75R16 116S	STD	BSW	-	7.5	2756	44	31.60	10.60	15.0	39.0	13
01054	215/70R16 100S	STD	BSW	-	6.5	1764	44	27.75	8.80	15.0	29.0	13
01056	225/70R16 103S	STD	BSW	-	6.5	1929	44	28.30	9.00	15.0	30.0	13
01058	235/70R16 106S	STD	BSW	-	7.0	2094	44	28.85	9.40	15.0	32.0	13
01060	245/70R16 107S	STD	BSW	-	7.0	2149	44	29.50	9.85	15.0	34.0	13
01062	255/70R16 111S	STD	BSW	-	7.5	2403	44	29.90	10.30	15.0	35.0	13
01064	265/70R16 112S	STD	BSW	-	8.0	2469	44	30.40	10.80	15.0	39.0	13
01148	255/65R16 109S	STD	BSW	-	7.5	2271	44	29.18	10.24	14.0	34.0	13
01109	245/70R17 110S	STD	BSW	-	7.0	2337	44	30.50	9.85	15.0	35.0	13
01071	255/70R17 112S	STD	BSW	-	7.5	2469	44	31.22	10.28	15.0	41.0	13
01066	265/70R17 115S	STD	BSW	-	8.0	2679	44	31.40	10.65	15.0	39.0	13
01102	235/65R17 104S	STD	BSW	-	7.0	1984	44	29.11	9.45	14.0	33.0	13
01146	245/65R17 107S	STD	BSW	-	7.0	2149	44	29.52	9.82	14.0	34.0	13
01108	255/70R18 113S	STD	BSW	-	7.5	2535	44	32.22	10.28	15.0	42.0	13
01182	235/65R18 106S	STD	BSW	-	7.0	2094	44	30.19	9.37	14.0	35.0	13
01104	275/65R18 116S	STD	BSW	-	8.0	2756	44	32.16	11.01	14.0	43.0	13
01180	235/60R18 103S	STD	BSW	-	7.0	1929	44	29.30	9.45	14.0	34.0	13
01184	265/60R18 110S	STD	BSW	-	8.0	2337	44	30.59	10.66	12.5	39.0	12
01068	255/55R18 109S	RE	BSW	-	8.0	2271	50	29.12	10.36	14.0	39.0	13
01070	275/60R20 119S	RE	BSW	-	8.0	2998	50	33.02	10.93	14.0	47.0	13
01106	275/55R20 117S	RE	BSW	-	8.5	2833	50	32.03	11.03	14.0	44.0	13


The Avalanche X-Treme SUV features a road hazard protection warranty. Road hazard warranty is valid in U.S. and Canada only.

* ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD



Hercules Avalanche X-Treme® LT

- Built for maximum traction in snow/ice conditions.
- Formulated with microfilament grip material that stays pliable in the coldest temperatures.
- Designed for driving in severe winter and harsh driving conditions.
- Features a winter specific compound to enhance traction on snow and ice.
- The Avalanche X-Treme has stud pin holes, providing a biting grip.



Item #	Tire Size & Service Description	Load Range	Sidewall	UTQG	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)	Stud Size
--------	---------------------------------	------------	----------	------	----------------	-----------------	----------------	---------------	--------------	-----------------------	--------------------	---------------------	-------------------	-----------

01028	LT235/75R15/6 104/101Q	C	BSW	-	6.5	1985	50	1820	50	28.82	9.00	17.0	34.0	15
01030	31X10.50R15LT/6 109Q	C	BSW	-	8.5	2270	50	-	-	30.25	10.50	19.0	40.0	15
01040	LT215/85R16/10 115/112Q	E	BSW	-	6.0	2680	80	2470	80	30.28	9.10	17.0	38.0	15
01032	LT235/85R16/10 120/116Q	E	BSW	-	6.5	3042	80	2778	80	31.78	9.31	17.0	42.0	15
01034	LT225/75R16/10 115/112Q	E	BSW	-	6.0	2680	80	2470	80	29.30	8.95	17.0	39.0	15
01036	LT245/75R16/6 108/104Q	C	BSW	-	7.0	2205	50	2006	50	30.44	9.57	17.0	40.0	15
01038	LT245/75R16/10 120/116Q	E	BSW	-	7.0	3042	80	2778	80	30.44	9.57	17.0	45.0	15
01042	LT265/75R16/6 112/109Q	C	BSW	-	7.5	2470	50	2270	50	31.54	10.33	17.0	44.0	15
01044	LT265/75R16/10 123/120Q	E	BSW	-	7.5	3415	80	3085	80	31.54	10.50	17.0	49.0	15
01116	LT285/75R16/10 126/123Q	E	BSW	-	8.0	3750	80	3415	80	32.57	11.36	17.0	53.0	15
01076	LT235/80R17/10 120/117Q	E	BSW	-	6.5	3085	80	2835	80	31.85	9.40	18.0	44.0	15
01087	LT245/75R17/10 121/118R	E	BSW	-	7.0	3195	80	2910	80	31.83	9.87	17.0	45.0	15
01046	LT245/70R17/10 119/116Q	E	BSW	-	7.0	3000	80	2755	80	30.45	10.07	17.0	44.0	15
01074	LT265/70R17/10 121/118Q	E	BSW	-	8.0	3195	80	2910	80	31.65	11.03	18.0	50.0	15
01080	LT275/70R18/10 125/122R	E	BSW	-	8.0	3640	80	3305	80	33.15	10.95	17.0	55.0	15
01186	LT275/65R18/10 123/120R	E	BSW	-	8.0	3415	80	3108	80	32.10	11.11	17.0	52.0	15
01111	LT275/65R20/10 126/123R	E	BSW	-	8.0	3750	80	3415	80	34.18	11.10	17.0	56.0	15

The Avalanche X-Treme LT features a road hazard protection warranty. Road hazard warranty is valid in U.S. and Canada only.

* ROAD HAZARD WARRANTY 1ST 50% USABLE TREAD



H-804 Ultra-Premium Long Haul Decoupling Groove Steer

- Newest-generation premium all-position tire optimized for the steer position.
- Five-rib design promotes even wear in long-haul applications.
- Enhanced shoulder rib design with decoupling grooves minimizes the initiation and spread of irregular wear.
- Innovative groove technology maximizes tear resistance while ejectors minimize stone retention.
- Low rolling resistance tread compound offers optimum fuel efficiency and significant removal mileage.



Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
92778	11R22.5/14 144/142M	BSW	14/G	8.25	6173	104	5842	104	41.50	10.98	18.5	118.17
92779	11R22.5/16 146/143M	BSW	16/H	8.25	6614	120	6008	120	41.50	10.98	18.5	118.17
92781	11R24.5/14 146/143M	BSW	14/G	8.25	6614	104	6008	104	43.46	10.98	18.5	130.03
92780	11R24.5/16 149/146M	BSW	16/H	8.25	7165	120	6614	120	43.46	10.98	18.5	130.03
92776	295/75R22.5/14 144/141M	BSW	14/G	9.00	6173	110	5677	110	39.92	11.73	18.5	115.52
92777	295/75R22.5/16 146/143M	BSW	16/H	9.00	6614	120	6008	120	39.92	11.73	18.5	115.52
92775	285/75R24.5/14 144/141M	BSW	14/G	8.25	6173	110	5677	110	41.34	11.14	18.5	121.47
92774	285/75R24.5/16 147/144M	BSW	16/H	8.25	6779	120	6173	120	41.34	11.14	18.5	121.47

*SmartWay® verification pending.

Available in second quarter.



H-801 EcoFT Premium Steer A/P

- Next generation all-position premium highway tire.
- Five-rib design with micro sipes and wide shoulder ribs with decoupling grooves resist irregular wear.
- Technologically advanced tread compound contributes to low rolling resistance for optimum fuel efficiency and significant removal mileage.
- Innovative groove technology leads to minimum stone retention, extending casing life.
- Engineered for optimum weight distribution to promote even wear.
- Fuel efficient and part of the EPA SmartWay® verified technologies of low rolling resistance tires.



Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
84277	11R22.5/14 144/142M	BSW	14/G	8.25	6175	105	5840	105	41.50	10.98	19.0	120.6
84278	11R22.5/16 146/143M	BSW	16/H	8.25	6610	120	6005	120	41.50	10.98	19.0	120.6
88318	11R24.5/14 146/143M	BSW	14/G	8.25	6610	105	6005	105	43.46	10.98	19.0	131.8
88319	11R24.5/16 149/146M	BSW	16/H	8.25	7160	120	6610	120	43.46	10.98	19.0	131.8
86837	295/75R22.5/14 144/141M	BSW	14/G	9.00	6175	110	5675	110	39.92	11.73	19.0	117.3
87005	295/75R22.5/16 146/143M	BSW	16/H	9.00	6610	120	6005	120	39.92	11.73	19.0	117.3
88320	285/75R24.5/14 144/141M	BSW	14/G	8.25	6175	110	5675	110	41.34	11.14	19.0	122.3
88321	285/75R24.5/16 147/144M	BSW	16/H	8.25	6780	120	6175	120	41.34	11.14	19.0	122.3



H-502 EcoFT Deep Tread A/P

- Regional all-position rib tire for both steer and trailer applications.
- Wide five-rib design delivers long mileage.
- Deep tread for additional mileage.
- Heavy-duty all-steel casing for excellent retreadability.
- Fuel efficient and part of the EPA SmartWay® verified technologies of low rolling resistance tires.



Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
83009	11R22.5/14 144/142L	BSW	14/G	8.25	6173	104	5842	104	41.57	10.94	22.0	119.9
83010	11R22.5/16 146/143L	BSW	16/H	8.25	6614	120	6008	120	41.57	10.94	22.0	124.6
83013	11R24.5/14 146/143L	BSW	14/G	8.25	6610	105	6005	105	43.62	10.94	22.0	132.4
83015	11R24.5/16 149/146L	BSW	16/H	8.25	7165	120	6614	120	43.62	10.94	22.0	133.4
89683	315/80R22.5/20 161/157L	BSW	20/L	9.00	10196	131	9094	131	42.40	12.28	20.0	145.5
83014	295/75R22.5/14 144/141L	BSW	14/G	8.25	6173	110	5677	110	40.24	10.83	22.0	116.5
83012	285/75R24.5/14 144/141L	BSW	14/G	8.25	6173	110	5677	110	41.61	10.83	22.0	124.1



H-309 Highway A/P

- Premium all-position tire for free-rolling applications.
- Five-rib design promotes even wear in regional applications.
- Enhanced shoulder rib design resists scrub wear and minimizes irregular wear.
- Innovative groove technology maximizes tear resistance while ejectors minimize stone retention.
- Low rolling resistance tread compound offers optimum fuel efficiency and significant removal mileage.



Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
92786	11R22.5/14 144/142M	BSW	14/G	8.25	6173	104	5842	104	41.50	10.98	18.5	118.48
92787	11R22.5/16 146/143M	BSW	16/H	8.25	6614	120	6008	120	41.50	10.98	18.5	118.48
92789	11R24.5/14 146/143M	BSW	14/G	8.25	6614	104	6008	104	43.46	10.98	18.5	130.38
92788	11R24.5/16 149/146M	BSW	16/H	8.25	7165	120	6614	120	43.46	10.98	18.5	130.38
92784	295/75R22.5/14 144/141M	BSW	14/G	9.00	6173	110	5677	110	39.92	11.73	18.5	116.03
92785	295/75R22.5/16 146/143M	BSW	16/H	9.00	6614	120	6008	120	39.92	11.73	18.5	116.03
92783	285/75R24.5/14 144/141M	BSW	14/G	8.25	6173	110	5677	110	41.34	11.14	18.5	122.13
92782	285/75R24.5/16 147/144M	BSW	16/H	8.25	6779	120	6173	120	41.34	11.14	18.5	122.13

Available in second quarter.



H-902 EcoFT/ H-902 Highway A/P

- Regional all-position rib tire for both steer and trailer applications.
- Five-rib design delivers long mileage and shoulder wear resistance on steer axle use.
- Designed with lower rolling resistance to provide better fuel efficiency.
- Fuel efficient and part of the EPA SmartWay® verified technologies of low rolling resistance tires



Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
H-902 EcoFT												
89997	11R22.5/14 144/142M	BSW	14/G	8.25	6173	104	5842	104	41.02	10.98	16.0	118.1
89998	11R22.5/16 146/143M	BSW	16/H	8.25	6614	120	6008	120	41.02	10.98	16.0	118.1
88322	295/75R22.5/14 144/141M	BSW	14/G	9.00	6175	110	5675	110	39.92	11.73	16.0	113.1
88413	295/75R22.5/16 146/143M	BSW	16/H	9.00	6610	120	6005	120	39.92	11.73	16.0	113.0
H-902*												
59545	215/75R17.5/16 135/133L	BSW	16/H	6.00	4806	125	4542	125	30.39	8.07	16.0	56.4
59546	235/75R17.5/16 143/141L	BSW	16/H	6.75	6008	125	5677	125	31.57	8.90	17.0	63.5
84279	245/70R17.5/14 143/141J	BSW	14/G	7.50	6005	125	5675	125	31.06	9.76	17.0	69.2
59217	225/70R19.5/14 128/126K	BSW	14/G	6.75	3968	110	3748	110	32.01	8.62	16.0	65.7
59216	245/70R19.5/14 133/131L	BSW	14/G	7.50	4542	110	4299	110	33.07	9.61	17.0	74.6
59219	255/70R22.5/16 140/137L	BSW	16/H	7.50	5512	120	5071	120	36.73	9.65	17.5	93.6
59979	275/70R22.5/16 148/145M	BSW	16/H	8.25	6945	131	6393	131	37.91	10.71	18.5	102.4
92640	265/70R19.5/16 143/141J	BSW	14/H	7.50	6008	123	5677	123	34.09	10.71	17.5	80.7

* Hercules H-902 items are not EPA SmartWay verified.



H-601 Highway A/P

- All-position rib tire for both steer and trailer applications.
- Five-rib design delivering long mileage and shoulder wear resistance on steer axle use.
- Heavy-duty all-steel casing for excellent retreadability.
- Designed with lower rolling resistance to provide better fuel efficiency.

Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load (lbs)	Single Max PSI	Dual Max Load (lbs)	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
64347	295/80R22.5/16 152/148M	BSW	16/H	9.00	7826	123	6945	123	41.10	11.65	20.5	138.2



H-901 Highway All Steel Commercial LT/ST

- Durable all steel construction distributes forces of acceleration, cornering, and braking for longer wear.
- Tread design features better foot print and more biting edges for better grip in snow.
- Active sipes for improved traction.
- Special tread compound provides exceptional wet handling and braking.
- Super high tensile steel belts for durability.
- Strong casing gives stability and strength for applications with demanding loads.

Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
92875	ST225/90R16/14 129/124L	BSW	14/G	6.00	4079	110	3527	110	31.49	8.66	14.0	60.6
91212	LT235/85R16/14 126/123 L	BSW	14/G	6.50	3756	110	3415	110	31.73	9.25	14.0	52.5
91994	LT225/75R16/12 119/116N TL	BSW	12/F	6.00	2998	94	2756	94	29.29	8.78	14.0	50.3
91995	LT245/75R16/12 123/120N TL	BSW	12/F	7.00	3417	94	3086	94	30.47	9.76	14.0	60.9



H-704 EcoFT Premium Long Haul Closed Shoulder Deep Drive

- Extra deep tread delivers long original tread life.
- Solid shoulder provides exceptional stability and resists irregular wear.
- Tread features aggressive lugs for superior traction and wide grooves to help prevent stone trapping.
- Heavy-duty all steel casing for excellent retreadability.
- Fuel efficient and part of the EPA SmartWay® verified technologies of low rolling resistance tires.



Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
88323	11R22.5/14 144/142L	BSW	14/G	8.25	6175	105	5840	105	41.93	10.98	30.0	134.8
88324	11R22.5/16 146/143L	BSW	16/H	8.25	6610	120	6005	120	41.93	10.98	30.0	134.8
88325	11R24.5/14 146/143L	BSW	14/G	8.25	6610	105	6005	105	43.94	10.98	30.0	145.8
88326	11R24.5/16 149/146L	BSW	16/H	8.25	7160	120	6610	120	43.94	10.98	30.0	145.8
88327	295/75R22.5/14 144/141L	BSW	14/G	9.00	6175	110	5675	110	40.16	11.73	30.0	130.2
88328	295/75R22.5/16 146/143L	BSW	16/H	9.00	6610	120	6005	120	40.16	11.73	30.0	130.2



H-903 EcoFT/ H-903 Trailer Rib

- Six-rib tire for short and long haul trailer application.
- Fights irregular tread wear.
- Sipes provide directional stability and drainage.
- Heavy-duty all-steel casing for excellent retreadability.
- Fuel efficient and part of the EPA SmartWay® verified technologies of low rolling resistance tires.



Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
H-903 EcoFT												
83878	11R22.5/14 144/142M	BSW	14/G	8.25	6173	104	5842	104	41.50	11.00	12.0	108.8
83876	11R22.5/16 146/143M	BSW	16/H	8.25	6614	120	6008	120	41.50	11.00	12.0	108.8
83877	11R24.5/14 146/143M	BSW	14/G	8.25	6614	104	6008	104	43.50	11.00	12.0	122.5
83875	11R24.5/16 149/146M	BSW	16/H	8.25	7165	120	6614	120	43.50	11.00	12.0	122.5
83879	295/75R22.5/14 144/141M	BSW	14/G	9.00	6175	110	5675	110	39.90	11.70	12.0	107.5
83874	285/75R24.5/14 144/141M	BSW	14/G	8.25	6173	110	5677	110	41.30	11.10	12.0	113.9
H-903*												
59551	255/70R22.5/16 140/137L	BSW	16/H	7.50	5512	120	5071	120	36.50	9.65	13.5	88.8

*Hercules H-903 items are not EPA SmartWay verified.



H-933 Winter Service Drive

- Specialized drive tire designed for enhanced acceleration and braking capability in winter conditions.
- Meets severe snow performance requirements in North America.
- Formulated with unique tread compound that stays pliable in the coldest temperatures.
- Deep tread (27/32nds) and extra-wide footprint delivers long original tread life and stability.
- Unique siping provides interlocking capability for enhanced tread block rigidity and maximizes biting edges for exceptional traction on snow and other surfaces.
- Heavy-duty all-steel casing for excellent retreadability.

Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
92644	11R22.5/16 146/143L	BSW	16/H	8.25	6614	120	6007	120	41.93	10.98	27.0	134.83
92645	11R24.5/16 149/146L	BSW	16/H	8.25	7165	120	6614	120	44.05	10.98	27.0	145.50



H-702 EcoFT/ H-702 Closed Shoulder Drive

- Premium closed shoulder design for drive axle.
- Solid shoulder provides superior stability and resistance to irregular wear.
- Heavy-duty all-steel casing for excellent retreadability.
- Fuel efficient and part of the EPA SmartWay® verified technologies of low rolling resistance tires.



Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
H-702 EcoFT												
82544	11R22.5/14 144/142L	BSW	14/G	8.25	6173	104	5842	104	41.50	10.94	25.5	127.2
82615	11R22.5/16 146/143L	BSW	16/H	8.25	6614	120	6008	120	41.50	11.00	25.5	127.4
82616	11R24.5/14 146/143L	BSW	14/G	8.25	6614	104	6008	104	43.50	11.00	25.5	134.8
82617	11R24.5/16 149/146L	BSW	16/H	8.25	7165	120	6614	120	43.50	11.00	25.5	137.4
82618	295/75R22.5/14 144/141L	BSW	14/G	9.00	6173	110	5677	110	39.90	11.70	25.5	120.4
82622	285/75R24.5/14 144/141L	BSW	14/G	8.25	6173	110	5677	110	41.30	11.10	25.5	128.4
H-702*												
59977	225/70R19.5/12 125/123L	BSW	12/F	6.75	3417	96	3638	96	32.24	8.62	20.0	68.1
59978	245/70R19.5/14 133/131L	BSW	14/G	7.50	4542	110	4299	110	33.00	9.80	21.0	78.0
92437	7.50R16LT/14 122/118N	BSW	14/G	6.00	3307	112	2910	112	32.09	8.66	19.0	71.2

*Hercules H-702 items are not EPA SmartWay verified.



H-703 EcoFT Open Shoulder Drive

- Deep tread for excellent mileage.
- Aggressive tread design to withstand irregular wear.
- Open shoulder design and tough, siped blocks provide excellent traction under all weather conditions.
- Heavy-duty all-steel casing for excellent retreadability.
- Fuel efficient and part of the EPA SmartWay® verified technologies of low rolling resistance tires.



Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
89296	11R22.5/14 144/142L	BSW	14/G	8.25	6173	104	5842	104	41.81	10.94	25.5	126.6
89297	11R22.5/16 146/143L	BSW	16/H	8.25	6614	120	6008	120	41.81	10.94	25.5	123.1
89303	11R24.5/14 146/143L	BSW	14/G	8.25	6614	104	6008	104	43.86	10.94	25.5	135.9
89304	11R24.5/16 149/146L	BSW	16/H	8.25	7165	120	6614	120	43.86	10.94	25.5	132.5
89306	295/75R22.5/14 144/141L	BSW	14/G	9.00	6173	110	5677	110	40.47	10.83	25.5	119.9
89305	285/75R24.5/14 144/141L	BSW	14/G	8.25	6173	110	5677	110	41.85	10.83	25.5	127.9

Please note: Sizes 11R22.5/14 and 11R24.5/14 available for special order. Minimum quantities apply.



H-803 Open Shoulder Drive

- Open shoulder drive axle tire.
- Large aggressive lugs for traction under all conditions.
- Siped for better water traction.
- Built for long mileage.

Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
73464	225/70R19.5/14 128/126L	BSW	14/G	6.75	3968	110	3748	110	32.24	8.62	20.0	67.9
73465	245/70R19.5/16 135/133L	BSW	16/H	7.50	4806	120	4542	120	33.35	9.61	21.0	77.7



H-301 Highway Mixed Service

- Premium chip and cut for all axles.
- Tread compound resists chipping and lacerations in severe conditions.
- Center groove designed with stone ejectors for improved resistance to stone trapping.
- Heavy-duty all-steel casing for excellent retreadability.

Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
72062	11R22.5/16 146/143K	BSW	16/H	8.25	6614	120	6008	120	41.65	10.94	23.0	124.6
59973	11R24.5/16 149/146K	BSW	16/H	8.25	7165	120	6614	120	43.70	10.94	23.0	133.8
72078	275/70R22.5/16 148/145K	BSW	16/H	8.25	6945	131	6393	131	38.11	10.71	22.0	103.7
59531	315/80R22.5/20 161/157G	BSW	20/L	9.00	10196	131	9094	131	42.76	12.09	22.0	147.2



H-402 Wide Base Mixed Service

- Wide base for mixed service.
- Aggressive wide base grooves reduce stone trapping.
- Excellent durability with strong resistance to cutting, chipping and tearing.
- Heavy-duty all-steel casing for excellent retreadability.

Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
77796	385/65R22.5/20 160K	BSW	20/L	11.75	9921	131	-	-	42.24	15.31	21.0	168.2
59980	425/65R22.5/20 165K	BSW	20/L	12.25	11354	120	-	-	44.29	16.38	22.5	194.4
84276	445/65R22.5/20 168K	BSW	20/L	13.00	12346	120	-	-	45.16	17.48	21.0	204.5
92436	315/80R22.5/20 161/157J	BSW	20/L	9.00	10196	131	9094	131	42.36	12.28	22.0	145.9



H-307 Deep Drive

- Extra-deep tread for long original tread life.
- Aggressive tread design for a powerful grip in mixed service applications.
- Severe application compound for resistance to cuts, chips, tearing and irregular wear.
- Outstanding braking and stability for mixed service – severe applications.

Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
83890	11R22.5/16 146/143G	BSW	16/H	8.25	6614	120	6008	120	42.09	10.98	31.0	131.8
83891	11R24.5/16 149/146G	BSW	16/H	8.25	7165	120	6614	120	43.90	10.98	31.0	143.2



H-302 Deep Lug

- Deep tread for long life and excellent traction.
- Chip and cut resistant compound.
- Heavy-duty all-steel casing for excellent retreadability.

Item #	Tire Size & Service Description	Sidewall	PR/LR	Rim Width (in)	Single Max Load	Single Max PSI	Dual Max Load	Dual Max PSI	Overall Diameter (in)	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs)
59532	11R22.5/16 146/143G	BSW	16/H	8.25	6614	120	6008	120	42.20	10.94	32.0	133.0
59975	11R24.5/16 149/146G	BSW	16/H	8.25	7165	120	6614	120	44.25	10.94	32.0	142.6

HERCULES WARRANTY PROGRAM

(Applicable in the United States and Canada only.)

Congratulations, you have just purchased what we believe is the finest value available in the tire industry. We are proud of the quality and performance of the wide range of Hercules Tires products, and we realize that your continued satisfaction is essential to our success. Millions of Hercules tires are on the road right now delivering long mileage and outstanding performance. These tires are backed by a support network of thousands of dealers worldwide. Additionally, Hercules offers a unique protection plan to ensure you'll never be caught in a town without a Hercules dealer in the unlikely event that you would need a warranty adjustment.

THIS WARRANTY AND ADJUSTMENT POLICY IS NOT A WARRANTY THAT YOUR TIRE WILL NOT FAIL OR BECOME UNSERVICEABLE IF NEGLECTED OR MISTREATED.

IMPORTANT

The following contains important warranty information which you must have in order to obtain a warranty adjustment. This warranty information also includes the Hercules Road Hazard Warranty Program and the Hercules Mileage Warranty Program. We suggest you keep this in the glove box of your car at all times. In the unlikely event that you ever need to request a warranty adjustment, present this to your Hercules dealer, and they will have all the information needed to promptly address your request.

ELIGIBILITY

Eligible tires are covered by this Limited Warranty and Adjustment Policy for a minimum of 36 months from the date of original tire manufacture date or purchase date. (Without proof of purchase, date of manufacture will be used to determine age.)

This Limited Warranty and Adjustment Policy applies to the original owner of new Hercules branded SUV/P-Metric/Light Truck and Passenger tires that are new replacement market tires bearing the Hercules brand name and D.O.T. Tire Identification Number, operated in normal service, and used on the same vehicle on which they were originally installed according to the vehicle manufacturer's recommendations. Additionally, tires used in commercial service including, but not limited to, taxicabs, police cars, emergency vehicles and non-passenger service vehicles are not eligible for the Road Hazard and Mileage Warranty Coverage set forth in this Limited Warranty and Adjustment Policy. Tire(s) on any vehicle registered and normally operated outside the United States and Canada are excluded from eligibility under this Limited Warranty and Adjustment Policy.

PASSENGER CAR TIRES

When used in normal noncommercial passenger car service, tires which become unserviceable due to defects in workmanship and material will be replaced on a "no charge" basis during the first 2/32nds of an inch (1.6 mm) of original useable tread. The cost of mounting, balancing and any other service charges including applicable taxes are excluded from

reimbursement. Thereafter, the adjustment replacement price will be based upon tread wear prorated upon the basis of the original purchase price. Passenger car tires are considered 100% worn when the remaining tread depth is 2/32nds of an inch or less. BLEMISH passenger car tires are not adjustable. Out of balance, out of round or ride disturbance tire adjustments will only be made during the first 2/32nds of an inch of the original useable tread depth. Three (3) or more tires from the same vehicle will not be accepted. All Hercules passenger car tire adjustments will be subject to and made in conformity with the following conditions and exclusions of the Hercules Limited Warranty.

LIGHT TRUCK TIRES

Hercules light truck tires which become unserviceable due to defects in workmanship and material will be considered adjustable according to the following terms of this Limited Warranty. BLEMISH truck tires are not adjustable. All Hercules truck tire adjustments will be subject to and made in conformity with the following conditions and exclusions of the Hercules Limited Warranty.

ROAD HAZARD PROTECTION

This Road Hazard Coverage is offered upon the purchase of any new Hercules branded SUV/P-Metric/Light Truck and passenger tire purchased in Canada or the United States to promote goodwill and is not a warranty that your tire will not fail or become unserviceable due to a road hazard injury. This Road Hazard Coverage is a prorated two (2) year protection plan that applies to all Hercules brand tires as mentioned above that are purchased new from an authorized Hercules Tires dealer and is valid under the certain specified conditions as detailed below.

This warranty is valid from the date of purchase for two (2) years or when the tire reaches 50% of useable tread depth, whichever comes first. When an eligible tire is damaged during the first 2/32nds of an inch (1.6 mm) of treadwear or first 12 months from date of purchase, whichever came first, the tire will be replaced with a comparable Hercules brand tire free of charge.

This warranty provides credit based upon 50% of remaining usable tread at the time of failure due to road hazard. "Usable Tread" is defined as the original tread depth of a tire less 2/32nds of an inch. Credit is prorated based on a tire's tread depth of between 2/32nds and 50% of treadwear.

When the tire has 2/32nds of an inch or less in tread depth, it is considered worn out.

ROAD HAZARD EXCLUSIONS

This Road Hazard protection excludes Hercules Tires Medium Truck tires. All exclusions described under the section of "What is not covered" within this Limited Warranty and other exclusions include, but are not limited to, effects caused by:

1. A tire that is damaged /failed due to vandalism.
2. A tire that is damaged /failed due to an accident.



3. A tire that is damaged /failed due to commercial, industrial or agricultural use.
4. A tire that is damaged /failed due to racing.
5. A tire that is damaged /failed due to off-road use.
6. A tire that is damaged /failed due to snow chains or studs.
7. A tire that is damaged /failed due to rapid or irregular wear.
8. A tire that is damaged /failed due to wear from worn mechanical components on the vehicle.
9. Tires transferred from the vehicle on which they were originally installed.
10. Loss of time, inconvenience, loss of use of vehicle or consequential damage.
11. Any tires used on any emergency response vehicle.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply.

Adjustment procedures are described in the Owner's General Obligation section.

Complete and sign a Hercules Claim Form which is available at any authorized dealer or online at www.herculestire.com.

IMPORTANT SAFETY NOTICE: IF THE TIRE OWNER ABUSES THE TIRES BY FAILING TO OBSERVE SAFETY WARNINGS AND TO MAINTAIN PROPER INFLATION PRESSURE, VEHICLE ALIGNMENT AND TIRE ROTATION, EXPECTED TIRE PERFORMANCE AND LIFE MAY NOT BE ACHIEVED, AND YOUR SAFETY CANNOT BE ENSURED.

Hercules cares about your safety and your tires. Please drive responsibly and maintain your vehicle properly. Visit our website for important tire safety tips provided by the Rubber Manufacturers' Association. We encourage every consumer to "Be Tire Smart, Play Your P.A.R.T." by understanding and practicing the additional tire safety tips available online at www.rma.org.

To be eligible, you need to present your original tire sales invoice showing date of purchase, along with this Limited Warranty and Adjustment Policy, with the Information Section completed. You are responsible for payment of all applicable taxes, demounting, mounting and balancing charges set forth under this Coverage. You are also responsible for payment of local tire disposal fees and any parts or service regardless of mileage or months of service. This includes payment for tire rotation, alignment, towing, road service and valve stems and all applicable taxes.

Tires replaced on an adjustment basis become the property of the Company. You will be required to sign the Hercules Limited Warranty Claim Form.

HERCULES LINE COVERAGE MILEAGE WARRANTY & ROAD HAZARD

Mileage Warranty

If the tire wears down to the treadwear indicator bars (2/32") and the tire has not delivered the warranted miles, Hercules will provide a pro-rated adjustment based on actual mileage delivered. The cost of mounting, balancing and any other service charges including applicable taxes are excluded from reimbursement.

HERCULES	MILEAGE WARRANTY (Mile/KM)	ROAD HAZARD		
Performance	Raptis R-T5	45,000/75,000	YES	
	H/P 4000	40,000/65,000	YES	
Touring	Roadtour Tour 855 SPE TR	85,000/135,000	YES	
	Roadtour Tour 855 SPE VR/HR	70,000/112,000	YES	
	Roadtour 655 VR/HR	50,000/80,000	YES	
	Roadtour 655 TR/SR	60,000/100,000	YES	
	Tour 4.0 plus	55,000/90,000	YES	
	MRX Plus V	40,000/65,000	YES	
	MRX Plus IV	40,000/65,000	YES	
	CUV/SUV/Light Truck	Roadtour XUV HR	50,000/80,000	YES
		Roadtour XUV TR	60,000/100,000	YES
		Terra Trac Cross-V (CUV/SUV)	70,000/112,000	YES
Terra Trac Cross-V (LT)		65,000/105,000	YES	
Terra Trac HTS (SUV)		50,000/80,000	YES	
Terra Trac HTS (LT)		45,000/75,000	YES	
Terra Trac AT II		60,000/100,000	YES	
Terra Trac D/T		N/A	YES	
Trail Digger M/T		N/A	NO	
Terra Trac Radial Rib		40,000/65,000	NO	
Winter	Avalanche R G2	N/A	YES	
	Avalanche X-Treme Passenger	N/A	YES	
	Avalanche X-Treme SUV	N/A	YES	
	Avalanche X-Treme Light Truck	N/A	YES	
Specialty Applications	Power STR Radial Trailer	N/A	NO	
	Bias Trailer LPT	N/A	NO	

WHAT IS NOT COVERED BY THIS LIMITED WARRANTY

THE FOLLOWING ARE NOT COVERED:

- Hercules does not warrant any repaired or "blem" tire.
- Road hazard: Also see exclusions under the Road Hazard Policy.
- Improper operation or maintenance: This includes, but is not limited to, effects caused by:
 - a) Improper tire inflation and/or improper load/speed practices.
 - b) Improper or insufficient tire rotation.

Any tire with premature or irregular wear caused by failing to follow the recommended tire rotation pattern and/or mileage intervals as delineated by this Limited Warranty and Adjustment Policy.

Wear due to improper vehicle alignment including but not limited to, uneven, cupping, irregular, spotty, and feathering wear.

Damage due to:

- Rim irregularities or rim damage.
- Snow chains.
- Vehicle mechanical problems, including brake problems, and vehicle wheel alignment.
- Extreme temperature exposure.
- Negligent and abusive driving such as tire spinning, or racing.
- Improper tire storage.
- Automotive accident.
- Chemical corrosion or fire.
- Use contrary to the vehicle manufacturer's tire recommendations.
- Improper stud size and/or installation.
- Improper mounting or demounting.
- Alteration: such as, but not limited to, adding a white inlay on blackwall, tread regrooving, tire truing or siping, or adding sealant materials to the tire.
- Weather checking/cracking: not covered after 24 months from the date of purchase.

HERCULES' OBLIGATIONS

Replacement of Eligible Tires will be made by any Hercules Tires authorized dealer or vehicle dealer authorized to handle Hercules brand tire adjustments ("Authorized Dealer"). Hercules will replace the tire pursuant to the terms of this Limited Warranty and Adjustment Policy. Tires that are replaced under an adjustment basis under this Limited Warranty and Adjustment Policy become the property of HERCULES.

OWNER'S OBLIGATIONS

To make an eligible claim under this Limited Warranty and Adjustment Policy, the owner must present a claim with the tire to an Authorized Dealer. For the nearest Authorized Dealer, consult a local directory, internet search engine, www.herculestire.com, or call 1-800-677-3573. Owner must present an original tire sales invoice indicating the date of purchase. Owner will be required to sign the Hercules Limited Warranty Claim Form. Owner is responsible for paying all applicable taxes set forth under this Limited Warranty and Adjustment Policy. Owner is also responsible for paying local tire disposal fees and any parts or service regardless of mileage or months of service. This includes payment for tire rotation, alignment, towing, road service, valve stems and tire repair. Owner is responsible for maintaining proper tire air pressure and for proper maintenance of the tire. Under the Mileage Coverage portion of this Limited Warranty and Adjustment Policy owner must present a claim with the original customer copy of an up-to-date Mileage

Coverage Rotation Schedule, which is printed in this Limited Warranty and Adjustment Policy. Owner must rotate tires at least every 6,000 to 8,000 miles (10-13,000 kilometers) or sooner if uneven tread wear begins to appear.

CONDITIONS AND EXCLUSIONS

The Limited Warranty described herein applies only to tires purchased in the United States or Canada. No representative, agent or employee of Hercules or its dealers has any authority to make any representation, promise, agreement or change to this Limited Warranty except as specifically stated herein. Passenger tires purchased prior to six years before the date you present them for warranty adjustment are excluded.

PASSENGER CAR TIRES

Hercules Tires passenger car tires which become unserviceable because of the following conditions are excluded from Limited Warranty coverage and are not subject to adjustment: tires run flat, underinflated or overloaded (refer to information molded on tire sidewalls and vehicle manufacturer's recommended load tables), tires worn unevenly or rapidly due to misalignment, improper mounting or other mechanical irregularity, repairable punctures, tires misused or abused, vandalism, loss from fire, wreck or collision, tires used in other than normal passenger car service (normal passenger car service includes tires used in normal passenger car service by the original owner in the furtherance of his trade or business but excludes the use of the tire in truck, racing, off the highway service, campers, emergency response vehicles or on vehicles which are leased or for hire, including taxis, limousines or similar vehicles), tires concerning which recommended maintenance has not been performed by the user.

LIGHT TRUCK TIRES

Hercules Tires light truck tires removed from service because of the following conditions are excluded from this Limited Warranty coverage and are not subject to adjustment: cuts, snags, punctures, tires run flat or underinflated, tires worn unevenly or rapidly due to misalignment, improper mounting or other mechanical irregularity, tires misused or abused, vandalism, loss from fire, wreck or collision, tires used in other than normal service including improper load and inflation (refer to information molded on tire sidewalls and vehicle manufacturer's recommended load tables), tires concerning which recommended maintenance has not been performed by the user.

USAGE OF PRODUCT

This Limited Warranty applies only to tires which are equivalent in size and load range rating to the size and load range rating recommended by the manufacturer of the vehicle on which the tires are mounted and operated in accordance with the vehicle manufacturer's recommendations.



GENERAL

All tire adjustments under this Limited Warranty are CONTINGENT upon:

- a. Completion of the Registration and Limited Warranty forms at the time of sale.
- b. The subject tire not having been mounted on any other vehicle than on that on which it was first mounted.
- c. The claim being presented by the original purchaser of the subject tire.
- d. Copy of original invoice. You must also present personal identification (e.g., driver's license) and vehicle registration upon request and must make the vehicle on which the tires were mounted available for inspection.

No adjustment pursuant to this Limited Warranty shall in any way be determined or construed as an admission or indication on the part of Hercules or on any other party that any tire or tube adjusted or determined to be adjustable is in fact either defective in workmanship and/or material, or poor or merchantable quality or in any way unfit for the use for which it was intended, or serve to set a precedent for any further adjustment. This Limited Warranty specifically excludes and does not cover you for any loss of time, loss of use of the vehicle, or any incidental or consequential damages relating to the quality, condition or performance of the product. Some states and provinces do not allow the exclusion or limitation of incidental or consequential damages so the above exclusion may not apply to you.

HERCULES TIRE & RUBBER COMPANY RESERVES THE RIGHT TO THE FINAL INSPECTION DECISION FOR ALL RETURNED TIRES. THIS LIMITED WARRANTY AND ADJUSTMENT POLICY IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. HERCULES EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SOME U.S. STATES AND/OR CANADIAN PROVINCES DO NOT ALLOW LIMITATIONS ON THE DURATION OF AN IMPLIED WARRANTY, SO THE ABOVE MAY NOT APPLY TO YOU. TO THE EXTENT PERMITTED BY LAW, HERCULES DISCLAIMS LIABILITY FOR ALL CONSEQUENTIAL AND INCIDENTAL DAMAGES. THE REMEDIES SET FORTH IN THIS LIMITED WARRANTY ARE THE SOLE AND EXCLUSIVE REMEDIES FOR BREACH OF WARRANTY. SOME U.S. STATES AND/OR CANADIAN PROVINCES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM U.S. STATE TO STATE OR CANADIAN PROVINCE TO PROVINCE. THIS IS THE ONLY EXPRESSED WARRANTY MADE BY HERCULES. NO HERCULES EMPLOYEE, RETAILER, OR DEALER HAS THE AUTHORITY TO MAKE ANY WARRANTY, REPRESENTATION, PROMISE OR AGREEMENT ON BEHALF OF HERCULES EXCEPT AS EXPRESSLY WRITTEN IN THIS LIMITED WARRANTY AND ADJUSTMENT POLICY. IN OBSERVANCE OF U.S. FEDERAL LAW, THIS LIMITED WARRANTY AND ADJUSTMENT POLICY HAS BEEN DESIGNATED A "LIMITED WARRANTY." HERCULES DOES NOT INTEND TO REPRESENT THROUGH THIS LIMITED WARRANTY AND ADJUSTMENT POLICY THAT TIRE FAILURES CAN OR CANNOT HAPPEN.

ARBITRATION CLAUSE

ALL CLAIMS ARISING OUT OF THIS LIMITED WARRANTY OR THE MARKETING, SALE OR PERFORMANCE OF THE PURCHASED TIRE(S) AGAINST HERCULES, ITS SUPPLIERS, DEALERS OR ANY OF THEIR AFFILIATES OR ANY OF THEIR AGENTS, EMPLOYEES, OFFICERS OR DIRECTORS (collectively for the purposes of this paragraph "Hercules") SHALL BE SUBJECT TO BINDING ARBITRATION.

You acknowledge that your agreement to subject any claim described above means that you waive and forego any rights you may otherwise have to litigate your claim in a court of law and that you freely choose to resolve any such claim by arbitration upon election of arbitration by you or by Hercules. You agree further that no claim described above shall be litigated or arbitrated as a class action or on a class wide or representative basis or on behalf of the general public. You agree that any judgment or award of the arbitrator(s) will be final and not subject to judicial review. You recognize and agree that the arbitrator(s) shall have no authority to award punitive or other damages not measured by the prevailing party's actual damages, except as may be specifically required by statute.

ADJUSTMENT POLICY

If found adjustable, a Hercules Tires dealer will promptly replace the tire with a tire of like quality, and the replacement charge will be determined by multiplying the consumer's original purchase price (as verified by consumer's invoice) or at the selling price established by the adjusting dealer by the percentage of original tread depth worn from the tire (the original purchase price does not include local, state taxes or Federal Excise Tax). Hercules may, at its option, make a proportionate refund in lieu of replacing an adjustment tire. ANY ADDITIONAL CHARGES FOR LOCAL TAXES, MOUNTING, BALANCING, OR A HIGHER PRICED TIRE ACCEPTED AS A REPLACEMENT SHALL BE PAID BY THE CONSUMER. Should any problem develop in obtaining your replacement tire, you are requested to contact the Consumer Relations Department, telephone 1-800-677-9535.

ADJUSTMENT PROCEDURES

Unserviceable Hercules tires adjustable under the terms of this Limited Warranty should be returned to a Hercules Tires dealer. To locate a Hercules Tires dealer:

1. Search for "Hercules Tires" or "tires" on an internet search engine
2. Check under "tires" in a local phone directory
3. Call Hercules Tire at 1-800-677-3573
4. Email Hercules Tire at info@herculestire.com
5. Contact the nearest Hercules Tire wholesale distributor (see Find a Dealer at www.herculestire.com).

WHO IS ELIGIBLE?

You are eligible for the benefits of this warranty if:

- You are the owner of new Hercules brand medium radial truck tires
- Your tires bear Department of Transportation-prescribed tire identification numbers and are not branded "NA" (Not Adjustable) or "Blem" (Blemish)
- Your Hercules truck tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturer's or tire manufacturer's recommendations

WHAT IS COVERED, AND FOR HOW LONG?

Free Tire Replacement – Hercules truck tires covered by this warranty that become unserviceable due to a defect in workmanship or material during the first 50% of the original usable tread life (original tread depth minus 2/32"), will be replaced with a comparable new Hercules tire without charge. You pay only for the mounting, balancing and full F.E.T. or T.S.F. (Without proof of purchase, date of manufacture will be used to determine age.) 50% free replacement applies to tires purchased after January 1, 2014.

Prorated Tire Replacement – Tires worn beyond the first 50% of usable tread that become unserviceable due to a defect in workmanship or material will be replaced on a prorated basis. You are responsible for mounting, balancing and full F.E.T. or T.S.F.

HOW WILL PRORATED CHARGES BE CALCULATED?

The replacement price will be calculated using the current Hercules selling price and multiplying by the percentage of original useable tread (that is remaining at the time of replacement).

WHAT IS A COMPARABLE TIRE?

A "comparable" new Hercules tire may either be the same line of tire or, in the event that the tire is not available, a tire of the same basic construction and quality with a different sidewall or tread design. If a higher-priced tire is accepted as replacement, the difference in price will be at an additional charge to you. Any replacement tire provided pursuant to this warranty will be covered by the new Hercules medium truck tire warranty in effect at the time of replacement.

WHAT IS NOT COVERED BY THIS WARRANTY?

1. Tires branded or marked "Non-adjustable" (N/A), "Blemished" (Blem), or that have been previously adjusted.
2. Irregular wear or tire damage due to:
 - a. Road Hazards (including punctures, cuts, snags, impact breaks, etc.).
 - b. Wreck, collision, fire, or vandalism.
 - c. Improper inflation, overloading, misapplication, misuse, negligence, high-speed tire spinning, chain damage, improper mounting or demounting.

- d. Mechanical condition of the vehicle, including misalignment, wheel imbalance, or faulty shocks or brakes.
3. Ride disturbance after the first 2/32nds of treadwear or due to damaged wheels or any vehicle condition.
4. Ozone or weather cracking on tires over five (5) years from date of manufacture.
5. Alteration of the tire or addition of alien material or transfer from one vehicle to another.
6. Loss of time or use inconvenience, or any incidental or consequential damages.
7. Failure due to improper or faulty tube.
8. Tires used for racing.

WHEN DOES THE WARRANTY END?

A tire has delivered its full original treadlife and the new tire coverage of this warranty ends when the treadwear indicators become visible, or five (5) years from the date of original tire manufacture or new tire purchase date (without proof of purchase, date of manufacture will be used to determine age), whichever comes first. SmartWay® Verified tires have an extended warranty of six (6) years from date of manufacture or new tire purchase date.

HOW DO YOU OBTAIN AN ADJUSTMENT?

In order to be eligible for Hercules Limited Warranty service, the owner must:

- Present the tire to an authorized Hercules retailer, and
- Present proof of purchase (if applicable to faction of the retailer), and
- Complete and sign a Hercules Warranty Claim Form, which is available at any authorized dealer, and
- Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges, or cost of other services ordered.

Contact your authorized Hercules Tires dealer for warranty information, policies and procedures.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of Hercules Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

Hercules brand medium radial truck tires are warranted when the tire becomes unserviceable or non-retreadable due to a defect in workmanship or material. Hercules will provide a predetermined casing allowance.

Casing warranty is valid during the 2nd retreaded life or for six (6) years from the date of manufacture, whichever comes first, for SmartWay verified tires and during the 2nd retreaded life or for five (5) years from the date of manufacture, whichever comes first, for non-SmartWay verified tires.

WHAT IS NOT COVERED BY THIS WARRANTY?

Tires used in mining and logging service are not covered under this warranty.

CASING ALLOWANCES

Size(s)	1st	2nd
LT225/75R16, LT245/75R16, LT235/85R16	\$ 10.00	–
LT7.50R16	\$ 10.00	–
215/75R17.5, 235/75R17.5, 245/70R17.5	\$ 30.00	\$ 15.00
8R17.5, 9R17.5, 10R17.5	\$ 30.00	\$ 15.00
225/70R19.5, 245/70R19.5, 265/70R19.5	\$ 30.00	\$ 15.00
445/45R19.5	\$100.00	\$ 50.00
8R19.5	\$ 10.00	–
9R22.5, 10R22.5	\$ 50.00	\$ 30.00
255/70R22.5, 275/70R22.5	\$ 65.00	\$ 30.00
295/75R22.5, 275/80R22.5, 295/80R22.5, 315/80R22.5	\$ 90.00	\$ 50.00
385/65R22.5, 425/65R22.5, 445/65R22.5	\$100.00	\$ 50.00
11R22.5, 12R22.5	\$ 90.00	\$ 50.00
12.00R24	–	–
285/75R24.5	\$ 90.00	\$ 50.00
11R24.5	\$ 90.00	\$ 50.00

WHEN DOES THE WARRANTY END?

A tire has delivered its full original tread life and the new tire coverage of this warranty ends when the tread wear indicators become visible, or six (6) years for SmartWay verified tires or five (5) years for non-SmartWay verified tires from the date of the original tire manufacture or new tire purchase date (without proof of purchase, date of manufacture will be used to determine age), whichever comes first. Casings may continue to be warranted beyond the new tire coverage.

HOW DO YOU OBTAIN AN ADJUSTMENT?

In order to be eligible for Hercules Limited Warranty service, you must:

- Present the adjusted tire to an authorized Hercules retailer, and
- Present proof of purchase (if applicable) to the retailer, and
- Complete and sign a Hercules Warranty Claim Form, which is available at any authorized dealer, and
- Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges, or cost of other services ordered.

DISCLAIMER

This warranty or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of Hercules Tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein. Casing Warranty valid only in North America.



H-SERIES BUFFING GUIDELINES

TIRE SIZE	TREAD DESIGN	BUFF RADIUS		MAXIMUM BUFF WIDTH	
		INCHES	MM	INCHES	MM
11R22.5	H-301	20	508	8.70	221
11R22.5	H-301	20	508	8.70	221
11R22.5	H-302	24	605	8.76	223
11R22.5	H-307	24	606	8.74	222
11R22.5	H-309	20	508	8.82	224
11R22.5	H-502 EcoFT	24	604	8.80	224
11R22.5	H-702 EcoFT	24	608	8.74	222
11R22.5	H-703 EcoFT	20	508	8.74	222
11R22.5	H-704 EcoFT	20	509	8.70	221
11R22.5	H-801 EcoFT	20	508	8.98	228
11R22.5	H-802 EcoFT	24	606	8.82	224
11R22.5	H-804	20	508	8.82	224
11R22.5	H-902 EcoFT	24	606	8.82	224
11R22.5	H-903 EcoFT	21	522	8.94	227
11R24.5	H-301	20	508	8.82	224
11R24.5	H-302	24	605	8.78	223
11R24.5	H-307	24	606	8.78	223
11R24.5	H-502 EcoFT	24	604	8.80	224
11R24.5	H-702 EcoFT	24	608	8.74	222
11R24.5	H-703 EcoFT	21	535	8.82	224
11R24.5	H-704 EcoFT	21	535	8.70	221
11R24.5	H-801 EcoFT	21	535	9.02	229
11R24.5	H-309	21	535	8.82	224
11R24.5	H-802 EcoFT	24	606	8.80	224
11R24.5	H-804	21	535	8.82	224
11R24.5	H-903 EcoFT	24	610	8.78	223
215/75R17.5	H-902	19	472	6.50	165
225/70R19.5	H-702	20	504	7.28	185
225/70R19.5	H-803	20	504	7.28	185
225/70R19.5	H-902	20	507	7.28	185
235/75R17.5	H-902	20	517	7.20	183
245/70R17.5	H-902	18	467	8.19	208
245/70R19.5	H-702	21	544	8.15	207
245/70R19.5	H-803	21	544	8.15	207
245/70R19.5	H-902	22	547	8.11	206
255/70R22.5	H-902	20	518	8.11	206
255/70R22.5	H-903	22	564	8.23	209
265/70R19.5	H-902	23	576	8.31	211
275/70R22.5	H-301	22	565	9.25	235
275/70R22.5	H-902	22	565	9.25	235
285/75R24.5	H-502 EcoFT	24	611	8.86	225
285/75R24.5	H-702 EcoFT	24	605	8.70	221
285/75R24.5	H-703 EcoFT	24	605	8.70	221
285/75R24.5	H-801 EcoFT	20	507	9.13	232
285/75R24.5	H-309	20	507	8.94	227
285/75R24.5	H-802 EcoFT	24	610	8.86	225
285/75R24.5	H-804	20	507	8.94	227
285/75R24.5	H-903 EcoFT	24	614	8.82	224
295/75R22.5	H-502 EcoFT	24	608	8.74	222
295/75R22.5	H-702 EcoFT	24	610	8.82	224
295/75R22.5	H-703 EcoFT	24	610	8.74	222
295/75R22.5	H-704 EcoFT	19	491	8.82	224
295/75R22.5	H-801 EcoFT	19	491	8.98	228
295/75R22.5	H-309	19	491	8.82	224
295/75R22.5	H-802 EcoFT	24	607	8.78	223
295/75R22.5	H-804	19	491	8.82	224
295/75R22.5	H-902 EcoFT	26	667	8.82	224
295/75R22.5	H-903 EcoFT	19	492	8.74	222
295/80R22.5	H-601	24	608	9.37	238
315/80R22.5	H-301	25	633	9.37	238
315/80R22.5	H-502 EcoFT	25	633	10.00	254
385/65R22.5	H-402	30	773	12.32	313
425/65R22.5	H-402	29	732	12.99	330
425/65R22.5	H-402	30	772	13.70	348

Please see www.herculestire.com for the most up-to-date buffing guidelines.





PERFORMANCE
TOURING
CUV/SUV/LT
SPECIALTY
WINTER
MEDIUM TRUCK

HERCULES TIRES

16380 SR 224 East, Suite 200
Findlay, Ohio 45840, U.S.A.
Tel: 419.425.6400
800.677.9535



HERCULESTIRE.COM

INDUSTRIAL & OTR



INDUSTRIAL & OTR TIRES

Contents

Gripper Skid Steer	3
X-Wall SKS Skid Steer	4
Hauler SKZ Skid Steer	5
XD44 Skid Steer	6
F3 Backhoe.....	7
Super Lug R4 Backhoe.....	8
Super Lug ADV R4 Backhoe.....	9
SKS R1 Tractionmaster	10
4L I3 Multipurpose.....	11
Radial E3/L3 Loader / HDR 325	12
L2 Loader	13
L3 Loader	14
E3/L3 Telehandler.....	15
G2/L2 Telehandler	16
Limited Protection Policy.....	17





GRIPPER SKID STEER



- Excellent medium duty tire provides excellent traction in off-road conditions along with a lower lug-to-void ratio for increased wear.
- Premium chunk-and tear-resistant compounding for best-in-class durability.
- Two plies heavier than most value offerings.
- Square shoulder design for even wear.

Item #	Tire Size & Service Description	PR/LR	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94681	10-16.5/8 TL 129A2	8/D	8.3	6550	60	30.1	10.8	19.0	49.00
94682	12-16.5/10 TL 140A2	10/E	9.8	8850	64	32.2	12.5	23.0	59.00



X-WALL SKS SKID STEER



- All-around tire for high-use, predominantly dirt applications.
- Wide lugs, square shoulders and deep tread combine for optimum traction and long wear.
- Staggered step lugs and middle breaker provide superior mud cleanout.
- Reinforced sidewalls and rim protectors reduce downtime and damage.

Item #	Tire Size & Service Description	PR/ LR	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94683	10-16.5/8 TL 134A2	8/D	8.3	7450	75	30.1	10.9	22.0	50.00
94684	12-16.5/10 TL 140A2	10/E	9.8	8850	64	32.3	12.5	23.0	67.00
94685	5.70-12/6 TL 93A2	6/C	4.5	2300	60	22.3	6.0	16.0	17.00
94686	7.00-15/6 TL 121A2	6/C	5.5	5050	59	30.5	8.7	20.0	44.00
94687	23X8.50-12/6 TL 101A2	6/C	7.0	2850	50	22.5	8.4	18.0	24.00
94688	26X12-12/10 TL 124A2	10/E	10.5	5700	64	25.8	11.7	27.0	46.00
94689	27X8.50-15/6 TL 112A2	6/C	7.0	3950	44	26.7	8.4	19.0	33.00
94690	31X15.50-15/8 TL 126A2	8/D	13.0	5900	44	31.0	15.1	30.0	77.00
94691	14-17.5/12 TL 152A2	12/F	10.5	12400	69	35.9	13.8	39.0	109.00



HAULER SKZ SKID STEER



- Non-directional, heavy-duty tire delivers excellent mixed surface performance.
- Flat and wide shoulder to shoulder tread design provides exceptional traction and ground contact.
- Deep tread, reinforced sidewalls and rim protectors guard against punctures as well as side impacts.
- Optimized durability and wear on all surfaces.
- Dependable traction moving forward and in reverse.

Item #	Tire Size & Service Description	PR/LR	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94692	10-16.5/10 TL 134A2	10/E	8.3	7450	75	30.9	10.8	39.0	76.00
94693	12-16.5/12 TL 145A2	12/F	9.8	10050	80	32.7	12.6	44.0	100.37
94697	15-19.5/14 TL 164A2	14/G	11.8	17700	80	40.2	15.7	35.0	130.00
94695	31X15.50-15/8 TL 126A2	8/D	13.0	5900	44	30.6	15.1	30.0	90.60
94694	33X15.50-16.5/14 TL 148A2	14/G	12.0	11000	70	32.9	15.0	44.0	126.00



XD44 SKID STEER



- Ultra-premium severe-duty and hard surface solution.
- Extra-deep L5 tread along with an 80% lug-to-void ratio provides long wear and excellent impact resistance.
- Excellent for foam fill and retreading.
- Reinforced sidewalls and rim protectors.

Item #	Tire Size & Service Description	PR/LR	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94696	10-16.5/10 TL 134A2	10/E	8.3	7450	75	30.9	10.7	44.0	84.00
94698	12-16.5/12 TL 145A2	12/F	9.8	10050	80	32.8	12.7	44.0	121.00



F3 BACKHOE

- Robust casing and flat profile reduce crowning for excellent wear and stability.
- Rib design for 2WD offers smooth ride and effective steering.
- Deep tread for maximum usage value.

Item #	Tire Size & Service Description	PR/ LR	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94699	11L-15SL/10 118 TL 118B	10/E	15.0	5850	43	30.2	11.0	17.0	58.00
94700	11L-16SL/12 TL 123B	12/F	16.0	6850	51	31.6	10.3	17.0	56.00
94701	14.5/75-16.1SL/10 TL 121A8	10/E	16.1	9600	40	37.0	14.2	21.0	89.00





SUPER LUG R4 BACKHOE

- Primarily available for 4WD fronts and select rear sizes.
- Square shoulders and deep tread increase tire life and off-road traction.
- Heavy duty casing for impact resistance.
- Staggered step lugs for optimal cleaning and improved traction.

Item #	Tire Size & Service Description	PR/ LR	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94702	10.5/80-18/10 TL 119A6	10/E	18.0	7100	53	34.4	11.1	28.0	64.55
94703	12.5/80-18/12 TL 129A6	12/F	18.0	9650	53	37.7	11.5	34.0	86.00
94704	14.9-24/12 TL 145A8	12/F	24.0	14700	41	48.7	15.9	38.0	156.00
94709	16.9-28/12 TL 152A8	12/F	28.0	18000	37	56.2	17.9	42.0	212.00



SUPER LUG ADV R4 BACKHOE



- Outstanding for road transportation and job site applications.
- Multi-angle tread lugs and spaded centerline minimize vibration, offering a smooth ride at transportation speeds.
- Staggered step lugs for optimal cleaning and improved traction.

Item #	Tire Size & Service Description	PR/ LR	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94705	16.9-24/12 TL 149A8	12/F	24.0	16500	38	51.2	17.5	34.0	166.00
94706	17.5L-24/10 TL 144A8	10/E	24.0	14200	31	49.5	17.5	38.0	160.00
94707	19.5L-24/12 TL 151A8	12/F	24.0	16500	33	51.7	19.1	35.0	188.00
94708	21L-24/12 TL 155A8	12/F	24.0	19700	31	54.7	21.0	48.0	211.00



SKS R1 TRACTIONMASTER



- Aggressive R1 tread provides optimum pulling and tractive effort.
- Great for trenchers and smaller three wheeled forklifts.
- Staggered step lugs for optimal cleaning and improved traction.
- Heavy-duty reinforced sidewall.

Item #	Tire Size & Service Description	PR/LR	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94710	26X12-12/8 TL 119A2	8/D	10.5	4750	50	26.3	11.8	26.0	40.00
94712	29X12.50-15/8 TL 123A2	8/D	10.0	5400	44	29.4	12.2	23.0	49.80
94711	31X15.50-15/8 TL 126A2	8/D	13.0	5900	44	31.7	15.0	26.0	64.00



4L I3 MULTIPURPOSE



- Designed primarily for smaller telehandlers and optimum stability under load.
- MPT tread and reinforced center design for maximum support.
- Steep lug angles for traction performance in soft soil conditions.
- Staggered step lugs for optimal cleaning and improved traction.

Item #	Tire Size & Service Description	PR/LR	Rim Width (In)	Single Max Load	Single Max PSI	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94714	405/70-20/14 TL 154A8	14/G	13.0	13650	50	42.6	17.4	33.0	144.00
94713	405/70-24/14 TL 156A8	14/G	13.0	14550	50	46.8	16.6	34.0	179.60

RADIAL E3/L3 LOADER HDR 325



- Cut and chip resistant compounding to assist with optimum performance and wear.
- E3/L3 tread design offers superior traction and stability.
- Excellent performance and value for both construction and quarry applications.

Item #	Tire Size & Service Description	Load Index & Speed Rating	Star Rating	Rim Width (in)	Overall Diameter	Section Width (in)	Tread Depth (32nds)	Tire Weight (lbs.)	Tire Weight (lbs.)
94645	17.5R25 E3/L3	167B/182A2	★★	14.0	52.8	17.5	35.3	338.8	338.8
94646	20.5R25 E3/L3	177B/193A2	★★	17.0	58.4	20.5	37.8	506.0	506.0
94647	23.5R25 E3/L3	185B/201A2	★★	19.5	63.3	23.5	41.6	690.8	690.8



L2 LOADER



- Robust traction tread with wide lugs for optimal wear and traction in soft soil conditions.
- Heavy-duty casing ensures stability and protects against impacts.
- Deep and flat tread profile eliminates crowning for optimum ground contact and overall wear.
- Staggered step lugs for optimal cleaning and improved traction.

Item #	Tire Size & Service Description	PR/LR	Rim Width (In)	Single Max Load	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94715	15.5-25/12 TL 168A2	12/F	12.0	9400	50.1	16.1	33.0	173.00
94716	17.5-25/12 TL 171A2	12/F	14.0	9400	52.6	15.2	33.0	191.00
94717	20.5-25/16 TL 181A2	16/H	17.0	12150	59.3	21.1	38.0	260.00



L3 LOADER

- Designed to provide excellent wear for telehandlers operating on hard surfaces.
- Heavy-duty casing ensures stability and protects against impacts.
- Superior performance and ability to withstand heat cycles as well as the additional weight of foam fill.
- Flat tread profile to reduce crowning and provide optimal wear.

Item #	Tire Size & Service Description	PR/LR	Rim Width (In)	Single Max Load	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94718	15.5-25/12 TL 168A2	12/F	12.0	9400	50.5	16.4	33.0	200.00
94719	17.5-25/12 TL 171A2	12/F	14.0	9400	54.3	18.4	33.0	248.00
94720	20.5-25/16 TL 181A2	16/H	17.0	12150	59.2	21.5	40.0	323.00
94721	23.5-25/20 TL 191A2	20/L	19.5	15450	63.8	25.0	47.0	487.00



E3/L3 TELEHANDLER



- Designed to provide excellent hard surface life and deliver traction on softer surfaces when necessary.
- Heavy-duty casing ensures stability and protects against impacts.
- Deep and flat tread profile eliminates crowning for optimum ground contact and overall wear.
- Staggered step lugs for optimal cleaning and improved traction.

Item #	Tire Size & Service Description	PR/ LR	Rim Width (In)	Single Max Load	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94724	13.00-24/12 TL 168A2	12/F	8.0	3750	51.3	14.4	35.0	170.00
94725	14.00-24/12 TL 166A2	12/F	8.0	4550	53.3	15.2	38.0	183.00



G2/L2 TELEHANDLER

- Designed to provide excellent wear for telehandlers operating on hard surfaces.
- Heavy-duty casing ensures stability and protects against impacts.
- Superior performance and ability to withstand heat cycles as well as the additional weight of foam fill.
- Flat tread profile to reduce crowning and provide optimal wear.
- Staggered step lugs for optimal cleaning and improved traction.

Item #	Tire Size & Service Description	PR/ LR	Rim Width (In)	Single Max Load	Overall Diameter	Section Width	Tread Depth	Tire Weight (lbs.)
94722	13.00-24/12 TL 143A8	12/F	8.0	3750	49.6	14.1	28.0	157.00
94723	14.00-24/12 TL 147A8	12/F	8.0	4550	52.1	15.1	28.0	182.00

Hercules Tires Industrial Products Limited Protection Policy

All Hercules brand industrial tires are covered against defects due to materials and workmanship for up to three (3) or five (5) years from the stated serial number date. See Limited Protection Policy Section below for protection term for specific products.

If a product is deemed defective upon examination and analysis, Hercules Tire will provide an allowance against the original purchase price. The allowance will be determined by Hercules Tire, to be applied toward the purchase of a new product, based on the remaining unused portion of the tread or covered lifetime on the defective product.

The cost of transportation, service, and sales tax already paid will be borne by the owner of the product making the claim. This Limited Protection Policy will not apply if the Hercules product has been installed incorrectly, altered, repaired or misused in any matter whatsoever, which, in Hercules' sole opinion, has affected performance.

This Protection Policy is the only one applicable from Hercules Tire for industrial products. The company does not recognize any other condition, representation, approval or protection, whether explicit or implicit, or otherwise prescribed by law, other than mentioned above.

Hercules Tire cannot be held responsible for damages or claims caused by the tire whether such damages are direct or indirect, special, consequential or otherwise. Any liability is strictly limited to repair or reduction of an applicable purchase, according to the provisions in the Adjustments Sections below. This Limited Protection Policy is for the exclusive benefit of the owner and is not assignable.

Limited Protection Policy

The following Hercules brand industrial tire(s) are covered against defects in workmanship and material for the original usable tread, limited to five (5) years from the date of manufacture (serial number on tire): GRIPPER SKID STEER, XD44 SKID STEER, F3 BACKHOE, SUPER LUG R4 BACKHOE, SUPER LUG ADV R4 BACKHOE, SKS R1 TRACTIONMASTER, 4L I3 MULTIPURPOSE, L2 LOADER, L3 LOADER, E3/L3 TELEHANDLER, G2/L2 TELEHANDLER.

The following Hercules brand industrial tire(s) are covered against defects in workmanship and material for the original usable tread, limited to three (3) years from the date of manufacture (serial number on tire): RADIAL E3/L3 LOADER / HDR 325.

If your Hercules brand industrial tire is not listed above, contact Hercules Tire to find out the length of coverage on your tire.

If an examination by Hercules Tire shows that any such tire became unserviceable as a result of a workmanship or material related condition, it will, at the option of Hercules Tire, either be repaired at no charge or a credit will be issued towards the purchase price of a replacement tire.

No Charge Adjustment

If a defect in workmanship and materials is found and the tire cannot be repaired within the first 10% of the original usable tread a no charge adjustment will be implemented.

Prorated Adjustment

If a defect in workmanship and materials is found and the tire cannot be repaired after 10% of the original usable tread or thereafter up to three (3) or five (5) years from the serial number date, the prorated credit will be determined by multiplying the original purchase price of the tire by the percentage of usable tread remaining on the tire. Costs for mounting, filling and any other service related charges or applicable taxes are payable by the customer.

General Standards and Exclusions

All Hercules brand industrial tires are designed and manufactured to carry the loads at the appropriate speeds given in the ETRTO-standards.

Mounting

- Sizes of tire and rim should correspond to each other.
- The sizes of the rim should correspond to the ETRTO-standards and tolerances, the type should be flat base or split wheel for solid resilient tires.
- The rim and the rings should be in good shape, without cracks, deformations or excessive rust. Deformed or damaged parts should be replaced.
- The rim load capacity should be equal to or exceed the tire load capacity.
- All rings making part of the rim should be used.
- Only trained people, using the right tooling, working in line with the general and local safety regulations should do tire-fitting

Speeds

Maximum speeds

The maximum speed of the vehicle should not exceed the ETRTO values. They are given for the unloaded vehicle.

Average speeds

As industrial tires are designed for intermittent service only and limited running distances, the working day average speed (WDAS) should not exceed 5 km/h at an average load of 75% of the maximum ETRTO load, this at an ambient temperature of 20°C, for solid tires. For pneumatic tires the maximum continuous average speed (WDAS) should not exceed 10 km/h at an average load of 75% of the maximum ETRTO-load. For average loads, average speeds and ambient temperatures exceeding the indicated values and for distances longer than 2 km per journey, the application has to be investigated in detail by Hercules Tire in order to check whether the tire working temperature remains within acceptable and safe limits.

Usage

Normal and moderate use is considered as long as no foreign materials are destroying the tire and as long as braking, accelerating and steering forces are within the normal driving-conditions.

Ambient Temperature

Hercules industrial tires can operate at ambient temperatures from -30°C up to +50°C. Higher ambient temperatures can however be allowed after a technical review and a written acceptance of the application by Hercules Tire. Tire parameters, such as deformation and rolling resistance might be influenced accordingly.

Storage

Hercules industrial tires have to be stored in a protected environment (a dark and dry place, away from ozone), as specified in the ETRTO Recommendations.

Tire-Fill

The protection policy will become void for all tire-wheel assemblies filled with tirefill, unless the material and filling process have been approved by Hercules Tire and the filling has been done in line with the filling specifications from the tire-fill supplier. One should also consider that stresses on wheels and impacts on carcasses will be intensified for tire-filled tires.

Exclusions

- Tires purchased as seconds, mark downs or used;
- Failures related to field or road hazards including cuts, punctures, impact breaks and stubble damage;
- Failures relating to improper mounting procedures;
- Failures relating to overloading or use at speeds in excess of the maximum recommended speed;
- Tires mounted on rims which are not recommended by the Tire and Rim Association;
- Uneven or rapid wear due to mechanical irregularity of the vehicle;
- Tires that have run under or over inflated;
- Damage resulting from fires, accidents, chemical corrosion or vandalism;
- Weather cracking or ozone damage on tires more than three years old;
- Tires that have been used in applications other than the application for which the tire was designed;
- Incidental or consequential damages.

Protection Clause

All Hercules industrial tires are covered against defects due to materials or workmanship. This Protection Policy remains valid for three (3) or five (5) years from the date of manufacturing. The validity of this protection Policy depends on the tire type and on the conditions described in the general standards:

- a) for solid resilients: as long as the safety line, marked on the sidewall of the tire by "60 J" is not reached.
- b) for press-on solid tires: as long as one third of the total rubber height has not been worn of (in other words, as long as 2/3rd of the rubber section height is still available).
- c) for pneumatic tires: as long as tread lugs are available in the center part of the tire.

If the customer finds a failure to a tire, a request for an adjustment should be made by calling 1-844-708-7291 or sending an e-mail to Hercules.adjustment@herculestire.com.

Thermal explosions due to a WDAS above 2.5 km/h on budget solid tires and 5 km/h on budget pneumatic tires are not considered a manufacturing defect and are therefore not warrantable.

If our analysis shows a tire has failed under this Limited Protection Policy, we will make an allowance against the current list price towards the purchase of a new Hercules tire relative to the unused portion of the tread on the defective tire. The cost of transportation, service and sales tax, already paid will be borne by the owner of the tire making the claim. This guarantee is for the exclusive benefit of the owner and this warranty is not assignable. Hercules Tire does not warrant against consequential or incidental damage arising from defective tire.

HERCULES TIRES

16380 SR 224 East,
Suite 200
Findlay, Ohio 45840,
U.S.A.
Tel: 844-432-9729



WWW.HERCULESTIRE.COM