



SNOWPLOW SPECIFICATIONS



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841



fisherplows.com |



STRAIGHT BLADES

Model	Blade Width	Blade Height	Blade Gauge	Trip Springs	Ribs	Lift Cylinder	Angling Rams	Plowing Width	Approximate Weight*	Cutting Edge	Wear Shoes
HT Series™	2.29 m	68.58 cm	1.90 mm	2	6+Tube	5.08 cm x 17.14 cm	3.81 cm x 20.32 cm	2.01 m	187 kg	0.95 cm x 15.24 cm steel*** 1.27 cm x 15.24 cm steel*** 2.54 cm x 15.24 cm poly***	Optional
SD Series	2.06 m	66.04 cm	1.90 mm	2	8	3.81 cm x 15.24 cm	3.81 cm x 25.40 cm	1.85 m	214 kg	2.54 cm x 15.24 cm poly	Optional
SD Series	2.29 m	66.04 cm	1.90 mm	2	8	3.81 cm x 15.24 cm	3.81 cm x 25.40 cm	2.06 m	220 kg	2.54 cm x 15.24 cm poly 0.95 cm x 15.24 cm steel***	Optional
HD2™	2.29 m	73.66 cm	2.66 mm	3	10	3.81 cm x 25.40 cm	3.81 cm x 30.48 cm	2.05 m	310 kg	0.95 cm x 15.24 cm	Optional
HD2	2.44 m	73.66 cm	2.66 mm	4	10	3.81 cm x 25.40 cm	3.81 cm x 30.48 cm	2.19 m	332 kg	1.27 cm x 15.24 cm	Optional
HD2	2.59 m	73.66 cm	2.66 mm	4	10	3.81 cm x 25.40 cm	3.81 cm x 30.48 cm	2.32 m	340 kg	1.27 cm x 15.24 cm	Optional
HD2	2.74 m	73.66 cm	2.66 mm	4	10	3.81 cm x 25.40 cm	3.81 cm x 30.48 cm	2.46 m	349 kg	1.27 cm x 15.24 cm	Optional
HDX™	2.44 m	73.66 cm**	1.90 mm	4	8	3.81 cm x 25.40 cm	3.81 cm x 30.48 cm	2.19 m	391 kg	1.27 cm x 15.24 cm	Optional
HDX	2.74 m	73.66 cm**	1.90 mm	4	8	3.81 cm x 25.40 cm	3.81 cm x 30.48 cm	2.46 m	409 kg	1.27 cm x 15.24 cm	Optional
MC Series	2.74 m	86.36 cm	3.04 mm	4	8	5.08 cm x 25.40 cm	5.08 cm x 40.64 cm	2.41 m	532 kg	1.27 cm x 20.32 cm (center punched)	Standard
MC Series	3.05 m	86.36 cm	3.04 mm	6	8	5.08 cm x 25.40 cm	5.08 cm x 40.64 cm	2.69 m	593 kg	1.27 cm x 20.32 cm (center punched)	Standard

HD2 and HDX are available with a universal skid-steer loader mounting plate

V-PLOWS

Model	Blade Width	Blade Height	Blade Gauge	Trip Springs	Ribs	Lift Cylinder	Angling Rams	Plowing Width	Approximate Weight*	Cutting Edge	Wear Shoes
XtremeV™ SS	2.29 m	78.11 cm at end 73.66 cm at hinge	2.66 mm	4	12	3.81 cm x 25.40 cm	4.44 cm x 27.94 cm	1.98 m full angle; 1.91 m scoop; 2.06 m full V	372 kg	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm***	Optional
XtremeV SS or PC	2.59 m	78.74 cm at end 73.66 cm at hinge	2.66 mm	4	12	3.81 cm x 25.40 cm	4.44 cm x 27.94 cm	2.26 m full angle; 2.16 m scoop; 2.31 m full V	407 kg	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm***	Optional
XtremeV SS or PC	2.90 m	83.82 cm at end 78.74 cm at hinge	2.66 mm	6	12	3.81 cm x 25.40 cm	4.44 cm x 27.94 cm	2.51 m full angle; 2.41 m scoop; 2.62 m full V	459 kg	1.27 cm x 15.24 cm	Optional
XV2™ SS	2.29 m	93.98 cm at end 78.74 cm at hinge	1.90 mm	4	12	4.44 cm x 25.40 cm	4.44 cm x 27.94 cm	2.01 m full angle; 1.93 m scoop; 2.08 m full V	414 kg	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm***	Optional
XV2 SS or PC	2.59 m	96.52 cm at end 78.74 cm at hinge	1.90 mm	4	12	4.44 cm x 25.40 cm	4.44 cm x 27.94 cm	2.26 m full angle; 2.18 m scoop; 2.34 m full V	434 kg	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm***	Optional
XV2 SS or PC	2.90 m	99.06 cm at end 78.74 cm at hinge	1.90 mm	6	12	4.44 cm x 25.40 cm	4.44 cm x 27.94 cm	2.59 m full angle; 2.49 m scoop; 2.62m full V	473 kg	1.27 cm x 15.24 cm	Optional

SS = Stainless Steel | PC = Powder Coated Steel

EXPANDABLE LENGTH SNOWPLOW

Model	Blade Width	Blade Height	Blade/Wing Gauge	Trip Springs	Ribs	Lift Cylinder	Angling Rams	Plowing Width at Full Angle	Approximate Weight*	Blade Cutting Edge Wing Cutting Edge	Wear Shoes
XLS™	2.44 m retracted 3.05 m expanded 2.69 m scoop	73.66 cm	2.66 mm	4	Blade Center: 6 full, 2 half Blade Wings: 1 full (each)	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	2.18 m retracted 2.74 m expanded 2.41 m windrow	788.45 kg	1.27 cm x 15.24 cm steel*** 3.81 cm x 22.86 cm poly	Optional

PUSHER PLOWS

STORM BOX™	Blade Width	Approximate Weight	Side Plate	Snow Capacity
Skid-Steer	2.44 m	332 kg	0.91 m x 0.91 m	6.40 m
Skid-Steer	3.05 m	358 kg	0.91 m x 0.91 m	8.23 m
Backhoe	3.05 m	467 kg	0.91 m x 0.91 m	8.23 m
Backhoe	3.66 m	521 kg	0.91 m x 0.91 m	10.06 m
Wheel Loader	3.66 m	762 kg	1.21 m x 1.21 m	13.72 m
Wheel Loader	4.27 m	823 kg	1.21 m x 1.21 m	16.46 m
Wheel Loader	4.88 m	884 kg	1.21 m x 1.21 m	19.20 m

* Plus vehicle mount: approx. 27.22 kg (approx. 83.46 kg MC Series)

** Blade height shown is for the 55° attack angle. The 65° attack angle blade height is 72.39 cm and the 75° attack angle blade height is 68.58 cm.

*** Optional accessory

The Legacy Rolls On



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings with a snowplow. Fisher Engineering offers a limited warranty on all snowplows and accessories. See separately printed page for this important information. The following are registered (®) and unregistered (™) trademarks of Douglas Dynamics, LLC: FISHER®, HD2™, HDX™, HT Series™, STORM BOX™, XLS™, XtremeV™ and XV2™.